

INSTRUCTIONS / NOTES		
1	DIMENSION	3.00" (W) X 2.00" (H); SHARP RADIUS
2	MATERIAL	GE: 8B35, LEXAN, 7 MIL THICK, TEXTURED SURFACE
3	ADHESIVE	3M: 468 MP, 5 MIL ADHESIVE, APPLY TO BACK SIDE
4	BKGND FLOOD	COLOR: WHITE
5	LOGO/TEXT	COLOR: BLACK

DigiTRAK® F SERIES™

FS – Short Range Transmitter 0.8 - 1.6V $\approx$ 150mA Max

This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

 **ARBN**
090 007 962

 **DIGITAL CONTROL INCORPORATED**

800-288-3610 or 425-251-0559
www.digitrak.com

FCC ID: KKGZ0619
IC: 2213A-Z0619

12kHz Frequency
450-0035-00-A

TITLEBLOCK: SIZE 8.5X11 (LETTER)	MN	01-12-10	INITIAL PRODUCTION RELEASE					A
	BY	DATE	DESCRIPTION					REV
THIS DRAWING IS CONFIDENTIAL AND IS SUPPLIED ON THE UNDERSTANDING THAT IT IS NOT SHOWN TO OTHER PERSONS OR COMPANIES WITHOUT WRITTEN CONSENT OF DIGITAL CONTROL INCORPORATED	APPROVAL	AH	TOLERANCES (STANDARD UNITS UNLESS OTHERWISE SPECIFIED)			 DIGITAL CONTROL INCORPORATED	TITLE DIGITRAK F SERIES SHORT RANGE TRANSMITTER	SHEET 1 / 1
	APPROVAL	SF					DRAWING NO. 450-0035-00	REV A
	DRAFTER	MN	DECIMAL .X ±.030 FRACTIONS ±1/32 .XX ±.010 .XXX ±.005 ANGLES ± 1°					
	ENGINEER	MN	19625 62ND AVE SOUTH, SUITE B103 KENT, WA 98032, WWW.DIGITRAK.COM 425-251-0701 · 425-251-0702 FAX					

FS Label Location



Side 1



Side 2