



Compliance Testing, LLC
Previously Flom Test Lab
EMI, EMC, RF Testing Experts Since 1963

toll-free: (866) 311-3268
fax: (480) 926-3598
<http://www.ComplianceTesting.com>
info@ComplianceTesting.com

Test Report

Prepared for: Freewave Technologies

Model: ZumLink Z9-C or Z9-T

Description: Digital Transmission System Radio Transceiver

Serial Number: N/A

FCC ID: KNYPMT0101AB

To

FCC Part 1.1310

Date of Issue: June 21, 2016

On the behalf of the applicant:

Freewave Technologies
5395 Pearl Parkway
Boulder, CO 80301

Attention of:

Dean Busch, Sr. Compliance Engineer
Ph: (303)962-7879
Email: dbusch@freewave.com

Prepared By
Compliance Testing, LLC
1724 S. Nevada Way
Mesa, AZ 85204
(480) 926-3100 phone / (480) 926-3598 fax
www.compliancetesting.com
Project No: p1660006



Alex Macon
Project Test Engineer

This report may not be reproduced, except in full, without written permission from Compliance Testing
All results contained herein relate only to the sample tested



Test Report Revision History

Revision	Date	Revised By	Reason for Revision
1.0	June 15, 2016	Alex Macon	Original Document
2.0	August 28, 2019	Michelle O'Hern	Corrected FCC ID on page 1



ILAC / A2LA

Compliance Testing, LLC, has been accredited in accordance with the recognized International Standard ISO/IEC 17025:2005. This accreditation demonstrates technical competence for a defined scope and the operation of a laboratory quality management system (refer joint ISO-ILAC-IAF Communiqué dated January 2009)

The tests results contained within this test report all fall within our scope of accreditation, unless below

Please refer to <http://www.compliancetesting.com/labscope.html> for current scope of accreditation.

Testing Certificate Number: **2152.01**



FCC Site Reg. #349717

IC Site Reg. #2044A-2

Non-accredited tests contained in this report:

N/A

EUT Description

Model: ZumLink Z9-C or Z9-T

Description: Digital Transmission System Radio Transceiver

Firmware: N/A

Software: N/A

S/N: N/A

Additional Information:

All tests are performed with a 6 dBi antenna in mind.

The data rate determines the frequency selected. Below are the high mid and low frequencies per data rate

115.2	250
902.477	902.534
914.918	914.976
927.821	927.418



MPE Evaluation

This is a fixed device used in Uncontrolled Exposure environment.

Limits Uncontrolled Exposure
47 CFR 1.1310
Table 1, (B)

0.3-1.234 MHz:	Limit [mW/cm ²] = 100
1.34-30 MHz:	Limit [mW/cm ²] = (180/f ²)
30-300 MHz:	Limit [mW/cm ²] = 0.2
300-1500 MHz:	Limit [mW/cm ²] = f/1500
1500-100,000 MHz	Limit [mW/cm ²] = 1.0

Test Data

Test Frequency, MHz	902.477
Power, Conducted, mW (P)	1000
Antenna Gain Isotropic	6dBi
Antenna Gain Numeric (G)	3.98
Antenna Type	
Distance (R)	20 cm

$S = \frac{P * G}{4\pi r^2}$
Power Density (S) mw/cm ²

Power Density (S) = 0.7918
Limit =(from above table) = 0.602

R=√(PG/4πL)	Distance (R) cm	Power mW (P)	Numeric Gain (G)	Limit (L)
	22.94290837	1000	3.98	0.602

The minimum safe distance is 22.94 cm.

END OF TEST REPORT