



FCC CFR47 PART 15 DIGITAL DEVICE

TEST REPORT

FOR

**17" COLOR MONITOR W/ MAX. RESOLUTION
OF 1280X1024 NON-INTERLACED(70 KHz)**

MODEL:CM-17J

PRODUCT FAMILY:IN-17, C1770D, UQ-1744

FCC ID: KODM173170

REPORT NUMBER: 99E7915

ISSUE DATE: MAY 13, 1999

Prepared for
DTS TECHNOLOGY CO., LTD.
NO. 4 LANE 8 SEC 1, TA FU RD. TAN TZU SHIANG
TAICHUNG SHIEN
TAIWAN, R. O. C.

Prepared by
COMPLIANCE ENGINEERING SERVICES, INC.
No. 199, CHUNG SHENG ROAD
HSIN TIEN CITY, TAIPEI, TAIWAN R.O.C.
TEL: (02) 2217-0894
FAX: (02) 2217-1254



**FCC, VCCI, CISPR, CE
UL, CSA, TÜV, VDE**

U.S.A. : P.O.BOX 612650, SAN JOSE, CA 95161-2650

TAIPEI : P.O.BOX 17-82, HSIN TIEN, TAIWAN, R.O.C.

TABLE OF CONTENTS

1.	VERIFICATION OF COMPLIANCE.....	1
2.	PRODUCT DESCRIPTION.....	2
3.	TESTED SYSTEM DETAILS.....	2
4.	TEST FACILITY.....	3
5.	ACCREDITATION AND LISTING.....	3
6.	MEASUREMENT INSTRUMENTATION.....	3
7.	MEASURING INSTRUMENT CALIBRATION.....	4
8.	UNITS OF MEASUREMENT.....	4
9.	ANTENNAS.....	4
10.	CLASSIFICATION OF DIGITAL DEVICE.....	5
11.	RADIATED EMISSION LIMITS.....	5
12.	CONDUCTED EMISSION LIMITS.....	6
13.	CONDUCTED EMISSION TEST PROCEDURE.....	6
14.	RADIATED EMISSION TEST PROCEDURE.....	7
15.	AMBIENT CONDITIONS.....	7
16.	SYSTEM TEST CONFIGURATION.....	7
17.	EQUIPMENT MODIFICATIONS.....	9
18.	EUT SETUP PHOTOS.....	10
19.	TEST EQUIPMENT LIST.....	12
20.	CORRECTION FACTOR.....	13
21.	TEST RESULT SUMMARY.....	14
APPENDICES		16
. EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION		
. CONFIGURATION BLOCK DIAGRAM		
. CONDUCTED EMISSION PLOT		
. RADIATED EMISSION DATA		
. EUT PHOTOGRAPHS		

1. VERIFICATION OF COMPLIANCE



COMPANY NAME: DTS TECHNOLOGY CO., LTD.
NO. 4 LANE 8 SEC 1, TA FU RD.
TAN TZU SHIANG, TAICHUNG SHIEN.
TAIWAN, R. O. C.

CONTACT PERSON:JOHNSON CHIANG / R&D MANAGER

TELEPHONE NO: (04) 534-8215

MODEL NO/NAME: CM-17J

PRODUCT FAMILY: IN-17 , C1770D , UQ-1744

SERIAL NO: N/A

DATE TESTED: MAY 4, 1999 ~ MAY 12, 1999

TYPE OF EQUIPMENT:	INFORMATION TECHNOLOGY EQUIPMENT (ITE)	
MEASUREMENT DISTANCE:	() 3 METER	(x) 10 METER
TECHNICAL LIMIT:	CLASS B	
FCC RULES:	PART 15	
MEASUREMENT PROCEDURE	ANSI C63.4:92 / EN55022	
EQUIPMENT AUTHORIZATION PROCEDURE	CERTIFICATION	
MODIFICATION MADE ON EUT	<input checked="" type="checkbox"/> YES	<input type="checkbox"/> NO
DEVIATIONS FROM MEASUREMENT PROCEDURE	<input type="checkbox"/> YES (refer to section 21 for comments) <input checked="" type="checkbox"/> NO	
RADIATED EMISSION TEST RESULT	-0.84 dB @ 113.839 MHz/HORIZONTAL	
CONDUCTED EMISSION TEST RESULT	-2.52 dB @ 4.598 MHz/L1	

The above equipment was tested by Compliance Engineering Services, Inc. for compliance with the requirements set forth in the FCC CFR 47, PART 15. The results of testing in this report apply to the product/system which was tested only. Other similar equipment will not necessarily produce the same results due to production tolerance and measurement uncertainties.

Approved By

MIKE C.I. KUO / VICE PRESIDENT
COMPLIANCE ENGINEERING SERVICES

Acknowledged By

JOHNSON CHIANG / R&D MANAGER
DTS TECHNOLOGY CO., LTD.

2. PRODUCT DESCRIPTION

CHASSIS TYPE	PLASTIC
LIST OF EACH OSC. OR XTAL. FREQ. (FREQ.>=1 MHz)	X101=8MHz
CHIPSET BRAND AND PART NO.	UMC, NT68P61A
NUMBER OF PCB LAYERS	1 LAYER
BOARD REVISION NO.	REV:A2
POWER REQUIREMENTS	AC 100~240V
NO. OF EXTERNAL I/O CONNECTORS	1
MAX. RESOLUTION	1280X1024
MAX. HOR/VERT FREQUENCY(KHz/Hz)	70KHz/100Hz

Model Differences:

Model Name	Brand Name	Tested (Checked)
CM-17J	DTS, ARCUS, ACETECH, COIN, MAGTRON, SENORG, SUAVE	<input checked="" type="checkbox"/>
IN-17	INTEX	<input type="checkbox"/>
C1770D	SUNNY	<input type="checkbox"/>
UQ-1744	UNIQ	<input type="checkbox"/>

3. TESTED SYSTEM DETAILS

The Model names for all equipment, plus descriptions of all cables used in the tested system (including inserted cards) are:

Host Computer

Device Type	Manufacturer	Model Number	Serial Number	FCC ID
HOST COMPUTER	VIVA	VIVA586-133	HS-02	DOC
HARD DRIVE	Maxtor	71336AP	HD-02	N/A
FLOPPY DRIVE	Panasonic	JU-257A606P	FD-02	N/A
DVD-ROM DRIVE	MATSUSHITA	SR-8582-B	N/A	IU09TB062CRB
VGA CARD	TNC	TRUE SPEED S3_968 PCI	CV08	JDF-968PCI-001
I/O CARD	BUILT-IN	N/A	N/A	N/A
SOUND CARD	LABWAY	A211A60	N/A	LWHA211A60

External Peripheral Devices

Device Type	Manufacturer	Model Number	Serial No.	FCC ID / Doc
-------------	--------------	--------------	------------	--------------

MONITOR (EUT)	DTS	CM-17J	N/A	KODM173170
KEYBOARD	Acer	6311-TW	KB-15	JVPKBS-WIN
MOUSE	LOGITECH	M-M35	ME-02	DZL210365
PRINTER	EPSON	LX-300	PRN-04	BKMP850A

4. TEST FACILITY

The open area test sites and conducted measurement facilities used to collect the radiated data are located at No. 199, Chung Sheng Road, Hsin Tien City, Taipei, Taiwan R.O.C. The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5. ACCREDITATION AND LISTING

The test facilities used to perform radiated and conducted emissions tests are accredited by National Voluntary Laboratory Accreditation Program for the specific scope of accreditation under Lab Code: 200064-0 to perform Electromagnetic Interference tests according to FCC PART 15 AND CISPR 22 requirements. No part of this report may be used to claim or imply product endorsement by NVLAP or any agency of the US Government. In addition, the test facilities are listed with Federal Communications Commission (reference no: 31040/SIT(1300F2))

6. MEASUREMENT INSTRUMENTATION

Radiated emissions were measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, ridged waveguide, liner horn. EMI receivers were used for line conducted readings, spectrum analyzers with pre-selectors and quasi-peak detectors were used to perform radiated measurements. Receiving equipment (i.e., receiver, analyzer, quasi-peak adapter, pre-selector) and LISNs conform to CISPR specification for "Radio Interference Measuring Apparatus and Measurement Methods," Publication 16.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

7. MEASURING INSTRUMENT CALIBRATION

The measuring equipment which was utilized in performing the tests documented herein has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment which is traceable to recognized national standards.

8. UNITS OF MEASUREMENT

Measurements of radiated interference are reported in terms of dB(uV/m) at a specified distance. The indicated readings on the spectrum analyzer were converted to dB(uV/m) by use of appropriate conversion factors. Measurements of conducted interference are reported in terms of dB(uV).

The field strength is calculated by adding the Antenna Factor and Cable Factors, then by subtracting the Amplifier Gain from the measured reading. The basic equation with a sample calculation is as follows:

$$FS = RA + AF + CF - AG$$

Where FS = Field Strength

RA = Receiver Amplitude

AF = Antenna Factor

CF = Cable Attenuation Factor

AG = Amplifier Gain

Assume a receiver reading of 52.5 dBuV is obtained. The Antenna Factor of 7.4dB/m and a Cable Factor of 1.1dB is added. The Amplifier Gain of 29 dB is subtracted, giving a field strength of 32 dBuV/m. The 32 dBuV/m value was mathematically converted to its corresponding level in uV/m.

$$FS = 52.5 + 7.4 + 1.1 - 29 = 32 \text{ dBuV/m}$$

$$\text{Level in uV/m} = \text{Common Antilogarithm} [(32 \text{ dBuV/m})/20] = 39.8 \text{ uV/m}$$

9. ANTENNAS

The calibrated antennas used to sample the radiated field strength are mounted on a non-conductive, motorized antenna mast 10 meters from the leading edge of the turn table.

10. CLASSIFICATION OF DIGITAL DEVICE

Class A includes digital devices that are marketed for use in commercial, industrial or business environments, excluding devices which are marketed for use by the general public or are intended to be used in the home.

Class B includes digital devices that are marketed for use in residential environments, notwithstanding use in commercial, business and industrial environments.

Note: The responsible party may also qualify a device intended to be marketed in a commercial, business or industrial environment as Class B device, and in fact is encouraged to do so provided the device complies with the technical specifications for a Class B digital device. In the event that a particular type of device has been found to repeatedly cause harmful interference to radio communications, the Commission may classify such a digital device as a Class B digital device, regardless of its intended use.

11. RADIATED EMISSION LIMITS

FCC PART 15 CLASS B

MEASURING DISTANCE OF 3 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54

FCC CLASS B ALTERNATIVE DISTANCE (CISPR 22:1993)

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	30	29.5
88-216	45	33.0
216-960	60	35.6
960-1000	150	43.5
ABOVE 1000	150	43.5

Note: Limits extrapolated 20dB/decade

FCC PART 15 CLASS A

MEASURING DISTANCE OF 10 METER		
FREQUENCY RANGE (MHz)	FIELD STRENGTH (Microvolts/m)	FIELD STRENGTH (dBuV/m)
30-88	90	39.1
88-216	150	43.5
216-960	210	46.4
Above 960	300	49.5

12. CONDUCTED EMISSION LIMITS

CLASS B

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-30MHz	250	48

CLASS A

FREQUENCY RANGE	FIELD STRENGTH (Microvolts)	FIELD STRENGTH (dBuV)
450kHz-1.705MHz	1000	60
1.705MHz - 30MHz	3000	69.54

13. CONDUCTED EMISSION TEST PROCEDURE

The EUT is located so that the distance between the boundary of the EUT and the closest surface to the LISN is 0.8m.

EUT test configuration is according to Section 7 of ANSI C63.4/1992.

Conducted disturbance shall be measured between the phase lead and the ground, and between the neutral lead and the ground. The frequency 0.450 - 30 MHz shall be investigated.

Set the EMI receiver to PEAK detector setting and sweep continuously over the frequency range to be investigated. Set resolution bandwidth to 9kHz minimum. Connect EMI receiver input cable to LINE 1 RF measurement connection on the LISN. Connect a 50ohm terminator to the unused RF connection on the LISN. For each mode of EUT operation, maximize emissions readings by manipulating cable and wire positions. Record the configuration for each EUT power cord which produces emissions closest to the limit. Repeat the same procedure for LINE 2 of each EUT power cord.

14. RADIATED EMISSION TEST PROCEDURE

The EUT and all other support equipment are placed on a wooden table 80 cm above the ground screen. Antenna to EUT distance is either

3 meters or 10 meters (Class B or Class A). During the test, the table is rotated 360 degrees to maximize emissions, and the antenna is positioned from 1 to 4 meters above the ground screen to further maximize emissions. The antenna is polarized in both vertical and horizontal positions.

EUT test configuration is according to Section 8 of ANSI C63.4/1992.

Monitor the frequency range of interest at a fixed antenna height and EUT azimuth. Frequency span should be small enough to easily differentiate between broadcast stations and intermittent ambients. Rotate EUT 360 degrees to maximize emissions received from EUT. If emission increases by more than 1 dB, or if another emission appears that is greater by 1 dB, return to azimuth where maximum occurred and perform additional cable manipulation to further maximize received emission.

Move antenna up and down to further maximize suspected highest amplitude signal. If emission increased by 1 dB or more, or if another emission appears that is greater by 1dB or more, return to antenna height where maximum signal was observed and manipulate cables to produce highest emissions, noting frequency and amplitude.

15. AMBIENT CONDITIONS

The ambient conditions at the time of final tests were as follows:

	Radiated Emission	Conducted Emission
Temperature	28°C	26°C
Humidity	76%	79%

16. SYSTEM TEST CONFIGURATION

The equipment under test was configured and operated in a manner which tended to maximize its emission characteristics in a typical application. Power and signal distribution, ground, interconnecting cabling and physical placement of equipment simulated the typical application and usage insofar as practicable.

SOFTWARE USED DURING THE TESTS	
Operating System	WINDOWS 95
File Name	EMCTEST.EXE, 968VH.EXE
Program Sequence	1. WINDOWS 95 BOOTS SYSTEM. 2. RUN EMCTEST.EXE TO ACTIVATE ALL PERIPHERALS AND DISPLAY "H" PATTERN ON MONITOR SCREEN. 3. SELECTION MS-DOS MODE. 4. RUN S3968 SOFTWARE DRIVER 968VH.EXE SETS

REPORT NO:99E7915

DATE: MAY 13, 1999

EUT:17" COLOR MONITOR W/ MAX. RESOLUTION OF
1280X1024 NON-INTERLACED(70 KHz)

FCC ID:KODM173170

RESOLUTION AND HORIZONTAL REFRESH RATE.

17. EQUIPMENT MODIFICATIONS

To achieve compliance to CLASS B levels, the following change(s) were made during compliance testing:

MOD. #1 ADDED A RING CORE WITH FOUR TURN FROM AC SOCKET GROUND PIN TO CHASSIS GROUND.

MOD. #2 REPLACED C604 TO $0.68 \mu F$ X-CAPACITOR.

MOD. #3 ADDED FERRITE BEAD ON G&S PIN OF Q605.

MOD. #4 ADDED FERRITE BEAD FROM 12,14 PIN OF T601 TO D614,D613.

MOD. #5 ADDED 33PF BYPASS CAPACITOR ON 1,2,3 PIN OF T5 AND GROUND.

MOD. #6 REPLACED R134 TO 39Ω .

MOD. #7 SERIAL A FERRITE BEAD ON 4th PIN OF U103

MOD. #8 ADDED WIRES AS BELOW.

- (A) PLACED A WIRE BETWEEN VGA CABLE'S GROUND AND CHASSIS GROUND.
- (B) A WIRE BETWEEN CHASSIS GROUND AND VGA BOARD SHIELDING GROUND.
- (C) TWO WIRES BETWEEN VGA BOARD SHIELDING GROUND AND CRT UPPER-LUG GROUND.
- (D) TWO WIRES BETWEEN CRT LOWER-LUG GROUND AND VGA BOARD SHIELDING GROUND.
- (E) TWO WIRES BETWEEN VGA BOARD SHIELDING GROUND AND HORIZONTAL HEATSINK GROUND.

MOD. #9 ADDED A JUMPER FROM 1st PIN OF U103 TO CHASSIS GROUND.

MOD. #10 ADDED FERRITE BEAD FROM 1,3,5 PIN OF T701 TO L701,L702 ,L703.


MOD. #11 ADDED A 0.7M WIRE FROM 10TH PIN OF FBT TO UPPER-RIGHT LUG OF CRT.(FOR MPRII SOLUTION).

MOD. #12 DELETED C109.

18. EUT SETUP PHOTOS



Radiated Emission Setup Photos (Worst Emission Position)



Conducted Emission Setup Photos (Worst Emission Position)

19. TEST EQUIPMENT LIST

Equipment	Manuf.	Model No.	Serial No.	Site	Cal Date	Due Date
EMI TEST DISPLAY	ROHDE & SCHWARZ	DSAI-D 804.8932.52	827832/001	D	10/98	10/99
EMI TEST RF UNIT	ROHDE & SCHWARZ	ESBI-RF/1005.4300.52	827832/003	D	10/98	10/99
AMPLIFIER	TEST EQUIPMENT	PA-102	43685	D	9/98	9/99
ANTENNA	CHASE	CBL 6111A	1547	D	12/98	12/99
LISN	EMCO	3825/2	1842	D	1/99	1/00
LISN(EUT)	EMCO	3825/2	1435	D	1/99	1/00
CABLE	TALLEY	HELIX FSJ4-50B	D0301	D	9/98	9/99
CABLE	TIME MICROWAVE	LMR-400-2	D1001	D	9/98	9/99
SPECTRUM ANALYZER	H.P.	8568B	2928A04814	E	2/99	2/00
SPECTRUM DISPLAY	H.P.	85662A	2848A18276	E	2/99	2/00
QUASI-PEAK DETECTOR	H.P.	85650A	2811A01439	E	2/99	2/00
AMPLIFIER	H.P.	8447D B	1644A02328	E	4/98	4/99
ANTENNA	EMC TEST SYSTEMS	3142	1310	E	8/98	2/00
TEST RECEIVER	ROHDE & SCHWARZ	ESHS20	840455/006	E	2/99	2/00
LISN	SOLAR	8012-50-R-24-BNC	8305114	E	7/98	7/99
LISN(EUT)	FISCHER	FCC-LISN-50/250-25-2	107	E	4/98	4/99
CABLE	TIME MICROWAVE	LMR-400-2	E1001	E	4/98	4/99
CABLE	TALLEY	HELIX FSJ4-50B	E0301	E	4/98	4/99

20. CORRECTION FACTOR

OATS NO. D

FREQ (MHZ)	ANTENNA 3 METER			ANTENNA 10 METER			SITE D
	HORI.	VERT.	CABLE LOSS (dB)	HORI.	VERT.	CABLE LOSS (dB)	AMP GAIN (dB)
30	20.05	18.37	0.41	17.80	16.30	0.64	21.45
35	17.24	16.40	0.46	16.00	15.05	0.61	21.68
40	14.52	12.68	0.56	13.27	12.58	0.73	21.70
45	11.90	10.73	0.59	10.59	10.08	0.71	21.73
50	9.72	8.44	0.58	8.56	8.24	0.76	21.75
60	6.61	5.60	0.71	6.02	5.06	0.99	21.67
70	6.30	6.38	0.78	6.34	5.87	0.96	21.70
80	7.90	7.89	0.81	7.45	7.91	0.97	21.73
90	9.35	10.17	0.81	8.61	9.20	1.07	21.72
100	11.15	11.51	0.92	10.12	10.05	1.20	21.70
120	12.31	12.86	1.09	11.75	12.13	1.27	21.59
125	12.46	13.09	1.07	11.87	11.82	1.30	21.65
140	12.25	13.11	1.19	11.97	12.03	1.42	21.57
150	11.65	12.50	1.17	11.34	11.27	1.45	21.49
160	11.08	11.56	1.30	10.44	10.77	1.60	21.48
175	9.99	10.51	1.32	9.65	9.62	1.62	21.42
180	9.72	10.00	1.27	9.21	9.58	1.47	21.42
200	10.75	10.26	1.42	8.98	10.06	1.67	21.35
250	12.90	12.75	1.57	12.21	12.46	1.93	21.25
300	14.04	13.70	1.88	13.33	13.59	2.27	21.20
400	16.87	16.33	2.11	16.24	16.20	2.69	21.10
500	18.05	18.36	2.33	17.97	17.81	2.79	21.12
600	20.06	20.03	2.54	19.64	19.52	3.12	20.79
700	21.24	21.61	2.77	20.61	20.87	3.46	20.56
800	22.52	22.59	2.92	21.98	21.89	3.45	20.53
900	23.50	23.58	3.32	22.76	22.98	3.98	20.23
1000	24.71	25.04	3.40	24.37	24.30	4.19	19.67
1100	25.33	25.46	3.83	24.62	24.94	4.24	20.28
1200	26.89	26.32	3.98	25.32	25.45	4.98	20.06
1300	29.05	28.56	3.86	27.78	28.07	4.82	20.38
1400	27.35	27.51	4.70	26.53	26.99	5.21	19.44
1500	29.70	30.09	5.28	27.94	28.16	5.82	19.39
1600	28.07	27.82	5.03	27.71	27.98	5.64	19.67
1700	31.93	31.40	5.24	29.00	29.42	5.41	20.25
1800	31.56	31.91	4.57	30.06	30.42	5.99	19.70
1900	32.49	32.73	5.18	31.85	30.72	6.53	20.33
2000	31.12	30.32	6.12	30.97	30.46	4.90	19.87

21. TEST RESULT SUMMARY

Preliminary Radiated Emission Tests were performed at the 10 meter open area test site. CCS test procedure no:CCSUE2001B and the procedure listed in ANSI C63.4 /1992 section 8.3.1.1. were used. The following preliminary tests were conducted to determine the worst mode of operation and configuration.

Preliminary Radiated Emission Test			
Frequency Range Investigated		30 MHz TO 1000 MHz	
Mode of operation	Date	Data Report No.	Worst Mode
1280X1024, HF=64KHz	05/04/99	7915D#(45)	<input type="checkbox"/>
1024X768, HF=68KHz	05/12/99	7915D#(162, 163)	<input checked="" type="checkbox"/>
640X480, HF=31.5KHz	05/05/99	7915D#(49)	<input type="checkbox"/>

Final Radiated Emission Test was conducted by operating the worst mode as indicated above.

OATS No: D / 10 M	Data Report No. 7915D#(162, 163)		Date 05/12/99		Tested By: JACKY CHEN							
Six Highest Radiated Emission Readings												
Frequency Range Investigated				30 MHz TO 1000 MHz								
Freq (MHz)	Meter Reading (dBuV)	C.F. (dB/m)	Corrected Reading (dBuV)	Limits (dBuV)	Margin (dB)	Reading Type P/Q/A	Pol. H/V					
30.193	26.16	1.49	27.65	30.0	-2.35	Q	V					
41.109	28.50	-2.82	25.68	30.0	-4.32	Q	V					
62.057	36.22	-9.45	26.77	30.0	-3.23	Q	V					
72.775	34.39	-7.99	26.40	30.0	-3.60	Q	V					
114.556	29.72	-2.97	26.75	30.0	-3.25	P	V					
113.839	32.49	-3.33	29.16	30.0	-0.84	Q	H					

C.F. (Correction Factor)=Antenna Factor+Attenuator (6dB)+Cable Loss
-Amplifier Gain

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading H=Horizontal Polarization/Antenna

Q=Quasi-peak V=Vertical Polarization/Antenna

A=Average Reading

Comments: N/A

Preliminary Conducted Emission Tests were performed according to CCS test procedure no:CCSUE2002B and ANSI C63.4/1992 section 7.2.3. The following preliminary tests were conducted to determine the worst mode of operation.

Preliminary Conducted Emission Test			
Frequency Range Investigated		150 kHz TO 30 MHz	
Mode of operation	Date	Data Report No.	Worst Mode
1280X1024, HF=64KHz	05/12/99	7915E#(799, 807)	<input type="checkbox"/>
1024X768, HF=68KHz	05/12/99	7915E#(751, 759, 767, 775)	<input checked="" type="checkbox"/>
640X480, HF=31.5KHz	05/12/99	7915E#(783, 791)	<input type="checkbox"/>

Final Conducted Emission Test was conducted by operating the worst mode as indicated above.

Conducted Room	Data Report No. 7915E#(767, 775)			Date 05/12/99		Tested By: ERIC LIN			
Six Highest Conducted Emission Readings									
Frequency Range Investigated			150 kHz TO 30 MHz						
Freq (MHz)	Meter Reading (dBuV)	C.F. (dB)	Corrected Reading (dBuV)	Limits (dBuV)	Margin (dB)	Reading Type (P/Q/A)	Line (L1/L2)		
4.224	45.20	0	45.20	56.00	-10.80	P	L1		
4.598	48.11	0	48.11	56.00	-7.89	P	L1		
4.598	43.48	0	43.48	46.00	-2.52	A	L1		
4.926	47.31	0	47.31	56.00	-8.69	P	L1		
4.926	42.57	0	42.57	46.00	-3.43	A	L1		
4.501	47.51	0	47.51	56.00	-8.49	P	L2		
4.501	43.04	0	43.04	46.00	-2.96	A	L2		
4.598	47.47	0	47.47	56.00	-8.53	P	L2		
4.598	42.49	0	42.49	46.00	-3.51	A	L2		
4.926	46.67	0	46.67	56.00	-9.33	P	L2		
4.926	41.88	0	41.88	46.00	-4.12	A	L2		

C.F. (Correction Factor) = Insertion Loss + Cable Loss

Corrected Reading = Metering Reading + C.F.

Margin=Corrected Reading - Limits

P=Peak Reading

L1=Hot

Q=Quasi-peak

T2=Neutral

Q Quasi mean
A=Average Reading

Comments: N/A

APPENDICES

EXTERNAL I/O CABLE CONSTRUCTION DESCRIPTION

CONFIGURATION BLOCK DIAGRAM

CONDUCTED EMISSION PLOT

RADIATED EMISSION DATA

EUT PHOTOGRAPHS

External I/O Cable Construction Description

CABLE NO: 1	Number of I/O ports of this type: 1
I/O Port: Serial Mouse	Connector Type: DB9
Capture Type: Screw-In	Type of Cable used: Un-Shielded
Cable Connector Type: Molded	Cable Length: 1.9 M
Bundled During Tests: No	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 2	Number of I/O ports of this type: 1
I/O Port: KB	Connector Type: Din-5 Pin
Capture Type: Snap-In	Type of Cable used: Shielded
Cable Connector Type: Molded	Cable Length: 1.2 M
Bundled During Tests: No	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 3	Number of I/O ports of this type: 1
I/O Port: Parallel Printer	Connector Type: DB25
Capture Type: Screw-In	Type of Cable used: Shielded
Cable Connector Type: Metal	Cable Length: 2.3 M
Bundled During Tests: Yes	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 4	Number of I/O ports of this type: 1
I/O Port: VGA	Connector Type: DB15
Capture Type: Screw-In	Type of Cable used: Shielded
Cable Connector Type: Molded	Cable Length: 1.2 M
Bundled During Tests: Yes	Data Traffic Generated: Yes
Remarks: N/A	

CABLE NO: 5~7	Number of I/O ports of this type: 3
I/O Port: Power Cord	Connector Type: AC Inlet
Capture Type: Snap-In	Type of Cable used: Un-Shielded
Cable Connector Type: Molded	Cable Length: 1.8 M
Bundled During Tests: No (Radiation), Yes (Line Conduction)	Data Traffic Generated: No
Remarks: N/A	

Configuration Block Diagram