



30/F. Wharf Cable Tower, 9 Hoi Shing Road, Tsuen Wan, Hong Kong.
Telephone: (852) 2416 4499 Facsimile: (852) 2417 4455, (852) 2417 4747

PRODUCT SPECIFICATIONS

- 1 . OPERATION VOLTAGE : 6 V (AAA SIZE BATTERY X 4)
- 2 . ANTENNA LOADING : 50 ohm
- 3 . DEVIATION : 2 KHZ
- 4 . TRANSMISSION POWER : FCC PART 15 STANDARD
- 5 . 20 dB S/N SENSITIVITY : 0.75 uV
- 6 . SQUELCHED SENSITIVITY : - 4 uV
- 7 . MAX SPEAKER POWER : 300 mW / 8 Ohm
- 8 . MICROPHONE SENSITIVITY : 70 ~ 80 dBspr
- 9 . HELP OSC FREQUENCY : 1 KHZ + 0.5 HZ
- 10 . OPERATION FREQUENCY : (5 CHANNELS)

CHANNEL 1 : 49.830 MHZ

CHANNEL 2 : 49.845 MHZ

CHANNEL 3 : 49.860 MHZ

CHANNEL 4 : 49.875 MHZ

CHANNEL 5 : 49.890 MHZ

BLOCK DIAGRAM

