



MODULAR APPROVAL REQUEST

May 2, 2014

To: Federal Communications Commission
Equipment Authorization Branch - Laboratory Division
Office of Engineering and Technology
7435 Oakland Mills Road
Columbia, Maryland
USA
21046

Subject: Modular Approval Request

Applicant: Murandi Communications Ltd.
106, 4715 – 13 St. NE,
Calgary, Alberta,
Canada
T2E 6M3

Type of Equipment: Transceiver

FCC Identifier: KQNMMLINK900

Dear Sir or Madam:

Please be advised that the manufacturer declares that the above mentioned product satisfies the requirements for single modular transmitters subject to section 15.212 of the FCC ruling:

- I. The radio elements must have the radio frequency circuitry shielded. Physical/discrete and tuning capacitors may be located external to the shield, but must be on the module assembly;
 - a. The radio frequency (RF) circuitry of MLink incorporates a solid ground plane layer, covered by a metal RF shield.
- II. The module must have buffered modulation/data inputs to ensure that the devices will comply with Part 15 requirements with any type of input signal;
 - a. All signals (including data) and voltage supplies entering and leaving the RF shielded portion of MLink incorporate decoupling/filtering circuitry to limit unwanted signals from entering and leaving the shielded area. In addition a microprocessor is used to process data to and from the user device and RF portion of MLink, thus buffering the RF portion of the MLink from the user. Please see the MLink Functional Circuit Description and MLink Block Diagram documents for additional information.
- III. The module must contain power supply regulation on the module;
 - a. The transmit Power Amplifier (PA) used in MLink is powered by a regulator incorporated in MLink. An RF Transceiver IC is implemented in MLink, which also incorporates several internal

low drop out regulators. Please see the MLink Functional Circuit Description and MLink Block Diagram documents for additional information.

- IV. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per Sections 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b);
 - a. The MLink G 900A FW incorporates permanently attached integral antenna and the MLink C 900A FW incorporates an MMCX connector for use with an external antenna. Please see the MLink Antenna Specification and MLink Users Guide documents for additional information.
- V. The module must demonstrate compliance in a stand-alone configuration;
 - a. A test fixture was used for regulatory testing which enabled MLink to operate stand alone.
- VI. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (See KDB Publication 997198 about labeling requirements);
 - a. Permanently affixed FCC ID labels are incorporated in the MLink modules. Please see MLink Labels document.
- VII. The module must comply with all specific rules applicable to the transmitter. The grantee must provide comprehensive instructions to explain compliance requirements;
 - a. Section 8 of the Users Guide (MLink Users Guide document) captures comprehensive instructions for the end users on compliance requirements.
- VIII. The module must comply with RF exposure requirements. For any transmitters intended for use in portable devices, SAR compliance must be demonstrated to be independent of the host device.
 - a. Maximum Permitted Exposure (MPE) compliance is demonstrated in the MLink 900 Maximum Permitted Exposure document. The MLink module is intended for fixed and mobile application where a minimum 20 cm separation from the users is required for SAR compliance.

Please contact the undersigned if you have any questions or need any further information.

Sincerely,



David Goulbourne
Murandi Communications Ltd
106, 4715 - 13 St. N.E.
Calgary, Alberta, Canada T2E 6M3
Phone: (403)-777-9988 x 228
Email: dave.goulbourne@murandi.com