

INTERTEK TESTING SERVICES

Company: Supertoys Industrial Company Ltd.
Model: KTU-4064-RC01-TX

Date of Test: June 29, 2000

Table 1

Radiated Emissions

Polarity	Frequency (M Hz)	Reading (dB μ V)	Antenna Factor (dB)	Pre-Amp Gain (dB)	Net at 3m (dB μ V /m)	Limit at 3m (dB μ V /m)	Margin (dB)
V	49.810	40.5	11	16	35.5	40.0	-4.5
V	49.861	80.1	11	16	75.1	80.0	-4.9
V	49.910	41.8	11	16	36.8	40.0	-3.2
H	99.627	37.6	11	16	32.6	43.5	-10.9
H	149.445	37.1	13	16	34.1	43.5	-9.4
H	199.265	33.6	16	16	33.6	43.5	-9.9
H	*249.105	30.6	20	16	34.6	46.0	-11.4
H	298.926	29.1	22	16	35.1	46.0	-10.9

Notes: 1. Peak Detector Data unless otherwise stated.

2. All measurements were made at 3 meter. Harmonic emissions not detected at the 3 meter distance were measured at 0.3 meter and an inverse proportional extrapolation was performed to compare the signal level to the 3 meter limit. No other harmonic emissions than those reported were detected at a test distance of 0.3 meter.
3. Negative value in the margin column shows emission below limit.
4. Horn antenna and average detector are used for the emission over 1000MHz.

*Emission within the restricted band meets the requirement of part 15.205. The corresponding limit as per 15.209 is based on Quasi peak detector data for frequencies below 1000 MHz and average detector data for frequencies over 1000 MHz.

Test Engineer: Ivan Y. M. Wong