



CMA Testing and Certification Laboratories

廠商會檢定中心

RF EXPOSURE EVALUATION

Report No. : AY00559772(8) Date: Feb 13, 2020

Application No. : LY023332(2)

Applicant : CAPITAL PROSPECT LTD
ROOM 1303, BLOCK B, VERISTRONG IND. CENTRE,
34-36 AU PUI WAN STREET, FOTAN,
SHATIN, N.T., HONGKONG

Sample Description : Two(2) items of submitted sample stated to be

Product Description : Garage Door Controller Mini Nova Hub
Model : 2NV9
Sample registration No. : RY037224-003(0) and RY037224-005(1)
Radio Frequency : 910 – 918MHz and 2412-2462MHz
Supply voltage : DC 7.5V (EUT)
AC 100 – 240V (AC Adapter)
No. of submitted sample : 2

FCC ID : KUT2NV9

Date Received : Oct 2, 2019

Evaluation Period : Oct 3, 2019 – Oct 30, 2019

Evaluation Method : 447498 D01 General RF Exposure Guidance v06 - RF Exposure Procedure and
Equipment Authorization Policies for Mobile and Portable Devices

Conclusion : The maximum simultaneous power of WiFi and 900MHz operation were satisfied
RF exposure requirements.

For and on behalf of
CMA Industrial Development Foundation Limited

Authorized Signature : _____

Mr. WONG Lap-pong, Andrew
Manager

Page 1 of 1

Document name: FCC RF exposure - Document Ref No: RT-EL-EMC-008 - Issue Date: 01 Dec 2017 - Edition: 1

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website www.cmateesting.org.
This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited
Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.
Tel : (852) 2698 8198 Fax : (852) 2695 4177 E-mail : info@cmateesting.org Web Site : <http://www.cmateesting.org>



CMA Testing and Certification Laboratories

廠商會檢定中心

RF EXPOSURE EVALUATION

Report No. : AY00559772(8)

Date: Feb 13, 2020

Simultaneous power

The device can operate the 900MHz and WiFi IEEE 802.11b/g/n transmitter simultaneously. Therefore the simultaneous power shall be evaluated for the RF exposure compliance of FCC rule.

RF Exposure Evaluation

Calculation

1) WiFi transmitter (FCC ID: 2ASEO-HM-WF8266A)

According to the RF exposure report of the FCC application with FCC ID: 2AESO-HM-WF8266A,

- The worst case total power density @ 20cm	: 0.003mW/cm ²
- Limit	: 1.0mW/cm ²
- Result	: PASS

2) 900MHz transmitter

According to the test result from the FCC test report AY0059771(7),

- Measured field strength @ 3m	: 90.8dBμV/m
- Calculated e.i.r.p.	: 0.363mW (-4.4dBm)
- Calculated Power density @ 20cm	: 0.00007mW/cm ²
- Limit	: 0.60667mW/cm ²
- Result	: PASS

3) Simultaneous transmission

According to above calculation,

- Weighted Power Density @ 20cm to limit (WiFi)	: 0.00300
- Weighted Power Density @ 20cm to limit (900MHz transmitter)	: 0.00012
- Total weighted power density @ 20cm	: 0.00312
- Limit	: 1.0
- Result	: PASS

Conclusion

Based on above calculation, the MPEs of two transmitters individually and simultaneously meet the requirement of OET Bulletin 65 and KDB447498 D01 v06.

***** End of Evaluation *****