



Nemko AS

RF Technical Brief Cover Sheet
RF Exposure Compliance
(Annex A & B of RSS-102)

**Annex C – Declaration of RF Exposure Compliance
for Exemption from Routine Evaluation Limits**

ATTESTATION: I attest that the radiocommunication apparatus meets the exemption from the routine evaluation limits in Section 2.5 of this standard; that the Technical Brief was prepared and the information contained therein is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed; and that the device meets the SAR and/or RF field strength limits of RSS-102.

Signature: Frode Sveinsen

Date: 17-Feb-2016

NAME (Please print or type): Frode Sveinsen

TITLE (Please print or type): Chief Engineer, Nemko AS

COMPANY (Please print or type): Phonak Communications AG

MODEL NUMBER (Please print or type): Roger Table Mic Remote Control

IC CERTIFICATION NUMBER (Please print or type): 2262A-TX23RCV1

Operating frequency: 434.050 MHz

Maximum Conducted Output Power: /

Maximum Radiated Output Power: 0.0244 mW (Peak)

Declared Tune Up Tolerance: 2.0 dB

Maximum Duty Cycle: 100 %

Source-based Time-averaged Power incl. Tune Up Tolerance: 0.0389 mW (Radiated)

Values above are from Nemko test report no. 290009-2

RSS-102, clause 2.5.1:

**Routine Evaluation Exemption limit for equipment used at separation distance of 5 mm
at 450 MHz: 130 mW (The EUT is a handheld device, the limit has therefore been multiplied by 2.5)**

Output Power is the highest of conducted or radiated (EIRP) source-based time-averaged power.