



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

Page 1 of 7

**APPLICANT:** (CODE : 017278)

STD MANUFACTURING LTD.

Unit F-J, 5/F, Block 2,

Kwai Tak Ind. Centre,

15-33 Kwai Tak Street,

Kwai Chung, N.T.,

Hong Kong.

**DATE OF SAMPLES RECEIVED:** 1998.06.30.

**DATE OF TESTING:** 1998.07.06. & 1998.07.05.

### DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: PC Propad 6

Manufacturer: STD Manufacturing Ltd.

Model Number: P-228

Brand Name: STD

Origin : China

### INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part B - Unintentional Radiators.  
The results obtained are to compare with the class B digital device limit.

**REMARK :** This product was tested as a system using the Ancillary Equipment listed in Appendix B.

**RESULTS:** Please see attached sheet(s).

### CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirement for the relevant clauses of Federal Communications Commission Rules for Class B digital device.

**TEST EQUIPMENT AUDIT:** Please see Appendix A

*Law Man Kit*  
Testing Engineer

*Fatty Wong*  
Verify by

*Patrick Wong*  
for Managing Director

#### Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication.



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

Page 2 of 7

### TEST SUMMARY

(A) Measurement of Radiated Emission

Result -- Satisfactory

Data -- See the attached data

(B) Measurement of Line-Conducted Voltage Test

Result -- Satisfactory

Data -- See the attached data



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

Page 3 of 7

### (A) Measurement of Radiated Interference

TEST REFERENCE: FCC Rules Part 15 Subpart B Section 15.109(a)

(Class B)

TEST CONDITION : Worst case Monitor Power supplied by computer & separately

TEST DATE : 1998.07.06

Emission Frequency	Meter Reading	Polarization (including antenna factor)	Field Strength (at 3m)	FCC Limit
MHz	dB(µV)		µV/m	µV/m
42.955	27.6	V	24.0	100
*66.644	34.9	V	55.6	100
66.670	32.2	H	40.7	100
75.170	30.7	H	34.3	100
128.850	29.9	H	31.3	150
128.865	35.9	V	62.4	150
186.178	30.0	V	31.6	150
200.499	34.2	H	51.3	150
225.510	36.7	H	68.4	200
225.520	34.0	V	50.1	200

- End -

### SUMMARY

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured.

polarizations at highest reading indicated as:

H -- Horizontal      V -- Vertical

Quasi-peak measurements were performed if the maximised measurements

were less than 6dB below the quasi-peak limit line.

Quasi-peak measurements are denoted by \* in the table above.



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

Page 4 of 7

### NOTES FOR THE RADIATION MEASUREMENT

#### (1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane in compliance with the requirements of ANSI C63.4:1992.

#### (2) Test Equipment

HP 8572A EMI receiver was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100KHz or 1MHz depending on the type of signal. A biconical log-periodic antenna was used for frequency range from 30MHz to 1000MHz.

#### (3) Test Set-Up:

The EUT and support equipment are placed in accordance with ANSI C63.4.

#### (4) Measuring Procedure:

An initial pre-scan measurement was performed in a semi-anechoic chamber using a 25dB gain pre-amplifier. The receive antenna in the chamber was 1.5m above the groundplane and 3m from the sample. The sample was placed 0.8m above the groundplane.

Measurements in both horizontal and vertical polarities were performed. All emissions recorded during the prescan were subsequently remeasured on the open field test site (described in 1 above) using the following procedure: The ambient noise scanning was made before powering on the EUT and support equipment to identify the emissions from the environment. During the test, each emission was maximized by: having the PC PROPAD 6 continuously working by running a special test program (PCB.exe) supplied by the customer, arranging and manipulating interconnecting cables, rotating turntable and varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The frequency range tested is from 30MHz to 1000MHz and the worst-case emissions are shown in Test Results.

Remark : Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC's Equipment Authorization Program. This test itself is not an Approval Test.

#### (5) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-  
30MHz to 200MHz =  $\pm 3.7$ dB, 200MHz to 1000MHz =  $+ 3.0$ dB/-2.7dB.



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

## TEST REPORT

Page 5 of 7

No.: HM1142/504

### (B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)  
(Class B)

TEST CONDITION : Normal

TEST DATE : 1998.07.05

#### (1) Between "Live" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
	MHz		dB(µV)	µV	µV
0.45	-	0.8	31.50	37.58	250.00
0.8	-	1.6	37.00	70.79	250.00
1.6	-	3.0	41.00	112.20	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	0.00	1.00	250.00
9.0	-	11.0	0.00	1.00	250.00
11.0	-	13.0	0.00	1.00	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	0.00	1.00	250.00
19.0	-	21.0	0.00	1.00	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

----- SUMMARY -----  
All data is within limits



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

## TEST REPORT

Page 6 of 7

No.: HM1142/504

### (B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)  
(Class B)

TEST CONDITION : Normal

TEST DATE : 1998.07.05

#### (1) Between "Neutral" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
	MHz		dB(µV)	µV	µV
0.45	-	0.8	30.00	31.62	250.00
0.8	-	1.6	36.00	63.10	250.00
1.6	-	3.0	39.50	94.41	250.00
3.0	-	5.0	0.00	1.00	250.00
5.0	-	7.0	0.00	1.00	250.00
7.0	-	9.0	0.00	1.00	250.00
9.0	-	11.0	0.00	1.00	250.00
11.0	-	13.0	0.00	1.00	250.00
13.0	-	15.0	0.00	1.00	250.00
15.0	-	17.0	0.00	1.00	250.00
17.0	-	19.0	0.00	1.00	250.00
19.0	-	21.0	0.00	1.00	250.00
21.0	-	23.0	0.00	1.00	250.00
23.0	-	25.0	0.00	1.00	250.00
25.0	-	27.0	0.00	1.00	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

----- SUMMARY -----  
All data is within limits



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

Page 7 of 7

### NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

#### (1) Test Facility:

The line conducted facility is located at a shielded enclosure. The 1m x 1.5m wooden table and the Line Impedance stabilization Networks (LISNs) are placed in compliance with the requirement of ANSI C63.4 - 1992.

#### (2) Test Equipment:

The test receiver (R&S ESHS10) was set to CISPR quasi-peak mode. The bandwidth of the receiver was set to 10KHz.

#### (3) Test Set-Up:

The EUT and the support equipment are placed in accordance with ANSI C63.4-1992 (See appendix A). The computer with the add-on EUT is powered from R & S ESH3-Z5 LISN and the support equipment is powered from EMC3 3825-2 LISN. All interconnecting cables more than 1m were shortened by non-inductive bundling to 1m length.

#### (4) Measurement procedure:

An initial peak measurement was performed between Live & Ground. Any peak emissions within 20dB of the limit line were subsequently remeasured using quasi-peak detection. This procedure was followed for measurements between live and ground, neutral and ground, monitor powered through computer and monitor powered separately.

The worse case quasi-peak data for each frequency was then recorded in section B of this report.

The product was exercised as follows :-

Power on the computer and all the support equipment. The PC PROPAD 6 was exercised continuously working by running special program (PCB.exe) supplied by the customer. The frequency range tested is from 450KHz to 30MHz and the worst-case emissions are shown in Test Result.

#### Remark :

Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under the FCC's Equipment Authorization Program. This test itself is not an Approval Test.

#### (6) Measuring Uncertainty:

The calculated uncertainty for conducted power-line measurement is =  $\pm 2.3\text{dB}$ .

\*\* End of document\*\*



# The Hong Kong Standards and Testing Centre Ltd.

## APPENDIX A

Page A1 of A1

Date: 1998-07-08

No.: HM1142/504

### TEST EQUIPMENT AUDIT

#### Pre-scan

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM131	PORTABLE SPECTRUM ANALYSER	H.P	8595EM	3710A00155	27/10/97
EM016	ANTENNA	ARA INC	LPB-2513/A	1047	TBD
EM034	AMPLIFIER	H.P	8447F OPT 1664	2944A04240	TBD
EM082	ANECHOIC CHAMBER	FELIAS & MASSON	N/A	N/A	NA

#### Radiated Emission

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM007	SPECTRUM ANALYZER	H.P	HP85660B	3144A21192	29/05/98
EM008	SPECTRUM ANALYZER DISPLAY	H.P	HP85662A	3144A20514	29/05/98
EM009	QUASI PEAK ADAPTOR	H.P	HP85650A	3303A01702	29/05/98
EM010	RF PRESELECTOR	H.P	HP85685A	3221A01410	29/05/98
EM011	ATTENUATOR/SWITCH	H.P	HP11713A	2508A10595	29/05/98
EM012	PRE-AMPLIFIER	H.P	HP8449B	3008A00262	29/05/98
EM013	CONTROLLER (COMPUTER), COLOR MONITOR, KEYBOARD & MOUSE FLOPPY DRIVE	H.P H.P H.P	HP9000 HPA1097C HP9133L	6226A60314 3151J39517 2623A02468	CM
EM017	ANTENNA	ARA INC	LPB-2513/A	1069	31/12/97
EM072	SIGNAL GENERATOR	HP	8640B	1948A11892	30/03/98
EM083	HKSTC OPEN AREA TEST SITE	HKSTC	N/A	N/A	16/02/98

#### Line Conducted

EQP NO.	DESCRIPTION	MANUFACTURER	MODEL NO.	SERIAL NO.	LAST CAL
EM003	SIGNAL GENERATOR	R & S	SMS	871603/529	TBD
EM117	IMPULSE LIMITER	R & S	ESH3Z2	0357.8810.52	05/02/98
EM119	LISN	R & S	ESH3-Z5	0831.5518.52	TBD
EM120	EMI TEST RECEIVER	R & S	ESHS10	1004.0401.10	TBD
EM081	SMALL SCREENED ROOM	MIKO INST. HK	N/A	N/A	23/08/97

#### ABBREVIATIONS:

CM = Corrective Maintenance

N/A = Not Applicable

TBD = To be determine



# The Hong Kong Standards and Testing Centre Ltd.

Date: 1998-07-08

No.: HM1142/504

## TEST REPORT

### APPENDIX B

Page B1 of B3

#### ANCILLARY EQUIPMENT

ITEM NO.	DESCRIPTION	MODEL NO.	FCC ID	REMARK
1	AST COMPUTER	AST PREMIUM II 486/33	DJKASTPII486-33	1.92m SVT SHIELDED CABLE
2	SVGA MONITOR	CM6P	GDRCM6P	RESOLUTION: 720*400 (DURING TESTING) 1.0M UNSHIELDED POWER CORD CONNECTED TO THE COMPUTER 1.8M SHIELDED CABLE CONNECTED TO THE COMPUTER
3	AST KEYBOARD	KB-101	AQ6MEMB-74004	1.8 SHIELDED COILED CABLE CONNECTED TO THE COMPUTER
4	MOUSE	PS12	FSUGMZC8	2.4M UNSHIELDED CABLE CONNECTED TO THE COMPUTER
5	SERIAL PROGRAM PAD (EUT)	SV-284	KYISV-284	2.6M SHIELDED CABLE CONNECTED TO COMPUTER KEYBOARD SOCKET 2.3M SHIELDED CABLE CONNECED TO SOUND CARD SOCKET OF THE COMPUTER
6	PARALLEL PRINTER	DMP3000	DE2850CDMP3000	1.8M UNDHIELDED POWER CORD 2.8M SHIELDED CABLE (BUNDLED TO 1M) CONNTCTED TO THE COMPUTER
7	SERIAL PRINTER	N/A	N/A	SAME AS PARALLELD PRINTER