

Date:1999-04-30

No.: HM100686

TEST REPORT

Page 1 of 7

APPLICANT: (CODE:STM001)

STD MANUFACTURING LTD.

Unit F-J, 5/F., Block 2, Kwai Tak Ind. Centre, 15-33 Kwai Tak Street, Kwai Chung, N.T., Hong Kong.

DATE OF SAMPLES RECEIVED: 1999-04-19

DATE OF TESTING: 1999-04-24 to 1999-04-30

DESCRIPTION OF SAMPLE(S):

A sample of product said to be:

Product: Raider Pro Digital
Manufacturer: STD MANUFACT LTD.
Model Number: SV-251
Brand Name: STD
Origin : CHINA

INVESTIGATIONS REQUESTED:

Measurement to the relevant clauses of F.C.C. Rules and Regulations Part B - Unintentional Radiators.
The results obtained are to compare with the class B digital device limit.

REMARK : This product was tested as a system using the Ancillary Equipment listed in Appendix B.

RESULTS: Please see attached sheet(s).

CONCLUSION:

From the measurement data obtained, the tested sample was considered to have COMPLIED with the requirement for the relevant clauses of Federal Communications Commission Rules for Class B digital device.

TEST EQUIPMENT AUDIT: Please see Appendix A.

LAW MAN KIT
Testing Engineer

KITTY CHOY
Verify by

PATRICK WONG
Patrick Wong
for Managing Director

Conditions in issuance of Test Report

1. This Report is issued in confidence to the client and it will be strictly treated as such by the Hong Kong Standards and Testing Centre Ltd. It may not be reproduced either in its entirety or in part and it may not be used for advertising. The client to whom the Report is issued may, however, show or send it, or a certified copy thereof prepared by the Hong Kong Standards and Testing Centre Ltd. to his customer, supplier or other persons directly concerned. The Hong Kong Standards and Testing Centre Ltd. will not, without the consent of the client, enter into any discussion or correspondence with any third party concerning the contents of the Report. 2. The report refers only to the sample tested and does not apply to the bulk, unless the sampling has been carried out by the Hong Kong Standards and Testing Centre Ltd. and is stated as such in the Report. 3. In the event of the improper use of the report, the Hong Kong Standards and Testing Centre Ltd. reserves the rights to withdraw it, and to adopt any other remedies which may be appropriate. 4. Samples submitted for testing are accepted on the understanding that the Report issued cannot form the basis of, or be the instrument for, any legal action against the Hong Kong Standards and Testing Centre Ltd. 5. The Hong Kong Standards and Testing Centre Ltd. will not be liable for or accept responsibility for any loss or damage howsoever arising from the use of information contained in any of its Reports or in any communication.

Date:1999-04-30
No.: HM100686

TEST REPORT

Page 2 of 7

TEST SUMMARY

(A) Measurement of Radiated Emission

Result -- Satisfactory
Data -- See the attached data and graph sheet

(B) Measurement of Line-Conducted Voltage Test

Result -- Satisfactory
Data -- See the attached data and graph sheet

TEST REPORT

(A) Measurement of Radiated Interference

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.109(a)

(Class B)

TEST CONDITION : Normal

TEST DATE : 1999-04-27

Emission Frequency	Meter Reading (including antenna factor)	Polarization	Field Strength (at 3m)	FCC Limit
MHz	dB(µV)		µV/m	µV/m
63.983	31.5	H	37.6	100.00
71.993	29.8	H	30.9	100.00
143.975	30.1	H	32.0	150.00
192.021	32.4	H	41.7	150.00
287.997	33.9	V	49.5	200.00
320.009	37.2	V	72.4	200.00
336.014	34.2	V	51.3	200.00
*432.074	39.2	V	91.2	200.00
*432.100	42.6	H	134.9	200.00

- End -

SUMMARY

All data is within limits

Broad-band Antennas were used and both polarizations of emissions were measured.
polarizations at highest reading indicated as:

H -- Horizontal V -- Vertical

Quasi-peak measurements were performed if the maximised measurements

were less than 6dB below the quasi-peak limit line.

Quasi-peak measurements are denoted by * in the table above.

TEST REPORT

NOTES FOR THE RADIATION MEASUREMENT

(1) Test site facility:

Open field test site located at Taipo (Hong Kong) with a metal ground plane in compliance with the requirements of ANSI C63.4:1992.

(2) Test Equipment

HP 8572A EMI receiver was set to CISPR quasi-peak mode and the bandwidth of the receiver was set to 100KHz or 1MHz depending on the type of signal. A biconical log-Periodic antenna was used for frequency range from 30MHz to 1000MHz.

(3) Test Set-Up:

The EUT and support equipment are placed in accordance with ANSI C63.4.

(4) Measuring Procedure:

An initial pre-scan measurement was performed in a semi-anechoic chamber using a 25dB gain pre-amplifier. The receive antenna in the chamber was 1.5m above the groundplane and 3m from the sample. The sample was placed 0.8m above the groundplane. Measurements in both horizontal and vertical polarities were performed. All emissions recorded during the prescan were subsequently remeasured on the open field test site (described in 1 above) using the following procedure: The ambient noise scanning was made before powering on the EUT and support equipment to identify the emissions from the environment. During the test, each emission was maximized by: having the Handheld Terminal continuously working by running a special test program (PCB.exe) supplied by the customer, arranging and manipulating interconnecting cables, rotating turntable and varying antenna height from 1m to 4m in both horizontal and vertical polarizations. The frequency range tested is from 30MHz to 1000MHz and the worst-case emissions are shown in Test Results.

(5) Measuring Uncertainty:

The calculated uncertainty for measurement performed at 3M test distance are:-
30MHz to 300MHz = ± 3.7 dB, 300MHz to 1000MHz = +3.0dB/-2.7dB.

Remark : Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC Equipment Authorization Program. This test itself is not an Approval Test.

Date:1999-04-30
No.: HM100686

TEST REPORT

Page 5 of 7

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)

TEST CONDITION : Normal

TEST DATE : 1999-04-30

(1) Between "Live" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
	MHz		dB(µV)	µV	µV
0.45	-	0.8	32.13	40.41	250.00
0.8	-	1.6	18.39	8.31	250.00
1.6	-	3.0	< 22.01	12.60	250.00
3.0	-	5.0	17.60	7.59	250.00
5.0	-	7.0	< 0.00	1.00	250.00
7.0	-	9.0	< 14.47	5.29	250.00
9.0	-	11.0	< 0.00	1.00	250.00
11.0	-	13.0	21.46	11.83	250.00
13.0	-	15.0	< 21.80	12.30	250.00
15.0	-	17.0	41.05	112.85	250.00
17.0	-	19.0	< 0.00	1.00	250.00
19.0	-	21.0	< 26.67	21.55	250.00
21.0	-	23.0	< 0.00	1.00	250.00
23.0	-	25.0	< 36.24	64.86	250.00
25.0	-	27.0	26.22	20.46	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

----- SUMMARY -----

All data is within limits

Date:1999-04-30

No.: HM100686

TEST REPORT

Page 6 of 7

(B) Measurement of Line-Conducted Voltage onto AC Power Line

TEST REFERENCE : FCC Rules Part 15 Subpart B Section 15.107(a)
(Class B)

TEST CONDITION : Normal

TEST DATE : 1999-04-30

(1) Between "Neutral" and "Ground"

Frequency Range of Emission			Maximum Measured Radio Noise		FCC Limit (Class B)
	MHz		dB(µV)	µV	µV
0.45	-	0.8	32.28	41.11	250.00
0.8	-	1.6	28.43	26.40	250.00
1.6	-	3.0	22.01	12.60	250.00
3.0	-	5.0	18.56	8.47	250.00
5.0	-	7.0	< 0.00	1.00	250.00
7.0	-	9.0	14.47	5.29	250.00
9.0	-	11.0	< 0.00	1.00	250.00
11.0	-	13.0	< 21.46	11.83	250.00
13.0	-	15.0	21.80	12.30	250.00
15.0	-	17.0	< 41.05	112.85	250.00
17.0	-	19.0	< 0.00	1.00	250.00
19.0	-	21.0	26.67	21.55	250.00
21.0	-	23.0	< 0.00	1.00	250.00
23.0	-	25.0	36.24	64.86	250.00
25.0	-	27.0	< 26.22	20.46	250.00
27.0	-	30.0	0.00	1.00	250.00

- End -

SUMMARY

All data is within limits

TEST REPORT

NOTES FOR THE CONDUCTED POWER-LINE MEASUREMENT

- (1) **LISN (Line Impedance Stabilization Network) used :**
50 μ H LISN in accordance with Section of ANSI C63.4:1992.
- (2) **Measurement Instrumentations:**
CISPR quasi-peak type radio noise meter (9 KHz - 30 MHz), 6dB bandwidth set at 9 KHz for measurement between 150 KHz & 30MHz.
- (3) **Frequency range scanned :**
The frequency range form 450 KHz to 30 MHz had been searched. Reading of the highest emissions relating to the limit were reported as above.
- (4) **Configuration of EUT**
Connection of equipment and operation conditions were same as those in the Radiation measurement.
- (5) **Measurement procedure :**
In accordance with the relevant sections of ANSI C63.4:1992 "FCC Methods of measurement of Radio Noise Emissions from Computing Devices".
- (6) **Measuring Uncertainty:**
The calculated uncertainty for conducted power-line measurement is = ± 2.3 dB.

Remark : Purpose of this test is to provide the Applicant with the necessary test data of their device for the submission to FCC with application for Equipment Authorization under FCC Equipment Authorization Program. This test itself is not an Approval Test.

** End of document **