



EXHIBIT B

Test Report

Report No.	C0915379
Specifications	FCC Part 15.109(g), Class B
Test Method	ANSI C63.4 1992
Applicant address	16F, No. 75 Hsin Tai Wu RD., Sec. 1 Bldg #A Hsi-Chih, Taipei Hsien, Taiwan
Applicant Items tested	CIS TECHNOLOGY INC. 10/100Mbps PCI Ethernet Card
Model No.	WS-R420/S (Sample # C09379)
Results	Compliance (As detailed within this report)
Sample received data	06/02/1999 (month / day / year)
Prepared by	 project engineer
Authorized by	 Vice General Manager
Issue date	 (Jacob Lin) (month / day / year)
Modifications	None
Tested by	Training Research Co., Ltd.
Office and	No. 15, Lane 530, Pa-Lian RD., Sec. 1, Hsichih Town,
Open site at	Taipei Hsien, Taiwan, R.O.C.

Conditions of issue:

- (1) **This test report shall not be reproduced except in full, without written approval of TRC. And the test result contained within this report only relate to the sample submitted for testing.**
- (2) **This report must not be used by the client to claim product endorsement by NVLAP or any agency of U.S. Government.**

★ **FCC ID: L40R420S**

Contents

Chapter 1 Introduction

Description of EUT	3
Configuration of Test Setup	4
List of Support Equipment	5

Chapter 2 Conducted Emission Test

Test Condition and Setup	7
Conducted Test Placement	8

Chapter 3 Radiated Emission Test

Test Condition and Setup	9
Radiated Test Placement	10

Appendix A:

Conducted test result	11
-----------------------------	----

Appendix B:

Radiated test result	13
----------------------------	----

Chapter 1 Introduction

Description of EUT:

The Lan Card is a data transmission / receiver facility. It is designed to install in the PC or compatible computer and makes your data equipment available to transmit / receive data via the EUT. During testing the EUT was operated at Tx or Rx mode for each emission measured. This was done in order to insure that maximum emission levels were attained.

Connections of EUT:

- (1)Put the EUT into a personal computer' PCI bus and screw it.
- (2)The RJ45 jack of EUT was connected with another Lan card installed in another PC located remotely.

Test method:


Pretest was found that the emission of operating mode is worse than standby mode. So, The final test is made at the operating mode.

During testing, the following modes were tested: 10Mbps and 100Mbps.

During testing, the EUT was operated at "transmitting" and "receiving" mode simultaneously.

The test placement as the photographs showed is the worst case emission placed. (If the emission is close to the ambient, the resolution BW and view resolution will be reduced and the data will be recorded by detection of maximum hold peak mode.)

The testing configuration of test setup is showing in the next page.

Configuration of test setup***Connections:******PC:***

- *Serial A port --- a external modem
- *Serial B port --- a 76 cm shielded RS232 cable
- *Printer port --- a Printer
- *Keyboard port --- a Keyboard
- *Mouse port --- a Mouse
- *Monitor port --- a monitor
- *USB ports --- two USB joysticks

(Each port on PC is connected with suitable device)

EUT:

- *RJ45 Jack --- via a 20m long, non-shielded, no ferrite core, RJ45 cable to another Lan card installed in another PC located remotely.

*List of support equipment***Conducted (Radiated) test:**

PC : **HP**
Model : VE6/350 SERIES 8
Serial No. : SG91002329
FCC ID : DoC Approval
Power type : AC 100~127 / 200~240 VAC, Switching
Power cord : non-Shielded, 1.7m long, Plastic, no ferrite core

Monitor : **HP**
Model No. : D2821
Serial No. : TW 73512262 (TW 73147163)
FCC ID : A3KMO64
Power type : AC 110~120 / 220~240 VAC, Switching
Power cord : Non-Shielded, 3m long, no ferrite core
Data cable : Shielded, 1.8m long, with ferrite core

Keyboard : **Digital**
Model No. : KB-5923
Serial No. : 9S74904837 (9S74904665)
FCC ID : E8HKB-5923
Power type : By PC
Data cable : Shielded, 1.8m long, with ferrite core

Printer : **HP**
Model No. : C2642A
Serial No. : SG69A196GV
FCC ID : B94C2642X
Power type : 220 VAC, 50Hz
Power cord : Non-shielded, 2m long, no ferrite core
Data cable : Shielded, 1.84m long, no ferrite core (1.7m)

Modem : **ACEEX**
Model No. : **XDM-9624**
FCC ID : **IFAXDM-9624**
Power type : **220VAC, 50Hz / 9VAC, 1A**
Power cord : **Non-shielded, 1.9m long, no ferrite cord**
Data cable : **RS232, Shielded, 1.2m long, no ferrite core**
 : **RJ11C x 2, 7' long non-shielded, no ferrite core**

Mouse : **Hewlett Packard Mouse**
Model No. : **C3751B**
Serial No. : **LCA52707170**
FCC ID : **DZL210582**
Power type : **Powered by PC**
Power Cable : **Non - Shielded. 5.5' long, Plastic hoods, No ferrite bead**

Joystick : **Padix**
Model : **QF-606U, QF-707U (DoC Approval)**
Power Type : **By PC**

Chapter 2 Conducted emission test

Test condition and setup:

All the equipment is placed and setup according to the CISPR 22.

The EUT is assembled on a wooden table that is 80 cm high, is placed 40 cm from the back-wall that is a vertical conducting plane. One LISN is for EUT, the other LISN is for support equipment. They are all placed on the conductive ground. The EUT's LISN connect a line switch box for selecting L1 or L2, then connect to a preamplifier and spectrum.

The spectrum scans from 150KHz to 30MHz. Conducted emission levels are detected at max. peak mode. But if the max. peak mode failed, it will be measured by CISPR's quasi-peak detection mode.

While testing, there is the worst-emission plot printed at peak detection mode, and there are more than 6 highest emissions relative to limit recorded. The plot is kept as the original data, not included in test report.

List of test Instrument:

<u>Instrument Name</u>	<u>Model No.</u>	<u>Brand</u>	<u>Serial No.</u>	<u>Calibration Date</u>	<u>Last time</u>	<u>Next time</u>
Spectrum analyzer	8594EM	H P	3710A00279	01/07/99	01/07/00	
LISN (EUT)	3825/2	EMCO	9411-2284	05/20/99	05/20/00	
LISN (Support E.)	AC3-001	TRC	-----	05/20/99	05/20/00	
Preamplifier	AC3-002	TRC	-----	05/20/99	05/20/00	
Line switch box	AC3-003	TRC	-----	05/20/99	05/20/00	

The level of confidence of 95%, the uncertainty of measurement of conducted emission is ± 2.4 dB.

Test Result: Pass (Appendix A)

Chapter 3 Radiated emission test

Test condition and setup:

Pretest: Prior to the final test (OATS test), the EUT is placed in a anechoic chamber and scan from 30MHz to 1GHz. This is done to ensure the radiation exactly emits form the EUT.

Final test: Final radiation measurements are made on a **10 - meter, open-field** test site. The EUT is placed on a nonconductive table that is 0.8m height, the top surface is 1.0 x 1.5 meter. The placement is according to CISPR 22.

The spectrum is examined from 30 MHz to 1000 MHz measured by HP spectrum.

The EMCO whole range Antenna is used to measure frequency from 30 MHz to 1GHz. The final test is used the spectrum HP 8594EM.

Measure more than six top marked frequencies generated form pretest by computer step by step at each frequency. The EUT is rotated 360 degrees, and antenna is raised and lowered from 1 to 4 meters to find the maximum emission levels. The antenna is used with both horizontal and vertical polarization.

Appropriated preamplifier which is made by TRC is used for improving sensitivity and precautions is taken to avoid overloading. The spectrum analyzer's 6dB bandwidth is set to 120 KHz, and the EUT is measured at quasi-peak mode.

If the emission is close to the frequency band of ambient, the data will be rechecked by the tester and the corrected data will be written in the test data sheet. If the emission is just within the ambient, the data from anechoic chamber will be taken as the final data.

List of test Instrument:

Calibration Date

Instrument Name	Model No.	Brand	Serial No.	Last	Next
Spectrum analyzer	8594EM	H P	3619A00198	11/17/98	11/17/99
RF Pre-selector	AC4-001	TRC	-----	05/20/99	05/20/00
Antenna (30M-2G Hz)	3141	EMCO	9711-1076	12/17/98	12/17/99
Open test side (Antenna, Amplify, cable calibrated together)				05/20/99	05/20/00

The level of confidence of 95%, the uncertainty of measurement of radiated emission is ± 4.96 dB.

Test Result: Pass (Appendix B)

Appendix A

Conducted Emission Test Result: (Test Mode: 10 MHz)

Testing room: Temperature : 22 ° C Humidity : 53 % RH

Line 1

FREQUENCY (KHz)	READING AMPLITUDE			LIMIT		MARGIN (dB)
	Peak (dB μ V/m)	Quasi-peak (dB μ V/m)	Average (dB μ V/m)	Quasi-Peak (dB μ V/m)	Average (dB μ V/m)	
225	41.35	*** **	*** **	63.86	53.86	-12.51
338	34.91	*** **	*** **	60.63	50.63	-15.72
4270	31.90	*** **	*** **	56.00	46.00	-14.10
4380	32.56	*** **	*** **	56.00	46.00	-13.44
4510	33.79	*** **	*** **	56.00	46.00	-12.21
4640	34.62	*** **	*** **	56.00	46.00	-11.38
5610	34.97	*** **	*** **	60.00	50.00	-15.03
6220	48.80	*** **	*** **	60.00	50.00	-1.20
8750	43.91	*** **	*** **	60.00	50.00	-6.09
10020	43.03	*** **	*** **	60.00	50.00	-6.97

Line 2

FREQUENCY (KHz)	READING AMPLITUDE			LIMIT		MARGIN (dB)
	Peak (dB μ V/m)	Quasi-peak (dB μ V/m)	Average (dB μ V/m)	Quasi-Peak (dB μ V/m)	Average (dB μ V/m)	
564	30.72	*** **	*** **	56.00	46.00	-15.28
680	30.71	*** **	*** **	56.00	46.00	-15.29
3750	39.43	*** **	*** **	56.00	46.00	-6.57
4300	32.14	*** **	*** **	56.00	46.00	-13.86
4380	33.25	*** **	*** **	56.00	46.00	-12.75
4580	35.09	*** **	*** **	56.00	46.00	-10.91
4700	33.75	*** **	*** **	56.00	46.00	-12.25
4840	32.40	*** **	*** **	56.00	46.00	-13.60
8750	40.55	*** **	*** **	60.00	50.00	-9.45
9960	37.86	*** **	*** **	60.00	50.00	-12.14

* The reading amplitudes are all under average limit.

Conducted Emission Test Result: (Test Mode: 100 MHz)

Testing room: Temperature : 22 ° C Humidity : 53 % RH

Line 1

FREQUENCY (KHz)	READING AMPLITUDE			LIMIT		MARGIN (dB)
	Peak (dB μ V/m)	Quasi-peak (dB μ V/m)	Average (dB μ V/m)	Quasi-Peak (dB μ V/m)	Average (dB μ V/m)	
226	40.93	*** **	*** **	63.83	53.83	-12.90
4240	32.60	*** **	*** **	56.00	46.00	-13.40
4610	35.27	*** **	*** **	56.00	46.00	-10.73
7930	37.64	*** **	*** **	60.00	50.00	-12.36
9320	37.03	*** **	*** **	60.00	50.00	-12.97
10020	36.82	*** **	*** **	60.00	50.00	-13.18
10740	37.43	*** **	*** **	60.00	50.00	-12.57
11850	37.79	*** **	*** **	60.00	50.00	-12.21
12800	37.22	*** **	*** **	60.00	50.00	-12.78
13360	36.49	*** **	*** **	60.00	50.00	-13.51

Line 2

FREQUENCY (KHz)	READING AMPLITUDE			LIMIT		MARGIN (dB)
	Peak (dB μ V/m)	Quasi-peak (dB μ V/m)	Average (dB μ V/m)	Quasi-Peak (dB μ V/m)	Average (dB μ V/m)	
4540	34.42	*** **	*** **	56.00	46.00	-11.58
4640	34.38	*** **	*** **	56.00	46.00	-11.62
4880	33.04	*** **	*** **	56.00	46.00	-12.96
8690	37.20	*** **	*** **	60.00	50.00	-12.80
9900	37.18	*** **	*** **	60.00	50.00	-12.82
10290	38.76	*** **	*** **	60.00	50.00	-11.24
11850	38.05	*** **	*** **	60.00	50.00	-11.95
12190	37.46	*** **	*** **	60.00	50.00	-12.54
12710	37.11	*** **	*** **	60.00	50.00	-12.89
13450	36.73	*** **	*** **	60.00	50.00	-13.27

* The reading amplitudes are all under average limit.

Appendix B***Radiated Emission Test Result: (Vertical) (Test Mode: 10 MHz)*****Test Conditions:**

Testing room : Temperature : 25 ° C Humidity : 52 % RH
 Testing site : Temperature : 27 ° C Humidity : 68 % RH

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dB μ V	m	degree	dB/m	dB μ V/m	dB μ V/m	dB
36.250	42.31	0.99	240	-23.02	19.29	30.00	-10.71
46.250	40.37	0.99	194	-22.07	18.30	30.00	-11.70
76.250	39.72	2.50	166	-24.01	15.71	30.00	-14.29
83.750	47.85	0.99	60	-25.67	22.18	30.00	-7.82
86.250	47.59	2.50	229	-25.40	22.19	30.00	-7.81
106.250	46.16	0.99	321	-23.66	22.50	30.00	-7.50
111.250	48.45	2.50	339	-23.13	25.32	30.00	-4.68
113.750	44.43	2.50	9	-22.81	21.62	30.00	-8.38

Note:

1. Margin = Amplitude - limit, if margin is minus means under limit.
2. Corrected Amplitude = Reading Amplitude + Correction Factors
3. Correction factor = Antenna factor + (Cable Loss - Amplitude gain)
 (For example: 30MHz correction factor = 15.5 + (-15.26) = 0.24 dB/m)
4. The emissions of the horizontal polarity of two testing modes are all under the limit more than 20dB in OATS.

Radiated Emission Test Result: (Vertical) (Test Mode: 100 MHz)

Frequency	Reading Amplitude	Ant. Height	Table	Correction Factors	Corrected Amplitude	Class B limit	Margin
MHz	dB μ V	m	degree	dB/m	dB μ V/m	dB μ V/m	dB
34.670	45.94	0.98	64	-23.31	22.63	30.00	-7.37
36.140	43.72	0.99	280	-23.04	20.68	30.00	-9.32
37.550	43.95	0.99	136	-22.73	21.22	30.00	-8.78
49.880	43.03	2.51	6	-21.80	21.23	30.00	-8.77
51.800	38.23	4.03	7	-22.52	15.71	30.00	-14.29
74.580	40.88	2.50	131	-23.74	17.14	30.00	-12.86
106.700	50.41	0.99	163	-23.62	26.79	30.00	-3.21
143.250	45.94	2.51	318	-20.82	25.12	30.00	-4.88

Final statement:

This test report, measurements made by TRC are traceable to the NIST.

EXHIBIT C

User Manual