



PCTEST ENGINEERING LABORATORY, INC.

6660-B Dobbin Road, Columbia, MD 21045 USA

Tel. 410.290.6652 / Fax 410.290.6554

<http://www.pctestlab.com>



MEASUREMENT REPORT FCC Part 22 & 24 / IC RSS-129/RSS-133

Applicant Name:

TELES AG, Informationstechnologien
Ernst-Reuter-Platz 8
10587 Berlin
GERMANY

Date of Testing:

February 11, 2011

Test Site/Location:

PCTEST Lab., Columbia, MD, USA

Test Report Serial No.:

0Y1102110262.L4Q

FCC ID:

L4QCDMA32VOIPUS

APPLICANT:

TELES AG, INFORMATIONSTECHNOLOGIEN

Application Type: Certification

FCC Classification: PCS Licensed Transmitter (PCB)

FCC Rule Part(s): §2; §22(H), §24(E)

IC Specification(s): RSS-129 Issue 2; RSS-133 Issue 5

EUT Type: CDMA Gateway

Model(s): CellX CDMA-8 VoIP

Tx Frequency Range: 824.70 - 848.31MHz (Cell. CDMA) / 1851.25 - 1908.75MHz (PCS CDMA)

Max. Conducted Power: 0.0129 W Cell. CDMA (11.1 dBm) / 0.0134 W PCS CDMA (11.28 dBm)

Emission Designator(s): 1M28F9W (CDMA) / 1M29F9W (PCS)

Test Device Serial No.: *identical prototype* [S/N: TAG39011028325925]

This equipment has been shown to be capable of compliance with the applicable technical standards as indicated in the measurement report and was tested in accordance with the measurement procedures specified in §2.947. Test results reported herein relate only to the item(s) tested.

I attest to the accuracy of data. All measurements reported herein were performed by me or were made under my supervision and are correct to the best of my knowledge and belief. I assume full responsibility for the completeness of these measurements and vouch for the qualifications of all persons taking them.

Grant Conditions: Power output listed is conducted for Part 22 and 24.

PCTEST certifies that no party to this application has been subject to a denial of Federal benefits that includes FCC benefits pursuant to Section 5301 of the Anti-Drug Abuse Act of 1988, 21 U.S.C. 862.



Randy Ortanez
President





FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 1 of 38

T A B L E O F C O N T E N T S

FCC PART 22 & 24 MEASUREMENT REPORT		3
1.0	INTRODUCTION	4
1.1	SCOPE.....	4
1.2	TESTING FACILITY.....	4
2.0	PRODUCT INFORMATION.....	5
2.1	EQUIPMENT DESCRIPTION	5
2.2	EMI SUPPRESSION DEVICE(S)/MODIFICATIONS	5
2.3	LABELING REQUIREMENTS.....	5
3.0	DESCRIPTION OF TESTS	6
3.1	MEASUREMENT PROCEDURE.....	6
3.2	OCCUPIED BANDWIDTH	6
3.3	CELLULAR - BASE FREQUENCY BLOCKS	6
3.4	CELLULAR - MOBILE FREQUENCY BLOCKS.....	7
3.5	PCS - BASE FREQUENCY BLOCKS.....	7
3.6	PCS - MOBILE FREQUENCY BLOCKS	7
3.7	SPURIOUS AND HARMONIC EMISSIONS AT ANTENNA TERMINAL	7
3.8	RADIATED POWER AND RADIATED SPURIOUS EMISSIONS	8
3.9	PEAK-AVERAGE RATIO	8
3.10	FREQUENCY STABILITY / TEMPERATURE VARIATION	8
4.0	TEST EQUIPMENT CALIBRATION DATA	9
5.0	SAMPLE CALCULATIONS	10
6.0	TEST RESULTS	11
6.1	SUMMARY	11
6.2	CONDUCTED OUTPUT POWER	12
6.3	EFFECTIVE RADIATED POWER OUTPUT DATA.....	13
6.4	EQUIVALENT ISOTROPIC RADIATED POWER OUTPUT DATA.....	14
6.5	CELLULAR CDMA RADIATED MEASUREMENTS	15
6.6	PCS CDMA RADIATED MEASUREMENTS	18
6.7	CELLULAR CDMA FREQUENCY STABILITY MEASUREMENTS	21
6.8	PCS CDMA FREQUENCY STABILITY MEASUREMENTS	23
6.9	RECEIVER SPURIOUS EMISSIONS.....	25
7.0	PLOT(S) OF EMISSIONS	26
8.0	CONCLUSION	38

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway

MEASUREMENT REPORT



FCC Part 22 & 24

§2.1033 General Information

APPLICANT: TELES AG, Informationstechnologien
APPLICANT ADDRESS: Ernst-Reuter-Platz 8
TEST SITE: 10587 Berlin, GERMANY
TEST SITE ADDRESS: PCTEST ENGINEERING LABORATORY, INC.
FCC RULE PART(S): 6660-B Dobbin Road, Columbia, MD 21045 USA
IC SPECIFICATION(S): §2; §22(H), §24(E)
BASE MODEL: RSS-129 Issue 2; RSS-133 Issue 5
FCC ID: CellX CDMA-8 VoIP
FCC CLASSIFICATION: L4QCDMA32VOIPUS
EMISSION DESIGNATOR(S): PCS Licensed Transmitter (PCB)
MODE: 1M28F9W (CDMA) / 1M29F9W (PCS)
FREQUENCY TOLERANCE: CDMA
Test Device Serial No.: ±0.00025 % (2.5 ppm)
DATE(S) OF TEST: TAG39011028325925 Production Pre-Production Engineering
TEST REPORT S/N: February 11, 2011
TEST REPORT S/N: 0Y1102110262.L4Q

Test Facility / Accreditations

Measurements were performed at PCTEST Engineering Lab. located in Columbia, MD 21045, U.S.A.



- PCTEST facility is an FCC registered (PCTEST Reg. No. 90864) test facility with the site description report on file and has met all the requirements specified in Section 2.948 of the FCC Rules and Industry Canada (2451A-1).
- PCTEST Lab is accredited to ISO 17025 by U.S. National Institute of Standards and Technology (NIST) under the National Voluntary Laboratory Accreditation Program (NVLAP Lab code: 100431-0) in EMC, FCC and Telecommunications.
- PCTEST Lab is accredited to ISO 17025-2005 by the American Association for Laboratory Accreditation (A2LA) in Specific Absorption Rate (SAR) testing, Hearing Aid Compatibility (HAC) testing, CTIA Test Plans, and wireless testing for FCC and Industry Canada Rules.
- PCTEST Lab is a recognized U.S. Conformity Assessment Body (CAB) in EMC and R&TTE (n.b. 0982) under the U.S.-EU Mutual Recognition Agreement (MRA).
- PCTEST TCB is a Telecommunication Certification Body (TCB) accredited to ISO/IEC Guide 65 by the American National Standards Institute (ANSI) in all scopes of FCC Rules and Industry Canada Standards (RSS).
- PCTEST facility is an IC registered (2451A-1) test laboratory with the site description on file at Industry Canada.
- PCTEST is a CTIA Authorized Test Laboratory (CATL) for AMPS, CDMA, and EVDO wireless devices and for Over-the-Air (OTA) Antenna Performance testing for AMPS, CDMA, GSM, GPRS, EGPRS, UMTS (W-CDMA), CDMA 1xEVDO, and CDMA 1xRTT.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 3 of 38

1.0 INTRODUCTION

1.1 Scope

Measurement and determination of electromagnetic emissions (EME) of radio frequency devices including intentional and/or unintentional radiators for compliance with the technical rules and regulations of the Federal Communications Commission and the Industry Canada Certification and Engineering Bureau.

1.2 Testing Facility

The map below shows the location of the PCTEST LABORATORY, its proximity to the FCC Laboratory, the Columbia vicinity, the Baltimore-Washington Intert'l (BWI) airport, the city of Baltimore and the Washington, DC area. (See *Figure 1-1*).

These measurement tests were conducted at the PCTEST Engineering Laboratory, Inc. facility in New Concept Business Park, Guilford Industrial Park, Columbia, Maryland. The site address is 6660-B Dobbin Road, Columbia, MD 21045. The test site is one of the highest points in the Columbia area with an elevation of 390 feet above mean sea level. The site coordinates are 39° 11'15" N latitude and 76° 49'38" W longitude. The facility is 1.5 miles North of the FCC laboratory, and the ambient signal and ambient signal strength are approximately equal to those of the FCC laboratory. There are no FM or TV transmitters within 15 miles of the site. The detailed description of the measurement facility was found to be in compliance with the requirements of § 2.948 according to ANSI C63.4-2003 on January 28, 2009.




Figure 1-1. Map of the Greater Baltimore and Metropolitan Washington, D.C. area

FCC ID: L4QCDMA32VOIPUS	FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 4 of 38

2.0 PRODUCT INFORMATION

2.1 Equipment Description

The Equipment Under Test (EUT) is the **TELES AG CDMA Gateway FCC ID: L4QCDMA32VOIPUS**. The EUT consisted of the following component(s):

Trade Name / Base Model	FCC ID	Description
TELES AG / Model: CellX CDMA-8 VoIP	L4QCDMA32VOIPUS	CDMA Gateway
Telit / Model: CC864-DUAL	RI7CC864-DUAL	CDMA Wireless Module

Table 2-1. EUT Equipment Description

The EUT was tested while plugged into an AC outlet. The EUT is fitted with 8 "CDMA Cards" that are connected via PCM Bus and passive ISA BackPlane. Each of the 8 "CDMA Cards" contain 4 Telit CDMA wireless modules, for a total of 32 Telit CDMA wireless modules. For radiated tests, the EUT was tested while connected to the *Hirschmann Car Communication* Magnetic Mount Antenna (Model: MCA 1890 MH). The gain for this antenna is 5.16 dBi for 850 and 1900 MHz. Please see test setup photos for more information.

2.2 EMI Suppression Device(s)/Modifications

No EMI suppression device(s) were added and no modifications were made during testing.

2.3 Labeling Requirements

Per 2.925

The FCC identifier shall be permanently affixed to the equipment and shall be readily visible to the purchaser at the time of purchase.

Per 15.19; Docket 95-19

In addition to this requirement, a device subject to certification shall be labeled as follows:

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

The label shall be permanently affixed at a conspicuous location on the device; instruction manual or pamphlet supplied to the user and be readily visible to the purchaser at the time of purchase. However, when the device is so small wherein placement of the label with specified statement is not practical, only the trade name and FCC ID must be displayed on the device per Section 15.19(b)(2).

Please see attachment for FCC ID label and label location.

FCC ID: L4QCDMA32VOIPUS		PCTEST [®] Engineering Laboratory, Inc.	FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 5 of 38

3.0 DESCRIPTION OF TESTS

3.1 Measurement Procedure

The radiated spurious measurements were made outdoors at a 3-meter test range (See Figure 3-1). The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This power level was recorded using a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same receive spectrum analyzer reading. This level is recorded with the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic antenna are taken into consideration.


Deviation from Measurement Procedure.....None

3.2 Occupied Bandwidth

§2.1049, RSS-Gen (4.6.1)


The occupied bandwidth, that is the frequency bandwidth such that, below its lower and above its upper frequency limits, the mean powers radiated are each equal to 0.5 percent of the total mean power radiated by a given emission shall be measured. The span of the analyzer shall be set to capture all products of the modulation process, including the emission skirts. The resolution bandwidth shall be set to as close to 1 percent of the selected span as is possible without being below 1 percent. The video bandwidth shall be set to 3 times the resolution bandwidth. Video averaging is not permitted. Where practical, a sampling detector shall be used since a peak or, peak hold, may produce a wider bandwidth than actual. The trace data points are recovered and are directly summed in linear terms. The recovered amplitude data points, beginning at the lowest frequency, are placed in a running sum until 0.5 percent of the total is reached and that frequency recorded. The process is repeated for the highest frequency data points. This frequency is recorded. The span between the two recorded frequencies is the occupied bandwidth.

3.3 Cellular - Base Frequency Blocks




FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 6 of 38


3.4 Cellular - Mobile Frequency Blocks



3.5 PCS - Base Frequency Blocks



3.6 PCS - Mobile Frequency Blocks



3.7 Spurious and Harmonic Emissions at Antenna Terminal

§2.1051, 22.917(a), 24.238(a)(b); RSS-132 (4.5.1), RSS-133 (6.5.1)

The level of the carrier and the various conducted spurious and harmonic frequencies is measured by means of a calibrated spectrum analyzer. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. On any frequency outside a licensee's frequency block, the power of any emission shall be attenuated below the transmitter power (P) by at least 43 + 10 log(P) dB. Compliance with these provisions is based on the use of measurement instrumentation employing a resolution bandwidth of 1 MHz or greater. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed. The emission bandwidth is defined as the width of the signal between two points, one below the carrier center frequency and one above the carrier center frequency, outside of which all emission are attenuated at least 26 dB below the transmitter power.

FCC ID: L4QCDMA32VOIPUS	 PCTEST	FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	 TELE	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 7 of 38

3.8 Radiated Power and Radiated Spurious Emissions

§2.1053, 22.913(a)(2), 22.917(a), 24.232(c), 24.238(a), RSS-129 (8.1.1), RSS-133 (6.5.1)

Radiated power and radiated spurious emissions are measured outdoors at our 3-meter test range. The equipment under test is placed on a wooden turntable 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotations were adjusted for the highest reading on the receive spectrum analyzer. This level is then measured with a broadband average power meter. The spectrum is scanned from the lowest frequency generated in the equipment up to a frequency including its 10th harmonic. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator with the level of the signal generator being adjusted to obtain the same receive average power meter reading. This spurious level is recorded with the power meter. For readings above 1 GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration. This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits.

3.9 Peak-Average Ratio

§24.232(d), RSS-133 (6.4)

A peak to average ratio measurement is performed at the conducted port of the EUT. For CDMA signals, the spectrum analyzers Complementary Cumulative Distribution Function (CCDF) measurement profile is used to determine the largest deviation between the average and the peak power of the EUT in a given bandwidth. The CCDF curve shows how much time the peak waveform spends at or above a given average power level. The percent of time the signal spends at or above the level defines the probability for that particular power level.

3.10 Frequency Stability / Temperature Variation

§2.1055, 22.355, 24.235, RSS-129 (9.2.1), RSS-133 (6.3)

The frequency stability of the transmitter is measured by:

- Temperature:** The temperature is varied from -30°C to +50°C in 10°C increments using an environmental chamber.
- Primary Supply Voltage:** The primary supply voltage is varied from 85% to 115% of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Specification – The frequency stability shall be sufficient to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within ±0.00025% (±2.5 ppm) of the center frequency.

Time Period and Procedure:

- The carrier frequency of the transmitter is measured at room temperature (20°C to provide a reference).
- The equipment is turned on in a "standby" condition for one minute before applying power to the transmitter. Measurement of the carrier frequency of the transmitter is made within one minute after applying power to the transmitter.
- Frequency measurements are made at 10°C intervals ranging from -30°C to +50°C. A sufficient stabilization period at each temperature shall be used prior to each frequency requirement.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 8 of 38

4.0 TEST EQUIPMENT CALIBRATION DATA

Test Equipment Calibration is traceable to the National Institute of Standards and Technology (NIST).

Manufacturer	Model	Description	Cal Date	Cal Interval	Cal Due	Serial Number
-	263-10dB	(DC-18GHz) 10 dB Attenuator	N/A		N/A	N/A
-	No. 166	(1000-26500MHz) Microwave RF Cable	N/A		N/A	N/A
-	No. 167	(100kHz - 100MHz) RG58 Coax Cable	N/A		N/A	N/A
Agilent	8449B	(1-26.5GHz) Pre-Amplifier	12/2/2010	Annual	12/2/2011	3008A00985
Agilent	85650A	Quasi-Peak Adapter	3/30/2010	Annual	3/30/2011	2043A00301
Agilent	8648D	(9kHz-4GHz) Signal Generator	10/11/2010	Annual	10/11/2011	3613A00315
Agilent	E4407B	ESA Spectrum Analyzer	3/30/2010	Annual	3/30/2011	US39210313
Agilent	E4448A	PSA (3Hz-50GHz) Spectrum Analyzer	10/11/2010	Annual	10/11/2011	US42510244
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46110872
Agilent	E5515C	Wireless Communications Test Set	10/11/2010	Annual	10/11/2011	GB46310798
Agilent	E5515C	Wireless Communications Test Set	8/12/2010	Annual	8/12/2011	GB41450275
Agilent	E8257D	(250kHz-20GHz) Signal Generator	3/30/2010	Annual	3/30/2011	MY45470194
Agilent	E8267C	Vector Signal Generator	10/11/2010	Annual	10/11/2011	US42340152
Agilent	N9020A	MXA Signal Analyzer	9/8/2010	Annual	9/8/2011	US46470561
Anritsu	ML2495A	Power Meter	10/13/2010	Annual	10/13/2011	941001
Anritsu	MA2411B	Pulse Sensor	11/13/2010	Annual	11/13/2011	1027293
Compliance Design	Roberts	Dipole Set	4/7/2010	Biennial	4/7/2012	146
Compliance Design	Roberts	Dipole Set	4/7/2010	Biennial	4/7/2012	147
Emco	3115	Horn Antenna (1-18GHz)	10/14/2009	Biennial	10/14/2011	9704-5182
Emco	3115	Horn Antenna (1-18GHz)	4/8/2010	Biennial	4/8/2012	9205-3874
Espec	ESX-2CA	Environmental Chamber	4/1/2010	Annual	4/1/2011	17620
Gigatronics	80701A	(0.05-18GHz) Power Sensor	10/11/2010	Annual	10/11/2011	1833460
Gigatronics	8651A	Universal Power Meter	10/11/2010	Annual	10/11/2011	8650319
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	1300/4000
K & L	11SH10	Band Pass Filter	N/A	Annual	N/A	4000/12000
MiniCircuits	VHF-1300+	High Pass Filter	N/A		N/A	30716
MiniCircuits	VHF-3100+	High Pass Filter	N/A		N/A	30721
Paternack	PE2208-6	Bidirectional Coupler	N/A		N/A	N/A
Rohde & Schwarz	CMU200	Base Station Simulator	6/21/2010	Annual	6/21/2011	833855/0010
Rohde & Schwarz	CMU200	Base Station Simulator	6/17/2010	Annual	6/17/2011	836536/0005
Rohde & Schwarz	FSQ 26	Spectrum Analyzer	8/28/2010	Annual	8/28/2011	200452
Rohde & Schwarz	CMW500	LTE Radio Communication Tester	8/30/2010	Annual	8/30/2011	100976
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Rx	7/17/2009	Biennial	7/17/2011	9105-2404
Schwarzbeck	UHA9105	Dipole Antenna (400 - 1GHz) Tx	7/17/2009	Biennial	7/17/2011	9105-2403
Sunol	DRH-118	Horn Antenna (1 - 18GHz)	5/14/2009	Biennial	5/14/2011	A050307
Sunol	JB5	Bi-Log Antenna (30M - 5GHz)	7/17/2009	Biennial	7/17/2011	A051107

Table 4-1. Test Equipment

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 9 of 38

5.0 SAMPLE CALCULATIONS

The calculations below are for sample purposes only. The values do not necessarily relate to the EUT.

Emission Designator

Emission Designator = 1M25F9W

CDMA BW = 1.25 MHz

F = Frequency Modulation

9 = Composite Digital Info

W = Combination (Audio/Data) (Measured at the 99.75% power bandwidth)

Spurious Radiated Emission - PCS Band

Example: Channel 25 PCS Mode 2nd Harmonic (3702.50 MHz)

The spectrum analyzer reading at 3 meters with the EUT on the turntable was -81.0 dBm. The gain of the substituted antenna is 8.1 dBi. The signal generator connected to the substituted antenna terminals is adjusted to produce a reading of -81.0 dBm on the spectrum analyzer. The loss of the cable between the signal generator and the terminals of the substituted antenna is 2.0 dB at 3702.50 MHz. So 6.1 dB is added to the signal generator reading of -30.9 dBm yielding -24.80 dBm. The fundamental EIRP was 25.501 dBm so this harmonic was 25.501 dBm - (-24.80) = 50.3 dBc.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 10 of 38

6.0 TEST RESULTS

6.1 Summary

Company Name: TELES AG, Informationstechnologien
 FCC ID: L4QCDMA32VOIPUS
 FCC Classification: PCS Licensed Transmitter (PCB)
 Mode(s): CDMA

FCC Part Section(s)	RSS Sections	Test Description	Test Limit	Test Condition	Test Result	Reference
TRANSMITTER MODE (TX)						
2.1049, 22.917(a), 24.238(a)	RSS-Gen (4.6.1) RSS-133 (2.3)	Occupied Bandwidth	N/A	CONDUCTED	PASS	Section 7.0
2.1051, 22.917(a), 24.238(a)	RSS-129 (8.1.1) RSS-133 (6.5.1)	Band Edge / Conducted Spurious Emissions	< 43 + 10log ₁₀ (P[Watts]) at Band Edge and for all out-of-band emissions		PASS	Section 7.0
24.232(d)	RSS-133 (6.4)	Peak-Average Ratio	< 13 dB		PASS	Section 7.0
2.1046	RSS-132 (4.4) RSS-133 (4.1)	Transmitter Conducted Output Power	N/A		PASS	Section 6.2
22.913(a)(2)	RSS-129 (9.1)	Effective Radiated Power	< 7 Watts max. ERP	RADIATED	PASS	Section 6.3
24.232(c)	RSS-133 (6.4) [SRSP-510 (5.1.2)]	Equivalent Isotropic Radiated Power	< 2 Watts max. EIRP		PASS	Section 6.4
2.1053, 22.917(a), 24.238(a)	RSS-129 (8.1.1) RSS-133 (6.5.1)	Undesirable Emissions	< 43 + 10log ₁₀ (P[Watts]) for all out-of-band emissions		PASS*	Sections 6.5, 6.6
2.1055, 22.355, 24.235	RSS-129 (9.2.1) RSS-133 (6.3)	Frequency Stability	< 2.5 ppm		PASS	Sections 6.7, 6.8
RECEIVER MODE (RX) / DIGITAL EMISSIONS						
N/A	RSS-129 (10(a,d)) RSS-133 (6.6)	Receiver Spurious Emissions Limits	< RSS-Gen limits [Section 6; Table 1]	RADIATED	PASS	Section 6.9

Table 6-1. Summary of Test Results

***Note:** Radiated testing for undesirable emissions were performed with 1 CDMA module connected to a CDMA call box. Additional testing was performed with 2 CDMA modules simultaneously connected to 2 separate call boxes, with the 2 simultaneously connected CDMA channels adjacent and far from each other. This additional testing was performed on both the Cellular and PCS bands, and resulted in no significant emissions. Please reference KDB Inquiry Track Number 806722.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 11 of 38	

6.2 Conducted Output Power

The EUT was tested in all supported modes and configurations. The conducted output power was measured using an Agilent 8960 CDMA test set with the EUT's power control bits set to "All Up."

		Loopback							
Band	Channel	SO2 [dBm]	SO2 [dBm]	SO2 [dBm]	SO55 [dBm]	SO55 [dBm]	SO9 [dBm]	SO9 [dBm]	
	F-RC	RC1	RC3	RC4	RC1	RC3	RC2	RC5	
Cellular	1013	11.07	11.06	10.89	11.10	10.94	11.07	11.04	
	384	11.01	10.99	10.98	11.01	11.01	11.08	11.00	
	777	10.84	10.79	10.78	10.90	10.76	10.87	10.88	
PCS	25	11.08	10.78	10.77	10.84	10.71	10.80	10.75	
	600	11.28	11.19	10.96	11.04	10.95	10.95	10.92	
	1175	10.56	10.44	10.51	10.43	10.23	10.34	10.31	

Table 6-2. Effective Radiated Power Output Data




Figure 6-1 Conducted Power Setup

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 12 of 38

6.3 Effective Radiated Power Output Data

§22.913(a)(2), RSS-129 (9.1)

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBd]	Pol [H/V]	ERP [dBm]	ERP [Watts]	Battery Type
824.70	CDMA850	-27.400	10.80	0.00	V	10.80	0.012	Standard
836.52	CDMA850	-27.300	10.90	0.00	V	10.90	0.012	Standard
848.31	CDMA850	-28.400	9.80	0.00	V	9.80	0.010	Standard

Table 6-3. Effective Radiated Power Output Data

NOTES:

Effective Radiated Power Output Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the dipole is measured. The ERP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 13 of 38

6.4 Equivalent Isotropic Radiated Power Output Data

§24.232(c), RSS-133 (6.4) [SRSP-510 (5.1.2)]

Frequency [MHz]	Mode	Measured Level [dBm]	Substitute Level [dBm]	Antenna Gain [dBi]	Pol [H/V]	EIRP [dBm]	EIRP [Watts]	Battery Type
1851.25	CDMA1900	-30.800	2.70	8.00	V	10.70	0.012	Standard
1880.00	CDMA1900	-31.800	1.70	8.00	V	9.70	0.009	Standard
1908.75	CDMA1900	-32.500	1.00	8.00	V	9.00	0.008	Standard

Table 6-4. Equivalent Isotropic Radiated Power Output Data

NOTES:

Equivalent Isotropic Radiated Power Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A Horn antenna was substituted in place of the EUT. This Horn antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This level is recorded using the power meter. The conducted power at the terminals of the Horn antenna is measured. The difference between the gain of the horn and an isotropic antenna is taken into consideration and the EIRP is recorded.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 14 of 38

6.5 Cellular CDMA Radiated Measurements

§2.1053, 22.917(a), RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 824.70 MHz
 CHANNEL: 1013
 MEASURED OUTPUT POWER: 10.900 dBm = 0.012 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 23.90 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1649.40	-72.81	6.42	-66.40	V	77.3
2474.10	-75.41	6.42	-69.00	V	79.9
3298.80	-97.86	6.74	-91.11	V	102.0
4123.50	-96.55	7.55	-89.00	V	99.9
4948.20	-93.55	7.57	-85.98	V	96.9

Table 6-5. Radiated Spurious Data (Cellular CDMA Mode – Ch. 1013)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 15 of 38



Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a), RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 836.52 MHz
CHANNEL: 384
MEASURED OUTPUT POWER: 10.900 dBm = 0.012 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 23.90 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1673.04	-74.96	6.43	-68.54	V	79.4
2509.56	-71.85	6.77	-65.09	V	76.0
3346.08	-96.37	7.55	-88.82	V	99.7
4182.60	-93.80	7.81	-85.99	V	96.9
5019.12	-93.85	9.02	-84.83	V	95.7

Table 6-6. Radiated Spurious Data (Cellular CDMA Mode – Ch. 384)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 16 of 38

Cellular CDMA Radiated Measurements (Cont'd)

§2.1053, 22.917(a), RSS-129 (8.1.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 848.31 MHz
 CHANNEL: 777
 MEASURED OUTPUT POWER: 10.900 dBm = 0.012 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 23.90 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBd)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
1696.62	-74.91	6.44	-68.48	V	79.4
2544.93	-71.94	6.83	-65.11	V	76.0
3393.24	-96.20	7.55	-88.65	V	99.6
4241.55	-94.04	8.05	-85.99	V	96.9
5089.86	-93.34	8.92	-84.42	V	95.3

Table 6-7. Radiated Spurious Data (Cellular CDMA Mode – Ch. 777)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 17 of 38

6.6 PCS CDMA Radiated Measurements

§2.1053, 24.238(a), RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1851.25 MHz
 CHANNEL: 25
 MEASURED OUTPUT POWER: 10.700 dBm = 0.012 W
 MODULATION SIGNAL: CDMA (Internal)
 DISTANCE: 3 meters
 LIMIT: $43 + 10 \log_{10} (W) =$ 23.70 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3702.50	-68.22	9.49	-58.73	V	69.4
5553.75	-67.01	10.40	-56.61	V	67.3
7405.00	-89.71	11.08	-78.63	V	89.3
9256.25	-87.74	12.26	-75.48	V	86.2
11107.50	-86.02	13.19	-72.83	V	83.5

Table 6-8. Radiated Spurious Data (PCS CDMA Mode – Ch. 25)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 18 of 38



PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a), RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1880.00 MHz
CHANNEL: 600
MEASURED OUTPUT POWER: 10.700 dBm = 0.012 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 23.70 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3760.00	-68.63	9.43	-59.20	V	69.9
5640.00	-66.99	10.24	-56.75	V	67.4
7520.00	-89.54	11.12	-78.43	V	89.1
9400.00	-87.87	12.32	-75.55	V	86.2
11280.00	-85.23	13.17	-72.06	V	82.8

Table 6-9. Radiated Spurious Data (PCS CDMA Mode – Ch. 600)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 19 of 38



PCS CDMA Radiated Measurements (Cont'd)

§2.1053, 24.238(a), RSS-133 (6.5.1)

Field Strength of SPURIOUS Radiation

OPERATING FREQUENCY: 1908.75 MHz
CHANNEL: 1175
MEASURED OUTPUT POWER: 10.700 dBm = 0.012 W
MODULATION SIGNAL: CDMA (Internal)
DISTANCE: 3 meters
LIMIT: $43 + 10 \log_{10} (W) =$ 23.70 dBc

FREQUENCY (MHz)	LEVEL @ ANTENNA TERMINALS (dBm)	SUBSTITUTE ANTENNA GAIN (dBi)	SPURIOUS EMISSION LEVEL (dBm)	POL (H/V)	(dBc)
3817.50	-66.15	9.37	-56.77	V	67.5
5726.25	-65.68	10.08	-55.60	V	66.3
7635.00	-89.44	11.21	-78.23	V	88.9
9543.75	-87.87	12.38	-75.49	V	86.2
11452.50	-84.45	13.15	-71.29	V	82.0

Table 6-10. Radiated Spurious Data (PCS CDMA Mode – Ch. 1175)

NOTES:

Radiated Spurious Emission Measurements by Substitution Method according to ANSI/TIA/EIA-603-C-2004, Aug. 17, 2004:

The EUT was placed on a wooden turn table 80cm above the ground plane and 3 meters from the receive antenna. The receive antenna height and turntable rotation was adjusted for the highest reading on the receive spectrum analyzer. Final power measurements are made with a broadband average power meter. A half-wave dipole was substituted in place of the EUT. This dipole antenna was driven by a signal generator and the level of the signal generator was adjusted to obtain the same spectrum analyzer reading. This spurious level is recorded using the power meter. For readings above 1GHz, the above procedure is repeated using horn antennas and the difference between the gain of the horn and an isotropic or dipole antenna are taken into consideration.

This device was tested under all R.C.s and S.O.s and the worst case is reported with RC1/SO2 with "All Up" power control bits. This unit was tested while plugged into an AC outlet. The EUT was tested in three orthogonal planes and in all possible test configurations and positioning. The worst case test configuration was found with the antennas sitting up. The data reported in the table above was measured in this test setup.

Note: Test results listed are from 1 CDMA module connected to the call box.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 20 of 38

6.7 Cellular CDMA Frequency Stability Measurements

§2.1055, 22.355, RSS-129 (9.2.1)

OPERATING FREQUENCY: 836,520,000 Hz

CHANNEL: 384

REFERENCE VOLTAGE: 12 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	12.00	+ 20 (Ref)	836,519,989	-11	-0.000001
100 %		- 30	836,520,012	12	0.000001
100 %		- 20	836,519,987	-13	-0.000002
100 %		- 10	836,519,991	-9	-0.000001
100 %		0	836,519,996	-4	-0.000001
100 %		+ 10	836,520,002	2	0.000000
100 %		+ 20	836,520,018	18	0.000002
100 %		+ 30	836,520,012	12	0.000001
100 %		+ 40	836,519,986	-14	-0.000002
100 %		+ 50	836,519,990	-10	-0.000001
115 %		+ 20	836,519,991	-9	-0.000001

Table 6-11. Frequency Stability Data (Cellular CDMA Mode – Ch. 384)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 21 of 38

Cellular CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 22.355, RSS-129 (9.2.1)




Figure 6-2. Frequency Stability Graph (Cellular CDMA Mode – Ch. 384)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 22 of 38



6.8 PCS CDMA Frequency Stability Measurements

§2.1055, 24.235, RSS-133 (6.3)

OPERATING FREQUENCY: 1,880,000,000 Hz

CHANNEL: 600

REFERENCE VOLTAGE: 12 VDC

DEVIATION LIMIT: ± 0.00025 % or 2.5 ppm

VOLTAGE (%)	POWER (VDC)	TEMP (°C)	FREQUENCY (Hz)	Freq. Dev. (Hz)	Deviation (%)
100 %	12.00	+ 20 (Ref)	1,880,000,011	11	0.000001
100 %		- 30	1,879,999,994	-6	0.000000
100 %		- 20	1,880,000,010	10	0.000001
100 %		- 10	1,880,000,011	11	0.000001
100 %		0	1,879,999,994	-6	0.000000
100 %		+ 10	1,880,000,002	2	0.000000
100 %		+ 20	1,880,000,007	7	0.000000
100 %		+ 30	1,879,999,982	-18	-0.000001
100 %		+ 40	1,879,999,996	-4	0.000000
100 %		+ 50	1,879,999,980	-20	-0.000001
115 %		+ 20	1,879,999,995	-5	0.000000

Table 6-12. Frequency Stability Data (PCS CDMA Mode – Ch. 600)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 23 of 38

PCS CDMA Frequency Stability Measurements (Cont'd)

§2.1055, 24.235, RSS-133 (6.3)




Figure 6-3. Frequency Stability Graph (PCS CDMA Mode – Ch. 600)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 24 of 38

6.9 Receiver Spurious Emissions

RSS-129 (10(a,d)), RSS-133 (6.6)

Frequency [MHz]	Level [dBm]	AFCL [dB]	Pol [H/V]	Height [m]	Azimuth [degrees]	Field Strength [dBmV/m]	Limit [dBmV/m]	Margin [dB]
42.00	-78.60	13.24	V	1.2	340	31.14	39.08	-7.94
67.80	-78.20	10.36	V	1.4	230	28.66	39.08	-10.43
82.20	-73.40	10.78	V	1.3	120	33.88	39.08	-5.20
133.20	-73.20	13.00	V	1.3	150	36.30	43.52	-7.23
155.40	-79.20	13.81	V	1.2	140	31.11	43.52	-12.41
200.70	-75.90	13.98	H	1.2	150	34.58	43.52	-8.94

Table 6-13. Radiated Measurements at 3-meters




Figure 6-4. 3-Meter Limits


NOTES:

1. All modes of operation were investigated and the worst-case emissions are reported.
2. The EUT was set to receive mode in the middle channel of operation.
3. Radiated emissions were measured from 30MHz to three times that of the highest tunable frequency or local oscillator.
4. The radiated limits are shown on Figure 6-4. Above 960MHz the limit is 500μV/m.


1. All readings are calibrated by a Signal Generator with accuracy traceable to the National Institute of Standards and Technology (NIST).
2. AFCL = Antenna Factor and Cable Loss
3. Measurements are made using CISPR quasi-peak mode. Average measurements are recorded above 1GHz.

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 25 of 38

7.0 PLOT(S) OF EMISSIONS




Plot 7-1. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-2. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 26 of 38




Plot 7-3. Band Edge Plot (Cellular CDMA Mode – Ch. 1013)




Plot 7-4. 4MHz Span Plot (Cellular CDMA Mode – Ch. 1013)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 27 of 38




Plot 7-5. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-6. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 384)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 28 of 38




Plot 7-7. Occupied Bandwidth Plot (Cellular CDMA Mode – Ch. 384)




Plot 7-8. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 29 of 38




Plot 7-9. Conducted Spurious Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-10. Band Edge Plot (Cellular CDMA Mode – Ch. 777)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 30 of 38




Plot 7-11. 4MHz Span Plot (Cellular CDMA Mode – Ch. 777)




Plot 7-12. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 31 of 38




Plot 7-13. Conducted Spurious Plot (PCS CDMA Mode – Ch. 25)




Plot 7-14. Band Edge Plot (PCS CDMA Mode – Ch. 25)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 32 of 38




Plot 7-15. 4MHz Span Plot (PCS CDMA Mode – Ch. 25)




Plot 7-16. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 33 of 38



Plot 7-17. Conducted Spurious Plot (PCS CDMA Mode – Ch. 600)




Plot 7-18. Occupied Bandwidth Plot (PCS CDMA Mode – Ch. 600)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 34 of 38




Plot 7-19. Peak-Average Ratio Plot (PCS CDMA Mode – Ch. 600)




Plot 7-20. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 35 of 38




Plot 7-21. Conducted Spurious Plot (PCS CDMA Mode – Ch. 1175)



Plot 7-22. Band Edge Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 36 of 38



Plot 7-23. 4MHz Span Plot (PCS CDMA Mode – Ch. 1175)

FCC ID: L4QCDMA32VOIPUS		FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)		Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway		Page 37 of 38



8.0 CONCLUSION

The data collected relate only to the item(s) tested and show that the **TELES AG CDMA Gateway** **FCC ID: L4QCDMA32VOIPUS** complies with all the requirements of Parts 2, 22, and 24 of the FCC rules and RSS-129 and RSS-133 of the Industry Canada rules.

FCC ID: L4QCDMA32VOIPUS		 FCC Pt. 22/24 CDMA MEASUREMENT REPORT (CERTIFICATION)	 Reviewed by: Quality Manager
Test Report S/N: 0Y1102110262.L4Q	Test Dates: February 11, 2011	EUT Type: CDMA Gateway	Page 38 of 38