



RF EXPOSURE REPORT

FCC Per 47 CFR 2.1093(d)

Report Reference No.....: TRE1308006501 R/C:17338

FCC ID.....: L5CR091GT

Compiled by

(position+printed name+signature)...: File administrators Jerome Luo

Supervised by

(position+printed name+signature)...: Test Engineer Yuchao Wang

Approved by

(position+printed name+signature)...: Manager Wenliang Li

Date of issue.....: Aug 27, 2013

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd

Address.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: Ansen Electronics Company

Address.....: Unit 1401B-1405A Telecom Tower, Wharf T&T Square, 123 Hoi Bun Road, Kwun Tong, Kowloon, Hong Kong

Test specification:

Standard: FCC Per 47 CFR 2.1093(d)

TRF Originator.....: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF.....: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Test item description: BONE BLUETOOTH SPEAKER

Trade Mark: /

Manufacturer: Ansen Electronics Company

Model/Type reference.....: R091GT

Listed Models: 06-ROQBONE

Operation Frequency.....: From 2402MHz to 2480MHz

Modulation Type.....: GFSK, π/4 DQPSK, 8DPSK

Rating: DC 5.0V from USB

Result.....: Positive

RF EXPOSURE REPORT

| | | |
|--------------------------|----------------------|---------------|
| Test Report No. : | TRE1308006502 | Aug 27, 2013 |
| | | Date of issue |

Equipment under Test : BONE BLUETOOTH SPEAKER

Model /Type : R091GT

Listed Models : 06-ROQBONE

Applicant : **Ansen Electronics Company**

Address : Unit 1401B-1405A Telecom Tower, Wharf T&T Square, 123 Hoi Bun Road, Kwun Tong, Kowloon, Hong Kong

Manufacturer : **Ansen Electronics Company**

Address : Chen Tung Industrial Zone, Ning Tau Administrative District, Qiao Tau Zhen, Dongguan, Guangdong

The test report merely corresponds to the test sample.

It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

| | | |
|-----------|--|----------|
| 1. | <u>SUMMARY</u> | 4 |
| 1.1. | EUT configuration | 4 |
| 1.2. | NOTE | 错 |
| 误! 未定义书签。 | | |
| 2. | <u>TEST ENVIRONMENT</u> | 5 |
| 2.1. | Address of the test laboratory | 5 |
| 2.2. | Environmental conditions | 5 |
| 2.3. | Statement of the measurement uncertainty | 5 |
| 3. | <u>METHOD OF MEASUREMENT</u> | 5 |
| 3.1. | Applicable Standard | 5 |
| 3.2. | Limit | 6 |
| 3.3. | RF Exposure | 6 |
| 4. | <u>CONCLUSION</u> | 7 |

1. SUMMARY

1.1. EUT configuration

The following peripheral devices and interface cables were connected during the measurement:

● - supplied by the manufacturer

○ - supplied by the lab

| | | | |
|-----------------------|-------------|----------------|---|
| <input type="radio"/> | Power Cable | Length (m) : | / |
| | | Shield : | / |
| | | Detachable : | / |
| <input type="radio"/> | Multimeter | Manufacturer : | / |
| | | Model No. : | / |

1.2. NOTE

1. The EUT is a BONE BLUETOOTH SPEAKER with Bluetooth function, The functions of the EUT listed as below:

| | Test Standards | Reference Report |
|-------------|--------------------------|------------------|
| Bluetooth | FCC Part 15 Subpart C | TRE1308006501 |
| RF Exposure | FCC Per 47 CFR 2.1093(d) | TRE1308006502 |

2. The frequency bands used in this EUT are listed as follows:

| Frequency Band(MHz) | 2400-2483.5 | 5150-5350 | 5470-5725 | 5725-5850 |
|---------------------|-------------|-----------|-----------|-----------|
| EUT | √ | — | — | — |

2. TEST ENVIRONMENT

2.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2009) and CISPR Publication 22.

2.2. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 15-35 ° C

Humidity: 30-60 %

Atmospheric pressure: 950-1050mbar

2.3. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

| Test Items | Measurement Uncertainty | Notes |
|-----------------------------|-------------------------|-------|
| Transmitter power conducted | 0.57 dB | (1) |

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=1.96.

3. Method of measurement

3.1. Applicable Standard

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §RSS-102, Devices that have a radiating element normally operating at separation distances greater than 20 cm between the user and the device shall undergo an RF exposure evaluation. SAR evaluation may be performed in lieu of an RF exposure evaluation for devices operating below 6 GHz with a separation distance of greater than 20 cm between the user and the device.

According to §1.1310,KDB447498 and §2.1093 RF exposure is required.

OET Bulletin 65 Supplement C [June 2001]: Evaluating Compliance with FCC Guidelines for Human Exposure to Radio frequency Electromagnetic Fields

3.2. Limit

According to KDB447498 D01 General RF Exposure Guidance v05r01 Appendix A:SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm, Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation Distances are illustrated in the following Table.

| MHz | 5 | 10 | 15 | 20 | 25 | mm |
|------|----|----|-----|-----|-----|-----------------------------------|
| 150 | 39 | 77 | 116 | 155 | 194 | SAR Test Exclusion Threshold (mW) |
| 300 | 27 | 55 | 82 | 110 | 137 | |
| 450 | 22 | 45 | 67 | 89 | 112 | |
| 835 | 16 | 33 | 49 | 66 | 82 | |
| 900 | 16 | 32 | 47 | 63 | 79 | |
| 1500 | 12 | 24 | 37 | 49 | 61 | |
| 1900 | 11 | 22 | 33 | 44 | 54 | |
| 2450 | 10 | 19 | 29 | 38 | 48 | |
| 3600 | 8 | 16 | 24 | 32 | 40 | |
| 5200 | 7 | 13 | 20 | 26 | 33 | |
| 5400 | 6 | 13 | 19 | 26 | 32 | |
| 5800 | 6 | 12 | 19 | 25 | 31 | |

3.3. RF Exposure

TEST RESULTS

From the peak EUT RF output power and power drift from Tune-up Procedure provide by manufacturer as following states:

Manufacturing tolerance

| GFSK | | | |
|----------------------|------------|------------|------------|
| Test Channel | Channel 00 | Chaanel 39 | Channel 78 |
| Target (dBm) | -3.00 | -3.00 | -3.00 |
| Tolerance \pm (dB) | 1.00 | 1.00 | 1.00 |
| 8DPSK | | | |
| Target (dBm) | -3.00 | -3.00 | -3.00 |
| Tolerance \pm (dB) | 1.00 | 1.00 | 1.00 |
| $\pi/4$ DQPSK | | | |
| Target (dBm) | -3.00 | -3.00 | -3.00 |
| Tolerance \pm (dB) | 1.00 | 1.00 | 1.00 |

For GFSK

| Test Frequency (MHz) | Output Power (dBm) | Output Power including Power Drift (dBm) | Output Power including Power Drift (mW) | SAR Test Exclusion Threshold (mW) | Verdict |
|----------------------|--------------------|--|---|-----------------------------------|---------|
| 2402 | -2.68 | -2.00 | 0.6310 | 10.00 | PASS |
| 2441 | -2.52 | -2.00 | 0.6310 | 10.00 | PASS |
| 2480 | -3.59 | -2.00 | 0.6310 | 10.00 | PASS |

For 8DPSK

| Test Frequency (MHz) | Output Power (dBm) | Output Power including Power Drift (dBm) | Output Power including Power Drift (mW) | SAR Test Exclusion Threshold (mW) | Verdict |
|----------------------|--------------------|--|---|-----------------------------------|---------|
| 2402 | -2.98 | -2.00 | 0.6310 | 10.00 | PASS |
| 2441 | -2.95 | -2.00 | 0.6310 | 10.00 | PASS |
| 2480 | -3.59 | -2.00 | 0.6310 | 10.00 | PASS |

For $\pi/4$ DQPSK

| Test Frequency (MHz) | Output Power (dBm) | Output Power including Power Drift (dBm) | Output Power including Power Drift (mW) | SAR Test Exclusion Threshold (mW) | Verdict |
|----------------------|--------------------|--|---|-----------------------------------|---------|
| 2402 | -2.74 | -2.00 | 0.6310 | 10.00 | PASS |
| 2441 | -2.92 | -2.00 | 0.6310 | 10.00 | PASS |
| 2480 | -3.47 | -2.00 | 0.6310 | 10.00 | PASS |

4. Conclusion

The measurement results comply with the FCC Limit per 47 CFR 2.1093 for the uncontrolled RF Exposure and SAR Exclusion Threshold per KDB 447498 v05r01.

.....**End of Report**.....