



TEST REPORT & FCC Part 15 Subpart C

FCC ID: L5CW044TX-0

Report Reference No.....: WE10030012

Compiled by

(position+printed name+signature)..
File administrators Wenliang Li

Wenliang Li

Supervised by

(position+printed name+signature)..
Test Engineer Cary Li

Cary Li

Approved by

(position+printed name+signature)..
Manager Jimmy Li

J Jimmy Li

Date of issue.....: Mar 25, 2010

Testing Laboratory Name: Shenzhen Huatongwei International Inspection Co., Ltd

Address.....: Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China

Applicant's name.....: Ansen Electronics Co

Address.....: Rm 78,2/F,Sino Industrial Plaza,9 Kai Cheung Rd,Kowloon Bay
Kowloon,Hong Kong

Manufacturer's name: Ansen Electronics Company

Address.....: Chen Tung Industrial Zone,Ning Tau Administrative District,Qiao
Tau Zhen,Dongguan,Guangdong

Test specification:

Standard: FCC Part Subpart 15C 2008 – Intentional Radiators

ANSI C63.4 - 2003

TRF Originator: Shenzhen Huatongwei International Inspection CO., Ltd

Master TRF: Dated 2006-06

Shenzhen Huatongwei International Inspection Co., Ltd. All rights reserved.

This publication may be reproduced in whole or in part for non-commercial purposes as long as the Shenzhen Huatongwei International Inspection Co., Ltd is acknowledged as copyright owner and source of the material. Shenzhen Huatongwei International Inspection Co., Ltd takes no responsibility for and will not assume liability for damages resulting from the reader's interpretation of the reproduced material due to its placement and context.

Equipment Under Test : Digital Thermo Hygro Sensor

Trade Mark: /

Model/Type reference.....: W044-0

Listed Models: /

Result.....: Complied

TEST REPORT

Test Report No. :	WE10030012	Mar 25, 2010
		Date of issue

Equipment under Test : Digital Thermo Hygro Sensor

Model /Type : W044-0

Listed Models : /

Applicant : Ansen Electronics Co

Address : Rm 78,2/F,Sino Industrial Plaza,9 Kai Cheung Rd,Kowloon Bay Kowloon,Hong Kong

Manufacturer : Ansen Electronics Company

Address : Chen Tung Industrial Zone,Ning Tau Administrative District,Qiao Tau Zhen,Dongguan,Guangdong

Test Result	Complied
--------------------	-----------------

The test report merely corresponds to the test sample.
It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Contents

<u>1.</u>	<u>TEST STANDARDS AND RESULT SUMMARY</u>	4
<u>2.</u>	<u>EUT SUMMARY</u>	5
2.1.	General Remarks	5
2.2.	Equipment Under Test Power Supply	5
2.3.	Short description of the Equipment under Test	5
2.4.	EUT operation mode	5
2.5.	Configuration of Tested System	6
2.6.	Related Submittal(s) / Grant (s)	6
2.7.	Modifications	6
<u>3.</u>	<u>TEST ENVIRONMENT</u>	7
3.1.	Address of the test laboratory	7
3.2.	Test Facility	7
3.3.	Environmental conditions	8
3.4.	Configuration of Tested System	8
3.5.	Statement of the measurement uncertainty	9
3.6.	Equipments Used during the Test	9
<u>4.</u>	<u>TEST CONDITIONS AND RESULTS</u>	10
4.1.	Radiated Emission	10
4.2.	Deactivation Time	17
4.3.	20dB Bandwidth	21
4.4.	Antenna Requirement	24
<u>5.</u>	<u>TEST SETUP PHOTOS OF THE EUT</u>	25
<u>6.</u>	<u>EXTERNAL AND INTERNAL PHOTOS OF THE EUT</u>	26

1. TEST STANDARDS AND RESULT SUMMARY

The tests were performed according to following standards:

FCC Rules Part 15 Subpart C (2008) - Intentional Radiators

ANSI C63.4 (2003) – American National Standard for Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9kHz to 40GHz

SUMMARY OF STANDARDS AND RUSELT

No.	Test Item	Test Standards and Procedure	Result
1	Radiated Emission	FCC Subpart 15C § 15.231(e) ANSI C63.4-2003 section 13.1.4	PASS
2	Deactivation Time	FCC Subpart 15C § 15.231(e)	PASS
3	20dB Bandwidth	FCC Subpart 15C § 15.231(c) ANSI C63.4-2003 section 13.1.7	PASS
4	Antenna Requirement	FCC Subpart 15C § 15.203	PASS

NOTE: 1), The detailed test result please see section 4.

2), The test report merely corresponds to the test sample.

3), It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

2. EUT SUMMARY

2.1. General Remarks

Date of receipt of test sample : Mar 19, 2010

Testing commenced on : Mar 22, 2010

Testing concluded on : Mar 25, 2010

2.2. Equipment Under Test Power Supply

Power supply voltage : 120V / 60 Hz 115V / 60Hz
 12 V DC 24 V DC
 Other (specified in blank below)

DC 3V (2x1.5V AAA Battery)

2.3. Short description of the Equipment under Test

Product Name : Digital Thermo Hygro Sensor
 Model Number : W044-0
 Operation Frequency : 433.92MHz
 Modulation Technology : ASK
 Transmitter Type : Periodic Transmitter
 Sample Type : Prototype
 Channel Number : 3 (use the same TX frequency 433.92MHz)
 Channel 1 : Transmit periodic time is 31s
 Channel 2 : Transmit periodic time is 33s
 Channel 3 : Transmit periodic time is 35s


For more details, refer to the user's manual.

2.4. EUT operation mode

The EUT has been tested under typical operating mode.

Test Item	Test Mode	Note
Radiated Emission	Tx mode(433.92MHz)	Y-axis
Deactivation Time	Tx mode(channel1,2,3)	/
20dB Bandwidth	Tx mode(channel1,2,3)	/
Duty cycle	Tx mode(433.92MHz)	/

2.5. Configuration of Tested System



Note: For actual sample please see test setup photos and EUT external photos.

The following peripheral devices and interface cables were connected during the measurement:

- supplied by the manufacturer

- supplied by the lab

Sensor Cable/Probe Length : /

AC Adaptor MODEL : /

 INPUT : /

 OUTPUT : /

Adaptor Cable Length : /

Shield

Unshield

Detachable

Undetachable

2.6. Related Submittal(s) / Grant (s)

This submittal(s) (test report) is intended for FCC ID: **L5CW044TX-0** filing to comply with the FCC Part 15 Subpart C 15.231(e) Rules 2008.

2.7. Modifications

No modifications were implemented to meet testing criteria.

3. TEST ENVIRONMENT

3.1. Address of the test laboratory

Shenzhen Huatongwei International Inspection Co., Ltd
Keji Nan No.12 Road, Hi-tech Park, Shenzhen, China
Phone: 86-755-26715686 Fax: 86-755-26748089

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 (2003) and CISPR Publication 22.

3.2. Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

CNAS-Lab Code: L1225

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed and proved to be in compliance with CNAS-CL01 Accreditation Criteria for Testing and Calibration Laboratories (identical to ISO/IEC 17025: 2005 General Requirements) for the Competence of Testing and Calibration Laboratories, Date of Registration: August 02, 2007. Valid time is until March 29, 2012.

A2LA-Lab Cert. No. 2243.01

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing. Valid time is from Aug 24, 2005 to Sept 30, 2009.

FCC-Registration No.: 662850

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory has been registered and fully described in a report filed with the FCC (Federal Communications Commission). The acceptance letter from the FCC is maintained in our files. Registration 662850, Renewal date September, 2009.

IC-Registration No.: 5377

The 3m Alternate Test Site of Shenzhen Huatongwei International Inspection Co., Ltd has been registered by Certification and Engineering Bureau of Industry Canada for the performance of radiated measurements with Registration No. 5377 on November 28th, 2005.

ACA

Shenzhen Huatongwei International Inspection Co., Ltd, EMC Laboratory can also perform testing for the Australian C-Tick mark as a result of our A2LA accreditation.

NEMKO-Aut. No.: ELA125

Shenzhen Huatongwei International Inspection Co., Ltd has been assessed the quality assurance system, the testing facilities, qualifications and testing practices of the relevant parts of the organization. The quality assurance system of the Laboratory has been validated against ISO/IEC 17025:2005 or equivalent. The laboratory also fulfils the conditions described in Nemko Document NLA-10, the Authorization is valid through April 25, 2009.

VCCI

The 3m Semi-anechoic chamber (12.2m×7.95m×6.7m) and Shielded Room (8m×4m×3m) of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: R-2484. Date of Registration: December 20, 2006. Valid time is until December 19, 2009.

Main Ports Conducted Interference Measurement of Shenzhen Huatongwei International Inspection Co., Ltd has been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: C-2726. Date of Registration: December 20, 2006. Valid time is until December 19, 2009.

DNV

Shenzhen Huatongwei International Inspection Co Ltd has been found to comply with the requirements of DNV towards subcontractor of EMC and safety testing services in conjunction with the EMC and Low voltage Directives and in the voluntary field. The acceptance is based on a formal quality Audit and follow-ups according to relevant parts of ISO/IEC Guide 17025(2005), in accordance with the requirements of the DNV Laboratory Quality Manual towards subcontractors. Valid time is until 09 July, 2010.

3.3. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Temperature: 22 ° C

Humidity: 65 %

Atmospheric pressure: 950-1050mbar

3.4. Configuration of Tested System

Equipment Used in Tested System

No.	Equipment	Manufacturer	Model No.	Serial No.	Note
1	--	--	--	--	--

Note: For actual sample please see test setup photos and EUT external photos.

3.5. Statement of the measurement uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to CISPR 16 - 4 „Specification for radio disturbance and immunity measuring apparatus and methods – Part 4: Uncertainty in EMC Measurements“ and is documented in the Shenzhen Huatongwei International Inspection Co., Ltd quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Hereafter the best measurement capability for Shenzhen Huatongwei laboratory is reported:

Test Item	Frequency Range	Measurement Uncertainty	Notes
Radiated Emission	30~1000MHz	4.24dB	(1)
Radiated Emission	1~18GHz	5.16dB	(1)
20dB Bandwidth	/	0.25dB	(1)
Deactivation Time	/	0.5ms	(1)

(1) This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

3.6. Equipments Used during the Test

Radiated Emissions					
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	ULTRA-BROADBAND ANTENNA	ROHDE & SCHWARZ	HL562	100015	2008/11
2	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESI 26	100009	2008/11
3	RF TEST PANEL	ROHDE & SCHWARZ	TS / RSP	335015/ 0017	2008/11
4	TURNTABLE	ETS	2088	2149	2008/11
5	ANTENNA MAST	ETS	2075	2346	2008/11
6	EMI TEST SOFTWARE	ROHDE & SCHWARZ	ESK1	N/A	2008/11
7	HORN ANTENNA	ROHDE & SCHWARZ	HF906	N/A	2008/06/


20dB Bandwidth & Deactivation Time & Duty Cycle					
No.	Test Equipment	Manufacturer	Model No.	Serial No.	Last Cal.
1	EMI TEST RECEIVER	ROHDE & SCHWARZ	ESCI	100106	2008/11
2	RECEIVER ANTENNA	/	/	/	/

4. TEST CONDITIONS AND RESULTS


4.1. Radiated Emission

TEST CONFIGURATION

Radiated Emission Test Set-Up, Frequency range 30 - 1000MHz



Radiated Emission Test Set-Up, Frequency range 1GHz - 5GHz



TEST PROCEDURE

- 1, The EUT was placed on a turn table which is 0.8m above ground plane.
- 2, The test was beforehand scan carried out with EUT placement X-axis,Y-axis and Z-axis. X-axis was the worst status. So finally test was be carried out under this X-axis.
- 3, Maximum procedure was performed by raising the receiving antenna from 1m to 4m and rotating the turn table from 0°C to 360°C to acquire the highest emissions from EUT.
- 4, And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
- 5, Repeat above procedures until all frequency measurements have been completed.

RADIATION LIMIT

For periodic transmitter, according to § 15.231(e), the field strength of fundamental from device at a distance of 3 meters shall not exceed the following values:

Fundamental frequency (MHz)	Distance (Meters)	Field strength of fundamental (dB μ V/m)	
		AV	Peak
433.92	3	72.87	92.87

Note: For the band 260-470MHz, μ V/m at 3 meters = $16.6667(F) - 2833.333$
Where F is fundamental frequency 433.92MHz

For periodic transmitter, according to § 15.231(e), the field strength radiated emissions from device at a distance of 3 meters shall not exceed the following values:

Fundamental frequency (MHz)	Distance (Meters)	Field strength of spurious emission	
		(microvolts/meter)	(dB μ V/m)
40.66-40.70	3	100	40
70-130	3	50	34
130-174	3	50 to 150	34 to 43.5
174-260	3	150	43.5
260-470	3	150 to 500	43.5 to 54
Above 470	3	500	54

Note: 1, For other bands limit pls refer 15.209
2, The limit below 1GHz based CISPR quasi-peak detector, the limit above 1GHz based average detector and peak limit is 74dB μ V/m.

TEST RESULTS

The emissions from 1GHz to 5GHz are peak measured and comply with average limit, detailed test data please see the following pages.

Field Strength Calculation

The field strength is calculated by adding the Antenna Factor and Cable Factor and subtracting the Amplifier Gain and Duty Cycle Correction Factor(if any) from the measured reading. The basic equation with a sample calculation is as follows:



$$FS = RA + AF + CL - AG$$

Where FS = Field Strength	CL = Cable Attenuation Factor (Cable Loss)
RA = Reading Amplitude	AG = Amplifier Gain
AF = Antenna Factor	

Duty Cycle Correction Factor

Duty Cycle = TX on/100ms X 100% = $30 \times 0.51 \text{ ms}/100\text{ms} \times 100\% = 15.3\%$

Duty Cycle Correction Factor = $20\log(\text{Duty Cycle}) = -16.3$




Time of a pulse = 510 μ s = 0.51ms

30MHz to 1GHz Test Data

EUT: Digital Thermo Hygro Sensor M/N:W044-0
 Manufacturer: Ansen
 Operating Condition: TX mode
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: DC 3V
 Comment: Y-axis
 Start of Test: 3/22/2010 / 8:45:42AM

SWEET TABLE: "test (30M-1G)"

Start Frequency	Stop Frequency	Detector	Meas.	IF Time	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09

***MEASUREMENT RESULT: "HTW0322403_red"***

3/22/2010 9:44AM

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det. QP	Height cm	Azimuth deg	Polarization
30.000000	22.60	-4.7	40.0	17.4	QP	100.0	136.00	VERTICAL
86.372745	12.60	-14.5	40.0	27.4	QP	100.0	26.00	VERTICAL
138.857715	20.60	-15.1	43.5	22.9	QP	100.0	184.00	VERTICAL
292.424850	17.50	-10.9	46.0	28.5	QP	100.0	49.00	VERTICAL
433.920000	63.86	-8.6	92.9	22.8	PEAK	100.0	42.00	VERTICAL
933.907816	30.50	2.6	46.0	15.5	QP	100.0	156.00	VERTICAL


Frequency (MHz)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Duty Cycle Correction Factor	Result (dB)	Margin (dB)	Det.
433.92	63.86	72.87	-16.3	47.56	25.61	AV

Note: Result = Field Strength + Duty Cycle Correction Factor

EUT: Digital Thermo Hygro Sensor M/N:W044-0
 Manufacturer: Ansen
 Operating Condition: TX mode
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: DC 3V
 Comment: Y-axis
 Start of Test: 3/22/2010 / 8:47:16AM

SWEEP TABLE: "test (30M-1G)"

Field Strength					
Start Frequency	Stop Frequency	Detector	Meas.	IF Time	Transducer
30.0 MHz	1.0 GHz	MaxPeak	Coupled	100 kHz	HL562 09



MEASUREMENT RESULT: "HTW0322404_red"

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
30.000000	22.90	-4.7	40.0	17.1	QP	100.0	133.00	HORIZONTAL
86.372745	12.80	-14.5	40.0	27.2	QP	100.0	12.00	HORIZONTAL
123.306613	14.90	-13.2	43.5	28.6	QP	100.0	73.00	HORIZONTAL
288.537074	18.10	-11.1	46.0	27.9	QP	100.0	113.00	HORIZONTAL
433.920000	69.74	-8.6	92.9	23.1	PEAK	100.0	113.00	HORIZONTAL
867.815631	33.40	0.2	46.0	12.6	QP	100.0	113.00	HORIZONTAL

Frequency (MHz)	Field strength (dB μ V/m)	Limit (dB μ V/m)	Duty Cycle Correction Factor	Result (dB)	Margin (dB)	Det.
433.92	69.74	72.87	-16.3	53.44	19.73	AV


Note: Result = Field Strength + Duty Cycle Correction Factor

1GHz to 5GHz Test Data

EUT: Digital Thermo Hygro Sensor M/N:W044-0
 Manufacturer: Ansen
 Operating Condition: TX mode
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: DC 3V
 Comment: Y-axis
 Start of Test: 3/22/2010 / 8:51:17AM

SWEET TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Stop Detector Meas. IF Transducer
 Frequency Frequency Time Bandw.
 1.0 GHz 18.0 GHz MaxPeak Coupled 1 MHz HF906 (2009)
 Average

***MEASUREMENT RESULT: "HTW0322405_red"***

3/22/2010 8:53AM	Frequency	Level	Transd	Limit	Margin	Det.	Height	Azimuth	Polarization
	MHz	dB μ V/m	dB	dB μ V/m	dB		cm	deg	
	1240.480962	33.90	-8.2	74.0	40.1	Peak	100.0	144.00	HORIZONTAL
	1665.330661	35.10	-6.9	74.0	38.9	Peak	100.0	70.00	HORIZONTAL
	2202.404810	38.50	-4.4	74.0	35.5	Peak	100.0	269.00	HORIZONTAL
	2402.805611	38.90	-3.4	74.0	35.1	Peak	100.0	186.00	HORIZONTAL
	3797.595190	41.70	0.9	74.0	32.3	Peak	100.0	144.00	HORIZONTAL
	4911.823647	44.50	3.6	74.0	29.5	Peak	100.0	222.00	HORIZONTAL


MEASUREMENT RESULT: "HTW0322405_red2"

3/22/2010 8:53AM	Frequency	Level	Transd	Limit	Margin	Det.	Height	Azimuth	Polarization
	MHz	dB μ V/m	dB	dB μ V/m	dB		cm	deg	
	1200.400802	24.40	-8.3	54.0	29.6	AV	100.0	80.00	HORIZONTAL
	1697.394790	25.60	-6.6	54.0	28.4	AV	100.0	279.00	HORIZONTAL
	2058.116232	28.00	-4.5	54.0	26.0	AV	100.0	336.00	HORIZONTAL
	2907.815631	29.50	-2.4	54.0	24.5	AV	100.0	326.00	HORIZONTAL
	3757.515030	32.50	0.8	54.0	21.5	AV	100.0	165.00	HORIZONTAL
	4935.871743	34.50	3.8	54.0	19.5	AV	100.0	70.00	HORIZONTAL

EUT: Digital Thermo Hygro Sensor M/N:W044-0
 Manufacturer: Ansen
 Operating Condition: TX mode
 Test Site: 3M CHAMBER
 Operator: Cary
 Test Specification: DC 3V
 Comment: Y-axis
 Start of Test: 3/22/2010 / 8:53:26AM

SWEEP TABLE: "test (1G-18G) P"

Short Description: EN 55022 Field Strength
 Start Frequency: 1.0 GHz
 Stop Frequency: 18.0 GHz
 Detector: MaxPeak
 Meas.: Coupled
 IF Time: 1 MHz
 Transducer: HF906(2009)
 Average



MEASUREMENT RESULT: "HTW0322406_red"


Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
1272.545090	34.00	-8.1	74.0	40.0	Peak	100.0	194.00	VERTICAL
1601.202405	35.30	-7.3	74.0	38.7	Peak	100.0	59.00	VERTICAL
2058.116232	38.00	-4.5	74.0	36.0	Peak	100.0	31.00	VERTICAL
2587.174349	38.50	-3.2	74.0	35.5	Peak	100.0	328.00	VERTICAL
3677.354709	43.10	0.6	74.0	30.9	Peak	100.0	223.00	VERTICAL
4991.983968	44.10	4.0	74.0	29.9	Peak	100.0	116.00	VERTICAL

MEASUREMENT RESULT: "HTW0322406_red2"

Frequency MHz	Level dB μ V/m	Transd dB	Limit dB μ V/m	Margin dB	Det.	Height cm	Azimuth deg	Polarization
1256.513026	24.10	-8.2	54.0	29.9	AV	100.0	297.00	VERTICAL
1689.378758	26.10	-6.7	54.0	27.9	AV	100.0	173.00	VERTICAL
2202.404810	28.30	-4.4	54.0	25.7	AV	100.0	348.00	VERTICAL
2907.815631	29.30	-2.4	54.0	24.7	AV	100.0	12.00	VERTICAL
3757.515030	32.80	0.8	54.0	21.2	AV	100.0	126.00	VERTICAL
4919.839679	34.40	3.7	54.0	19.6	AV	100.0	136.00	VERTICAL

4.2. Deactivation Time

TEST CONFIGURATION



TEST PROCEDURE

- 1 The EUT was placed on a wooden table which is 0.8m height and close to receiver antenna of spectrum analyzer.
- 2 The spectrum analyzer resolution bandwidth was set to 100kHz and video bandwidth was set to 300kHz to encompass all significant spectral components during the test. The spectrum analyzer was operated in linear scale and zero span mode after tuning to the transmitter carrier frequency.

Limit

For periodic transmitter, according to FCC Part 15C § 15.231(e)



Item	Limit (second)
One transmission time	not greater than 1 second
Transmission period	at least 30 times the duration of the transmission but in no case less than 10 second



TEST RESULTS



EUT statement: The transmitter was automatically activated, and there were 3 channels use same carrier frequency 433.92MHz:

Channel 1: transmission period was 31 second
Channel 2: transmission period was 33 second
Channel 3: transmission period was 35 second

Channel	One transmission time (second)	Transmission period (second)	Result
1	0.99	31.0	Pass
2	0.99	33.0	Pass
3	0.99	35.2	Pass


For channel 1

For channel 2

For channel 3

4.3. 20dB Bandwidth

TEST CONFIGURATION



TEST PROCEDURE

- 1 The EUT was placed on a wooden table which is 0.8m height and close to receiver antenna of spectrum analyzer.
- 2 The spectrum analyzer resolution bandwidth was set to 100kHz and video bandwidth was set to 300kHz to encompass all significant spectral components during the test. The detector was set to peak and hold mode to clearly observe the components.



TEST LIMIT


According to FCC Part 15C § 15.231(c)

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70MHz and below 900MHz.

TEST RESULTS

Channel	Measurement Bandwidth (KHz)	Limit (kHz)	Result
1	200	1085	Pass
2	206	1085	Pass
3	198	1085	Pass

For Channel 1For Channel 2

For Channel 3

4.4. Antenna Requirement

According to FCC Part 15C § 15.203,

- a), An intentional radiator shall be de-signed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.
- b), The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

The antenna is permanently attached on the PCB inside the EUT and no consideration of replacement.

The EUT complied the antenna requirement.

