

Exhibit V:

L5X-PMP-04-280

RF SAFETY COMPLIANCE STATEMENT AND NOTIFICATION LABEL

The P-COM Remote ODU is considered a Subscriber Unit. Under the terms specified in Table 1 “Transmitters, Facilities and Operations Subject to Routine Environmental Evaluation” of **47 CFR 1.1307**, the P-COM Remote ODU does not exceed the limits for “(Multipoint Distribution Service) *Building-mounted antennas*: power > 1640 W EIRP”. The Max EIRP for the P-COM Remote ODU is 1320 W.

The P-COM Remote ODU will be installed on a Building-mounted Antenna and should fall under the limits for Maximum Permissible Exposure (MPE) for Occupational/Controlled Exposures listed under **Table 1.A of 47 CFR 1.1310**. The Limit listed for frequency range 1500 MHz to 100,000 MHz is 5 mW/cm². Equation (4) of **OET Bulletin 65 Edition 97-01** “Equations for Predicting RF Fields” is a “worst case or conservative prediction” for power density levels around typical RF sources. This equation was used to predict a safe minimum separation distance required between users and transceiver antenna. The P-COM 28 GHz Remote ODU has a **TX P1dB of +24 dBm** and the antenna has a **gain of 37.2 dBi**. The results of this equation predict a minimum safe separation distance of 150 cm between the antenna and all persons.

Label Information:

The following notice of FCC Radio-frequency exposure limits will be placed on all P-COM 28 GHz Remote ODU antennas.

