

CETECOM ICT Services GmbH

Untertürkheimer Straße 6-10 . D-66117 Saarbrücken Phone: +49 (0) 681-598-0 Fax: -9075
RSC-Laboratory



Accredited testing-laboratory

DAR registration number: DGA-PL-176/94-D1

Federal Motor Transport Authority (KBA)
DAR registration number: KBA-P 00070-97

Recognized by the Federal Communications Commission
Anechoic chamber registration no.: 90462 (FCC)
Anechoic chamber registration no.: 3462C-1 (IC)

Certification ID: DE 0001
Accreditation ID: DE 0002

Accredited Bluetooth® Test Facility (BQTF)
The Bluetooth word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by Cetecom ICT is under license

Test report no. : 1-2031-01-09/10
Type identification : RCV72UW
Applicant : Research In Motion Limited
FCC ID : L6ARCV70UW
IC Certification No : 2503A-RCV70UW
Test standards : 47 CFR Part 15
RSS - 210 Issue 7

Table of contents

1 General information.....	3
1.1 Notes	3
1.2 Testing laboratory	4
1.3 Details of applicant	4
1.4 Application details	4
2 Test standard/s	5
3 Technical tests	6
3.1 Details of manufacturer.....	6
3.1.1 Test item.....	6
3.1.2 Additional EUT information for IC Canada (appendix 2).....	7
3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102	8
3.1.4 EUT operating modes.....	9
3.1.5 Extreme conditions testing values	9
4 Summary of Measurement Results and list of all performed test cases	10
5 RF measurement testing	11
5.1 Description of test set-up.....	11
5.1.1 Radiated measurements.....	11
5.1.2 Conducted measurements.....	11
5.2 Referenced documents	12
5.3 Additional comments	12
5.4 Antenna gain	12
5.5 Carrier frequency separation §15.247(a)(1)	13
5.6 Number of hopping channels §15.247(a)(1)	14
5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii).....	15
5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan) §15.247(e)	16
5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1).....	17
5.10 Maximum output power (conducted) § 15.247 (b)(1).....	18
5.11 Max. peak output power (radiated) § 15.247 (b)(1)	19
5.12 Band-edge compliance of conducted emissions §15.247 (d)	20
5.13 Band-edge compliance of radiated emissions §15.205	22
5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)	23
5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1).....	26
5.16 Spurious Emissions - radiated (Receiver) § 15.109	35
5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209	36
5.18 Conducted Emissions <30 MHz § 15.107/207.....	37
6 Test equipment and ancillaries used for tests.....	38

1 General information

1.1 Notes

The test results of this test report relate exclusively to the test item specified in 3.1.1. The CETECOM ICT Services GmbH does not assume responsibility for any conclusions and generalisations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

Test laboratory manager:

2010-03-31 **Stefan Bös**
Date Name


Signature

Technical responsibility for area of testing:

2010-03-31 **Michael Berg**
Date Name


Signature

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

1.2 Testing laboratory

CETECOM ICT Services GmbH

Untertürkheimer Straße 6 - 10

66117 Saarbrücken

Germany

Phone: + 49 681 5 98 - 0

Fax: + 49 681 5 98 - 9075

e-mail: info@ICT.cetecom.de

Internet: http://www.cetecom-ict.de

State of accreditation: The test laboratory (area of testing) is accredited according to
DIN EN ISO/IEC 17025
DAR registration number: DGA-PL-176/94-D1

Accredited by: **Federal Motor Transport Authority (KBA)**
DAR registration number: KBA-P 00070-97

Testing location, if different from CETECOM ICT Services GmbH:

Name :

Street :

Town :

Country :

Phone :

Fax :

1.3 Details of applicant

Name:	Research In Motion Limited
Street:	305 Phillip Street
Town:	Waterloo, ON N2L 3W8
Country:	Canada
Telephone:	+1-519-888-7465
Fax:	+1-519-888-6906
Contact:	Masud Attayi
E-mail:	mattayi@rim.com
Telephone:	+1-519-888-7465

1.4 Application details

Date of receipt of order: **2010-02-11**

Date of receipt of test item: **2010-03-22**

Date of start test: **2010-03-24**

Date of end test **2010-03-30**

Persons(s) who have been present during the test: **-/-**

2 Test standard/s

47 CFR Part 15	2009-10	Title 47 of the Code of Federal Regulations; Chapter I-Federal Communications Commission subchapter A - general, Part 15-Radio frequency devices
RSS - 210 Issue 7	2007-06	Spectrum Management and Telecommunications - Radio Standards Specification Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment

3 Technical tests

3.1 Details of manufacturer

Name:	Research In Motion Limited
Street:	305 Phillip Street
Town:	Waterloo, ON N2L 3W8
Country:	Canada

3.1.1 Test item

Kind of test item :	Mobile Phone
Type identification :	RCV72UW
S/N serial number :	Rad. RTS-2747-3.0 Sample 1 Stratus 1,2,5 RCV72UW 14 key CER-31369-001
HW hardware status :	-
SW software status :	-
Frequency Band [MHz] :	ISM 2.400 - 2.483,5
Type of Modulation :	FHSS
Number of channels :	79
Antenna :	Integrated antenna
Power Supply :	3.7 V DC supplied by Li-Ion-Battery

Max. power radiated: Not performed

Max. power conducted: Not performed

FCC ID: **L6ARCV70UW**
IC: **2503A-RCV70UW**

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

3.1.2 Additional EUT information for IC Canada (appendix 2)

IC Registration Number:	2503A-RCV70UW
Model Name:	RCV72UW
Manufacturer (complete Address):	Research In Motion Limited 305 Phillip Street Waterloo, ON N2L 3W8 Canada
Tested to Radio Standards Specification (RSS) No.:	RSS-210 Issue 7
Open Area Test Site Industry Canada Number:	IC 3462C-1
Frequency Range (or fixed frequency) [MHz]:	2400 – 2483.5 MHz
RF: Power [W] (max):	Rad. EIRP: not performed Conducted : not performed
Antenna Type:	Integrated antenna
Occupied Bandwidth (99% BW) [kHz]:	not performed
Type of Modulation:	GFSK, Pi/4 DQPSK, 8 DPSK
Emission Designator (TRC-43):	not performed
Transmitter Spurious (worst case) [μ V/m in 3m]:	363
Receiver Spurious (worst case) [μ V/m in 3m]:	not performed

ATTESTATION:

I attest that the testing was performed or supervised by me; that the test measurements were made in accordance with the above-mentioned departmental standard(s), and that the radio equipment identified in this application has been subject to all applicable test conditions specified in the departmental standards and all of the requirements of the standards have been met.

Signature:



Test engineer: Stefan Bös

Date: 2010-03-31

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

3.1.3 RF Technical Brief Cover Sheet acc. To RSS-102

All Fields must be completed with the requested information or the following codes: N/A for Not Applicable, N/P for Not Performed or N/V for Not Available. Where applicable, check appropriate box.

1. COMPANY NUMBER: **2503A**

2. MODEL NUMBER: **RCV72UW**

3. MANUFACTURER: **Research In Motion Limited**

4. TYPE OF EVALUATION: **N.A.**

(c) RF Evaluation

- Evaluated against exposure limits: General Public Use Controlled Use
- Duty cycle used in evaluation: %
- Standard used for evaluation: RSS-102 Issue 2 (2005-11)
- Measurement distance: 0.20 m
- RF value: _____ * V/m A/m W/m²

Measured Computed Calculated

Declaration of RF Exposure Compliance

ATTESTATION:

I attest that the information provided in this test report are correct; that a Technical Brief was prepared and the information it contains is correct; that the device evaluation was performed or supervised by me; that applicable measurement methods and evaluation methodologies have been followed and that the device meets the SAR and/or RF exposure limits of RSS-102.



Name: Stefan Bös
Company: Cetecom ICT Services GmbH

3.1.4 EUT operating modes

EUT operating mode no.*)	Description of operating modes	Additional information
Op. 0	Normal mode	Normal temperature and power source conditions
Op. 1		low temperature, low power source conditions
Op. 2		low temperature, high power source conditions
Op. 3		high temperature, low power source conditions
Op. 4		high temperature, high power source conditions

*) EUT operating mode no. is used to simplify the test plan

3.1.5 Extreme conditions testing values

Description	Shortcut	Unit	Value
Nominal Temperature	T _{nom}	°C	23
Nominal Humidity	H _{nom}	%	53
Nominal Power Source	V _{nom}	V	3.7 V

Type of power source: **DC supplied by Li-Ion-Battery**

4 Summary of Measurement Results and list of all performed test cases

- No deviations from the technical specifications were ascertained**
- There were deviations from the technical specifications ascertained

TC identifier	Description	verdict	date	Remark
RF-Testing	FCC Part 15 §15.247 - CANADA RSS-210	Pass	2010-03-31	-/-

Test Specification Clause	Test Case	Modulation	Pass	Fail	N/A	Not performed
None	Antenna Gain	GFSK				Yes
§15.247(a1)	Carrier frequency separation	GFSK				Yes
§15.247(a1)	Number of hopping channels	GFSK				Yes
§15.247(a)(1)(iii)	Time of occupancy (dwell time)	--	Yes			
§15.247(e)	Power Spectral density (Hybrid system in Inquiry mode/Page scan)	--			Yes	
§15.247(a)(1)	Spectrum Bandwidth of a FHSS System / 20dB Bandwith	GFSK Pi/4 DQPSK 8 DPSK				Yes Yes Yes
§ 15.247 (b)(1)	Maximum output power (conducted)	GFSK Pi/4 DQPSK 8 DPSK				Yes Yes Yes
§ 15.247 (b)(1)	Max. peak output power (radiated)	GFSK Pi/4 DQPSK 8 DPSK				Yes Yes Yes
§ 15.247 (d)	Band-edge compliance of conducted emissions	Widest modulation				Yes
§ 15.205	Band-edge compliance of radiated emissions	GFSK Pi/4 DQPSK 8 DPSK				Yes Yes Yes
§ 15.247 (d)	Spurious Emission - conducted (Transmitter)	GFSK				Yes
§ 15.247 (d)	Spurious Emission - radiated (Transmitter) >30 MHz	Pi/4 DQPSK	Yes			
§ 15.109	Spurious Emissions - radiated (Receiver)	GFSK				Yes
§ 15.209	Spurious Emissions - radiated (Transmitter) <30 MHz	GFSK				Yes
§ 15.107/207	Conducted Emissions <30 MHz	GFSK				Yes

5 RF measurement testing

5.1 Description of test set-up

5.1.1 Radiated measurements

The radiated measurements are performed in vertical and horizontal plane in the frequency range from 9 kHz to 25 GHz in semi-anechoic chambers. The EUT is positioned on a non-conductive support with a height of 0.80 m above a conductive ground plane that covers the whole chamber. The receiving antennas are confirmed with specifications ANSI C63.2-1996 clause 15 and ANSI C63.4-2003 clause 4.1.5. These antennas can be moved over the height range between 1.0 m and 4.0 m in order to search for maximum field strength emitted from EUT. The measurement distances between EUT and receiving antennas are indicated in the test setups for the various frequency ranges. For each measurement, the EUT is rotated in all three axes until the maximum field strength is received. The wanted and unwanted emissions are received by spectrum analysers where the detector modes and resolution bandwidths over various frequency ranges are set according to requirement ANSI C63.4-2003 clause 4.2.

Antennas are confirmed with ANSI C63.2-1996 item 15.

9 kHz - 150 kHz: Quasi Peak measurement, 200 Hz Bandwidth, active loop antenna.

150 kHz - 30 MHz: Quasi Peak measurement, 9 kHz Bandwidth, active loop antenna.

30 MHz - 1GHz: Quasi Peak measurement, 120 kHz Bandwidth, Trilog antenna


>1GHz: Average, RBW 1MHz, VBW 10 Hz, waveguide horn

All measurements are done in accordance with the Filing and Measurement Guidelines for Frequency Hopping Spread Spectrum Systems DA 00-705 and Appendix A "BLUETOOTH APPROVALS"

The EUT is powered by an external power supply with nominal voltage. The signalling is performed from outside the chamber with a signalling unit (CMU200 or other) by air link using signalling antenna.

5.1.2 Conducted measurements

The EUT's RF signal is coupled out by the antenna connector which is supplied by the manufacturer. The signal is first 10dB attenuated before it is power divided (~6dB loss per branch). One of the signal paths is connected to the communication base Station (CMU200 or other), the other one is connected to the spectrum analyzer. The specific losses for both signal paths are first checked within a calibration. The measurement readings on the signalling unit/spectrum analyzer are corrected by the specific test set-up loss. The attenuator, power divider, signalling unit and the spectrum analyzer are impedance matched on 50 Ohm.



5.2 Referenced documents

None

5.3 Additional comments

None

5.4 Antenna gain

Not performed

The antenna gain of the complete system is calculated by the difference of radiated power in EIRP and the conducted power of the module.

	low channel 2402 MHz	mid channel 2441 MHz	high channel 2480 MHz
Conducted power [dBm] Measured, GFSK modulation			
Radiated power [dBm] Measured, GFSK modulation			
Gain [dBi] Calculated			

5.5 Carrier frequency separation §15.247(a)(1)

Not performed

Modulation: GFSK

Plot 1 of 1:

Result: Channel separation is: ~ 1 MHz

Limits:

Under normal test conditions only	Minimum 25 kHz or 20 dB Bandwidth of the hopping system
-----------------------------------	---

5.6 Number of hopping channels §15.247(a)(1)

Not performed

Modulation: GFSK

Plot 1 of 2:

Plot 2 of 2:

Result: The number of hopping channels is: 79

Limits:

Under normal test conditions only	at least 15 non-overlapping channels
-----------------------------------	--------------------------------------

5.7 Time of occupancy (dwell time) §15.247(a)(1)(iii)

For Bluetooth devices:

The dwell time of 0.4 s within a 31.6 second period in data mode is independent from the packet type (packet length). The calculation for a 31.6 second period is as follows:

Dwell time = time slot length * hop rate / number of hopping channels * 31.6 s

Example for a DH1 packet (with a maximum length of one time slot)

Dwell time = $625 \mu\text{s} * 1600 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

For multi-slot packet the hopping is reduced according to the length of the packet.

Example for a DH5 packet (with a maximum length of five time slots)

Dwell time = $5 * 625 \mu\text{s} * 1600 * 1/5 \text{ 1/s} / 79 * 31.6 \text{ s} = 0.4 \text{ s}$ (in a 31.6 s period)

This is according the Bluetooth Core Specification V 1.1 & V 1.2 & V2.0 (+ critical errata) for all Bluetooth devices. Therefore, all Bluetooth devices comply with the FCC dwell time requirement in the data mode.

This was checked during the Bluetooth Qualification tests.

The Dwell time in hybrid mode is approximately 2.6 ms (in a 12.8s period)

**5.8 Power Spectral density (Hybrid system in Inquiry mode/Page scan)
§ 15.247(e)**

Not performed

Plot 1 of 1:

Not applicable

Result: Power density: $- \text{dBm/Hz} = - \text{dBm} / 3 \text{ kHz}$
Correction factor from dBm/Hz to dBm / 3 kHz is +34,8 dB

Limits:

Under normal test conditions only	For digitally modulated systems, the peak power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission
-----------------------------------	---

5.9 Spectrum Bandwidth of a FHSS System / 20dB Bandwidth §15.247(a)(1)

Not performed

Result:

Modulation	20 dB BANDWIDTH [kHz]		
	2402	2441	2480
<i>GFSK</i>			
<i>Pi/4 DQPSK</i>			
<i>8DPSK</i>			
Measurement uncertainty	$\pm 1\text{kHz}$		

RBW / VBW as provided in the „Measurement Guidelines“ (DA 00-705, March 30, 2000)

RBW: 10 kHz / VBW 10 kHz

Limits:

Under normal test conditions only	GFSK < 1000 kHz Pi/4 DQPSK < 1500 8DPSK < 1500
-----------------------------------	--

5.10 Maximum output power (conducted) § 15.247 (b)(1)

Not performed

Results:

Modulation	Max. peak output power [dBm]		
	2402	2441	2480
<i>GFSK</i>			
<i>Pi/4 DQPSK</i>			
<i>8DPSK</i>			
Measurement uncertainty	$\pm 2\text{dB}$		

RBW / VBW: 3 MHz

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

5.11 Max. peak output power (radiated) § 15.247 (b)(1)

Not performed

Modulation: GFSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-	-	-
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m

Modulation: Pi/4-DQPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-	-	-
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m

Modulation: 8DPSK

Results:

Test conditions		Max. peak output power EIRP [dBm]		
Frequency [MHz]		2402	2442	2480
T _{nom}	V _{nom}	-	-	-
Measurement uncertainty		±3dB		

RBW / VBW: 3 MHz

Measured at a distance of 3m

Limits:

Under normal test conditions only, for frequency range 2400-2483.5 MHz	Max. 1.0 Watt
--	---------------

5.12 Band-edge compliance of conducted emissions §15.247 (d)

Not performed

Modulation: GFSK

Plot 1 of 4 (hopping off, lowest frequency):

Plot 2 of 4 (hopping on, lowest frequency):

Plot 3 of 4 (hopping off, highest frequency):

Plot 4 of 4 (hopping on, highest frequency):

Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Modulation: Pi/4 DQPSK

Plot 1 of 4 (hopping off, lowest frequency):

Plot 2 of 4 (hopping on, lowest frequency):

Plot 3 of 4 (hopping off, highest frequency):

Plot 4 of 4 (hopping on, highest frequency):

Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Modulation: 8 DPSK

Plot 1 of 4 (hopping off, lowest frequency):

Plot 2 of 4 (hopping on, lowest frequency):

Plot 3 of 4 (hopping off, highest frequency):

Plot 4 of 4 (hopping on, highest frequency):

Results:

SZENARIO	DELTA VALUE [DB]
hopping off, lowest frequency	> 20 dB
hopping on, lowest frequency	> 20 dB
hopping off, highest frequency	> 20 dB
hopping on, highest frequency	> 20 dB
Measurement uncertainty	±1,5dB

Limits:

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 5.205(c)).
-----------------------------------	--

5.13 Band-edge compliance of radiated emissions §15.205

Not performed

Modulation: GFSK

Plot 1: Band Edge Low (worst case for both polarizations)

Plot 2: Band Edge High (worst case for both polarizations)

Modulation: Pi/4-DQPSK

Plot 3: Band Edge Low (worst case for both polarizations)

Plot 4: Band Edge High (worst case for both polarizations)

Modulation: 8-DPSK

Plot 5: Band Edge Low (worst case for both polarizations)

Plot 6: Band Edge High (worst case for both polarizations)

5.14 Spurious Emissions - conducted (Transmitter) § 15.247 (c)(1)**Not performed**Modulation: GFSK

Plot 1 of 3: lowest channel

Plot 2 of 3: middle channel

Plot 3 of 3: highest channel

Result & Limits:

Emission Limitation				
f [MHz]	amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402		30 dBm		Operating frequency
		-20 dBc		complies
				complies
2441		30 dBm		Operating frequency
		-20 dBc		complies
				complies
2480		30 dBm		Operating frequency
		-20 dBc		complies
				complies
Measurement uncertainty		± 3dB		

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
 F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Modulation: Pi/4 DQPSK

Plot 1 of 3: lowest channel

Plot 2 of 3: middle channel

Plot 3 of 3: highest channel

Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402			30 dBm		Operating frequency
			-20 dBc		complies
					complies
2441					
2441			30 dBm		Operating frequency
			-20 dBc		complies
					complies
2480					
2480			30 dBm		Operating frequency
			-20 dBc		complies
					complies
Measurement uncertainty		± 3dB			

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Modulation: 8 DPSK

Plot 1 of 3: lowest channel

Plot 2 of 3: middle channel

Plot 3 of 3: highest channel

Result & Limits:

Emission Limitation					
f [MHz]		amplitude of emission [dBm]	limit max. allowed emission power	actual attenuation below frequency of operation [dB]	results
2402			30 dBm		Operating frequency
			-20 dBc		complies
					complies
2441					
2441			30 dBm		Operating frequency
			-20 dBc		complies
					complies
2480					
2480			30 dBm		Operating frequency
			-20 dBc		complies
					complies
Measurement uncertainty		± 3dB			

F < 1 GHz: RBW: 100 kHz VBW: 100 kHz
F > 1 GHz: RBW: 1 MHz VBW: 1 MHz

Under normal test conditions only	In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
-----------------------------------	--

Note: For emissions that fall into restricted bands you find the radiated emissions later in the report.

5.15 Spurious Emissions > 30 MHz- radiated (Transmitter) § 15.247 (c)(1)

Modulation: Pi/4-DQPSK


Plot 1: 0.03 - 1 GHz (lowest channel)

Common Information

EUT:	RCV72UW
Serial Number:	IMEI: 004401.13.589563.5
Test Description:	FCC part 15 C class B @ 10m
Operating Conditions:	BT-Testmode; CH:1
Operator Name:	Lang
Comment:	Battery powered

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup:	Electric Field (NOS)			
Level Unit:	dB μ V/m			
Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
38.798700	9.4	15000.000	120.000	120.0	V	230.0	13.3	20.6	30.0	
53.802750	10.8	15000.000	120.000	220.0	V	47.0	13.0	19.2	30.0	
101.727450	11.6	15000.000	120.000	98.0	V	146.0	11.7	21.9	33.5	
712.639650	20.0	15000.000	120.000	120.0	H	127.0	22.7	16.0	36.0	
838.564500	21.4	15000.000	120.000	120.0	V	316.0	24.4	14.6	36.0	
909.657000	22.5	15000.000	120.000	209.0	H	28.0	25.2	13.5	36.0	

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1


Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

EMC 32 Version 8.10.00

CETECOM ICT Services GmbH


Test report no.: **1-2031-01-09/10**

Plot 2: 1 – 12.75 GHz horizontal (lowest channel)



Carrier suppressed with a rejection filter

Plot 3: 1 – 12.75 GHz vertical (lowest channel)




Carrier suppressed with a rejection filter

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Plot 4: 12 - 25 GHz vertical/horizontal (valid for all channels)




Date: 30.MAR.2010 15:56:45

CETECOM ICT Services GmbH


Test report no.: **1-2031-01-09/10**

Plot 5: 1 – 12.75 GHz horizontal (middle channel)



Carrier suppressed with a rejection filter

Plot 6: 1 – 12.75 GHz vertical (middle channel)



Carrier suppressed with a rejection filter

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Plot 7: 0.03 - 1 GHz (highest channel)


Common Information

EUT: RCV72UW
Serial Number: IMEI: 004401.13.589563.5
Test Description: FCC part 15 C class B @ 10m
Operating Conditions: BT-Testmode; CH:78
Operator Name: Lang
Comment: Battery powered

Scan Setup: STAN_Fin [EMI radiated]

Hardware Setup: Electric Field (NOS)
Level Unit: dB μ V/m

Subrange	Detectors	IF Bandwidth	Meas. Time	Receiver
30 MHz - 1,05 GHz	QuasiPeak	120 kHz	15 s	Receiver



Final Result 1

Frequency (MHz)	QuasiPeak (dB μ V/m)	Meas. Time (ms)	Bandwidth (kHz)	Antenna height (cm)	Polarity	Turntable position (deg)	Corr. (dB)	Margin (dB)	Limit (dB μ V/m)	Comment
54.006600	16.3	15000.000	120.000	220.0	V	134.0	13.0	13.7	30.0	
361.565100	12.2	15000.000	120.000	132.0	V	163.0	16.2	23.8	36.0	
724.121400	20.2	15000.000	120.000	220.0	V	140.0	23.0	15.8	36.0	
786.611550	20.9	15000.000	120.000	220.0	V	275.0	23.7	15.1	36.0	
934.315200	22.6	15000.000	120.000	220.0	H	209.0	25.3	13.4	36.0	
956.962200	22.8	15000.000	120.000	197.0	V	41.0	25.4	13.2	36.0	

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Hardware Setup: EMI radiated\Electric Field (NOS) - [EMI radiated]

Subrange 1


Frequency Range:	30 MHz - 2 GHz
Receiver:	Receiver [ESCI 3] @ GPIB0 (ADR 20), SN 100083/003, FW 4.32
Signal Path:	without Notch FW 1.0
Antenna:	VULB 9163 SN 9163-295, FW --- Correction Table (vertical): VULP6113 Correction Table (horizontal): VULP6113 Correction Table: Cable_EN_1GHz (0909)
Antenna Tower:	Tower [EMCO 2090 Antenna Tower] @ GPIB0 (ADR 8), FW REV 3.12
Turntable:	Turntable [EMCO Turntable] @ GPIB0 (ADR 9), FW REV 3.12

EMC 32 Version 8.10.00

CETECOM ICT Services GmbH


Test report no.: **1-2031-01-09/10**

Plot 8: 1 – 12.75 GHz horizontal (highest channel)



Carrier suppressed with a rejection filter

Plot 9: 1 – 12.75 GHz vertical (highest channel)



Carrier suppressed with a rejection filter

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

Results: Pi/4-DQPSK-Modulation

SPURIOUS EMISSIONS LEVEL (dB μ V/m)								
2402 MHz			2441 MHz			2480 MHz		
F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]	F [MHz]	Detector	Level [dB μ V/m]
3200 (v)	Pk	51.1	3200 (h)	Pk	48.8	3306 (h)	Pk	49.6
3253 (v)	Pk	49.9	3253 (h)	Pk	46.2	7440 (h)	Avg	47.9
3306 (v)	Pk	39.9				9920 (h)	Avg	51.2
Measurement uncertainty		± 3 dB						

f < 1 GHz : RBW/VBW: 100 kHz

f \geq 1GHz : RBW = 1 MHz / VBW = 10 Hz

Limits: § 15.247 (c)

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the desired power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

Limits: § 15.209

Frequency [MHz]	Field strength [μ V/m]	Measurement distance (m)
30 - 88	100 (40 dB μ V/m)	3
88 - 216	150 (43.5 dB μ V/m)	3
216 - 960	200 (46 dB μ V/m)	3
above 960	500 (54 dB μ V/m)	3

5.16 Spurious Emissions - radiated (Receiver) § 15.109

Not performed

Modulation: GFSK

Results:

See above plots

Measurement distance see table

Limits: § 15.109

Frequency (MHz)	Field strength (μ V/m)	Measurement distance (m)
30 - 88	100 (40 dB μ V/m)	3
88 - 216	150 (43.5 dB μ V/m)	3
216 - 960	200 (46 dB μ V/m)	3
above 960	500 (54 dB μ V/m)	3

5.17 Spurious Emissions < 30 MHz - Transmitter radiated § 15.209

Not performed

Modulation: valid for all modes

Measured at 3 m distance.

Values recalculated with 40 dB/decade according to FCC rules.

Plot 1:

Limits:

Frequency (MHz)	Field strength (μ V/m)	Measurement distance (m)
0.009 – 0.490	2400/F(kHz)	300
0.490 – 1.705	24000/F(kHz)	30
1.705 – 30.0	30 / 29.5 dB μ V/m	30

5.18 Conducted Emissions <30 MHz § 15.107/207

Not performed

Modulation: GFSK

Plot 1:

Limits:

Under normal test conditions only	See plots
-----------------------------------	-----------

CETECOM ICT Services GmbH

Test report no.: **1-2031-01-09/10**

6 Test equipment and ancillaries used for tests

In order to simplify the identification of the equipment used at each specific test, each item of test equipment and ancillaries are provided with an identifier or number in the equipment list below.

Typically, the calibrations of the test apparatus are commissioned to and performed by an accredited calibration laboratory. The calibration intervals are determined in accordance with the DIN EN ISO/IEC 17025. In addition to the external calibrations, the laboratory executes comparison measurements with other calibrated test systems or effective verifications. Weekly chamber inspections and range calibrations are performed. Where possible, rf-generating and signalling equipment as well as measuring receivers and analyzers are connected to an external high-precision 10 MHz reference (GPS-based or rubidium frequency standard).

No.	Labor / Item	Equipment	Type	Manufact.	Serial No.	INV. No Cetecon	Kal. Art	Last Calibration	Next Calibration
1	n. a.	System Autoranging DC power supply, 60Vdc, 50A, 1200 W	6032A	HP Meßtechnik	2818A03450	300001040	Ve	08.01.2009	08.01.2012
2	n. a.	PowerAttenuator Double-Ridged	8325	Byrd	1530	300001595	vl		
3	n. a.	Waveguide Horn Antenna 1-26.5GHz	3115	EMCO	8812-3088	300001032	KI !	05.03.2009	05.03.2011
4	n. a.	Active Loop Antenna	6502	EMCO	2210	300001015	ne		
5	n. a.	Anechoic chamber		MWB	87400/02	300000996			
6	Spec.A. 2_2e	System-Rack	85900	HP I.V.	*	300000222	ne		
7	9	Artificial Mains 9 kHz to 30 MHz, 4 x 25 Ampere	ESH3-Z5	R&S	828576/020	300001210	Ve	06.01.2010	06.01.2012
8	n. a.	Relais Matrix	3488A	HP Meßtechnik	2719A15013	300001156	ne		
9	n. a.	Relais Matrix	PSU	R&S	890167/024	300001168	ne		
10	n. a.	Isolating Transformer	RT5A	Grundig	9242	300001263	ne		
11	n. a.	Three-Way Power Splitter, 50 Ohm	11850C	HP Meßtechnik		300000997	ne		
12	n. a.	Switch / Control Unit	3488A	HP	2605e08770	300001443	ne		
13	n. a.	Band Reject filter	WRCG1855/191 0-1835/1925-40/8SS	Wainwright	7	300003350	ev		
14	n. a.	Band Reject filter	WRCG2400/248 3-2375/2505-50/10SS	Wainwright	11	300003351	ev		
15	n. a.	TILE-Software Emission	Quantum Change, Modell TILE-ICS/FULL	EMCO	none	300003451	ne		
16	n. a.	Highpass Filter	WHKX2.9/18G-12SS	Wainwright	1	300003492	ev		
17	n. a.	Highpass Filter	WHK1.1/15G-10SS	Wainwright	3	300003255	ev		
18	n. a.	Highpass Filter	WHKX7.0/18G-8SS	Wainwright	18	300003789	ne		
19	n. a.	PSA Spectrum Analyzer 3 Hz - 26.5 GHz	E4440A	Agilent Vertr. Bad Hom	MY48250080	300003812	k	05.08.2008	05.08.2010
20	n. a.	MXG Microwave Analog Signal Generator	N5183A	Agilent Vertr. Bad Hom	MY47420220	300003813	k	06.08.2008	06.08.2010
21	n. a.	RF Filter Section 9kHz - 1GHz	N9039A	Agilent Vertr. Bad Hom	MY48260003	300003825	vl KI !	19.08.2008	19.08.2010
22	n. a.	TRILOG Super Breitband Antenne	VULB9163	Schwarzbeck	371	300003854	vl KI !	17.12.2008	17.12.2010
23	n. a.	CBT (Bluetooth EDR Signalisierung)	CBT 1153.9000K35, CBT-B55, CBT-K55	R&S	100313	300003516	k	03.09.2008	03.09.2010