

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 1(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

APPENDIX A: SAR DISTRIBUTION COMPARISON FOR ACCURACY VERIFICATION

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 2(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 1/27/2011 6:48:32 PM

Test Laboratory: RIM Testing Services

DipoleValidation_835MHz_Amb_Tem_23.5_Liq_Tem_21.8C_01_27_11

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:446

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.903 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1643; ConvF(6.01, 6.01, 6.01); Calibrated: 3/9/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement

grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 109.1 V/m ; Power Drift = -0.028 dB

Peak SAR (extrapolated) = 13.3 W/kg

SAR(1 g) = 9.18 mW/g ; SAR(10 g) = 6.02 mW/g


Maximum value of SAR (measured) = 9.91 mW/g

d=15mm, Pin=1000mW/Area Scan (31x121x1): Measurement grid: $dx=15\text{mm}$,

$dy=15\text{mm}$

Maximum value of SAR (interpolated) = 9.83 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 3(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 4(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 4/20/2011 2:37:03 PM, Date/Time: 4/20/2011 2:44:45 PM

Test Laboratory: RIM Testing Services

DipoleValidation_835MHz_Amb_Tem_23.9_Liq_Tem_22.1C_04_20_11

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:446

Communication System: CW; Communication System Band: **Not Specified**; Frequency: 835 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.875 \text{ mho/m}$; $\epsilon_r = 40.074$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.47, 6.47, 6.47); Calibrated: 1/13/2011
 - Modulation Compensation: **Not calibrated**
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

Configuration/d=15mm, Pin=1000mW/Area Scan (31x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 9.747 mW/g

Configuration/d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube

0: Measurement grid: dx=7.5mm, dy=7.5mm, dz=5mm


Reference Value = 106.7 V/m; Power Drift = -0.00087 dB

Peak SAR (extrapolated) = 13.589 W/kg

SAR(1 g) = 9.1 mW/g; SAR(10 g) = 5.97 mW/g

Maximum value of SAR (measured) = 9.810 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 5(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 6(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 1/19/2011 11:35:01 PM

Test Laboratory: RIM Testing Services

DipoleValidation_1900MHz_Amb_Tem_23.8_Liq_Tem_21.9C_01_19_11

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:545

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.34 \text{ mho/m}$; $\epsilon_r = 39.8$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1644; ConvF(5.09, 5.09, 5.09); Calibrated: 11/16/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement

grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 193.3 V/m ; Power Drift = -0.009 dB

Peak SAR (extrapolated) = 75.5 W/kg

SAR(1 g) = 41 mW/g ; SAR(10 g) = 21.3 mW/g


Maximum value of SAR (measured) = 46.0 mW/g

d=15mm, Pin=1000mW/Area Scan (31x61x1): Measurement grid: $dx=15\text{mm}$,

$dy=15\text{mm}$

Maximum value of SAR (interpolated) = 46.0 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 7(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 8(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 1/25/2011 4:57:34 PM

Test Laboratory: RIM Testing Services

DipoleValidation_1900MHz_Amb_Tem_23.8_Liq_Tem_22.1C_01_25_11

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:545

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.34 \text{ mho/m}$; $\epsilon_r = 38.6$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1643; ConvF(4.99, 4.99, 4.99); Calibrated: 3/9/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 190.9 V/m; Power Drift = 0.006 dB

Peak SAR (extrapolated) = 64.9 W/kg


SAR(1 g) = 38.4 mW/g; SAR(10 g) = 20.4 mW/g

Maximum value of SAR (measured) = 43.3 mW/g

d=15mm, Pin=1000mW/Area Scan (31x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 43.8 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 9(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 10(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 4/14/2011 7:39:23 PM, Date/Time: 4/14/2011 7:41:58 PM

Test Laboratory: RIM Testing Services

DipoleValidation_1900MHz_Amb_Tem_23.3_Liq_Tem_21.9_04_14_11

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:545

Communication System: CW; Communication System Band: **Not Specified**; Frequency: 1900 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.337 \text{ mho/m}$; $\epsilon_r = 39.751$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(5.26, 5.26, 5.26); Calibrated: 1/13/2011
 - Modulation Compensation: **Not calibrated**
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

Configuration/d=15mm, Pin=1000mW/Area Scan (31x61x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 41.584 mW/g

Configuration/d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (7x7x7)/Cube

0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 178.3 V/m; Power Drift = -0.03 dB

Peak SAR (extrapolated) = 67.708 W/kg

SAR(1 g) = 36.7 mW/g; SAR(10 g) = 19.2 mW/g

Maximum value of SAR (measured) = 41.383 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 11(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 12(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 1/14/2011 8:38:01 PM

Test Laboratory: RIM Testing Services

DipoleValidation_2450MHz_Amb_Tem_24.6_Liq_Tem_22.8C

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:747

Communication System: CW; Frequency: 2450 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.87 \text{ mho/m}$; $\epsilon_r = 38.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1644; ConvF(4.5, 4.5, 4.5); Calibrated: 11/11/2009
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 193.9 V/m ; Power Drift = -0.007 dB

Peak SAR (extrapolated) = 133.9 W/kg


SAR(1 g) = 57.7 mW/g ; SAR(10 g) = 26.3 mW/g

Maximum value of SAR (measured) = 64.5 mW/g

d=15mm, Pin=1000mW/Area Scan (31x41x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 65.1 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 13(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document			Page
	Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			14(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 4/26/2011 11:31:28 PM, Date/Time: 4/26/2011 11:33:21 PM

Test Laboratory: RIM Testing Services

DipoleValidation_2450MHz_Amb_Tem_23.5_Liq_Tem_22.3C

DUT: Dipole 2450 MHz; Type: D2450V2; Serial: D2450V2 - SN:747

Communication System: CW; Communication System Band: **Not Specified**; Frequency: 2450 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 2450 \text{ MHz}$; $\sigma = 1.886 \text{ mho/m}$; $\epsilon_r = 39.002$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(4.6, 4.6, 4.6); Calibrated: 1/13/2011
 - Modulation Compensation: **Not calibrated**
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASYS2, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

Configuration/d=15mm, Pin=1000mW/Area Scan (31x41x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 65.108 mW/g

Configuration/d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (7x7x7)/Cube

0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 180.5 V/m; Power Drift = 0.05 dB

Peak SAR (extrapolated) = 115.1 W/kg

SAR(1 g) = 56 mW/g; SAR(10 g) = 25.9 mW/g

Maximum value of SAR (measured) = 63.463 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 15(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 16(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

RDP71UW

	Document			Page
	Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			17(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 2/7/2011 6:47:04 PM

Test Laboratory: RIM Testing Services

DipoleValidation_835MHz_Amb_Tem_23.3_Liq_Tem_22.3C_02_07_11

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:446

Communication System: CW; Frequency: 835 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.903 \text{ mho/m}$; $\epsilon_r = 42.1$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1643; ConvF(6.01, 6.01, 6.01); Calibrated: 3/9/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 110.6 V/m; Power Drift = -0.019 dB

Peak SAR (extrapolated) = 13.6 W/kg


SAR(1 g) = 9.38 mW/g; SAR(10 g) = 6.15 mW/g

Maximum value of SAR (measured) = 10.2 mW/g

d=15mm, Pin=1000mW/Area Scan (31x121x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 10.1 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 18(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



0 dB = 10.1mW/g

	Document			Page
	Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			19(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 4/6/2011 9:21:47 PM, Date/Time: 4/6/2011 9:26:36 PM

Test Laboratory: RIM Testing Services

DipoleValidation_835MHz_Amb_Tem_23.7_Liq_Tem_21.8C_04_06_11

DUT: Dipole 835 MHz; Type: D835V2; Serial: D835V2 - SN:446

Communication System: CW; Communication System Band: **Not Specified**; Frequency: 835 MHz; Communication System PAR: 0 dB

Medium parameters used: $f = 835 \text{ MHz}$; $\sigma = 0.928 \text{ mho/m}$; $\epsilon_r = 42.86$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY5 Configuration:

- Probe: ES3DV3 - SN3225; ConvF(6.47, 6.47, 6.47); Calibrated: 1/13/2011
 - Modulation Compensation: **Not calibrated**
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn473; Calibrated: 1/21/2011
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY52, Version 52.6 (2); SEMCAD X Version 14.4.4 (2829)

Configuration/d=15mm, Pin=1000mW/Area Scan (31x121x1): Measurement grid: dx=15mm, dy=15mm

Maximum value of SAR (interpolated) = 10.104 mW/g

Configuration/d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (7x7x7)/Cube

0: Measurement grid: dx=5mm, dy=5mm, dz=5mm


Reference Value = 104.9 V/m; Power Drift = -0.05 dB

Peak SAR (extrapolated) = 14.008 W/kg

SAR(1 g) = 9.3 mW/g; SAR(10 g) = 6.08 mW/g

Maximum value of SAR (measured) = 10.041 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 20(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW



	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 21(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

Date/Time: 2/14/2011 5:48:17 PM

Test Laboratory: RIM Testing Services

DipoleValidation_1900MHz_Amb_Tem_23.5_Liq_Tem_22.1_02_14_11

DUT: Dipole 1900 MHz; Type: D1900V2; Serial: D1900V2 - SN:545

Communication System: CW; Frequency: 1900 MHz; Duty Cycle: 1:1

Medium parameters used: $f = 1900 \text{ MHz}$; $\sigma = 1.39 \text{ mho/m}$; $\epsilon_r = 38.2$; $\rho = 1000 \text{ kg/m}^3$

Phantom section: Flat Section

DASY4 Configuration:

- Probe: ET3DV6 - SN1643; ConvF(4.99, 4.99, 4.99); Calibrated: 3/9/2010
- Sensor-Surface: 4mm (Mechanical Surface Detection)
- Electronics: DAE3 Sn472; Calibrated: 5/17/2010
- Phantom: SAM 1; Type: SAM 4.0; Serial: 1076
- Measurement SW: DASY4, V4.7 Build 80; Postprocessing SW: SEMCAD, V1.8 Build 186

d=15mm, Pin=1000mW/Zoom Scan (5x5x7) 2 (5x5x7)/Cube 0: Measurement grid: $dx=7.5\text{mm}$, $dy=7.5\text{mm}$, $dz=5\text{mm}$

Reference Value = 187.0 V/m; Power Drift = 0.016 dB

Peak SAR (extrapolated) = 65.6 W/kg

SAR(1 g) = 38.3 mW/g; SAR(10 g) = 20.2 mW/g

Maximum value of SAR (measured) = 43.2 mW/g

d=15mm, Pin=1000mW/Area Scan (31x61x1): Measurement grid: $dx=15\text{mm}$, $dy=15\text{mm}$

Maximum value of SAR (interpolated) = 44.1 mW/g

	Document Appendix A for the BlackBerry® Smartphone Model RDH71CW/RDP71UW SAR Report			Page 22(22)
Author Data Hang Wang	Dates of Test Jan 14 – June 09, 2011	Test Report No RTS-2605-1102-05A	FCC ID: L6ARDH70CW L6ARDP70UW	IC ID 2503A-RDH70CW 2503A-RDP70UW

