



SAR Test Report

FOR:

Manufacturer: Research In Motion Limited
Model Name: RDS41CW
FCC ID: L6ARDS40CW
IC ID: 2503A-RDS40CW

Test Report #: SAR_CETE4_015_11001_RDS41CW

Date of Report: 2011-10-28



Bluetooth
Bluetooth Qualification
Test Facility
(BQTF)

CTIA Authorized Test Lab
LAB CODE 20020328-00

FCC Listed #:
A2LA Accredited

IC Recognized #:
3462B-1

CETECOM Inc.

411 Dixon Landing Road • Milpitas, CA 95035 • U.S.A.

Phone: + 1 (408) 586 6200 • Fax: + 1 (408) 586 6299 • E-mail: info@cetecomusa.com • <http://www.cetecom.com>

CETECOM Inc. is a Delaware Corporation with Corporation number: 2113686
Board of Directors: Dr. Harald Ansorge, Hans Peter May.

TABLE OF CONTENTS

1. Assessment.....	4
2. Administrative Data	5
2.1. Identification of the Testing Laboratory Issuing the EMC Test Report	5
2.2. Identification of the Client	5
2.3. Identification of the Manufacturer	5
3. Equipment under Test (EUT)	6
3.1. Specification of the Equipment under Test	6
3.2. Identification of the Equipment Under Test (EUT).....	7
3.3. Identification of Accessory equipment.....	7
4. Subject of Investigation	8
4.1. The IEEE Standard C95.1 and the FCC Exposure Criteria.....	8
4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies	8
4.3. Distinction between Maximum Permissible Exposure and SAR Limits.....	9
4.4. SAR Limit.....	9
5. The FCC Measurement Procedure and IC Measurement Procedure	10
5.1. General Requirements.....	10
5.2. Body-worn and Other Configurations.....	10
5.3. Procedure for assessing the peak spatial-average SAR.....	11
5.4. Determination of the largest peak spatial-average SAR	13
6. The Measurement System	14
6.1. Robot system specification	14
6.2. Isotropic E-Field Probe for Dosimetric Measurements	15
6.3. Data Acquisition Electronics.....	15
6.4. Phantoms	15

6.5. Interpolation and Extrapolation schemes.....	15
7. Uncertainty Assessment	16
7.1. Measurement Uncertainty Budget	16
8. Test results summary	17
8.1. Conducted Average Output Power	17
8.2. Test Positions and Configurations.....	18
8.3. SAR Results for Body	18
8.4. Dipole verification.....	19
9. References	20
10. Report History	21

1. Assessment

The following device was tested against the limits for general population uncontrolled exposure specified in FCC 2.1093 and RSS 102, Issue 4. The device was tested according to measurement standards and procedures specified in FCC OET Bulletin 65, Supplement C (Edition 01-01) and IEEE 1528:2003, December 19, 2003 and no deviations were ascertained during the course of the tests performed.

Company	Description	Model #
Research In Motion Limited	Blackberry Smartphone	RDS41CW

Responsible for Testing Laboratory:

2011-10-28	Compliance	Sajay Jose (Test Lab Manager)
Date	Section	Name

Responsible for the Report:

2011-10-28	Compliance	Josie Sabado (Project Engineer)
Date	Section	Name

The test results of this test report relate exclusively to the test item specified in Section 3. CETECOM Inc. USA does not assume responsibility for any conclusions and generalizations drawn from the test results with regard to other specimens or samples of the type of the equipment represented by the test item. The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of CETECOM Inc. USA.

2. Administrative Data

2.1. Identification of the Testing Laboratory Issuing the EMC Test Report

Company Name:	CETECOM Inc.
Department:	Compliance
Address:	411 Dixon Landing Road Milpitas, CA 95035 U.S.A.
Telephone:	+1 (408) 586 6200
Fax:	+1 (408) 586 6299
Test Lab Director:	Heiko Strehlow
Responsible Project Leader:	Josie Sabado

2.2. Identification of the Client

Applicant's Name:	Research In Motion Limited
Street Address:	295 Phillip Street
City/Zip Code	Waterloo, ON N2L 3W8
Country	Canada
Contact Person:	Masud Attayi
Phone No.	+1 51 98 88 74 65
Fax:	+1 51 98 88 69 06
e-mail:	mattayi@rim.com

2.3. Identification of the Manufacturer

Same as above client.

3. Equipment under Test (EUT)

3.1. Specification of the Equipment under Test

Product Type:	Portable
RF Exposure Environment:	General / Uncontrolled
Exposure Conditions:	Held next to the ear Body worn
Model No:	RDS41CW
Supported Radios*:	GSM/GPRS/EGRPS, MS Class 10, Power Class 4/1 CDMA 2000, 1xEV-DO WLAN 802.11 b/g Bluetooth + 2.1EDR
Hardware Revision :	Rev 2
Software Revision :	7.1 Bundle 96 (v7.1.0.45)
FCC-ID:	L6ARD40CW
IC-ID :	2503A-RDS40CW
Frequency Range*:	GSM 850: 824.2 – 848.8 MHz PCS 1900: 1850.2 – 1909.8 MHz CDMA BC0: 824.7 – 848.31 MHz CDMA BC10: 820.5 – 823.1 MHz 802.11 b/g: 2412 – 2472 MHz Bluetooth: 2402 – 2480 MHz
Type(s) of Modulation*:	GSM/GPRS/EGPRS: GMSK, 8PSK CDMA: QPSK, HPSK EVDO: HPSK 802.11b/g: BPSK, QPSK Bluetooth: GFSK, $\pi/4$ DQPSK, 8DPSK
Antenna Type:	Internal
Maximum Conduted Output Power:	CDMA BC0: 23.75 dBm CDMA BC10: 23.79 dBm

*Note: Only CDMA is reported in this test report. See section 4.

Test Report #:

SAR_CETE4_015_11001_RDS41CW

FCC ID:

L6ARDS40CW

IC ID:

2503A-RDS40CW

Date of Report :

2011-10-28



Page 7 of 21

3.2. Identification of the Equipment Under Test (EUT)

EUT #	MEID – HEX	HW Version	SW Version
1	A0000025D76C81	Rev 2	7.1 Bundle 96 (v7.1.0.45)

3.3. Identification of Accessory equipment

No accessory equipment

4. Subject of Investigation

The objective of the measurements done by Cetecom Inc. was the dosimetric assessment of one device. The tests were performed in configurations for devices operated next to a person's body. The examinations were carried out with the dosimetric assessment system DASY52 described in Section 6.

Body SAR evaluation for hot spot mode in the CDMA technology is reported here. Refer to CETECOM ICT test report number 1-3851/11-01-17 for additional SAR measurements for hot spot mode.

4.1. The IEEE Standard C95.1 and the FCC Exposure Criteria

In the USA the recent FCC exposure criteria [FCC 2001] are based upon the IEEE Standard C95.1 [IEEE 1999]. The IEEE standard C95.1 sets limits for human exposure to radio frequency electromagnetic fields in the frequency range 3 kHz to 300 GHz.

4.2. Distinction Between Exposed Population, Duration of Exposure and Frequencies

The American Standard [IEEE 1999] distinguishes between controlled and uncontrolled environment. Controlled environments are locations where there is exposure that may be incurred by persons who are aware of the potential for exposure as a concomitant of employment or by other cognizant persons. Uncontrolled environments are locations where there is the exposure of individuals who have no knowledge or control of their exposure. The exposures may occur in living quarters or workplaces. For exposure in controlled environments higher field strengths are admissible. In addition the duration of exposure is considered. Due to the influence of frequency on important parameters, as the penetration depth of the electromagnetic fields into the human body and the absorption capability of different tissues, the limits in general vary with frequency.

4.3. Distinction between Maximum Permissible Exposure and SAR Limits

The biological relevant parameter describing the effects of electromagnetic fields in the frequency range of interest is the specific absorption rate SAR (dimension: power/mass). It is a measure of the power absorbed per unit mass. The SAR may be spatially averaged over the total mass of an exposed body or its parts. The SAR is calculated from the r.m.s. electric field strength E inside the human body, the conductivity σ and the mass density ρ of the biological tissue:

$$SAR = \sigma \frac{E^2}{\rho} = c \frac{\partial T}{\partial t} \Big|_{t \rightarrow 0+}$$

The specific absorption rate describes the initial rate of temperature rise $\partial T / \partial t$ as a function of the specific heat capacity c of the tissue. A limitation of the specific absorption rate prevents an excessive heating of the human body by electromagnetic energy.

As it is sometimes difficult to determine the SAR directly by measurement (e.g. whole body averaged SAR), the standard specifies more readily measurable maximum permissible exposures in terms of external electric E and magnetic field strength H and power density S , derived from the SAR limits. The limits for E , H and S have been fixed so that even under worst case conditions, the limits for the specific absorption rate SAR are not exceeded.

For the relevant frequency range the maximum permissible exposure may be exceeded if the exposure can be shown by appropriate techniques to produce SAR values below the corresponding limits.

4.4. SAR Limit

In this report the comparison between the American exposure limits and the measured data is made using the spatial peak SAR; the power level of the device under test guarantees that the whole body averaged SAR is not exceeded.

Having in mind a worst case consideration, the SAR limit is valid for uncontrolled environment and mobile respectively portable transmitters. According to Table 1 the SAR values have to be averaged over a mass of 1 g (SAR_{1g}) with the shape of a cube.

Standard	Status	SAR limit (W/kg)
IEEE C95.1	In force	1.6

Table 1: Relevant spatial peak SAR limit averaged over a mass of 1 g

5. The FCC Measurement Procedure and IC Measurement Procedure

The Federal Communications Commission (FCC) has published a report and order on the 1st of August 1996 [FCC 1996], which requires routine dosimetric assessment of mobile telecommunications devices, either by laboratory measurement techniques or by computational modeling, prior to equipment authorization or use. In 2001 the Commission's Office of Engineering and Technology has released Edition 01-01 of Supplement C to OET Bulletin 65. This revised edition, which replaces Edition 97-01, provides additional guidance and information for evaluating compliance of mobile and portable devices with FCC limits for human exposure to radiofrequency emissions [FCC 2001]. The following KDB Publications have also been used:

- 447498 – Mobile and portable device RF Exposure Procedures
- 648474 – SAR Evaluation Considerations for Handsets with Multiple Transmitters and Antennas
- 941225 – SAR Measurement Procedures for 3G Devices
- 450824 – SAR Probe Calibration and System Verification Considerations for Measurements at 150 MHz – 3 GHz

The Industry Canada (IC) measurement procedure follows many of the same procedures as the FCC.

5.1. General Requirements

The test shall be performed in a laboratory with an environment which avoids influence on SAR measurements by ambient EM sources and any reflection from the environment itself. The ambient temperature shall be in the range of 20°C to 26°C and 30-70% humidity.

5.2. Body-worn and Other Configurations

Phantom Requirements

For body-worn and other configurations a flat phantom shall be used which is comprised of material with electrical properties similar to the corresponding tissues.

Test Position

The body-worn configurations shall be tested with the supplied accessories (belt-clips, holsters, etc.) attached to the device in normal use configuration. Devices with a headset output shall be tested with a connected headset.

Test to be Performed

For purpose of determining test requirements, accessories may be divided into two categories: those that do not contain metallic components and those that do. For multiple accessories that do not contain metallic components, the device may be tested only with that accessory which

provides the closest spacing to the body. For multiple accessories that contain metallic components, the device must be tested with each accessory that contains a unique metallic component. If multiple accessories share an identical metallic component, only the accessory that provides the closest spacing to the body must be tested. If the manufacturer provides none body-worn accessories a separation distance of 1.5 cm between the back of the device and the flat phantom is recommended. Other separation distances may be used, but they shall not exceed 2.5 cm. In these cases, the device may use body-worn accessories that provide a separation distance greater than that tested for the device provided however that the accessory contains no metallic components.

For devices with retractable antenna the SAR test shall be performed with the antenna fully extended and fully retracted. Other factors that may affect the exposure shall also be tested. For example, optional antennas or optional battery packs which may significantly change the volume, lengths, flip open/closed, etc. of the device, or any other accessories which might have the potential to considerably increase the peak spatial-average SAR value.

5.3. Procedure for assessing the peak spatial-average SAR

Step 1: Power reference measurement:

Prior to the SAR test, a local SAR measurement should be taken at a user-selected spatial reference point to monitor power variations during testing. For example, this power reference point can be spaced 10 mm or less in the normal direction from the liquid-shell interface and within \pm 10 mm transverse to the normal line at the ear reference point.

Step 2: Area scan

The measurement procedures for evaluating SAR associated with wireless handsets typically start with a coarse measurement grid in order to determine the approximate location of the local peak SAR values. This is referred to as the "area scan" procedure. The SAR distribution is scanned along the inside surface of typically half of the head of the phantom but at least larger than the areas projected (normal to the phantom's surface) by the handset and antenna. An example grid is given in Figure 4. The distance between the measured points and phantom surface should be less than 8 mm, and should remain constant (variation less than \pm 1 mm) during the entire scan in order to determine the locations of the local peak SAR with sufficient precision. The distance between the measurement points should enable the detection of the location of local maximum with an accuracy of better than half the linear dimension of the tissue cube after interpolation. The resolution can also be tested using the functions in Annex E (see E.5.2). The approximate locations of the peak SARs should be determined from area scan. Since a given amplitude local peak with steep gradients may produce lower spatial-average SAR than slightly lower amplitude peaks with less steep gradients, it is necessary to evaluate the other peaks as well. However, since the spatial gradients of local SAR peaks are a function of wavelength inside the tissue simulating liquid and incident magnetic field strength, it is not necessary to evaluate peaks that are less than 2dB of the local maximum. Two-dimensional spline algorithms [Press, et al, 1996],

[Brishoual, 2001] are typically used to determine the peaks and gradients within the scanned area. If the peak is closer than one-half of the linear dimension of the 1 g or 10 g tissue cube to the scan border, the measurement area should be enlarged if possible, e.g., by tilting the probe or the phantom (see Figure 5).




Figure 4 – Example of an area scan including the position of the handset. The scanned area (white dots) should be larger than the area projected by the handset and antenna.

Step 3: Zoom scan

In order to assess the peak spatial SAR values averaged over a 1 g and 10 g cube, fine resolution volume scans, called "zoom scans", are performed at the peak SAR locations determined during the "area scan." The zoom scan volume should have at least 1.5 times the linear dimension of either a 1 g or a 10 g tissue cube for whichever peak spatial-average SAR is being evaluated. The peak local SAR locations that were determined in the area scan (interpolated value) should be on the centerline of the zoom scans. The centerline is the line that is normal to the surface and in the center of the volume scan. If this is not possible, the zoom scan can be shifted but not by more than half the dimension of the 1 g or a 10 g tissue cube.

The maximum spatial-average SAR is determined by a numerical analysis of the SAR values obtained in the volume of the zoom scan, whereby interpolation (between measured points) and extrapolation (between surface and closest measured points) routines should be applied. A 3-D spline algorithm [Press, et al, 1996], [Kreyszig, 1983], [Brishoual, 2001] can be used for interpolation and a trapezoidal algorithm for the integration (averaging). Scan resolutions of larger than 2 mm can be used provided the uncertainty is evaluated according to E (see E.5).

In some areas of the phantom, such as the jaw and upper head region, the angle of the probe with respect to the line normal to the surface might become large, e.g., at angles larger than $\pm 30^\circ$ (see Figure 5), which may increase the boundary effect to an unacceptable level. In these cases, a change in the orientation of the probe and/or the phantom is recommended during the zoom scan

so that the angle between the probe housing tube and the line normal to the surface is significantly reduced (<30°).

Step 4: Power reference measurement

The local SAR should be measured at exactly the same location as in Step 1. The absolute value of the measurement drift (the difference between the SAR measured in Step 4 and Step 1) should be recorded in the uncertainty budget. It is recommended that the drift be kept within ± 5%. If this is not possible, even with repeat testing, additional information may be used to demonstrate the power stability during the test. Power reference measurements can be taken after each zoom scan, if more than one zoom scan is needed. However, the drift should always be referred to the initial state with fully charged battery.

5.4. Determination of the largest peak spatial-average SAR

In order to determine the largest value of the peak spatial-average SAR of a handset, all device positions, configurations and operational modes should be tested for each frequency band according to steps 1 to 3 below.

Step 1: The tests of 6.4 should be conducted at the channel that is closest to the center of the transmit frequency band (f_c) for:

- a) all device positions (cheek and tilt, for both left and right sides of the SAM phantom,
- b) all configurations for each device position in (a), e.g. antenna extended and retracted, and
- c) all operational modes for each device position in (a) and configuration in (b) in each frequency band, e.g. analog and digital.

If more than three frequencies need to be tested, (i.e., $N_c > 3$), then all frequencies, configurations and modes must be tested for all of the above positions.

Step 2: For the condition providing highest spatial peak SAR determined in Step 1 conduct all tests of 6.4 at all other test frequencies, e.g. lowest and highest frequencies. In addition, for all other conditions (device position, configuration and operational mode) where the spatial peak SAR value determined in Step 1 is within 3dB of the applicable SAR limit, it is recommended that all other test frequencies should be tested as well¹.

Step 3: Examine all data to determine the largest value of the peak spatial-average SAR found in Steps 1 to 2.

6. The Measurement System

6.1. Robot system specification

The SAR measurement system being used is the SPEAG DASY52 system, which consists of a Stäubli TX90XL 6-axis robot arm and CS8c controller, SPEAG SAR Probe, Data Acquisition Electronics, and SAM Twin Phantom. The robot is used to articulate the probe to programmed positions inside the phantom to obtain the SAR readings from the EUT.

The system is controlled remotely from a PC, which contains the software to control the robot and data acquisition equipment. The software also displays the data obtained from test scans.




Figure 5: Schematic diagram of the SAR measurement system

In operation, the system first does an area (2D) scan at a fixed depth within the liquid from the inside wall of the phantom. When the maximum SAR point has been found, the system will then carry out a 3D scan centered at that point to determine volume averaged SAR level.

6.2. Isotropic E-Field Probe for Dosimetric Measurements

The probes are constructed using three orthogonal dipole sensors arranged on an interlocking, triangular prism core. The probes have built-in shielding against static charges and are contained within a PEEK cylindrical enclosure material at the tip. Probe calibration is described in the probe's calibration certificate (see appendix C).

6.3. Data Acquisition Electronics

The DAE contains a signal amplifier, multiplexer, 16bit A/D converter and control logic. It uses an optical link for communication with the DASY5 system. The DAE has a dynamic range of -100 to 300 mV. It also contains a two step probe touch detector for mechanical surface detection and emergency robot stop.

6.4. Phantoms

The Twin SAM V4.0 Phantom is designed to specifications defined in IEEE 1528 and IEC 62209-1. It enables the dosimetric evaluation of left and right hand phone usage as well as body mounted usage at the flat phantom region.

Additionally, the Oval Flat ELI V4.0 Phantom is designed to specification defined in IEEE 1528 and IEC 62209-2. It enables the dosimetric evaluation of body mounted usage.

6.5. Interpolation and Extrapolation schemes

The interpolation, extrapolation and maximum search routines are all based on the modified Quadratic Shepard's method. The interpolation scheme combines a least-square fitted function method and a weighted average method which are the two basic types of computational interpolation and approximation. The routines construct a once-continuously differentiable function that interpolates the measurement values.

7. Uncertainty Assessment

Measurement uncertainty values were evaluated for SAR measurements performed by Cetecom Inc. The uncertainty values for components specified in *FCC Supplement C (01-01) to OET Bulletin 65 (97-01)* were evaluated according to the procedures of *IEEE 1528-200X December 29, 2002, NIST 1297 1994 edition and ISO Guide to the Expression of Uncertainty in Measurements (GUM)*.

7.1. Measurement Uncertainty Budget

<i>a</i>	<i>b</i>	<i>c</i>	<i>d</i>	<i>e=f(d,k)</i>	<i>f</i>	<i>g = c x f / e</i>	<i>k</i>
Uncertainty Component	Sec.	Tol. (± %)	Prob. Dist.	Div.	<i>c_i</i> (1-g)	1-g <i>u_i</i> (±%)	<i>v_i</i>
Measurement System							
Probe Calibration	E2.1	5.5	N	1	1	5.5	∞
Axial Isotropy	E2.2	4.7	R	√3	0.7	1.9	∞
Hemispherical Isotropy	E2.2	9.6	R	√3	0.7	3.9	∞
Boundary Effect	E2.3	1.0	R	√3	1	0.6	∞
Linearity	E2.4	4.7	R	√3	1	2.7	∞
System Detection Limits	E2.5	1.0	R	√3	1	0.6	∞
Readout Electronics	E2.6	0.3	N	1	1	0.3	∞
Response Time	E2.7	0.8	R	√3	1	0.5	∞
Integration Time	E2.8	2.6	R	√3	1	1.5	∞
RF Ambient Noise	E6.1	3.0	R	√3	1	1.7	∞
RF Ambient Reflections	E6.1	3.0	R	√3	1	1.7	∞
Probe Positioner Mechanical Tolerance	E6.2	0.4	R	√3	1	0.2	∞
Probe Positioning with respect to Phantom Shell	E6.3	2.9	R	√3	1	1.7	∞
Extrapolation, interpolation and Integration Algorithms for Max. SAR Evaluation	E5.2	1.0	R	√3	1	0.6	∞
Test sample Related							
Test Sample Positioning	E4.2	2.9	N	1	1	2.9	145
Device Holder Uncertainty	E4.1	3.6	N	1	1	3.6	5
Output Power Variation - SAR drift measurement	6.6.2	5.0	R	√3	1	2.9	∞
Phantom and Tissue Parameters							
Phantom Uncertainty (shape and thickness tolerances)	E3.1	4.0	R	√3	1	2.3	∞
Liquid Conductivity Target - tolerance	E3.2	5.0	R	√3	0.7	1.8	∞
Liquid Conductivity - measurement uncertainty	E3.3	2.5	N	1	0.7	1.6	∞
Liquid Permittivity Target tolerance	E3.2	5.0	R	√3	0.6	1.7	∞
Liquid Permittivity - measurement uncertainty	E3.3	2.5	N	1	0.6	1.5	∞
Combined Standard Uncertainty							
Expanded Uncertainty (95% CONFIDENCE INTERVAL)				<i>k</i> = 2.00705		± 10.7%	
						± 21.4%	

8. Test results summary

8.1. Conducted Average Output Power

Measurement uncertainty for conducted measurements is $\pm 0.5\text{dB}$

In Mobile Hotspot UI Mode there is software power back-off in some bands to comply with RF exposure requirements with a 10mm distance.

CDMA

Band	Channel	Frequency [MHz]	Average Power [dBm]			
			SO55		SO32	
			RC 1/1	RC 3/3	SCH0 Disabled	SCH0 Enabled
BC0	1013	824.7	23.57	23.53	23.55	23.5
	384	836.52	23.67	23.73	23.74	23.75
	777	848.31	23.65	23.6	23.6	23.57
BC10	476	817.9	23.75	23.75	23.7	23.71
	580	820.5	23.75	23.78	23.79	23.76
	684	823.1	23.7	23.72	23.73	23.5

8.2. Test Positions and Configurations

SAR evaluation is conducted for body positions including front, rear, left edge, right edge, and bottom edge. All positions were with a 10 mm air gap between the EUT and phantom. Each side of the EUT with the transmitting antenna within 2.5 cm of that side is tested. The area scan is over the transmitting antenna. See Appendix B for test setup photos.

If the SAR value on the middle channel was more than 3dB below the limit, high and low channels were not evaluated.

SAR evaluation for TDSO322 with SCH0 enabled is not required because the conducted average output power is less than $\frac{1}{4}$ dB with SCH0 disabled. SAR evaluation for Loopback SO55 is not required when the conducted average output power is less than $\frac{1}{4}$ dB for TDSO32 with SCH0 enabled.

8.3. SAR Results for Body

Band	Operation Mode	Channel	Frequency (MHz)	Position	SAR 1g (W/kg)	Results (Appendix A)	Positioning Photo (Appendix B)
CDMA BC0	TDSO32, SCH0 Disabled	384	836.52	Front	0.410	Plot 1	Photo 1
				Rear	0.718	Plot 2	Photo 2
				Left Edge	0.299	Plot 3	Photo 3
				Right Edge	0.369	Plot 4	Photo 4
				Bottom Edge	0.093	Plot 5	Photo 5
CDMA BC10	TDSO32, SCH0 Disabled	580	820.5	Front	0.484	Plot 6	Photo 1
				Rear	0.825	Plot 7	Photo 2
				Left Edge	0.365	Plot 8	Photo 3
				Right Edge	0.420	Plot 9	Photo 4
				Bottom Edge	0.101	Plot 10	Photo 5
		476	817.9	Rear	0.834	Plot 11	Photo 2
		684	823.1	Rear	0.788	Plot 12	Photo 2

8.4. Dipole verification

Prior to formal testing at each frequency a system verification was performed in accordance with IEEE 1528. The 1 Watt reference SAR value is taken from the Speag dipole calibration report as required by FCC KDB 450824 D01. All of the testing described in this report was performed within 24 hours of the system verification. The following results were obtained:

Date	Frequency (MHz)	CW input at dipole feed (Watts)	1g SAR (W/kg)	Reference Speag Report		Results (Appendix A)
				1 Watt reference SAR value (W/kg)	Difference reference SAR value to normalized SAR	
2011-10-06	835	1	10.9	10.2	3.92%	Plot 13
2011-10-07	835	1	10.5	10.2	2.94%	Plot 14

9. References

1. [FCC 2001] Federal Communications Commission: Evaluating Compliance with FCC Guidelines for Human Exposure to Radiofrequency Electromagnetic Fields, Supplement C (Edition 01-01) to OET Bulletin 65 (Edition 97-01), FCC, 2001.
2. [IEEE 2005] IEEE Std C95.1-2005: IEEE Standard for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz, Inst. of Electrical and Electronics Engineers, Inc., 2005.
3. [IEEE 2003] IEEE Std 1528-2003: IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head From Wireless Communications Devices: Measurement Techniques. Inst. of Electrical and Electronics Engineers, Inc., 2003.
4. [NIST 1994] NIST: Guidelines for Evaluating and Expressing the Uncertainty of NIST Measurement Results, Technical Note 1297 (TN1297), United States Department of Commerce Technology Administration, National Institute of Standards and Technology, 1994.
5. [IC 2010] RSS-102: Radio Frequency (RF) Exposure Compliance of Radiocommunication Apparatus (All Frequency Bands), Industry Canada, 2010.
6. [IEEE 2002] IEEE Std C95.3-2002: IEEE Recommended Practice for the Measurement of Potentially Hazardous Electromagnetic Fields – RF and Microwave, 2002.

Test Report #:

SAR_CETE4_015_11001_RDS41CW

FCC ID:

L6ARDS40CW

IC ID:

2503A-RDS40CW

Date of Report :

2011-10-28

Page 21 of 21



10. Report History

2011-10-28: Original Report