

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 1 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Annex A: Measurement data and plots

A.1 MIF validation plots

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 2 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 12:00:00 AM

Test Laboratory: BlackBerry RTS

MIF_measurements_03_18-24_14

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ; Calibrated: 1/17/2014
- Sensor-Surface: 0mm (Fix Surface), z = 2.5
- Electronics: DAE3 Sn473; Calibrated: 1/15/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.6(1115); SEMCAD X 14.6.9(7117)

Configuration/MIF Measurements/MIF_AM80%_1KHz_Measurement

Calibration Factors: 1.089, 1.089; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-1.29 dB		0.00 dB	Power High
PMF	3.81 dB	1.551	0.00 dB	Power High
Detector Level	10.61 dBm		0.00 dB	Power High
RFAIP	9.32 dBm		0.00 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements/MIF_AM10%_1KHz_Measurement

Calibration Factors: 1.089, 1.089; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.22 dB		0.00 dB	Power OK
PMF	0.78 dB	1.094	0.00 dB	Power OK
Detector Level	10.46 dBm		0.00 dB	Power OK
RFAIP	1.24 dBm		0.00 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 3 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements/MIF_AM1%_1KHz_Measurement

Calibration Factors: 1.090, 1.089; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-19.18 dB		0.00 dB	Power OK
PMF	0.08 dB	1.010	0.00 dB	Power OK
Detector Level	10.43 dBm		0.00 dB	Power OK
RFAIP	-8.75 dBm		0.00 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements/MIF_GSM_Measurement

Calibration Factors: 1.089, 1.089; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	3.44 dB		0.00 dB	Power OK
PMF	9.86 dB	3.112	0.01 dB	Power OK
Detector Level	-0.64 dBm		0.00 dB	Power OK
RFAIP	2.80 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF

Measurements/MIF_WCDMA_Voice_AMR12_2kps_Measurement

Calibration Factors: 1.089, 1.089; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-25.91 dB		0.18 dB	Power OK
PMF	0.06 dB	1.007	0.00 dB	Power OK
Detector Level	0.11 dBm		0.02 dB	Power OK
RFAIP	-25.80 dBm		0.19 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 4 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 12:00:00 AM

Test Laboratory: BlackBerry RTS

MIF_WiFi_measurements_11_14_14

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 333CB445

Communication System: UID 0, CW (0); Frequency: 0.001 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ; Calibrated: 1/17/2014
- Sensor-Surface: 0mm (Fix Surface), $z = 2.5$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM80%_1KHz_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-1.30 dB		0.00 dB	
PMF	3.81 dB	1.550	0.00 dB	
Detector Level	8.07 dBm		0.00 dB	
RFAIP	6.78 dBm		0.00 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM10%_1KHz_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 5 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.30 dB		0.00 dB	
PMF	0.77 dB	1.093	0.00 dB	
Detector Level	8.09 dBm		0.00 dB	
RFAIP	-1.20 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM1%_1KHz_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-19.26 dB		0.01 dB	
PMF	0.09 dB	1.010	0.00 dB	
Detector Level	8.06 dBm		0.00 dB	
RFAIP	-11.20 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_1Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-13.06 dB		0.09 dB	
PMF	0.44 dB	1.052	0.04 dB	
Detector Level	5.11 dBm		0.02 dB	
RFAIP	-7.95 dBm		0.11 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_2Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-12.28 dB		0.08 dB	
PMF	0.48 dB	1.056	0.03 dB	
Detector Level	5.22 dBm		0.01 dB	
RFAIP	-7.06 dBm		0.09 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 6 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_5.5Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.76 dB		0.06 dB	
PMF	0.67 dB	1.080	0.05 dB	
Detector Level	5.41 dBm		0.01 dB	
RFAIP	-4.35 dBm		0.07 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_11Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.99 dB		0.11 dB	
PMF	0.80 dB	1.096	0.04 dB	
Detector Level	5.31 dBm		0.01 dB	
RFAIP	-3.68 dBm		0.12 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_6Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.07 dB		0.04 dB	
PMF	0.89 dB	1.108	0.01 dB	
Detector Level	5.83 dBm		0.01 dB	
RFAIP	-4.24 dBm		0.05 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_9Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.40 dB		0.08 dB	
PMF	1.05 dB	1.129	0.01 dB	
Detector Level	5.70 dBm		0.01 dB	
RFAIP	-3.70 dBm		0.09 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 7 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_18Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.13 dB		0.14 dB	
PMF	1.08 dB	1.132	0.03 dB	
Detector Level	5.52 dBm		0.00 dB	
RFAIP	-2.61 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.62 dB		0.13 dB	
PMF	1.91 dB	1.246	0.05 dB	
Detector Level	2.40 dBm		0.01 dB	
RFAIP	-6.23 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_6.5Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.94 dB		0.06 dB	
PMF	0.95 dB	1.116	0.02 dB	
Detector Level	4.13 dBm		0.01 dB	
RFAIP	-6.81 dBm		0.06 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_39Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.94 dB		0.14 dB	
PMF	1.32 dB	1.164	0.01 dB	
Detector Level	2.02 dBm		0.01 dB	
RFAIP	-5.93 dBm		0.15 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 8 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_65Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.91 dB		0.13 dB	
PMF	1.63 dB	1.206	0.01 dB	
Detector Level	0.90 dBm		0.01 dB	
RFAIP	-7.01 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_6Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.19 dB		0.09 dB	
PMF	0.95 dB	1.116	0.05 dB	
Detector Level	2.92 dBm		0.10 dB	
RFAIP	-7.27 dBm		0.19 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_24Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.98 dB		0.15 dB	
PMF	1.47 dB	1.184	0.02 dB	
Detector Level	1.95 dBm		0.01 dB	
RFAIP	-6.03 dBm		0.16 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.92 dB		0.11 dB	
PMF	1.77 dB	1.227	0.02 dB	
Detector Level	-0.05 dBm		0.01 dB	
RFAIP	-8.97 dBm		0.12 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 9 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_6.5Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-11.07 dB		0.03 dB	
PMF	1.04 dB	1.128	0.02 dB	
Detector Level	3.06 dBm		0.01 dB	
RFAIP	-8.01 dBm		0.04 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_39Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.14 dB		0.14 dB	
PMF	1.43 dB	1.179	0.04 dB	
Detector Level	1.61 dBm		0.01 dB	
RFAIP	-6.53 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_65Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.11 dB		0.14 dB	
PMF	1.67 dB	1.212	0.01 dB	
Detector Level	-0.79 dBm		0.01 dB	
RFAIP	-8.89 dBm		0.15 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_6.5Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.21 dB		0.05 dB	
PMF	0.83 dB	1.101	0.00 dB	
Detector Level	-0.89 dBm		0.02 dB	
RFAIP	-11.10 dBm		0.07 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 10 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_39Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.23 dB		0.16 dB	
PMF	0.99 dB	1.121	0.08 dB	
Detector Level	-1.26 dBm		0.00 dB	
RFAIP	-9.50 dBm		0.17 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.80 dB		0.16 dB	
PMF	1.94 dB	1.250	0.02 dB	
Detector Level	-2.07 dBm		0.01 dB	
RFAIP	-10.87 dBm		0.17 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 11 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

A.2 Dipole validation

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 12 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 6:49:57 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_835 validation_11_05_14

DUT: HAC-Dipole 835 MHz; Type: CD835V3; Serial: 1089

Communication System: UID 0, CW For MIF; Frequency: 835 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 9.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

CD835 Dipole E-Field measurement (E-field scan for ANSI C63.19-2011 compliance)/E Scan - measurement distance from the probe sensor center to CD835 = 15mm/Hearing Aid Compatibility Test at 15mm distance (41x361x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 105.9 V/m; Power Drift = -0.00 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 110.1 V/m

Near-field category: M4 (AWF 0 dB)

PMF scaled E-field

Grid 1 M4 105.2 V/m	Grid 2 M4 107.6 V/m	Grid 3 M4 107.2 V/m
Grid 4 M4 61.73 V/m	Grid 5 M4 62.38 V/m	Grid 6 M4 60.89 V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 13 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW


Grid 7 M4 107.0 V/m	Grid 8 M4 110.1 V/m	Grid 9 M4 109.1 V/m
--------------------------------------	--------------------------------------	--------------------------------------

Cursor:

Total = 68.35 V/m

E Category: M4

Location: 10, -90, 9.7 mm



0 dB = 110.1 V/m = 40.84 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 14 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 7:48:20 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_1880 validation_11_05_14

DUT: HAC Dipole 1880 MHz; Type: CD1880V3; Serial: 1068

Communication System: UID 0, CW For MIF; Frequency: 1880 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 9.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

CD1880 Dipole E-Field measurement (E-field scan for ANSI C63.19-2011 compliance)/E Scan - measurement distance from the probe sensor center to CD1880 = 15mm/Hearing Aid Compatibility Test at 15mm distance (41x181x1):

Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 147.5 V/m; Power Drift = 0.06 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 84.46 V/m

Near-field category: M3 (AWF 0 dB)

PMF scaled E-field

Grid 1 M3 82.18 V/m	Grid 2 M3 84.30 V/m	Grid 3 M3 83.95 V/m
Grid 4 M3 66.91 V/m	Grid 5 M3 67.79 V/m	Grid 6 M3 67.20 V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 15 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW


Grid 7 M3	Grid 8 M3	Grid 9 M3
81.05 V/m	84.46 V/m	84.16 V/m

Cursor:

Total = 57.08 V/m


E Category: M4

Location: 10, -45, 9.7 mm



0 dB = 84.46 V/m = 38.53 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 16 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	



The green line in this figure shows the axis along which the points lie.

Comparison of 5mm and 2mm step sizes

An additional set of measurements was taken: dipole validations were performed using 5mm and 2mm step sizes. The delta between the two readings is insignificant for both field types ($< 0.4\%$ for E and 0% for H), demonstrating that 5mm is sufficient. The plots follow.

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 17 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 14/07/2005 11:35:24 AM

Page 1 of 2

Date/Time: 14/07/2005 11:35:24 AM

Lab: RIM Testing Services (RTS)

Dipole Validation 1880 MHz_E-Field 07_14_05

DUT: HAC Dipole 1880 MHz; Type: CD1880V3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1000$ kg/m³
Phantom section: H Device Section

DASY4 Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 10/12/2004
- Sensor-Surface: 0mm (Fix Surface) Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/01/2005
- Phantom: HAC Test Arch; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (5x19x1):

Measurement grid: dx=5mm, dy=5mm
Maximum value of Total (measured) = 134.8 V/m

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (41x181x1):

Measurement grid: dx=5mm, dy=5mm
Maximum value of Total field (slot averaged) = 131.0 V/m

Hearing Aid Near-Field Category: M2 (AWF 0 dB)

E in V/m (Time averaged) E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
123.2	138.1	138.4	123.2	138.1	138.4
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
80.9	92.3	92.2	80.9	92.3	92.2
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
119.8	131.0	130.7	119.8	131.0	130.7


Category	AWF (dB)	Limits for E-Field Emissions (V/m)	Limits for H-Field Emissions (A/m)
M1	0	199.5 - 354.8	0.6 - 1.07
	-5	149.6 - 266.1	0.45 - 0.8
M2	0	112.2 - 199.5	0.34 - 0.6
	-5	84.1 - 149.6	0.25 - 0.45
M3	0	63.1 - 112.2	0.19 - 0.34
	-5	47.3 - 84.1	0.15 - 0.25
M4	0	<63.1	<0.19

file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

	Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)			Page 18 (55)
	Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 14/07/2005 11:35:24 AM

Page 2 of 2



file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 19 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 14/07/2005 11:44:51 AM

Page 1 of 2

Date/Time: 14/07/2005 11:44:51 AM

Lab: RIM Testing Services (RTS)

Dipole Validation 1880 MHz_2mm step_E-Field 07_14_05

DUT: HAC Dipole 1880 MHz; Type: CD1880V3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1000$ kg/m³
Phantom section: H Device Section

DASY4 Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 10/12/2004
- Sensor-Surface: 0mm (Fix Surface) Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/01/2005
- Phantom: HAC Test Arch; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (11x46x1):

Measurement grid: dx=2mm, dy=2mm
Maximum value of Total (measured) = 138.0 V/m

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (101x451x1):

Measurement grid: dx=2mm, dy=2mm
Maximum value of Total field (slot averaged) = 131.2 V/m

Hearing Aid Near-Field Category: M2 (AWF 0 dB)

E in V/m (Time averaged) E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
123.1	138.6	138.6	123.1	138.6	138.6
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
81.4	92.1	91.6	81.4	92.1	91.6
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
121.3	131.2	131.0	121.3	131.2	131.0


Category	AWF (dB)	Limits for E-Field Emissions (V/m)	Limits for H-Field Emissions (A/m)
M1	0	199.5 - 354.8	0.6 - 1.07
	-5	149.6 - 266.1	0.45 - 0.8
M2	0	112.2 - 199.5	0.34 - 0.6
	-5	84.1 - 149.6	0.25 - 0.45
M3	0	63.1 - 112.2	0.19 - 0.34
	-5	47.3 - 84.1	0.15 - 0.25
M4	0	<63.1	<0.19

file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 20 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 14/07/2005 11:44:51 AM

Page 2 of 2



file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 21 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

A.3 RF emission field plots

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 22 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/5/2014 9:07:15 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM850

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, GSM 850; Frequency: 824.2 MHz, Frequency: 836.8 MHz,
Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility

Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 74.26 V/m; Power Drift = 0.03 dB

Applied MIF = 3.44 dB

RF audio interference level = 38.98 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 38.54 dBV/m	Grid 2 M4 39.28 dBV/m	Grid 3 M4 38.94 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		23 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

38.18 dBV/m	38.98 dBV/m	38.82 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
37.91 dBV/m	38.76 dBV/m	38.45 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.89 dBV/m

E Category: M4

Location: 25, -25, 8.7 mm

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility

Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 76.91 V/m; Power Drift = 0.00 dB

Applied MIF = 3.44 dB

RF audio interference level = 39.38 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
38.56 dBV/m	39.64 dBV/m	39.36 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
38.24 dBV/m	39.38 dBV/m	39.28 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
37.87 dBV/m	39.17 dBV/m	39.08 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 24 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.37 dBV/m

E Category: M4

Location: 25, -25, 8.7 mm

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 71.97 V/m; Power Drift = -0.04 dB

Applied MIF = 3.44 dB

RF audio interference level = 38.87 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 38.17 dBV/m	Grid 2 M4 39.2 dBV/m	Grid 3 M4 38.97 dBV/m
Grid 4 M4 37.6 dBV/m	Grid 5 M4 38.87 dBV/m	Grid 6 M4 38.76 dBV/m
Grid 7 M4 37.08 dBV/m	Grid 8 M4 38.45 dBV/m	Grid 9 M4 38.35 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m


Cursor:

Total = 35.87 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 25 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

E Category: M4

Location: 25, -25, 8.7 mm



0 dB = 92.08 V/m = 39.28 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 26 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/6/2014 10:05:38 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 850_telecoil

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, GSM 850 (0); Frequency: 824.2 MHz, Frequency: 836.8 MHz,
Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan_telecoil/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 74.90 V/m; Power Drift = 0.07 dB

Applied MIF = 3.44 dB

RF audio interference level = 39.00 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 38.23 dBV/m	Grid 2 M4 39.1 dBV/m	Grid 3 M4 38.91 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		27 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

38.13 dBV/m	39 dBV/m	38.82 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
38.54 dBV/m	38.91 dBV/m	38.5 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.12 dBV/m

E Category: M4

Location: 25, -10, 8.7 mm

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan_telecoil/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 77.41 V/m; Power Drift = -0.00 dB

Applied MIF = 3.44 dB

RF audio interference level = 39.29 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
38.22 dBV/m	39.41 dBV/m	39.32 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
37.98 dBV/m	39.29 dBV/m	39.17 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
37.78 dBV/m	38.93 dBV/m	38.79 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 28 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 35.48 dBV/m

E Category: M4

Location: 25, -10, 8.7 mm

Device E-Field GSM850 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan_telecoil/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 73.13 V/m; Power Drift = -0.10 dB

Applied MIF = 3.44 dB

RF audio interference level = 38.63 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 37.7 dBV/m	Grid 2 M4 39.03 dBV/m	Grid 3 M4 38.95 dBV/m
Grid 4 M4 37.26 dBV/m	Grid 5 M4 38.63 dBV/m	Grid 6 M4 38.53 dBV/m
Grid 7 M4 36.49 dBV/m	Grid 8 M4 37.96 dBV/m	Grid 9 M4 37.85 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 35.02 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 29 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

E Category: M4
Location: 25, -10, 8.7 mm



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 30 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 9:34:31 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM1900

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, GSM 1900; Frequency: 1850.2 MHz, Frequency: 1880 MHz,
Frequency: 1909.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility

Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 28.50 V/m; Power Drift = -0.17 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.45 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4 25.4 dBV/m	Grid 2 M3 30.5 dBV/m	Grid 3 M3 30.51 dBV/m
Grid 4 M4	Grid 5 M3	Grid 6 M3

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		31 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

28.6 dBV/m	32.45 dBV/m	32.45 dBV/m
Grid 7 M3	Grid 8 M3	Grid 9 M3
30.8 dBV/m	33.72 dBV/m	33.63 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 24.06 dBV/m

E Category: M4

Location: 25, -25, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011:
15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility
Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 28.34 V/m; Power Drift = -0.06 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.57 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4	Grid 2 M3	Grid 3 M3
26.48 dBV/m	30.87 dBV/m	30.96 dBV/m
Grid 4 M4	Grid 5 M3	Grid 6 M3
29.06 dBV/m	32.57 dBV/m	32.57 dBV/m
Grid 7 M3	Grid 8 M3	Grid 9 M3
31.21 dBV/m	33.9 dBV/m	33.83 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 32 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 22.12 dBV/m

E Category: M4

Location: 25, -25, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011:
15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility
Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 26.88 V/m; Power Drift = -0.04 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.27 dBV/m

Emission category: M3

MIF scaled E-field


Grid 1 M4 25.58 dBV/m	Grid 2 M3 30.27 dBV/m	Grid 3 M3 30.35 dBV/m
Grid 4 M4 28.7 dBV/m	Grid 5 M3 32.27 dBV/m	Grid 6 M3 32.27 dBV/m
Grid 7 M3 31.42 dBV/m	Grid 8 M3 33.9 dBV/m	Grid 9 M3 33.81 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 24.80 dBV/m

E Category: M4
 Location: 25, -25, 8.7 mm



0 dB = 48.54 V/m = 33.72 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 34 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/6/2014 9:37:42 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Telecoil

DUT: BlackBerry Smartphone; Type: Sample; Serial: 2FFEDD03

Communication System: UID 0, GSM 1900 (0); Frequency: 1850.2 MHz, Frequency: 1880 MHz, Frequency: 1909.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA; DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011:
15 mm from Probe Center to the Device_Low_Chan_telecoil/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 28.36 V/m; Power Drift = -0.39 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.63 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4 28.33 dBV/m	Grid 2 M3 32.28 dBV/m	Grid 3 M3 32.25 dBV/m
Grid 4 M3	Grid 5 M3	Grid 6 M3

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		35 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

30.83 dBV/m	33.63 dBV/m	33.57 dBV/m
Grid 7 M3	Grid 8 M3	Grid 9 M3
33.09 dBV/m	34.5 dBV/m	34.2 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 23.26 dBV/m

E Category: M4

Location: 25, -10, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011:
15 mm from Probe Center to the Device_Mid_Chan_telecoil/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 28.41 V/m; Power Drift = 0.07 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.59 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4	Grid 2 M3	Grid 3 M3
28.88 dBV/m	32.38 dBV/m	32.37 dBV/m
Grid 4 M3	Grid 5 M3	Grid 6 M3
30.89 dBV/m	33.59 dBV/m	33.57 dBV/m
Grid 7 M3	Grid 8 M3	Grid 9 M3
33.24 dBV/m	34.72 dBV/m	34.4 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 36 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 21.49 dBV/m

E Category: M4

Location: 25, -10, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe/E Scan - ER3D - 2011:
15 mm from Probe Center to the Device_High_Chan_telecoil/Hearing Aid**

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 26.23 V/m; Power Drift = -0.13 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.86 dBV/m

Emission category: M3

MIF scaled E-field


Grid 1 M4 28.01 dBV/m	Grid 2 M3 32.16 dBV/m	Grid 3 M3 32.18 dBV/m
Grid 4 M3 31.01 dBV/m	Grid 5 M3 33.86 dBV/m	Grid 6 M3 33.84 dBV/m
Grid 7 M3 34 dBV/m	Grid 8 M2 35.45 dBV/m	Grid 9 M2 35.12 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 24.64 dBV/m

E Category: M4
 Location: 25, -10, 8.7 mm



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 38 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 10:00:23 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_V

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD V; Frequency: 826.4 MHz, Frequency: 836.4 MHz, Frequency: 846.6 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band V measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 76.23 V/m; Power Drift = -0.04 dB

Applied MIF = -25.91 dB

RF audio interference level = 9.80 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 9.25 dBV/m	Grid 2 M4 10.08 dBV/m	Grid 3 M4 9.86 dBV/m
Grid 4 M4 8.77 dBV/m	Grid 5 M4 9.8 dBV/m	Grid 6 M4 9.66 dBV/m

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		39 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Grid 7 M4 8.43 dBV/m	Grid 8 M4 9.54 dBV/m	Grid 9 M4 9.34 dBV/m
---------------------------------------	---------------------------------------	---------------------------------------

Cursor:

Total = 10.08 dBV/m

E Category: M4

Location: -2.5, -25, 8.7 mm

Device E-Field UMTS band V measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 70.60 V/m; Power Drift = 0.02 dB

Applied MIF = -25.91 dB

RF audio interference level = 9.27 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 8.53 dBV/m	Grid 2 M4 9.51 dBV/m	Grid 3 M4 9.24 dBV/m
Grid 4 M4 8.14 dBV/m	Grid 5 M4 9.27 dBV/m	Grid 6 M4 9.16 dBV/m
Grid 7 M4 7.83 dBV/m	Grid 8 M4 9.09 dBV/m	Grid 9 M4 8.97 dBV/m

Cursor:

Total = 9.51 dBV/m

E Category: M4

Location: -3, -25, 8.7 mm

Device E-Field UMTS band V measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 40 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Device Reference Point: 0, 0, -6.3 mm
Reference Value = 75.34 V/m; Power Drift = -0.00 dB
Applied MIF = -25.91 dB
RF audio interference level = 9.75 dBV/m
Emission category: M4

MIF scaled E-field

Grid 1 M4 9.33 dBV/m	Grid 2 M4 10.05 dBV/m	Grid 3 M4 9.78 dBV/m
Grid 4 M4 8.77 dBV/m	Grid 5 M4 9.75 dBV/m	Grid 6 M4 9.59 dBV/m
Grid 7 M4 8.37 dBV/m	Grid 8 M4 9.44 dBV/m	Grid 9 M4 9.2 dBV/m

Cursor:
Total = 10.05 dBV/m
E Category: M4
Location: -2.5, -25, 8.7 mm



Document

**Annex A to Hearing Aid Compatibility RF Emissions Test Report
for the BlackBerry® Smartphone RGV161LW (SQW100-3)**

Page

41 (55)

Author Data

Daoud Attayi


Dates of Test

March 18-24, Nov. 05-14, 2014

Report No

RTS-6057-1411-18

FCC ID

L6ARGV160LW

0 dB = 3.190 V/m = 10.08 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 42 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/5/2014 10:20:02 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_V_Telecoil

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD V (0); Frequency: 826.4 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band V measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 67.21 V/m; Power Drift = 0.00 dB

Applied MIF = -25.91 dB

RF audio interference level = 8.60 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 7.87 dBV/m	Grid 2 M4 8.73 dBV/m	Grid 3 M4 8.51 dBV/m
Grid 4 M4 7.73 dBV/m	Grid 5 M4 8.6 dBV/m	Grid 6 M4 8.38 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 43 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	


Grid 7 M4 7.86 dBV/m	Grid 8 M4 8.32 dBV/m	Grid 9 M4 8.04 dBV/m
---------------------------------------	---------------------------------------	---------------------------------------

Cursor:

Total = 8.73 dBV/m

E Category: M4

Location: -3.5, -10, 8.7 mm



0 dB = 2.732 V/m = 8.73 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 44 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/5/2014 10:27:18 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_IV

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD IV; Frequency: 1712.4 MHz, Frequency:
1732.6 MHz, Frequency: 1752.6 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band IV measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 26.35 V/m; Power Drift = 0.10 dB

Applied MIF = -25.91 dB

RF audio interference level = 2.92 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 -4.48 dBV/m	Grid 2 M4 0.12 dBV/m	Grid 3 M4 0.21 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		45 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

-0.31 dBV/m	2.92 dBV/m	2.92 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
1.96 dBV/m	4.36 dBV/m	4.28 dBV/m

Cursor:

Total = 4.36 dBV/m

E Category: M4

Location: -6, 25, 8.7 mm

Device E-Field UMTS band IV measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 32.05 V/m; Power Drift = -0.08 dB

Applied MIF = -25.91 dB

RF audio interference level = 4.32 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
-2.57 dBV/m	2.02 dBV/m	2.09 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
0.8 dBV/m	4.32 dBV/m	4.32 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
2.83 dBV/m	5.54 dBV/m	5.47 dBV/m

Cursor:

Total = 5.54 dBV/m

E Category: M4

Location: -6.5, 25, 8.7 mm

Device E-Field UMTS band IV measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 46 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 35.49 V/m; Power Drift = -0.01 dB

Applied MIF = -25.91 dB

RF audio interference level = 5.25 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 -1.58 dBV/m	Grid 2 M4 3.17 dBV/m	Grid 3 M4 3.25 dBV/m
Grid 4 M4 1.47 dBV/m	Grid 5 M4 5.25 dBV/m	Grid 6 M4 5.25 dBV/m
Grid 7 M4 3.63 dBV/m	Grid 8 M4 6.48 dBV/m	Grid 9 M4 6.42 dBV/m

Cursor:

Total = 6.48 dBV/m

E Category: M4

Location: -6.5, 25, 8.7 mm



Document

**Annex A to Hearing Aid Compatibility RF Emissions Test Report
for the BlackBerry® Smartphone RGV161LW (SQW100-3)**

Page

47 (55)

Author Data

Daoud Attayi


Dates of Test

March 18-24, Nov. 05-14, 2014

Report No

RTS-6057-1411-18

FCC ID

L6ARGV160LW

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 48 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 10:44:18 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_IV_Telecoil

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD IV (0); Frequency: 1752.6 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band IV measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 34.32 V/m; Power Drift = 0.00 dB

Applied MIF = -25.91 dB

RF audio interference level = 6.14 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 1.02 dBV/m	Grid 2 M4 4.81 dBV/m	Grid 3 M4 4.82 dBV/m
Grid 4 M4 3.32 dBV/m	Grid 5 M4 6.14 dBV/m	Grid 6 M4 6.1 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 49 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014		Report No RTS-6057-1411-18	FCC ID L6ARGV160LW


Grid 7 M4 5.57 dBV/m	Grid 8 M4 7.01 dBV/m	Grid 9 M4 6.7 dBV/m
---------------------------------------	---------------------------------------	--------------------------------------

Cursor:

Total = 7.01 dBV/m

E Category: M4

Location: -3, 40, 8.7 mm



0 dB = 2.242 V/m = 7.01 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 50 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Date/Time: 11/5/2014 10:49:56 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_II

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD II; Frequency: 1852.4 MHz, Frequency: 1880 MHz, Frequency: 1907.6 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band II measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid

Compatibility Test (101x101x1): Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 39.25 V/m; Power Drift = -0.03 dB

Applied MIF = -25.91 dB

RF audio interference level = 5.82 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 -0.46 dBV/m	Grid 2 M4 4.26 dBV/m	Grid 3 M4 4.31 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		51 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

2.01 dBV/m	5.82 dBV/m	5.82 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
3.81 dBV/m	6.65 dBV/m	6.59 dBV/m

Cursor:

Total = 6.65 dBV/m

E Category: M4

Location: -6.5, 25, 8.7 mm

**Device E-Field UMTS band II measurement with ER probe/E Scan - ER3D -
2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 37.19 V/m; Power Drift = 0.06 dB

Applied MIF = -25.91 dB

RF audio interference level = 5.44 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
-0.43 dBV/m	4.19 dBV/m	4.26 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
1.93 dBV/m	5.44 dBV/m	5.44 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
4.11 dBV/m	6.53 dBV/m	6.43 dBV/m

Cursor:

Total = 6.53 dBV/m

E Category: M4

Location: -6, 25, 8.7 mm

**Device E-Field UMTS band II measurement with ER probe/E Scan - ER3D -
2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid**

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		Page 52 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW	

Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 33.44 V/m; Power Drift = 0.04 dB

Applied MIF = -25.91 dB

RF audio interference level = 4.94 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 -1.19 dBV/m	Grid 2 M4 3.23 dBV/m	Grid 3 M4 3.33 dBV/m
Grid 4 M4 1.52 dBV/m	Grid 5 M4 4.94 dBV/m	Grid 6 M4 4.94 dBV/m
Grid 7 M4 3.94 dBV/m	Grid 8 M4 6.34 dBV/m	Grid 9 M4 6.26 dBV/m

Cursor:

Total = 6.34 dBV/m

E Category: M4

Location: -6, 25, 8.7 mm



Document

**Annex A to Hearing Aid Compatibility RF Emissions Test Report
for the BlackBerry® Smartphone RGV161LW (SQW100-3)**

Page

53 (55)

Author Data

Daoud Attayi


Dates of Test

March 18-24, Nov. 05-14, 2014

Report No

RTS-6057-1411-18

FCC ID

L6ARGV160LW

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)	Page 54 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW

Date/Time: 11/5/2014 11:06:20 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_UMTS_II_Telecoil

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 2FFEDD03

Communication System: UID 0, WCDMA FDD II (0); Frequency: 1852.4 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ConvF(1, 1, 1); Calibrated: 1/17/2014;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE3 Sn472; Calibrated: 3/18/2014
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field UMTS band II measurement with ER probe/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 38.96 V/m; Power Drift = 0.00 dB

Applied MIF = -25.91 dB

RF audio interference level = 6.55 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 1.85 dBV/m	Grid 2 M4 5.65 dBV/m	Grid 3 M4 5.65 dBV/m
Grid 4 M4 3.71 dBV/m	Grid 5 M4 6.55 dBV/m	Grid 6 M4 6.51 dBV/m

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RGV161LW (SQW100-3)		55 (55)
Author Data Daoud Attayi	Dates of Test March 18-24, Nov. 05-14, 2014	Report No RTS-6057-1411-18	FCC ID L6ARGV160LW


Grid 7 M4	Grid 8 M4	Grid 9 M4
5.87 dBV/m	7.15 dBV/m	6.84 dBV/m

Cursor:

Total = 7.15 dBV/m

E Category: M4

Location: -3, 40, 8.7 mm



0 dB = 2.278 V/m = 7.15 dBV/m