

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 1 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Annex A: Measurement data and plots

A.1 MIF validation plots

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 2 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 12:00:00 AM

Test Laboratory: BlackBerry RTS

MIF_measurements_08_31_15

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 111340110

Communication System: UID 0, CW; Frequency: 835 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ; Calibrated: 1/19/2015
- Sensor-Surface: 0mm (Fix Surface), z = 2.5
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/MIF Measurements/MIF_AM80%_1KHz_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-1.29 dB		0.00 dB	
PMF	3.80 dB	1.549	0.00 dB	
Detector Level	4.32 dBm		0.00 dB	
RFAIP	3.03 dBm		0.00 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements/MIF_AM10%_1KHz_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
----------	-------------	----------	-------------	--------

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 3 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

MIF	-9.26 dB		0.00 dB
PMF	0.78 dB	1.094	0.00 dB
Detector Level	4.24 dBm		0.00 dB
RFAIP	-5.02 dBm		0.00 dB (MIF+CF+Detector Level)

Configuration/MIF Measurements/MIF_AM1%_1KHz_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-19.22 dB		0.01 dB	
PMF	0.09 dB	1.010	0.00 dB	
Detector Level	4.21 dBm		0.00 dB	
RFAIP	-15.01 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements/MIF_GSM_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	3.44 dB		0.00 dB	
PMF	9.19 dB	2.881	0.01 dB	
Detector Level	-2.52 dBm		0.00 dB	
RFAIP	0.94 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF

Measurements/MIF_WCDMA_Voice_AMR12_2kps_Mute_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-25.78 dB		0.08 dB	MIF Low
PMF	0.06 dB	1.007	0.00 dB	
Detector Level	-1.56 dBm		0.00 dB	
RFAIP	-27.34 dBm		0.08 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 4 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 12:00:00 AM

Test Laboratory: BlackBerry RTS

MIF_WiFi_measurements_08_31_15

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 111340110

Communication System: UID 0, 802.11 b (2450) (0); Frequency: 2437 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ; Calibrated: 1/19/2015
- Sensor-Surface: 0mm (Fix Surface), $z = 2.5$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA;
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM80%_1KHz_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-1.30 dB		0.00 dB	
PMF	3.81 dB	1.550	0.00 dB	
Detector Level	8.07 dBm		0.00 dB	
RFAIP	6.78 dBm		0.00 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM10%_1KHz_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
----------	-------------	----------	-------------	--------

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 5 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

MIF	-9.30 dB		0.00 dB
PMF	0.77 dB	1.093	0.00 dB
Detector Level	8.09 dBm		0.00 dB
RFAIP	-1.20 dBm		0.01 dB (MIF+CF+Detector Level)

Configuration/MIF Measurements

WiFi_VoIP/MIF_AM1%_1KHz_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-19.26 dB		0.01 dB	
PMF	0.09 dB	1.010	0.00 dB	
Detector Level	8.06 dBm		0.00 dB	
RFAIP	-11.20 dBm		0.01 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_1Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-13.06 dB		0.09 dB	
PMF	0.44 dB	1.052	0.04 dB	
Detector Level	5.11 dBm		0.02 dB	
RFAIP	-7.95 dBm		0.11 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_2Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-12.28 dB		0.08 dB	
PMF	0.48 dB	1.056	0.03 dB	
Detector Level	5.22 dBm		0.01 dB	
RFAIP	-7.06 dBm		0.09 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_5.5Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 6 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.76 dB		0.06 dB	
PMF	0.67 dB	1.080	0.05 dB	
Detector Level	5.41 dBm		0.01 dB	
RFAIP	-4.35 dBm		0.07 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11b_Rate_11Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.99 dB		0.11 dB	
PMF	0.80 dB	1.096	0.04 dB	
Detector Level	5.31 dBm		0.01 dB	
RFAIP	-3.68 dBm		0.12 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_6Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.07 dB		0.04 dB	
PMF	0.89 dB	1.108	0.01 dB	
Detector Level	5.83 dBm		0.01 dB	
RFAIP	-4.24 dBm		0.05 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_9Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.40 dB		0.08 dB	
PMF	1.05 dB	1.129	0.01 dB	
Detector Level	5.70 dBm		0.01 dB	
RFAIP	-3.70 dBm		0.09 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_18Mbps

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 7 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.13 dB		0.14 dB	
PMF	1.08 dB	1.132	0.03 dB	
Detector Level	5.52 dBm		0.00 dB	
RFAIP	-2.61 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11g_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.62 dB		0.13 dB	
PMF	1.91 dB	1.246	0.05 dB	
Detector Level	2.40 dBm		0.01 dB	
RFAIP	-6.23 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_6.5Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.94 dB		0.06 dB	
PMF	0.95 dB	1.116	0.02 dB	
Detector Level	4.13 dBm		0.01 dB	
RFAIP	-6.81 dBm		0.06 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_39Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.94 dB		0.14 dB	
PMF	1.32 dB	1.164	0.01 dB	
Detector Level	2.02 dBm		0.01 dB	
RFAIP	-5.93 dBm		0.15 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_65Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 8 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.91 dB		0.13 dB	
PMF	1.63 dB	1.206	0.01 dB	
Detector Level	0.90 dBm		0.01 dB	
RFAIP	-7.01 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_6Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.19 dB		0.09 dB	
PMF	0.95 dB	1.116	0.05 dB	
Detector Level	2.92 dBm		0.10 dB	
RFAIP	-7.27 dBm		0.19 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_24Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-7.98 dB		0.15 dB	
PMF	1.47 dB	1.184	0.02 dB	
Detector Level	1.95 dBm		0.01 dB	
RFAIP	-6.03 dBm		0.16 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11a_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.92 dB		0.11 dB	
PMF	1.77 dB	1.227	0.02 dB	
Detector Level	-0.05 dBm		0.01 dB	
RFAIP	-8.97 dBm		0.12 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_6.5Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 9 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-11.07 dB		0.03 dB	
PMF	1.04 dB	1.128	0.02 dB	
Detector Level	3.06 dBm		0.01 dB	
RFAIP	-8.01 dBm		0.04 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_39Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.14 dB		0.14 dB	
PMF	1.43 dB	1.179	0.04 dB	
Detector Level	1.61 dBm		0.01 dB	
RFAIP	-6.53 dBm		0.14 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11n_Rate_65Mbps 2

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.11 dB		0.14 dB	
PMF	1.67 dB	1.212	0.01 dB	
Detector Level	-0.79 dBm		0.01 dB	
RFAIP	-8.89 dBm		0.15 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_6Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.21 dB		0.05 dB	
PMF	0.83 dB	1.101	0.00 dB	
Detector Level	-0.89 dBm		0.02 dB	
RFAIP	-11.10 dBm		0.07 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_9Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 10 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-9.59 dB		0.07 dB	
PMF	0.94 dB	1.114	0.01 dB	
Detector Level	-1.09 dBm		0.01 dB	
RFAIP	-10.68 dBm		0.08 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_18Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.23 dB		0.16 dB	
PMF	0.99 dB	1.121	0.08 dB	
Detector Level	-1.26 dBm		0.00 dB	
RFAIP	-9.50 dBm		0.17 dB	(MIF+CF+Detector Level)

Configuration/MIF Measurements WiFi_VoIP/MIF_802.11ac_Rate_54Mbps

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-8.80 dB		0.16 dB	
PMF	1.94 dB	1.250	0.02 dB	
Detector Level	-2.07 dBm		0.01 dB	
RFAIP	-10.87 dBm		0.17 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 11 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 12:00:00 AM

Test Laboratory: BlackBerry RTS

MIF_VoLTE_measurements_09_23_15

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161340110

Communication System: UID 0, LTE 4 (0); Frequency: 1732.5 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: TCoil Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2286; ; Calibrated: 1/19/2015
- Sensor-Surface: 0mm (Fix Surface), $z = 2.5$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB1_Offset0_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-14.84 dB		0.13 dB	
PMF	1.46 dB	1.183	0.17 dB	
Detector Level	8.98 dBm		0.04 dB	
RFAIP	-5.86 dBm		0.17 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB1_Offset50_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-14.74 dB		0.15 dB	

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 12 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

PMF	1.50 dB	1.188	0.18 dB	
Detector Level	8.70 dBm		0.05 dB	
RFAIP	-6.04 dBm		0.20 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB1_Offset99_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-14.68 dB		0.26 dB	
PMF	1.48 dB	1.186	0.21 dB	
Detector Level	8.60 dBm		0.06 dB	
RFAIP	-6.07 dBm		0.33 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB50_Offset0_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-21.24 dB		0.01 dB	
PMF	0.17 dB	1.020	0.00 dB	
Detector Level	8.01 dBm		0.00 dB	
RFAIP	-13.23 dBm		0.02 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB50_Offset50_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-21.23 dB		0.02 dB	
PMF	0.17 dB	1.020	0.00 dB	
Detector Level	8.17 dBm		0.00 dB	
RFAIP	-13.06 dBm		0.03 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_QPSK_RB100_Offset0_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-21.88 dB		0.02 dB	

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 13 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

PMF	0.15 dB	1.018	0.00 dB	
Detector Level	8.13 dBm		0.00 dB	
RFAIP	-13.75 dBm		0.02 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB1_Offset0_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.42 dB		0.23 dB	
PMF	2.45 dB	1.326	0.13 dB	
Detector Level	8.00 dBm		0.04 dB	
RFAIP	-2.41 dBm		0.28 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB1_Offset50_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.41 dB		0.17 dB	
PMF	2.46 dB	1.328	0.10 dB	
Detector Level	7.89 dBm		0.01 dB	
RFAIP	-2.53 dBm		0.18 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB1_Offset99_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.32 dB		0.44 dB	
PMF	2.51 dB	1.335	0.12 dB	
Detector Level	7.91 dBm		0.03 dB	
RFAIP	-2.41 dBm		0.47 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB24_Offset0_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 14 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-16.54 dB		0.08 dB	
PMF	0.53 dB	1.063	0.03 dB	
Detector Level	6.78 dBm		0.01 dB	
RFAIP	-9.76 dBm		0.09 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB24_Offset76_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-16.38 dB		0.09 dB	
PMF	0.57 dB	1.068	0.02 dB	
Detector Level	6.98 dBm		0.00 dB	
RFAIP	-9.39 dBm		0.09 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_20MHz_BW_16QAM_RB100_Offset0_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-17.69 dB		0.06 dB	
PMF	0.34 dB	1.040	0.01 dB	
Detector Level	6.95 dBm		0.02 dB	
RFAIP	-10.74 dBm		0.07 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.07 dB		0.02 dB	
PMF	2.27 dB	1.299	0.29 dB	
Detector Level	7.97 dBm		0.04 dB	
RFAIP	-2.10 dBm		0.07 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 15 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Measurements/MIF_VoLTE_10MHz_BW_16QAM_RB1_Offset49_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.10 dB		0.06 dB	
PMF	2.32 dB	1.307	0.11 dB	
Detector Level	8.32 dBm		0.03 dB	
RFAIP	-1.78 dBm		0.10 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_5MHz_BW_16QAM_RB1_Offset24_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.74 dB		0.40 dB	
PMF	2.57 dB	1.345	0.25 dB	
Detector Level	7.99 dBm		0.04 dB	
RFAIP	-2.75 dBm		0.44 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_3MHz_BW_16QAM_RB1_Offset14_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.22 dB		0.09 dB	
PMF	2.15 dB	1.281	0.19 dB	
Detector Level	7.92 dBm		0.03 dB	
RFAIP	-2.30 dBm		0.13 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_1.4MHz_BW_16QAM_RB1_Offset5_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-14.89 dB		0.23 dB	
PMF	1.34 dB	1.167	0.16 dB	
Detector Level	8.68 dBm		0.05 dB	

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 16 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

RFAIP -6.21 dBm 0.28 dB (MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Narrow_Band_Codec_4.75kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.06 dB		0.03 dB	
PMF	2.28 dB	1.301	0.11 dB	
Detector Level	7.99 dBm		0.02 dB	
RFAIP	-2.07 dBm		0.06 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Narrow_Band_Codec_7.4kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.06 dB		0.07 dB	
PMF	2.31 dB	1.305	0.14 dB	
Detector Level	7.90 dBm		0.03 dB	
RFAIP	-2.16 dBm		0.10 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Narrow_Band_Codec_12.2kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.09 dB		0.06 dB	
PMF	2.35 dB	1.310	0.09 dB	
Detector Level	7.91 dBm		0.03 dB	
RFAIP	-2.17 dBm		0.09 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Wide_Band_Codec_6.6kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 17 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.07 dB		0.04 dB	
PMF	2.30 dB	1.303	0.09 dB	
Detector Level	7.92 dBm		0.06 dB	
RFAIP	-2.15 dBm		0.10 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Wide_Band_Codec_15.85kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.095, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.04 dB		0.06 dB	
PMF	2.34 dB	1.310	0.19 dB	
Detector Level	7.82 dBm		0.04 dB	
RFAIP	-2.22 dBm		0.10 dB	(MIF+CF+Detector Level)

Measurements/MIF_VoLTE_Wide_Band_Codec_23.85kbits_15MHz_BW_16QAM_RB1_Offset74_Measurement

Calibration Factors: 1.096, 1.095; MIF Scale: 0.00 dB; Coupling Factor (CF): 0.00 dB

Quantity	Value [log]	[linear]	Fluctuation	Remark
MIF	-10.05 dB		0.10 dB	
PMF	2.34 dB	1.309	0.22 dB	
Detector Level	7.82 dBm		0.05 dB	
RFAIP	-2.24 dBm		0.15 dB	(MIF+CF+Detector Level)

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 18 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

A.2 Dipole validation

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 19 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 3:18:01 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_validation_835MHz_10_08_15

DUT: HAC-Dipole 835 MHz; Type: CD835V3; Serial: 1011

Communication System: UID 0, CW For MIF; Frequency: 835 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 9.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

CD835 Dipole E-Field measurement (E-field scan for ANSI C63.19-2011 compliance)/E Scan - measurement distance from the probe sensor center to CD835 = 15mm/Hearing Aid Compatibility Test at 15mm distance (41x361x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 106.8 V/m; Power Drift = -0.00 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 109.7 V/m

Near-field category: M4 (AWF 0 dB)

PMF scaled E-field

Grid 1 M4 107.3 V/m	Grid 2 M4 109.7 V/m	Grid 3 M4 109.4 V/m
Grid 4 M4 61.39 V/m	Grid 5 M4 62.31 V/m	Grid 6 M4 61.36 V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 20 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	


Grid 7 M4 101.9 V/m	Grid 8 M4 106.7 V/m	Grid 9 M4 106.6 V/m
--------------------------------------	--------------------------------------	--------------------------------------

Cursor:

Total = 109.7 V/m

E Category: M4

Location: -2, -72, 9.7 mm



0 dB = 109.7 V/m = 40.80 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 21 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 3:53:07 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_validation_1880MHz_10_08_15

DUT: HAC Dipole 1880 MHz; Type: CD1880V3; Serial: 1008

Communication System: UID 0, CW For MIF; Frequency: 1880 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2007)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 9.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

CD1880 Dipole E-Field measurement (E-field scan for ANSI C63.19-2011 compliance)/E Scan - measurement distance from the probe sensor center to CD1880 = 15mm/Hearing Aid Compatibility Test at 15mm distance (41x181x1):

Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 143.0 V/m; Power Drift = -0.00 dB

PMR not calibrated. PMF = 1.000 is applied.

E-field emissions = 85.31 V/m

Near-field category: M3 (AWF 0 dB)

PMF scaled E-field

Grid 1 M3 81.34 V/m	Grid 2 M3 85.31 V/m	Grid 3 M3 85.31 V/m
Grid 4 M3 65.61 V/m	Grid 5 M3 67.74 V/m	Grid 6 M3 67.72 V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 22 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW


Grid 7 M3	Grid 8 M3	Grid 9 M3
79.80 V/m	84.90 V/m	84.83 V/m

Cursor:

Total = 85.31 V/m


E Category: M3

Location: -3.5, -32, 9.7 mm



0 dB = 85.31 V/m = 38.62 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 23 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	



The green line in this figure shows the axis along which the points lie.

Comparison of 5mm and 2mm step sizes

An additional set of measurements was taken: dipole validations were performed using 5mm and 2mm step sizes. The delta between the two readings is insignificant for both field types (< 0.4% for E and 0% for H), demonstrating that 5mm is sufficient. The plots follow.

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 24 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 14/07/2005 11:35:24 AM

Page 1 of 2

Date/Time: 14/07/2005 11:35:24 AM

Lab: RIM Testing Services (RTS)

Dipole Validation 1880 MHz_E-Field 07_14_05

DUT: HAC Dipole 1880 MHz; Type: CD1880V3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1000$ kg/m³
Phantom section: H Device Section

DASY4 Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 10/12/2004
- Sensor-Surface: 0mm (Fix Surface) Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/01/2005
- Phantom: HAC Test Arch; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (5x19x1):

Measurement grid: dx=5mm, dy=5mm
Maximum value of Total (measured) = 134.8 V/m

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (41x181x1):

Measurement grid: dx=5mm, dy=5mm
Maximum value of Total field (slot averaged) = 131.0 V/m

Hearing Aid Near-Field Category: M2 (AWF 0 dB)

E in V/m (Time averaged) E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
123.2	138.1	138.4	123.2	138.1	138.4
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
80.9	92.3	92.2	80.9	92.3	92.2
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
119.8	131.0	130.7	119.8	131.0	130.7

Category	AWF (dB)	Limits for E-Field Emissions (V/m)	Limits for H-Field Emissions (A/m)
M1	0	199.5 - 354.8	0.6 - 1.07
	-5	149.6 - 266.1	0.45 - 0.8
M2	0	112.2 - 199.5	0.34 - 0.6
	-5	84.1 - 149.6	0.25 - 0.45
M3	0	63.1 - 112.2	0.19 - 0.34
	-5	47.3 - 84.1	0.15 - 0.25
M4	0	<63.1	<0.19

file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005



Document

**Annex A to Hearing Aid Compatibility RF Emissions Test Report
for the BlackBerry® Smartphone RHT181LW (STV100-2)**

Page

25 (80)

Author Data

Daoud Attayi

Dates of Test

August 31- October 27, 2015

Report No


RTS-6066-1511-05

FCC ID

L6ARHT180LW

Date/Time: 14/07/2005 11:35:24 AM

Page 2 of 2



file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 26 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 14/07/2005 11:44:51 AM

Page 1 of 2

Date/Time: 14/07/2005 11:44:51 AM

Lab: RIM Testing Services (RTS)

Dipole Validation 1880 MHz_2mm step_E-Field 07_14_05

DUT: HAC Dipole 1880 MHz; Type: CD1880V3

Communication System: CW; Frequency: 1880 MHz; Duty Cycle: 1:1
Medium: Air Medium parameters used: $\sigma = 0$ mho/m, $\epsilon_r = 1$; $\rho = 1000$ kg/m³
Phantom section: H Device Section

DASY4 Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 10/12/2004
- Sensor-Surface: 0mm (Fix Surface) Sensor-Surface: (Fix Surface)
- Electronics: DAE3 Sn472; Calibrated: 03/01/2005
- Phantom: HAC Test Arch; Type: SD HAC P01 BA;
- Measurement SW: DASY4, V4.5 Build 19; Postprocessing SW: SEMCAD, V1.8 Build 146

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (11x46x1):

Measurement grid: dx=2mm, dy=2mm
Maximum value of Total (measured) = 138.0 V/m

E Scan 10mm above CD 1880 MHz/Hearing Aid Compatibility Test (101x451x1):

Measurement grid: dx=2mm, dy=2mm
Maximum value of Total field (slot averaged) = 131.2 V/m


Hearing Aid Near-Field Category: M2 (AWF 0 dB)

E in V/m (Time averaged) E in V/m (Slot averaged)

Grid 1	Grid 2	Grid 3	Grid 1	Grid 2	Grid 3
123.1	138.6	138.6	123.1	138.6	138.6
Grid 4	Grid 5	Grid 6	Grid 4	Grid 5	Grid 6
81.4	92.1	91.6	81.4	92.1	91.6
Grid 7	Grid 8	Grid 9	Grid 7	Grid 8	Grid 9
121.3	131.2	131.0	121.3	131.2	131.0

Category	AWF (dB)	Limits for E-Field Emissions (V/m)	Limits for H-Field Emissions (A/m)
M1	0	199.5 - 354.8	0.6 - 1.07
	-5	149.6 - 266.1	0.45 - 0.8
M2	0	112.2 - 199.5	0.34 - 0.6
	-5	84.1 - 149.6	0.25 - 0.45
M3	0	63.1 - 112.2	0.19 - 0.34
	-5	47.3 - 84.1	0.15 - 0.25
M4	0	<63.1	<0.19

file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005



file://C:\Program%20Files\DASY4\Print_Templates\Dipole%20Validation%201880%20... 14/07/2005

		Document		Page
		Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		28 (80)
Author Data	Dates of Test	Report No	FCC ID	
Daoud Attayi	August 31- October 27, 2015	RTS-6066-1511-05	L6ARHT180LW	

A.3 RF emission field plots

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 29 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/7/2015 6:02:53 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 835_Slider Closed

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, GSM 850; Frequency: 824.2 MHz, Frequency: 836.8 MHz,
Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM850 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 55.77 V/m; Power Drift = -0.04 dB

Applied MIF = 3.44 dB

RF audio interference level = 36.55 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 35.39 dBV/m	Grid 2 M4 36.51 dBV/m	Grid 3 M4 36.44 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		30 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

35.4 dBV/m	36.55 dBV/m	36.47 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
35.25 dBV/m	36.31 dBV/m	36.24 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.55 dBV/m

E Category: M4

Location: -5.5, -5, 8.7 mm

**Device E-Field GSM850 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 60.31 V/m; Power Drift = 0.01 dB

Applied MIF = 3.44 dB

RF audio interference level = 37.47 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
35.99 dBV/m	37.4 dBV/m	37.39 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
35.9 dBV/m	37.47 dBV/m	37.45 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
35.59 dBV/m	37.28 dBV/m	37.25 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 31 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 37.47 dBV/m

E Category: M4

Location: -7, -1.5, 8.7 mm

Device E-Field GSM850 measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 65.21 V/m; Power Drift = 0.02 dB

Applied MIF = 3.44 dB

RF audio interference level = 38.06 dBV/m

Emission category: M4

MIF scaled E-field


Grid 1 M4 36.72 dBV/m	Grid 2 M4 38.16 dBV/m	Grid 3 M4 38.12 dBV/m
Grid 4 M4 36.48 dBV/m	Grid 5 M4 38.06 dBV/m	Grid 6 M4 38.05 dBV/m
Grid 7 M4 36.09 dBV/m	Grid 8 M4 37.78 dBV/m	Grid 9 M4 37.72 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 38.16 dBV/m

E Category: M4
 Location: -6, -25, 8.7 mm



0 dB = 67.22 V/m = 36.55 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 33 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/7/2015 6:15:00 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 835_Slider Closed_Telecoil Centered

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, GSM 850; Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM850 measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan_Telecoil_center/Hearing Aid Compatibility Test

(101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 65.08 V/m; Power Drift = 0.02 dB

Applied MIF = 3.44 dB

RF audio interference level = 38.09 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 36.76 dBV/m	Grid 2 M4 38.15 dBV/m	Grid 3 M4 38.09 dBV/m
Grid 4 M4 36.56 dBV/m	Grid 5 M4 38.09 dBV/m	Grid 6 M4 38.07 dBV/m

		Document	Page
		Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	34 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4	Grid 8 M4	Grid 9 M4
36.47 dBV/m	38.03 dBV/m	38.01 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 38.15 dBV/m

E Category: M4

Location: -6, -24.5, 8.7 mm



0 dB = 80.77 V/m = 38.15 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 35 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 5:51:14 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Slider Closed

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791942

Communication System: UID 0, GSM 1900; Frequency: 1850.2 MHz, Frequency: 1880 MHz,
Frequency: 1909.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.43 V/m; Power Drift = 0.01 dB

Applied MIF = 3.44 dB

RF audio interference level = 31.14 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 31.46 dBV/m	Grid 2 M3 32.62 dBV/m	Grid 3 M3 32.3 dBV/m
Grid 4 M4 27.84 dBV/m	Grid 5 M3 30.36 dBV/m	Grid 6 M3 30.37 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 36 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 25.8 dBV/m	Grid 8 M3 31.07 dBV/m	Grid 9 M3 31.14 dBV/m
---------------------------------------	--	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 32.62 dBV/m

E Category: M3

Location: -2.5, -25, 8.7 mm

Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 25.60 V/m; Power Drift = -0.25 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.52 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 32.41 dBV/m	Grid 2 M3 34.49 dBV/m	Grid 3 M3 34.47 dBV/m
Grid 4 M4 29.27 dBV/m	Grid 5 M3 32.49 dBV/m	Grid 6 M3 32.52 dBV/m
Grid 7 M4 26.38 dBV/m	Grid 8 M3 30.01 dBV/m	Grid 9 M3 30.29 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 37 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.49 dBV/m

E Category: M3

Location: -7, -25, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 23.32 V/m; Power Drift = -0.07 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.19 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 31.12 dBV/m	Grid 2 M3 33.6 dBV/m	Grid 3 M3 33.57 dBV/m
Grid 4 M4 28.33 dBV/m	Grid 5 M3 32.07 dBV/m	Grid 6 M3 32.19 dBV/m
Grid 7 M4 29.99 dBV/m	Grid 8 M3 30.38 dBV/m	Grid 9 M3 30.98 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 33.60 dBV/m

E Category: M3

Location: -7, -25, 8.7 mm



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 39 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 5:51:14 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Slider Closed

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791942

Communication System: UID 0, GSM 1900; Frequency: 1850.2 MHz, Frequency: 1880 MHz,
Frequency: 1909.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.43 V/m; Power Drift = 0.01 dB

Applied MIF = 3.44 dB

RF audio interference level = 31.14 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 31.46 dBV/m	Grid 2 M3 32.62 dBV/m	Grid 3 M3 32.3 dBV/m
Grid 4 M4 27.84 dBV/m	Grid 5 M3 30.36 dBV/m	Grid 6 M3 30.37 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 40 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 25.8 dBV/m	Grid 8 M3 31.07 dBV/m	Grid 9 M3 31.14 dBV/m
---------------------------------------	--	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 32.62 dBV/m

E Category: M3

Location: -2.5, -25, 8.7 mm

Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 25.60 V/m; Power Drift = -0.25 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.52 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 32.41 dBV/m	Grid 2 M3 34.49 dBV/m	Grid 3 M3 34.47 dBV/m
Grid 4 M4 29.27 dBV/m	Grid 5 M3 32.49 dBV/m	Grid 6 M3 32.52 dBV/m
Grid 7 M4 26.38 dBV/m	Grid 8 M3 30.01 dBV/m	Grid 9 M3 30.29 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 41 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.49 dBV/m

E Category: M3

Location: -7, -25, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 23.32 V/m; Power Drift = -0.07 dB

Applied MIF = 3.44 dB

RF audio interference level = 32.19 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 31.12 dBV/m	Grid 2 M3 33.6 dBV/m	Grid 3 M3 33.57 dBV/m
Grid 4 M4 28.33 dBV/m	Grid 5 M3 32.07 dBV/m	Grid 6 M3 32.19 dBV/m
Grid 7 M4 29.99 dBV/m	Grid 8 M3 30.38 dBV/m	Grid 9 M3 30.98 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m


Cursor:

Total = 33.60 dBV/m

E Category: M3

Location: -7, -25, 8.7 mm

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 42 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015		Report No RTS-6066-1511-05	FCC ID L6ARHT180LW



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 43 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 6:48:00 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Slider Closed_Telecoil Centered

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791942

Communication System: UID 0, GSM 1900; Frequency: 1880 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM 1900 measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan_Telecoil center/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 24.82 V/m; Power Drift = 0.12 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.70 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 32.9 dBV/m	Grid 2 M3 34.83 dBV/m	Grid 3 M3 34.74 dBV/m
Grid 4 M3 31.28 dBV/m	Grid 5 M3 33.7 dBV/m	Grid 6 M3 33.69 dBV/m

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		44 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 27.26 dBV/m	Grid 8 M3 31.5 dBV/m	Grid 9 M3 31.6 dBV/m
--	---------------------------------------	---------------------------------------


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.83 dBV/m

E Category: M3

Location: -6, -35, 8.7 mm



0 dB = 55.13 V/m = 34.83 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 45 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/7/2015 6:36:51 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 835_Slider Open

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, GSM 850; Frequency: 824.2 MHz, Frequency: 836.8 MHz,
Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASYS (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASYS 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM850 measurement with ER probe_slider open/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 48.74 V/m; Power Drift = -0.00 dB

Applied MIF = 3.44 dB

RF audio interference level = 35.50 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 34.37 dBV/m	Grid 2 M4 35.73 dBV/m	Grid 3 M4 35.67 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		46 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

34.1 dBV/m	35.5 dBV/m	35.49 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
33.83 dBV/m	35.22 dBV/m	35.14 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 35.73 dBV/m

E Category: M4

Location: -6, -25, 8.7 mm

**Device E-Field GSM850 measurement with ER probe_slider open/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 50.69 V/m; Power Drift = 0.05 dB

Applied MIF = 3.44 dB

RF audio interference level = 36.13 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4	Grid 2 M4	Grid 3 M4
34.54 dBV/m	36.2 dBV/m	36.19 dBV/m
Grid 4 M4	Grid 5 M4	Grid 6 M4
34.24 dBV/m	36.13 dBV/m	36.12 dBV/m
Grid 7 M4	Grid 8 M4	Grid 9 M4
33.94 dBV/m	35.9 dBV/m	35.89 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 47 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.20 dBV/m

E Category: M4

Location: -7.5, -25, 8.7 mm

Device E-Field GSM850 measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 59.27 V/m; Power Drift = -0.00 dB

Applied MIF = 3.44 dB

RF audio interference level = 37.37 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 35.83 dBV/m	Grid 2 M4 37.52 dBV/m	Grid 3 M4 37.49 dBV/m
Grid 4 M4 35.5 dBV/m	Grid 5 M4 37.37 dBV/m	Grid 6 M4 37.36 dBV/m
Grid 7 M4 35.15 dBV/m	Grid 8 M4 37.07 dBV/m	Grid 9 M4 37.05 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m


Cursor:

Total = 37.52 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 48 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

E Category: M4

Location: -7, -25, 8.7 mm



0 dB = 61.17 V/m = 35.73 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 49 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/7/2015 6:54:15 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 835_Slider Open_Telecoil Centered

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, GSM 850; Frequency: 848.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM850 measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chann_Telecoil center/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: $dx=0.5000$ mm, $dy=0.5000$ mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 59.22 V/m; Power Drift = 0.03 dB

Applied MIF = 3.44 dB

RF audio interference level = 37.46 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 35.93 dBV/m	Grid 2 M4 37.49 dBV/m	Grid 3 M4 37.47 dBV/m
Grid 4 M4 35.67 dBV/m	Grid 5 M4 37.46 dBV/m	Grid 6 M4 37.44 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 50 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Grid 7 M4	Grid 8 M4	Grid 9 M4
35.5 dBV/m	37.34 dBV/m	37.32 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 37.49 dBV/m

E Category: M4

Location: -7, -22.5, 8.7 mm



0 dB = 74.87 V/m = 37.49 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 51 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 7:02:05 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Slider Open

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791942

Communication System: UID 0, GSM 1900; Frequency: 1850.2 MHz, Frequency: 1880 MHz,
Frequency: 1909.8 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

**Device E-Field GSM 1900 measurement with ER probe_slider open/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 34.66 V/m; Power Drift = -0.06 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.98 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 32.28 dBV/m	Grid 2 M3 33.47 dBV/m	Grid 3 M3 33.42 dBV/m
Grid 4 M3 30.24 dBV/m	Grid 5 M3 33.98 dBV/m	Grid 6 M3 34.04 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 52 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 29.1 dBV/m	Grid 8 M3 34.14 dBV/m	Grid 9 M3 34.18 dBV/m
---------------------------------------	--	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.18 dBV/m

E Category: M3

Location: -10.5, 16, 8.7 mm

Device E-Field GSM 1900 measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 34.75 V/m; Power Drift = -0.01 dB

Applied MIF = 3.44 dB

RF audio interference level = 34.09 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 32.47 dBV/m	Grid 2 M3 34.09 dBV/m	Grid 3 M3 34.06 dBV/m
Grid 4 M3 30.3 dBV/m	Grid 5 M3 33.72 dBV/m	Grid 6 M3 33.78 dBV/m
Grid 7 M4 28.87 dBV/m	Grid 8 M3 33.68 dBV/m	Grid 9 M3 33.73 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 53 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.09 dBV/m

E Category: M3

Location: -7, -25, 8.7 mm

**Device E-Field GSM 1900 measurement with ER probe_slider open/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 31.13 V/m; Power Drift = -0.02 dB

Applied MIF = 3.44 dB

RF audio interference level = 33.62 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 31.18 dBV/m	Grid 2 M3 32.79 dBV/m	Grid 3 M3 32.93 dBV/m
Grid 4 M4 28.8 dBV/m	Grid 5 M3 33.62 dBV/m	Grid 6 M3 33.74 dBV/m
Grid 7 M4 28.16 dBV/m	Grid 8 M3 33.76 dBV/m	Grid 9 M3 33.86 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 33.86 dBV/m

E Category: M3

Location: -11, 15, 8.7 mm



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 55 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/8/2015 7:41:02 AM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_GSM 1900_Slider Open_Telecoil Centered

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791942

Communication System: UID 0, GSM 1900 (0); Frequency: 1880 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field GSM 1900 measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan_Telecoil center/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 35.14 V/m; Power Drift = -0.10 dB

Applied MIF = 3.44 dB

RF audio interference level = 34.39 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M3 33.29 dBV/m	Grid 2 M3 34.39 dBV/m	Grid 3 M3 34.32 dBV/m
Grid 4 M3 31.55 dBV/m	Grid 5 M3 33.76 dBV/m	Grid 6 M3 33.81 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 56 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Grid 7 M4	Grid 8 M3	Grid 9 M3
29.69 dBV/m	33.78 dBV/m	33.82 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.39 dBV/m

E Category: M3

Location: -5, -35, 8.7 mm



0 dB = 52.56 V/m = 34.41 dBV/m

		Document		Page
		Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		57 (80)
Author Data	Dates of Test	Report No	FCC ID	
Daoud Attayi	August 31- October 27, 2015	RTS-6066-1511-05	L6ARHT180LW	

Date/Time: 10/19/2015 1:03:43 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC0_slider close

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, CDMA 850 1/8th Rate; Frequency: 824.7 MHz, Frequency: 836.52 MHz, Frequency: 848.31MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC0_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 24.06 V/m; Power Drift = 0.03 dB

Applied MIF = 2.79 dB

RF audio interference level = 36.49 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 35.05 dBV/m	Grid 2 M4 32.9 dBV/m	Grid 3 M4 34.89 dBV/m
Grid 4 M4 31.4 dBV/m	Grid 5 M4 36.49 dBV/m	Grid 6 M4 35.11 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 58 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 31.61 dBV/m	Grid 8 M4 37.15 dBV/m	Grid 9 M4 33.33 dBV/m
--	--	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 37.15 dBV/m

E Category: M4

Location: -5, 10, 8.7 mm

Device E-Field CDMA BC0_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 23.24 V/m; Power Drift = 7.59 dB

Applied MIF = 2.79 dB

RF audio interference level = 35.89 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 34.38 dBV/m	Grid 2 M4 33.17 dBV/m	Grid 3 M4 30.9 dBV/m
Grid 4 M4 35.36 dBV/m	Grid 5 M4 35.89 dBV/m	Grid 6 M4 34.31 dBV/m
Grid 7 M4 34.28 dBV/m	Grid 8 M4 36.48 dBV/m	Grid 9 M4 36.05 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 59 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.48 dBV/m

E Category: M4

Location: 5, 25, 8.7 mm

Device E-Field CDMA BC0_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 25.47 V/m; Power Drift = 0.12 dB

Applied MIF = 2.79 dB

RF audio interference level = 37.88 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 34.98 dBV/m	Grid 2 M4 37.88 dBV/m	Grid 3 M4 35.87 dBV/m
Grid 4 M4 32.39 dBV/m	Grid 5 M4 37.88 dBV/m	Grid 6 M4 36.19 dBV/m
Grid 7 M4 33.56 dBV/m	Grid 8 M4 36.9 dBV/m	Grid 9 M4 36.8 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m


Cursor:

Total = 37.88 dBV/m

E Category: M4

Location: -0.5, 0, 8.7 mm

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 60 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	



0 dB = 71.77 V/m = 37.12 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 61 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/19/2015 1:18:52 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC0_slider close_telecoil center

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, CDMA 850 1/8th Rate (0); Frequency: 848.31MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC0_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 29.04 V/m; Power Drift = 0.05 dB

Applied MIF = 2.79 dB

RF audio interference level = 36.33 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 36.33 dBV/m	Grid 2 M4 35.83 dBV/m	Grid 3 M4 34.09 dBV/m
Grid 4 M4 32.85 dBV/m	Grid 5 M4 36.3 dBV/m	Grid 6 M4 32.88 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 62 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Grid 7 M4 34.65 dBV/m	Grid 8 M4 36.94 dBV/m	Grid 9 M4 32.31 dBV/m
--	--	--


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 36.94 dBV/m

E Category: M4

Location: -5, 10, 8.7 mm



0 dB = 70.32 V/m = 36.94 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 63 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/19/2015 1:24:51 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC1_slider closed

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, CDMA 1900 1/8th Rate; Frequency: 1851.25 MHz, Frequency: 1880 MHz, Frequency: 1908.75 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC1_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 9.663 V/m; Power Drift = 0.07 dB

Applied MIF = 2.79 dB

RF audio interference level = 31.41 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4 26.54 dBV/m	Grid 2 M3 31.86 dBV/m	Grid 3 M3 30.68 dBV/m
Grid 4 M4 21.69 dBV/m	Grid 5 M4 27.16 dBV/m	Grid 6 M3 30.75 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 64 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 19.57 dBV/m	Grid 8 M4 23.6 dBV/m	Grid 9 M3 31.41 dBV/m
--	---------------------------------------	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 31.86 dBV/m

E Category: M3

Location: 5, -25, 8.7 mm

Device E-Field CDMA BC1_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 10.83 V/m; Power Drift = -0.03 dB

Applied MIF = 2.79 dB

RF audio interference level = 29.92 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 29.92 dBV/m	Grid 2 M3 32.56 dBV/m	Grid 3 M3 31.29 dBV/m
Grid 4 M4 24.62 dBV/m	Grid 5 M4 29.37 dBV/m	Grid 6 M3 30.73 dBV/m
Grid 7 M4 25.43 dBV/m	Grid 8 M4 27.47 dBV/m	Grid 9 M4 29.41 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 65 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 32.56 dBV/m

E Category: M3

Location: 0, -20, 8.7 mm

Device E-Field CDMA BC1_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 10.29 V/m; Power Drift = -0.15 dB

Applied MIF = 2.79 dB

RF audio interference level = 30.82 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4 27.99 dBV/m	Grid 2 M3 32.07 dBV/m	Grid 3 M3 33.76 dBV/m
Grid 4 M4 24.59 dBV/m	Grid 5 M4 27.73 dBV/m	Grid 6 M3 30.67 dBV/m
Grid 7 M4 28.21 dBV/m	Grid 8 M4 26.27 dBV/m	Grid 9 M3 30.82 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m


Cursor:

Total = 33.76 dBV/m

E Category: M3

Location: -15, -20, 8.7 mm

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 66 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	



0 dB = 39.05 V/m = 31.83 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 67 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/19/2015 1:40:23 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC1_slider closed_telecoil center

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161791688

Communication System: UID 0, CDMA 1900 1/8th Rate (0); Frequency: 1851.25 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC1_measurement with ER probe_slider closed/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 10.57 V/m; Power Drift = -0.11 dB

Applied MIF = 2.79 dB

RF audio interference level = 30.88 dBV/m

Emission category: M3

MIF scaled E-field

Grid 1 M4 24.92 dBV/m	Grid 2 M3 34.79 dBV/m	Grid 3 M3 31.2 dBV/m
Grid 4 M4 26.62 dBV/m	Grid 5 M4 29.58 dBV/m	Grid 6 M4 29.63 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 68 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015		Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4	Grid 8 M4	Grid 9 M3
22.9 dBV/m	28.51 dBV/m	30.88 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.79 dBV/m

E Category: M3

Location: -1.5, -35, 8.7 mm



0 dB = 54.87 V/m = 34.79 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 69 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/19/2015 2:40:06 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC0_slider open

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161463503

Communication System: UID 0, CDMA 850 1/8th Rate; Frequency: 824.7 MHz, Frequency: 836.52 MHz, Frequency: 848.31MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC0_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.02 V/m; Power Drift = 0.14 dB

Applied MIF = 2.79 dB

RF audio interference level = 34.25 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 34.25 dBV/m	Grid 2 M4 33.53 dBV/m	Grid 3 M4 34.13 dBV/m
Grid 4 M4 33.56 dBV/m	Grid 5 M4 32.64 dBV/m	Grid 6 M4 33.43 dBV/m

	Document		Page
	Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		70 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 30.95 dBV/m	Grid 8 M4 31.7 dBV/m	Grid 9 M4 34.12 dBV/m
--	---------------------------------------	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.25 dBV/m

E Category: M4

Location: 15, -15, 8.7 mm

Device E-Field CDMA BC0_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 25.14 V/m; Power Drift = 0.05 dB

Applied MIF = 2.79 dB

RF audio interference level = 34.55 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 31.93 dBV/m	Grid 2 M4 34.55 dBV/m	Grid 3 M4 28.58 dBV/m
Grid 4 M4 32.76 dBV/m	Grid 5 M4 32.88 dBV/m	Grid 6 M4 32.17 dBV/m
Grid 7 M4 26.31 dBV/m	Grid 8 M4 31.77 dBV/m	Grid 9 M4 29.82 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 71 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 34.55 dBV/m

E Category: M4

Location: -5, -25, 8.7 mm

Device E-Field CDMA BC0_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 22.37 V/m; Power Drift = 0.09 dB

Applied MIF = 2.79 dB

RF audio interference level = 30.17 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 29.02 dBV/m	Grid 2 M4 30.07 dBV/m	Grid 3 M4 29.06 dBV/m
Grid 4 M4 28.82 dBV/m	Grid 5 M4 30.17 dBV/m	Grid 6 M4 29.49 dBV/m
Grid 7 M4 28.3 dBV/m	Grid 8 M4 29.16 dBV/m	Grid 9 M4 29.69 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 30.17 dBV/m

E Category: M4

Location: -5, 0, 8.7 mm



0 dB = 51.38 V/m = 34.22 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 73 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/19/2015 4:27:32 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC0_slider open_telecoil center

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161463503

Communication System: UID 0, CDMA 850 1/8th Rate; Frequency: 836.52 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC0_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 21.30 V/m; Power Drift = 0.03 dB

Applied MIF = 2.79 dB

RF audio interference level = 29.39 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 28.83 dBV/m	Grid 2 M4 29.39 dBV/m	Grid 3 M4 29.25 dBV/m
Grid 4 M4 28.16 dBV/m	Grid 5 M4 29.05 dBV/m	Grid 6 M4 29.44 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 74 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Grid 7 M4 28.86 dBV/m	Grid 8 M4 29.57 dBV/m	Grid 9 M4 28.73 dBV/m
--	--	--


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 29.57 dBV/m

E Category: M4

Location: 0, 5, 8.7 mm



0 dB = 30.00 V/m = 29.54 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 75 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/27/2015 12:50:07 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC1 1900_slider open

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161463503

Communication System: UID 0, CDMA 1900 1/8th Rate; Frequency: 1851.25 MHz, Frequency: 1880 MHz, Frequency: 1908.75 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC1_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Low_Chan/Hearing Aid Compatibility Test (101x101x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 17.33 V/m; Power Drift = 0.10 dB

Applied MIF = 2.79 dB

RF audio interference level = 28.15 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 25.67 dBV/m	Grid 2 M4 28.15 dBV/m	Grid 3 M4 28.09 dBV/m
Grid 4 M4 24.19 dBV/m	Grid 5 M4 28.15 dBV/m	Grid 6 M4 28.26 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 76 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Grid 7 M4 22.99 dBV/m	Grid 8 M4 28.04 dBV/m	Grid 9 M4 28.27 dBV/m
--	--	--

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 28.27 dBV/m

E Category: M4

Location: -10, 9.5, 8.7 mm

Device E-Field CDMA BC1_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan/Hearing Aid Compatibility Test (101x101x1): Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 18.76 V/m; Power Drift = -0.01 dB

Applied MIF = 2.79 dB

RF audio interference level = 28.60 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 26.67 dBV/m	Grid 2 M4 28.67 dBV/m	Grid 3 M4 28.7 dBV/m
Grid 4 M4 24.29 dBV/m	Grid 5 M4 28.41 dBV/m	Grid 6 M4 28.69 dBV/m
Grid 7 M4 23.31 dBV/m	Grid 8 M4 28.32 dBV/m	Grid 9 M4 28.6 dBV/m

Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 77 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 28.70 dBV/m

E Category: M4

Location: -9.5, -19.5, 8.7 mm

**Device E-Field CDMA BC1_measurement with ER probe_slider open/E Scan -
ER3D - 2011: 15 mm from Probe Center to the Device_High_Chan/Hearing Aid
Compatibility Test (101x101x1):** Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 16.98 V/m; Power Drift = -0.07 dB

Applied MIF = 2.79 dB

RF audio interference level = 28.19 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 24.9 dBV/m	Grid 2 M4 27.36 dBV/m	Grid 3 M4 27.54 dBV/m
Grid 4 M4 23.02 dBV/m	Grid 5 M4 28.19 dBV/m	Grid 6 M4 28.27 dBV/m
Grid 7 M4 23.69 dBV/m	Grid 8 M4 28.55 dBV/m	Grid 9 M4 28.59 dBV/m


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 28.59 dBV/m

E Category: M4

Location: -9.5, 20.5, 8.7 mm



		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)	Page 79 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW

Date/Time: 10/27/2015 1:03:32 PM

Test Laboratory: BlackBerry RTS

HAC RF_E-Field_CDMA BC1 1900_telecoil center

DUT: BlackBerry Smartphone; Type: Sample ; Serial: 1161463503

Communication System: UID 0, CDMA 1900 1/8th Rate (0); Frequency: 1880 MHz

Medium parameters used: $\sigma = 0$ S/m, $\epsilon_r = 1$; $\rho = 0$ kg/m³

Phantom section: RF Section

Measurement Standard: DASY5 (IEEE/IEC/ANSI C63.19-2011)

DASY Configuration:

- Probe: ER3DV6 - SN2285; ConvF(1, 1, 1); Calibrated: 3/11/2015;
- Sensor-Surface: (Fix Surface), $z = 8.7$
- Electronics: DAE4 Sn881; Calibrated: 1/13/2015
- Phantom: HAC RF Test Arch with AMCC; Type: SD HAC P01 BA
- DASY52 52.8.8(1222); SEMCAD X 14.6.10(7331)

Device E-Field CDMA BC1_measurement with ER probe_slider open/E Scan - ER3D - 2011: 15 mm from Probe Center to the Device_Mid_Chan_telecoil/Hearing Aid Compatibility Test (101x101x1):

Interpolated grid: dx=0.5000 mm, dy=0.5000 mm

Device Reference Point: 0, 0, -6.3 mm

Reference Value = 20.89 V/m; Power Drift = 0.04 dB

Applied MIF = 2.79 dB

RF audio interference level = 28.62 dBV/m

Emission category: M4

MIF scaled E-field

Grid 1 M4 27.83 dBV/m	Grid 2 M4 29.01 dBV/m	Grid 3 M4 28.89 dBV/m
Grid 4 M4 25.46 dBV/m	Grid 5 M4 28.42 dBV/m	Grid 6 M4 28.57 dBV/m

		Document Annex A to Hearing Aid Compatibility RF Emissions Test Report for the BlackBerry® Smartphone RHT181LW (STV100-2)		Page 80 (80)
Author Data Daoud Attayi	Dates of Test August 31- October 27, 2015	Report No RTS-6066-1511-05	FCC ID L6ARHT180LW	

Grid 7 M4 23.98 dBV/m	Grid 8 M4 28.37 dBV/m	Grid 9 M4 28.62 dBV/m
--	--	--


Category	Limits for E-Field Emissions < 960MHz	Limits for E-Field Emissions > 960MHz
M1	50 dBV/m - 55 dB V/m	40 dBV/m - 45 dB V/m
M2	45 dBV/m - 50 dB V/m	35 dBV/m - 40 dB V/m
M3	40 dBV/m - 45 dB V/m	30 dBV/m - 35 dB V/m
M4	<40 dBV/m	<30 dBV/m

Cursor:

Total = 29.01 dBV/m

E Category: M4

Location: -6, -35, 8.7 mm



0 dB = 28.20 V/m = 29.00 dBV/m