



FCC RF Test Report

APPLICANT : BlackBerry Ltd.
EQUIPMENT : GSM Quad-band / UMTS Penta-band / LTE
Deca-band mobile phone
BRAND NAME : BlackBerry
MODEL NAME : STH100-2 (RJD211LW)
FCC ID : L6ARLD210LW
STANDARD : 47 CFR Part 2, 24(E), 27(M)
CLASSIFICATION : PCS Licensed Transmitter Held to Ear (PCE)

The product was received on Apr. 29, 2016 and completely tested on Jun. 20, 2016. We, SPORTON INTERNATIONAL (KUNSHAN) INC., would like to declare that the tested sample has been evaluated in accordance with the test procedures given in ANSI / TIA / EIA-603-D-2010 and the testing has shown the tested sample to be in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval of SPORTON INTERNATIONAL (KUNSHAN) INC., the test report shall not be reproduced except in full.

Prepared by: James Huang / Manager

Approved by: Jones Tsai / Manager



SPORTON INTERNATIONAL (KUNSHAN) INC.
No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China



TABLE OF CONTENTS

REVISION HISTORY	4
SUMMARY OF TEST RESULT	5
1 GENERAL DESCRIPTION	6
1.1 Applicant	6
1.2 Manufacturer	6
1.3 Product Feature of Equipment Under Test.....	6
1.4 Specification of Accessory	7
1.5 Product Specification of Equipment Under Test.....	8
1.6 Modification of EUT	8
1.7 Maximum EIRP Power, Frequency Tolerance, and Emission Designator	9
1.8 Testing Location	10
1.9 Applicable Standards.....	10
2 TEST CONFIGURATION OF EQUIPMENT UNDER TEST	11
2.1 Test Mode	11
2.2 Connection Diagram of Test System	13
2.3 Support Unit used in test configuration and system	14
2.4 Measurement Results Explanation Example.....	14
2.5 Frequency List of Low/Middle/High Channels	15
3 CONDUCTED TEST ITEMS	17
3.1 Measuring Instruments	17
3.2 Test Setup	17
3.3 Test Result of Conducted Test	17
3.4 Conducted Output Power	18
3.5 Peak-to-Average Ratio	18
3.6 Occupied Bandwidth	19
3.7 Conducted Band Edge	20
3.8 Conducted Spurious Emission	22
3.9 Frequency Stability	23
4 RADIATED TEST ITEMS	24
4.1 Measuring Instruments	24
4.2 Test Setup	24
4.3 Test Result of Radiated Test	24
4.4 Effective Isotropic Radiated Power	25
4.5 Radiated Spurious Emission	27
5 LIST OF MEASURING EQUIPMENT	28
6 UNCERTAINTY OF EVALUATION	29



APPENDIX A. TEST RESULTS OF CONDUCTED TEST

APPENDIX B. TEST RESULTS OF RADIATED TEST

APPENDIX C. TEST SETUP PHOTOGRAPHS



REVISION HISTORY

REPORT NO.	VERSION	DESCRIPTION	ISSUED DATE
FG642912B	Rev. 01	Initial issue of report	Jun. 24, 2016

**SUMMARY OF TEST RESULT**

Report Section	FCC Rule	Description	Limit	Result	Remark
3.4	§2.1046	Conducted Output Power	Reporting Only	PASS	-
3.5	§24.232(d)	Peak-to-Average Ratio	<13 dB	PASS	-
3.6	§2.1049	Occupied Bandwidth	Reporting Only	PASS	-
3.7	§2.1051 §24.238(a)	Conducted Band Edge Measurement (Band 2)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
	§27.53(m)(4)	Conducted Band Edge Measurement (Band 7) (Band 38) (Band 41)	§27.53(m)(4)		
3.8	§2.1051 §24.238(a)	Conducted Spurious Emission (Band 2)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	-
	§2.1051 §27.53(m)(4)	Conducted Spurious Emission (Band 7) (Band 38) (Band 41)	$< 55+10\log_{10}(P[\text{Watts}])$		
3.9	§2.1055 §24.235 §27.54	Frequency Stability Temperature & Voltage	Within Authorized Band	PASS	-
4.4	§24.232(c) §27.50(h)(2)	Equivalent Isotropic Radiated Power	EIRP < 2Watt	PASS	-
4.5	§2.1053 §24.238(a)	Radiated Spurious Emission (Band 2)	$< 43+10\log_{10}(P[\text{Watts}])$	PASS	Under limit 0.60 dB at 7772.000 MHz
	§2.1053 §27.53(m)(4)	Radiated Spurious Emission (Band 7) (Band 38) (Band 41)	$< 55+10\log_{10}(P[\text{Watts}])$		



1 General Description

1.1 Applicant

BlackBerry Ltd.

2200 University Ave E., Waterloo, ON, CAN. N2K0A7

1.2 Manufacturer

TCL Communication Ltd.

5F, C building, No. 232, Liang Jing Road ZhangJiang High-Tech Park, Pudong Area Shanghai, P.R. China. 201203

1.3 Product Feature of Equipment Under Test

Product Feature	
Equipment	GSM Quad-band / UMTS Penta-band / LTE Deca-band mobile phone
Brand Name	BlackBerry
Model Name	STH100-2 (RJD211LW)
FCC ID	L6ARLD210LW
EUT supports Radios application	GSM/GPRS/EGPRS/WCDMA/HSPA/DC-HSDPA/ HSPA+(16QAM uplink is not supported)/LTE/NFC/ WLAN 2.4GHz 802.11b/g/n HT20/ WLAN 5GHz 802.11a/n HT20/HT40/ WLAN 5GHz 802.11ac VHT20/VHT40/VHT80/ Bluetooth v3.0+EDR/Bluetooth v4.0 LE/ Bluetooth v4.2 LE
IMEI Code	Conducted: 004402243119934 Radiation: 004402243119942 EIRP: 004402243119959
HW Version	PIO
SW Version	AAF155
EUT Stage	Identical Prototype

1.4 Specification of Accessory

Specification of Accessory				
AC Adapter	Brand Name	N/A	Model Name	UC13US
	Power Rating	I/P: 100 - 240Vac 0.5A, O/P:5V 2.0A		
	Manufacturer	BYD		
	S/N	CBA0059AG4C1		
Battery 1	Brand Name	N/A	Model Name	TLp026EJ
	Power Rating	3.85V 2610mAh		
	Manufacturer	COSLIGHT		
	P/N	C2610010CJ		
Battery 2	Brand Name	N/A	Model Name	TLp026E2
	Power Rating	3.84V 2610mAh		
	Manufacturer	SCUD		
	P/N	C2610011C2		
USB Cable 1	Brand Name	NA	Model Name	NA
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
	P/N	CDA0000043C8		
USB Cable 2	Brand Name	NA	Model Name	NA
	Signal Line Type	1.0 meter, shielded cable, without ferrite core		
	P/N	CDA0000043C2		
Earphone	Brand Name	NA	Model Name	NA
	Signal Line Type	1.25 meter, non-shielded cable, without ferrite core		
	P/N	CCB0045A15C3		



1.5 Product Specification of Equipment Under Test

Standards-related Product Specification	
Tx Frequency	LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2557.5 MHz ~ 2652.5 MHz
Rx Frequency	LTE Band 2 : 1930.7 MHz ~ 1989.3 MHz LTE Band 7 : 2622.5MHz ~ 2687.5 MHz LTE Band 38 : 2572.5 MHz ~ 2617.5 MHz LTE Band 41 : 2557.5 MHz ~ 2652.5 MHz
Bandwidth	LTE Band 2 : 1.4MHz / 3MHz / 5MHz / 10MHz / 15MHz / 20MHz LTE Band 7 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 38 : 5MHz / 10MHz / 15MHz / 20MHz LTE Band 41 : 5MHz / 10MHz / 15MHz / 20MHz
Maximum Output Power to Antenna	LTE Band 2 : 22.59 dBm LTE Band 7 : 22.65 dBm LTE Band 38 : 22.20 dBm LTE Band 41 : 22.88 dBm
Type of Modulation	QPSK / 16QAM

1.6 Modification of EUT

No modifications are made to the EUT during all test items.



1.7 Maximum EIRP Power, Frequency Tolerance, and Emission Designator

LTE Band 2		QPSK		16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
1.4	1M10G7D	-	0.4114	1M10W7D	-	0.3131
3	2M72G7D	-	0.4048	2M72W7D	-	0.3058
5	4M48G7D	-	0.3979	4M50W7D	-	0.2694
10	9M01G7D	0.0017	0.3643	9M01W7D	-	0.2658
15	13M3G7D	-	0.3572	13M4W7D	-	0.2458
20	18M3G7D	-	0.3511	18M3W7D	-	0.2666
LTE Band 7		QPSK		16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	4M49G7D	-	0.4987	4M49W7D	-	0.3461
10	9M05G7D	0.0052	0.5267	8M99W7D	-	0.3608
15	13M4G7D	-	0.5015	13M5W7D	-	0.3490
20	18M3G7D	-	0.4874	18M3W7D	-	0.3426
LTE Band 38		QPSK		16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	4M52G7D	-	0.4522	4M50W7D	-	0.3248
10	9M07G7D	0.0032	0.4317	9M05W7D	-	0.3872
15	13M5G7D	-	0.4291	13M4W7D	-	0.3026
20	18M4G7D	-	0.4200	18M5W7D	-	0.3081
LTE Band 41		QPSK		16QAM		
BW(MHz)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)	Emission Designator (99%OBW)	Frequency Tolerance (ppm)	Maximum EIRP(W)
5	4M50G7D	-	0.4576	4M49W7D	-	0.3119
10	9M07G7D	0.0026	0.3999	9M05W7D	-	0.3257
15	13M5G7D	-	0.4063	13M5W7D	-	0.2986
20	18M4G7D	-	0.4137	18M3W7D	-	0.3053

1.8 Testing Location

Test Site	SPORTON INTERNATIONAL (KUNSHAN) INC.		
Test Site Location	No. 3-2, PingXiang Road, Kunshan, Jiangsu Province, P. R. China TEL: +86-0512-5790-0158 FAX: +86-0512-5790-0958		
Test Site No.	Sporton Site No.		FCC Registration No.
	TH01-KS	03CH02-KS	418269

1.9 Applicable Standards

According to the specifications of the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ 47 CFR Part 2, 24(E), 27(M)
- ♦ ANSI / TIA / EIA-603-D-2010
- ♦ FCC KDB 971168 D01 Power Meas. License Digital Systems v02r02

Remark:

1. All test items were verified and recorded according to the standards and without any deviation during the test.
2. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

2.1 Test Mode

Antenna port conducted and radiated test items listed below are performed according to KDB 971168 D01 Power Meas. License Digital Systems v02r02 with maximum output power.

Radiated measurements are performed by rotating the EUT in three different orthogonal test planes to find the maximum emission.


Test Items	Band	Bandwidth (MHz)						Modulation		RB #			Test Channel		
		1.4	3	5	10	15	20	QPSK	16QAM	1	Half	Full	L	M	H
Max. Output Power	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	7	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	38	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
Peak-to-Average Ratio	2						✓	✓	✓	✓		✓	✓	✓	✓
	7	-	-				✓	✓	✓	✓		✓	✓	✓	✓
	38	-	-				✓	✓	✓	✓		✓	✓	✓	✓
	41	-	-				✓	✓	✓	✓		✓	✓	✓	✓
26dB and 99% Bandwidth	2	✓	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	7	-	-	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	38	-	-	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓			✓	✓	✓	✓
Conducted Band Edge	2	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	7	-	-	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	38	-	-	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓		✓	✓		✓
Conducted Spurious Emission	2	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓		✓	✓	✓
	7	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	38	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
	41	-	-	✓	✓	✓	✓	✓	✓	✓			✓	✓	✓
Frequency Stability	2				✓			✓				✓		✓	
	7	-	-		✓			✓				✓		✓	
	38	-	-		✓			✓				✓		✓	
	41	-	-		✓			✓				✓		✓	




E.I.R.P.	2	v	v	v	v	v	v	v	v	v	v		v	v	v
	7	-	-	v	v	v	v	v	v	v			v	v	v
	38	-	-	v	v	v	v	v	v	v			v	v	v
	41	-	-	v	v	v	v	v	v	v			v	v	v
Radiated Spurious Emission	2	v	v	v	v	v	v	v		v				v	
	7	-	-	v	v	v	v	v		v				v	
	38	-	-	v	v	v	v	v		v				v	
	41	-	-	v	v	v	v	v		v				v	
Note	1. The mark “v” means that this configuration is chosen for testing 2. The mark “-” means that this bandwidth is not supported. 3. The device is investigated from 30MHz to 10 times of fundamental signal for radiated spurious emission test under different RB size/offset and modulations in exploratory test. Subsequently, only the worst case emissions are reported.														

2.2 Connection Diagram of Test System

For LTE Band 2 / 7 / 38



For LTE Band 41



2.3 Support Unit used in test configuration and system

Item	Equipment	Trade Name	Model No.	FCC ID	Data Cable	Power Cord
1.	LTE Base Station	Anritsu	MT8820C	N/A	N/A	Unshielded, 1.8 m
2.	DC Power Supply	GW INSTEK	GPS-3030D	N/A	N/A	Unshielded, 1.8 m

2.4 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

The spectrum analyzer offset is from RF cable loss.

Offset = RF cable loss.

Following shows an offset computation example with cable loss 5.0 dB.

Example :

Offset(dB) = RF cable loss(dB).

=5.0 (dB)



2.5 Frequency List of Low/Middle/High Channels

LTE Band 2 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	18700	18900	19100
	Frequency	1860	1880	1900
15	Channel	18675	18900	19125
	Frequency	1857.5	1880	1902.5
10	Channel	18650	18900	19150
	Frequency	1855	1880	1905
5	Channel	18625	18900	19175
	Frequency	1852.5	1880	1907.5
3	Channel	18615	18900	19185
	Frequency	1851.5	1880	1908.5
1.4	Channel	18607	18900	19193
	Frequency	1850.7	1880	1909.3

LTE Band 7 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	20850	21100	21350
	Frequency	2510	2535	2560
15	Channel	20825	21100	21375
	Frequency	2507.5	2535	2562.5
10	Channel	20800	21100	21400
	Frequency	2505	2535	2565
5	Channel	20775	21100	21425
	Frequency	2502.5	2535	2567.5

LTE Band 38 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	37850	38000	38150
	Frequency	2580	2595	2610
15	Channel	37825	38000	38175
	Frequency	2577.5	2595	2612.5
10	Channel	37800	38000	38200
	Frequency	2575	2595	2615
5	Channel	37775	38000	38225
	Frequency	2572.5	2595	2617.5

LTE Band 41 Channel and Frequency List				
BW [MHz]	Channel/Frequency(MHz)	Lowest	Middle	Highest
20	Channel	40340	40740	41140
	Frequency	2565	2605	2645
15	Channel	40315	40740	41165
	Frequency	2562.5	2605	2647.5
10	Channel	40290	40740	41190
	Frequency	2560	2605	2650
5	Channel	40265	40740	41215
	Frequency	2557.5	2605	2652.5


3 Conducted Test Items

3.1 Measuring Instruments


See list of measuring instruments of this test report.

3.2 Test Setup


3.2.1 Conducted Output Power



3.2.2 Peak-to-Average Ratio, Occupied Bandwidth ,Conducted Band-Edge and Conducted Spurious Emission



3.2.3 Frequency Stability



3.3 Test Result of Conducted Test

Please refer to Appendix A.

3.4 Conducted Output Power

3.4.1 Description of the Conducted Output Power Measurement

A system simulator was used to establish communication with the EUT. Its parameters were set to force the EUT transmitting at maximum output power. The measured power in the radio frequency on the transmitter output terminals shall be reported.

3.4.2 Test Procedures

1. The transmitter output port was connected to the system simulator.
2. Set EUT at maximum power through the system simulator.
3. Select lowest, middle, and highest channels for each band and different modulation.
4. Measure and record the power level from the system simulator.

3.5 Peak-to-Average Ratio

3.5.1 Description of the PAR Measurement

Power Complementary Cumulative Distribution Function (CCDF) curves provide a means for characterizing the power peaks of a digitally modulated signal on a statistical basis. A CCDF curve depicts the probability of the peak signal amplitude exceeding the average power level. Most contemporary measurement instrumentation include the capability to produce CCDF curves for an input signal provided that the instrument's resolution bandwidth can be set wide enough to accommodate the entire input signal bandwidth. In measuring transmissions in this band using an average power technique, the peak-to-average ratio (PAR) of the transmission may not exceed 13 dB.

3.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.7.1.
2. The EUT was connected to spectrum and system simulator via a power divider.
3. Set the CCDF (Complementary Cumulative Distribution Function) option in spectrum analyzer.
4. The highest RF powers were measured and recorded the maximum PAPR level associated with a probability of 0.1 %.
5. Record the deviation as Peak to Average Ratio.

3.6 Occupied Bandwidth

3.6.1 Description of Occupied Bandwidth Measurement

The occupied bandwidth is the width of a frequency band such that, below the lower and above the upper frequency limits, the mean powers emitted are each equal to a specified percentage 0.5% of the total mean transmitted power.

The 26 dB emission bandwidth is defined as the frequency range between two points, one above and one below the carrier frequency, at which the spectral density of the emission is attenuated 26 dB below the maximum in-band spectral density of the modulated signal. Spectral density (power per unit bandwidth) is to be measured with a detector of resolution bandwidth equal to approximately 1.0% of the emission bandwidth.

3.6.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 4.2.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The spectrum analyzer center frequency is set to the nominal EUT channel center frequency. The span range for the spectrum analyzer shall be between two and five times the anticipated OBW.
4. The nominal resolution bandwidth (RBW) shall be in the range of 1 to 5 % of the anticipated OBW, and the VBW shall be at least 3 times the RBW.
5. Set the detection mode to peak, and the trace mode to max hold.
6. Determine the reference value: Set the EUT to transmit a modulated signal. Allow the trace to stabilize. Set the spectrum analyzer marker to the highest level of the displayed trace.
(this is the reference value)
7. Determine the “-26 dB down amplitude” as equal to (Reference Value – X).
8. Place two markers, one at the lowest and the other at the highest frequency of the envelope of the spectral display such that each marker is at or slightly below the “-X dB down amplitude” determined in step 6. If a marker is below this “-X dB down amplitude” value it shall be placed as close as possible to this value. The OBW is the positive frequency difference between the two markers.
9. Use the 99 % power bandwidth function of the spectrum analyzer and report the measured bandwidth.

3.7 Conducted Band Edge

3.7.1 Description of Conducted Band Edge Measurement

24.238 (a) for Band 2

For operations in the 1850-1910 and 1930-1990 MHz band, the FCC limit is $43 + 10\log_{10}(P[\text{Watts}])$ dB below the transmitter power $P(\text{Watts})$ in a 1MHz bandwidth. However, in the 1 MHz bands immediately outside and adjacent to the frequency block a resolution bandwidth of at least one percent of the emission bandwidth of the fundamental emission of the transmitter may be employed.

27.53(m)(4) for Band 7, 38, 41:

For mobile digital stations, the attenuation factor shall be not less than $40 + 10 \log (P)$ dB on all frequencies between the channel edge and 5 megahertz from the channel edge, $43 + 10 \log (P)$ dB on all frequencies between 5 megahertz and X megahertz from the channel edge, and $55 + 10 \log (P)$ dB on all frequencies more than X megahertz from the channel edge, where X is the greater of 6 megahertz or the actual emission bandwidth as defined in paragraph (m)(6) of this section. In addition, the attenuation factor shall not be less than $43 + 10 \log (P)$ dB on all frequencies between 2490.5 MHz and 2496 MHz and $55 + 10 \log (P)$ dB at or below 2490.5 MHz. Mobile Satellite Service licensees operating on frequencies below 2495 MHz may also submit a documented interference complaint against BRS licensees operating on channel BRS Channel 1 on the same terms and conditions as adjacent channel BRS or EBS licensees.

3.7.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The band edges of low and high channels for the highest RF powers were measured.
4. Set RBW $\geq 1\%$ EBW in the 1MHz band immediately outside and adjacent to the band edge.
5. Beyond the 1 MHz band from the band edge, RBW=1MHz was used or a narrower RBW was used and the measured power was integrated over the full required measurement bandwidth of 1 MHz.
6. Set spectrum analyzer with RMS detector.
7. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
8. Offset has included the duty factor for LTE Band 41 and LTE Band 38. Duty factor $= 10 \log (1/x)$, where x is the measured duty cycle.
9. Checked that all the results comply with the emission limit line.

Example:

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

$$= P(W) - [43 + 10\log(P)] \text{ (dB)}$$

$$= [30 + 10\log(P)] \text{ (dBm)} - [43 + 10\log(P)] \text{ (dB)} = -13\text{dBm}.$$

10. For LTE Band 7, 38, 41, the other 40 dB, and 55 dB have additionally applied same calculation above.

3.8 Conducted Spurious Emission

3.8.1 Description of Conducted Spurious Emission Measurement

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 38, 41:

The power of any emission outside of the authorized operating frequency ranges must be lower than the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

It is measured by means of a calibrated spectrum analyzer and scanned from 30 MHz up to a frequency including its 10th harmonic.

3.8.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 6.0.
2. The EUT was connected to spectrum analyzer and system simulator via a power divider.
3. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator.
The path loss was compensated to the results for each measurement.
4. The middle channel for the highest RF power within the transmitting frequency was measured.
5. The conducted spurious emission for the whole frequency range was taken.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz.
7. Set spectrum analyzer with RMS detector.
8. Taking the record of maximum spurious emission.
9. Offset has included the duty factor for LTE Band 41 and LTE Band 38. Duty factor = $10 \log (1/x)$, where x is the measured duty cycle.
10. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.
11. The limit line is derived from $43 + 10 \log (P)$ dB below the transmitter power P(Watts)
 $= P(W) - [43 + 10 \log (P)]$ (dB)
 $= [30 + 10 \log (P)]$ (dBm) - $[43 + 10 \log (P)]$ (dB)
 $= -13$ dBm.
12. For Band 7, 38, 41
The limit line is derived from $55 + 10 \log (P)$ dB below the transmitter power P(Watts)
 $= P(W) - [55 + 10 \log (P)]$ (dB)
 $= [30 + 10 \log (P)]$ (dBm) - $[55 + 10 \log (P)]$ (dB)
 $= -25$ dBm.

3.9 Frequency Stability

3.9.1 Description of Frequency Stability Measurement

The frequency stability shall be measured by variation of ambient temperature and variation of primary supply voltage to ensure that the fundamental emission stays within the authorized frequency block. The frequency stability of the transmitter shall be maintained within $\pm 0.00025\%$ ($\pm 2.5\text{ppm}$) of the center frequency.

3.9.2 Test Procedures for Temperature Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was set up in the thermal chamber and connected with the system simulator.
3. With power OFF, the temperature was decreased to -30°C and the EUT was stabilized before testing. Power was applied and the maximum change in frequency was recorded within one minute.
4. With power OFF, the temperature was raised in 10°C step up to 50°C . The EUT was stabilized at each step for at least half an hour. Power was applied and the maximum frequency change was recorded within one minute.

3.9.3 Test Procedures for Voltage Variation

1. The testing follows FCC KDB 971168 v02r02 Section 9.0.
2. The EUT was placed in a temperature chamber at $25\pm 5^{\circ}\text{C}$ and connected with the system simulator.
3. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
4. The variation in frequency was measured for the worst case.


4 Radiated Test Items

4.1 Measuring Instruments


See list of measuring instruments of this test report.

4.2 Test Setup

4.2.1 For radiated test from 30MHz to 1GHz



4.2.2 For radiated test above 1GHz



4.3 Test Result of Radiated Test

Please refer to Appendix B.



4.4 Effective Isotropic Radiated Power

4.4.1 Description of the EIRP Measurement

Equivalent isotropic radiated power output measurements by substitution method according to ANSI / TIA / EIA-603-D-2010, and the spectrum analyzer configuration follows KDB 971168 D01 Power Meas. License Digital Systems v02r02. Mobile and portable (hand-held) stations operating are limited to average EIRP of 2 watts with LTE band 2 / 7 / 38 / 41.

4.4.2 Test Procedures

1. The EUT was placed on a non-conductive rotating platform 0.8 meters high in a semi-anechoic chamber. The radiated emission at the fundamental frequency was measured at 3 m with a test antenna and a spectrum analyzer with RMS detector per section 5. of KDB 971168 D01.
2. During the measurement, the system simulator parameters were set to force the EUT transmitting at maximum output power. The maximum emission was recorded from analyzer power level (LVL) from the 360 degrees rotation of the turntable and the test antenna raised and lowered over a range from 1 to 4 meters in both horizontally and vertically polarized orientations.
3. Effective Isotropic Radiated Power (EIRP) was measured by substitution method according to TIA/EIA-603-D. The EUT was replaced by the substitution antenna at same location, and then a known power from S.G. was applied into the dipole antenna through a Tx cable, and then recorded the maximum Analyzer reading through raised and lowered the test antenna. The correction factor (in dB) = S.G. - Tx Cable loss + Substitution antenna gain - Analyzer reading. Then the EUT's EIRP was calculated with the correction factor, $EIRP = LVL + \text{Correction factor}$ and $ERP = EIRP - 2.15$. Take the record of the output power at substitution antenna.



	LTE Average					
LTE BW	1.4M	3M	5M	10M	15M	20M
Span	3MHz	6MHz	10MHz	20MHz	30MHz	40MHz
RBW	30kHz	100kHz	100kHz	300kHz	300kHz	300kHz
VBW	100kHz	300kHz	300kHz	1MHz	1MHz	1MHz
Detector	RMS	RMS	RMS	RMS	RMS	RMS
Trace	Average	Average	Average	Average	Average	Average
Average Type	Power	Power	Power	Power	Power	Power
Sweep Count	100	100	100	100	100	100

4.5 Radiated Spurious Emission

4.5.1 Description of Radiated Spurious Emission

The radiated spurious emission was measured by substitution method according to ANSI / TIA / EIA-603-D-2010. The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $43 + 10 \log (P)$ dB.

For Band 7, 38, 41

The power of any emission outside of the authorized operating frequency ranges must be attenuated below the transmitter power (P) by a factor of at least $55 + 10 \log (P)$ dB.

The spectrum is scanned from 30 MHz up to a frequency including its 10th harmonic.

4.5.2 Test Procedures

1. The testing follows FCC KDB 971168 v02r02 Section 5.8 and ANSI / TIA-603-D-2010 Section 2.2.12.
2. The EUT was placed on a rotatable wooden table with 0.8 meter above ground.
3. The EUT was set 3 meters from the receiving antenna, which was mounted on the antenna tower.
4. The table was rotated 360 degrees to determine the position of the highest spurious emission.
5. The height of the receiving antenna is varied between one meter and four meters to search the maximum spurious emission for both horizontal and vertical polarizations.
6. Make the measurement with the spectrum analyzer's RBW = 1MHz, VBW = 3MHz, taking the record of maximum spurious emission.
7. A horn antenna was substituted in place of the EUT and was driven by a signal generator.
8. Tune the output power of signal generator to the same emission level with EUT maximum spurious emission.
9. Taking the record of output power at antenna port.
10. Repeat step 7 to step 8 for another polarization.
11. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

The limit line is derived from $43 + 10\log(P)$ dB below the transmitter power P(Watts)

= $P(W) - [43 + 10\log(P)]$ (dB)

= $[30 + 10\log(P)]$ (dBm) - $[43 + 10\log(P)]$ (dB)

= -13dBm.

For Band 7, 38, 41:

The limit line is derived from $55 + 10\log(P)$ dB below the transmitter power P(Watts)

12. EIRP (dBm) = S.G. Power – Tx Cable Loss + Tx Antenna Gain

13. ERP (dBm) = EIRP - 2.15



5 List of Measuring Equipment

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Test Date	Due Date	Remark
Spectrum Analyzer	R&S	FSV40	101040	10Hz~40GHz	Sep. 10, 2015	Jun. 02, 2016~ Jun. 18, 2016	Sep. 09, 2016	Conducted (TH01-KS)
Thermal Chamber	Ten Billion	TTC-B3S	TBN-960502	-40~+150°C	Oct. 24, 2015	Jun. 02, 2016~ Jun. 18, 2016	Oct. 23, 2016	Conducted (TH01-KS)
EXA Spectrum Analyzer	Keysight	N9010A	MY55150208	10Hz~44GHz; Max 30dB	Apr. 22, 2016	May 23, 2016~ Jun. 20, 2016	Apr. 21, 2017	Radiation (03CH02-KS)
Bilog Antenna	TeseQ	CBL6112D	35406	25MHz~2GHz	Apr. 16, 2016	May 23, 2016~ Jun. 20, 2016	Apr. 15, 2017	Radiation (03CH02-KS)
Double Ridge Horn Antenna	ETS-Lindgren	3117	75957	1GHz~18GHz	Nov. 07, 2015	May 23, 2016~ Jun. 20, 2016	Nov. 06, 2016	Radiation (03CH02-KS)
SHF-EHF Horn	Schwarzbeck	BBHA 9170	BBHA170249	15GHz~40GHz	Mar. 03, 2016	May 23, 2016~ Jun. 20, 2016	Mar. 02, 2017	Radiation (03CH02-KS)
Amplifier	com-power	PA-103A	161069	1kHz~1000MHz / 32 dB	Apr. 22, 2016	May 23, 2016~ Jun. 20, 2016	Apr. 21, 2017	Radiation (03CH02-KS)
Amplifier	Agilent	8449B	3008A02384	1~26.5GHz Gain 30dB	Oct. 24, 2015	May 23, 2016~ Jun. 20, 2016	Oct. 23, 2016	Radiation (03CH02-KS)
Amplifier	MITEQ	TTA1840-35 -HG	1887435	18GHz~40GHz	Jan. 20, 2016	May 23, 2016~ Jun. 20, 2016	Jan. 19, 2017	Radiation (03CH02-KS)
AC Power Source	Chroma	61601	616010002473	N/A	NCR	May 23, 2016~ Jun. 20, 2016	NCR	Radiation (03CH02-KS)
Turn Table	MF	MF7802	N/A	0~360 degree	NCR	May 23, 2016~ Jun. 20, 2016	NCR	Radiation (03CH02-KS)
Antenna Mast	MF	MF7802	N/A	1 m~4 m	NCR	May 23, 2016~ Jun. 20, 2016	NCR	Radiation (03CH02-KS)

NCR: No Calibration Required



6 Uncertainty of Evaluation

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.1dB
--	-------

Uncertainty of Radiated Emission Measurement (1GHz ~ 18GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	4.5dB
--	-------

Uncertainty of Radiated Emission Measurement (18GHz ~ 40GHz)

Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_c(y)$)	5.1dB
--	-------



Appendix A. Test Results of Conducted Test

Conducted Output Power(Average power)

LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.10	21.92	21.71
20	1	49		22.59	22.15	22.04
20	1	99		21.67	22.14	21.55
20	50	0		21.30	21.29	21.16
20	50	24		21.28	21.12	21.14
20	50	50		21.11	21.21	20.97
20	100	0		21.29	21.21	21.16
20	1	0	16-QAM	21.04	20.77	20.84
20	1	49		20.76	20.60	20.83
20	1	99		20.64	20.89	20.63
20	50	0		20.42	20.28	20.11
20	50	24		20.31	20.21	20.06
20	50	50		19.95	20.04	19.84
20	100	0		20.15	20.19	19.98
15	1	0	QPSK	22.37	22.16	21.86
15	1	37		22.11	22.20	22.28
15	1	74		21.99	22.19	22.01
15	36	0		21.26	21.20	21.19
15	36	20		21.15	21.10	21.08
15	36	39		21.22	21.14	21.03
15	75	0		21.29	21.07	21.14
15	1	0	16-QAM	21.47	20.99	20.77
15	1	37		21.11	21.17	20.81
15	1	74		21.15	20.78	20.68
15	36	0		20.38	20.16	20.09
15	36	20		20.17	20.10	20.06
15	36	39		20.36	20.12	20.05
15	75	0		20.47	20.22	20.15



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.16	21.99	21.78
10	1	25		22.46	22.30	22.40
10	1	49		22.01	22.22	21.80
10	25	0		21.40	21.16	21.15
10	25	12		21.23	21.17	21.12
10	25	25		21.17	21.03	21.06
10	50	0		21.32	21.22	21.18
10	1	0	16-QAM	20.85	20.86	20.81
10	1	25		20.88	20.82	20.68
10	1	49		20.83	20.89	20.64
10	25	0		20.46	20.48	20.20
10	25	12		20.36	20.17	20.23
10	25	25		20.22	20.09	20.09
10	50	0		20.40	20.20	20.00
5	1	0	QPSK	22.05	21.69	21.61
5	1	12		22.48	22.21	21.99
5	1	24		22.30	21.81	21.46
5	12	0		21.40	21.06	21.12
5	12	7		21.43	21.15	21.09
5	12	13		21.43	21.06	20.92
5	25	0		21.36	21.15	20.95
5	1	0	16-QAM	20.80	20.78	21.05
5	1	12		21.24	20.80	20.59
5	1	24		20.72	20.61	20.45
5	12	0		20.47	19.91	20.15
5	12	7		20.46	20.12	20.14
5	12	13		20.48	20.19	20.00
5	25	0		20.41	20.09	19.93



LTE Band 2 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
3	1	0	QPSK	22.23	21.76	21.96
3	1	8		22.46	21.90	21.89
3	1	14		22.16	21.80	21.67
3	8	0		21.32	21.10	21.02
3	8	4		21.46	21.13	21.03
3	8	7		21.50	21.04	20.99
3	15	0		21.42	21.01	21.05
3	1	0	16-QAM	21.46	21.00	21.06
3	1	8		21.50	21.08	20.89
3	1	14		21.03	20.97	20.88
3	8	0		20.43	20.09	20.31
3	8	4		20.49	20.13	19.96
3	8	7		20.39	20.06	20.01
3	15	0		20.21	20.08	20.08
1.4	1	0	QPSK	22.28	21.70	21.82
1.4	1	3		22.39	21.88	21.97
1.4	1	5		22.29	21.73	21.87
1.4	3	0		22.37	21.89	22.11
1.4	3	1		22.46	22.01	22.02
1.4	3	3		22.44	21.89	21.95
1.4	6	0		21.42	20.92	20.97
1.4	1	0	16-QAM	20.72	20.83	20.53
1.4	1	3		20.88	20.43	20.51
1.4	1	5		21.21	20.46	20.27
1.4	3	0		21.35	20.89	20.86
1.4	3	1		20.91	21.15	21.07
1.4	3	3		21.46	21.20	21.05
1.4	6	0		20.06	19.94	20.04



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	21.94	21.82	21.84
20	1	49		22.65	22.00	22.39
20	1	99		22.26	21.84	21.97
20	50	0		21.34	21.32	21.46
20	50	24		21.50	21.33	21.48
20	50	50		21.33	21.17	21.39
20	100	0		21.48	21.33	21.46
20	1	0	16-QAM	21.08	21.06	21.19
20	1	49		21.41	21.16	21.78
20	1	99		21.29	21.10	20.81
20	50	0		20.28	20.34	20.47
20	50	24		20.44	20.35	20.32
20	50	50		20.33	20.30	20.37
20	100	0		20.26	20.22	20.44
15	1	0	QPSK	22.10	22.07	22.15
15	1	37		22.31	22.39	22.60
15	1	74		22.14	22.24	22.23
15	36	0		21.28	21.41	21.41
15	36	20		21.27	21.24	21.48
15	36	39		21.34	21.36	21.30
15	75	0		21.28	21.40	21.40
15	1	0	16-QAM	20.97	20.95	21.11
15	1	37		21.06	20.93	21.17
15	1	74		21.08	20.84	20.96
15	36	0		20.17	20.20	20.34
15	36	20		20.16	20.26	20.36
15	36	39		20.23	20.15	20.21
15	75	0		20.29	20.21	20.49



LTE Band 7 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	21.90	22.02	22.05
10	1	25		22.56	22.44	22.23
10	1	49		22.12	21.98	22.14
10	25	0		21.43	21.38	21.47
10	25	12		21.29	21.21	21.47
10	25	25		21.28	21.36	21.40
10	50	0		21.25	21.31	21.47
10	1	0	16-QAM	21.20	21.10	21.27
10	1	25		21.51	21.55	21.21
10	1	49		21.23	21.19	21.05
10	25	0		20.17	20.21	20.60
10	25	12		20.28	20.29	20.54
10	25	25		20.36	20.18	20.21
10	50	0		20.27	20.24	20.38
5	1	0	QPSK	21.74	22.01	22.19
5	1	12		22.43	22.27	22.42
5	1	24		21.96	21.81	22.01
5	12	0		21.31	21.28	21.56
5	12	7		21.32	21.18	21.48
5	12	13		21.27	21.38	21.38
5	25	0		21.42	21.30	21.40
5	1	0	16-QAM	20.84	20.54	20.83
5	1	12		20.94	20.75	21.42
5	1	24		20.82	20.40	20.76
5	12	0		20.17	20.10	20.55
5	12	7		20.29	20.17	20.70
5	12	13		20.25	20.25	20.47
5	25	0		20.10	20.53	20.39



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	21.96	21.30	21.73
20	1	49		22.20	21.90	22.01
20	1	99		21.58	21.87	21.68
20	50	0		21.07	20.95	20.94
20	50	24		21.44	21.32	20.96
20	50	50		21.10	20.91	20.93
20	100	0		21.40	20.92	20.95
20	1	0	16-QAM	20.69	20.51	20.39
20	1	49		20.75	20.59	20.68
20	1	99		20.38	20.25	20.29
20	50	0		20.18	20.37	20.18
20	50	24		20.12	19.97	19.93
20	50	50		20.03	20.19	20.18
20	100	0		20.20	20.01	20.10
15	1	0	QPSK	21.76	22.00	21.63
15	1	37		22.16	21.96	22.12
15	1	74		21.67	21.67	21.65
15	36	0		21.46	21.00	20.96
15	36	20		21.27	20.81	21.11
15	36	39		21.26	20.97	21.03
15	75	0		21.26	21.15	20.96
15	1	0	16-QAM	20.64	20.60	20.48
15	1	37		20.88	20.73	21.12
15	1	74		20.62	20.49	20.62
15	36	0		20.19	20.02	19.87
15	36	20		20.18	19.98	20.07
15	36	39		20.16	19.98	20.07
15	75	0		20.26	20.11	19.95



LTE Band 38 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	21.92	21.80	21.70
10	1	25		22.19	22.11	22.18
10	1	49		21.83	21.65	21.73
10	25	0		21.03	20.79	21.14
10	25	12		21.29	20.80	21.23
10	25	25		21.10	20.93	21.05
10	50	0		21.14	20.87	21.00
10	1	0	16-QAM	20.79	20.58	20.42
10	1	25		20.77	20.71	20.72
10	1	49		20.62	20.36	20.55
10	25	0		20.35	20.03	20.31
10	25	12		20.41	20.41	20.48
10	25	25		20.34	20.21	20.28
10	50	0		20.10	19.96	19.99
5	1	0	QPSK	21.69	21.45	21.75
5	1	12		22.18	21.97	22.09
5	1	24		21.73	21.76	21.50
5	12	0		21.12	21.03	21.04
5	12	7		21.08	20.80	21.04
5	12	13		21.14	20.94	21.01
5	25	0		21.05	20.96	20.92
5	1	0	16-QAM	20.82	20.49	20.61
5	1	12		20.97	20.74	20.74
5	1	24		20.58	20.46	20.45
5	12	0		20.12	19.82	19.99
5	12	7		20.20	19.91	20.06
5	12	13		20.18	19.87	19.94
5	25	0		20.46	20.12	20.23



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
20	1	0	QPSK	22.22	22.16	22.24
20	1	49		22.71	22.20	22.88
20	1	99		21.91	21.91	22.16
20	50	0		21.39	21.10	21.40
20	50	24		21.34	20.98	21.28
20	50	50		21.26	21.07	21.22
20	100	0		21.39	21.07	21.40
20	1	0	16-QAM	20.77	20.68	20.45
20	1	49		21.14	20.86	21.22
20	1	99		20.99	20.45	20.67
20	50	0		20.46	20.07	20.26
20	50	24		20.51	20.12	20.40
20	50	50		20.84	20.04	20.34
20	100	0		20.41	20.05	20.33
15	1	0	QPSK	22.28	21.82	22.24
15	1	37		22.21	22.16	22.69
15	1	74		22.15	22.14	22.25
15	36	0		21.41	21.07	21.11
15	36	20		21.47	20.91	21.29
15	36	39		21.43	21.06	21.30
15	75	0		21.44	21.02	21.19
15	1	0	16-QAM	20.82	20.91	20.30
15	1	37		21.31	21.01	21.17
15	1	74		20.72	20.63	20.78
15	36	0		20.36	20.01	20.26
15	36	20		20.52	20.11	20.46
15	36	39		20.54	20.06	20.30
15	75	0		20.55	19.98	20.34



LTE Band 41 Maximum Average Power [dBm]						
BW [MHz]	RB Size	RB Offset	Mod	Lowest	Middle	Highest
10	1	0	QPSK	22.21	21.96	22.57
10	1	25		22.52	21.85	22.35
10	1	49		22.53	22.16	22.40
10	25	0		21.40	21.00	21.22
10	25	12		21.35	21.15	21.33
10	25	25		21.33	21.04	21.34
10	50	0		21.45	21.04	21.29
10	1	0	16-QAM	20.84	20.59	20.73
10	1	25		21.03	20.89	21.11
10	1	49		21.02	20.51	20.82
10	25	0		20.65	20.21	20.58
10	25	12		20.66	20.21	20.59
10	25	25		20.64	20.16	20.56
10	50	0		20.62	19.98	20.33
5	1	0	QPSK	22.22	21.65	22.03
5	1	12		22.50	22.09	22.61
5	1	24		22.04	21.89	22.30
5	12	0		21.17	20.95	21.26
5	12	7		21.37	20.96	21.59
5	12	13		21.25	20.96	21.62
5	25	0		21.36	21.02	20.86
5	1	0	16-QAM	20.58	20.75	21.08
5	1	12		21.18	20.94	21.12
5	1	24		21.01	20.77	20.81
5	12	0		20.27	19.90	19.86
5	12	7		20.46	20.01	20.10
5	12	13		20.39	19.97	20.20
5	25	0		20.31	19.96	20.75

Peak-to-Average Ratio

Mode	LTE Band 2 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	4.72	4.81	5.68	5.86	PASS
Middle CH	4.78	4.72	5.28	5.88	
Highest CH	4.43	4.93	5.65	5.88	

Mode	LTE Band 7 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.91	4.64	4.78	5.65	PASS
Middle CH	4.17	4.67	5.45	5.74	
Highest CH	4.12	4.46	4.81	5.54	


Mode	LTE Band 38 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	3.91	5.19	5.62	6.06	PASS
Middle CH	4.17	5.88	6.06	5.62	
Highest CH	4.67	4.84	5.42	5.86	

Mode	LTE Band 41 / 20MHz				
Mod.	QPSK		16QAM		Limit: 13dB
RB Size	1RB	Full RB	1RB	Full RB	Result
Lowest CH	5.13	4.67	6.52	5.91	PASS
Middle CH	4.52	5.62	6.52	6.67	
Highest CH	5.16	4.84	5.16	5.45	




LTE Band 2 / 20MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 2 / 20MHz / 16QAM

Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 7 / 20MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB



Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 7 / 20MHz / 16QAM


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB



Highest Channel / 1RB



Highest Channel / Full RB






LTE Band 38 / 20MHz / QPSK

Lowest Channel / 1RB



Lowest Channel / Full RB




Middle Channel / 1RB




Middle Channel / Full RB









Highest Channel / 1RB



Highest Channel / Full RB




LTE Band 38 / 20MHz / 16QAM
Lowest Channel / 1RB

Lowest Channel / Full RB

Middle Channel / 1RB

Middle Channel / Full RB

Highest Channel / 1RB

Highest Channel / Full RB





LTE Band 41 / 20MHz / QPSK


Lowest Channel / 1RB




Lowest Channel / Full RB




Middle Channel / 1RB



Middle Channel / Full RB



Highest Channel / 1RB




Highest Channel / Full RB






LTE Band 41 / 20MHz / 16QAM

Lowest Channel / 1RB




Date: 16 JUN 2016 15:32:07

Lowest Channel / Full RB




Date: 16 JUN 2016 15:33:00

Middle Channel / 1RB



Date: 16 JUN 2016 15:40:12

Middle Channel / Full RB



Date: 16 JUN 2016 15:40:26

Highest Channel / 1RB



Date: 16 JUN 2016 15:46:45

Highest Channel / Full RB



Date: 16 JUN 2016 15:43:40


**26dB Bandwidth**

Mode	LTE Band 2 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	1.25	1.27	3.02	3.02	4.96	4.91	9.95	9.67	14.42	14.36	20.34	19.94
Middle CH	1.28	1.27	3.03	3.02	4.88	4.84	10.03	9.63	14.39	14.36	20.14	20.02
Highest CH	1.24	1.26	2.99	3.03	4.94	4.91	9.81	9.75	14.27	14.36	19.98	20.06


Mode	LTE Band 7 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.91	4.93	9.81	9.67	14.33	14.21	20.18	20.14
Middle CH	-	-	-	-	4.92	4.93	9.83	9.77	14.27	14.45	20.10	20.14
Highest CH	-	-	-	-	4.77	4.91	9.75	9.63	14.18	14.33	20.18	20.14

Mode	LTE Band 38 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	5.01	4.97	9.71	9.71	14.42	14.12	20.18	20.30
Middle CH	-	-	-	-	4.82	4.80	9.63	9.85	14.36	14.30	20.14	19.94
Highest CH	-	-	-	-	4.94	4.80	9.71	9.81	14.33	14.30	19.94	20.14


Mode	LTE Band 41 : 26dB BW(MHz)											
BW	1.4MHz		3MHz		5MHz		10MHz		15MHz		20MHz	
Mod.	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM	QPSK	16QAM
Lowest CH	-	-	-	-	4.79	4.82	9.79	9.71	14.18	14.15	20.22	20.18
Middle CH	-	-	-	-	4.76	4.94	9.67	9.95	14.12	14.21	20.22	20.14
Highest CH	-	-	-	-	5.02	4.98	9.65	9.71	14.15	14.42	20.30	20.22

LTE Band 2
Lowest Channel / 1.4MHz / QPSK



Date: 2 JUN 2016 02:26:58

Lowest Channel / 1.4MHz / 16QAM



Date: 2 JUN 2016 02:27:08

Middle Channel / 1.4MHz / QPSK



Date: 2 JUN 2016 02:34:03

Middle Channel / 1.4MHz / 16QAM


Date: 2 JUN 2016 02:34:13

Highest Channel / 1.4MHz / QPSK


Date: 2 JUN 2016 02:36:36


Highest Channel / 1.4MHz / 16QAM


Date: 2 JUN 2016 02:36:46




LTE Band 2


Lowest Channel / 3MHz / QPSK




Lowest Channel / 3MHz / 16QAM




Middle Channel / 3MHz / QPSK




Middle Channel / 3MHz / 16QAM



Highest Channel / 3MHz / QPSK




Highest Channel / 3MHz / 16QAM






LTE Band 2

Lowest Channel / 5MHz / QPSK




Date: 2 JUN 2016 03:00:23

Lowest Channel / 5MHz / 16QAM




Date: 2 JUN 2016 03:00:34

Middle Channel / 5MHz / QPSK




Date: 2 JUN 2016 03:07:28

Middle Channel / 5MHz / 16QAM




Date: 2 JUN 2016 03:07:38

Highest Channel / 5MHz / QPSK



Date: 2 JUN 2016 03:10:00

Highest Channel / 5MHz / 16QAM




Date: 2 JUN 2016 03:10:11




LTE Band 2

Lowest Channel / 10MHz / QPSK




Date: 2 JUN 2016 03:17:05

Lowest Channel / 10MHz / 16QAM




Date: 2 JUN 2016 03:17:15

Middle Channel / 10MHz / QPSK




Date: 2 JUN 2016 03:24:09

Middle Channel / 10MHz / 16QAM




Date: 2 JUN 2016 03:24:19

Highest Channel / 10MHz / QPSK



Date: 2 JUN 2016 03:26:41

Highest Channel / 10MHz / 16QAM



Date: 2 JUN 2016 03:26:52