

- SPEC TABLE

LAMP WATT (W)	20 W	23 W	26 W	32 W
INPUT VOLT (V)	110 V 50 / 60 Hz			
INPUT CURRENT (A)	0.18 A	0.20 A	0.21 A	0.22 A
LUMINOUS FLUX(Lm)	1200	1500	1750	2250
COLOR TEMPERATURE (k)	6500 K / 3000 K			
LENGTH (m/m)	126	130	137	142
DIAMETER (□)	50 □			
WEIGHT(G)	75	80	85	90
SOK	E26 / B22D			

- Warnning

- Do not cover the paper and towel on the lamp.
- Do not put down flammable object beside of the lamp.
- Do not use dimmable lighting fixture.
- Do not contact with A.C.
- Turn off the switch during setting, separating and cleaning.
- Do not use making waterdrop.
- Do not hold too strong, schretch and crash.
- Do not touch upon turning off or turning on.
- Assemble the lamp with socket completely.

- Caution is use

- Do not separate and retrofit.
- Do not apply with enclosed fixture.
- Frequent on/off switch caused short lifetime.
- Do not use over 40 □.

- Guarantee

- Lifetime : 10 times of incandescent lamp.
- Energy saving : 80 % than incandescent lamp.
- Replacement if any defects when buying.

- FCC NOTICE

THIS PRODUCT MAY CAUSE INTERFERENCE TO RADIO EQUIPMENT AND SHOULD NOT BE
INSTALLED NEAR MARITIME SAFETY COMMUNICATIONS EQUIPMENT OR OTHER CRITICAL
NAVIGATION OR COMMUNICATION EQUIPMENT OPERATING BETWEEN .45-30 MHZ.