



BUREAU
VERITAS

FCC RF Exposure Test Report



FCC RF Exposure Test Report

Report No. : W7L-220214W001SA01
Applicant : Continental Automotive Systems, Inc.
Address : 21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Product : FE5NA0010, FE5NA0011
FCC ID : LHJ-FE5NA0010
Brand : Continental
Model No. : FE5NA0010, FE5NA0011
Standards : FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06

Sample Received Date : Mar. 15, 2022
Date of Testing : Mar. 15, 2022 ~ Jul. 30, 2022

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

Jerry Chen

Jerry Chen / Engineer

Approved By :

Luke Lu

Luke Lu / Manager

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU
VERITAS

FCC RF Exposure Test Report



Table of Contents

RELEASE CONTROL RECORD.....	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST	4
2. MPE(MAXIMUM PERMISSIBLE EXPOSURE) ASSESSMENT	5
2.1 INTRODUCTION.....	5
2.2 RF RADIATION EXPOSURE LIMITS.....	5
2.3 MPE ASSESSMENT METHOD.....	6
2.4 MPE CALCULATION FOR STANDALONE OPERATIONS.....	6
3. INFORMATION ON THE TESTING LABORATORIES.....	9



**BUREAU
VERITAS** FCC RF Exposure Test Report



Release Control Record

BUREAU
VERITAS

FCC RF Exposure Test Report



1. Description of Equipment Under Test

EUT Type	FE5NA0010, FE5NA0011
FCC ID	LHJ-FE5NA0010
Brand Name	Continental
Model Name	FE5NA0010, FE5NA0011
Tx Frequency Bands (Unit: MHz)	WCDMA Band II : 1852.4 ~ 1907.6 WCDMA Band IV: 1712.4 ~ 1752.6 WCDMA Band V : 826.4 ~ 846.6 LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 7 : 2502.5 MHz ~ 2567.5 MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 14 : 790.5 MHz ~ 795.5 MHz LTE Band 66 : 1710.7 MHz ~ 1779.3 MHz LTE Band 71 : 665.5 MHz ~ 695.5 MHz LTE Band CA_5B: 825.6MHz ~ 847.4MHz LTE Band CA_7C: 2505.5MHz ~ 2564.7Hz LTE Band CA_66B: 1712.5MHz ~ 1777.5MHz LTE Band CA_66C: 1713.3MHz ~ 1776.7MHz NR Band n2(NSA):1852.5MHz ~ 1907.5MHz NR Band n5(NSA):826.5MHz ~ 846.5MHz NR Band n25(SA):1852.5MHz ~1912.5MHz NR Band n41/n41 HPUE(SA): 2506.02MHz ~ 2679.99MHz NR Band n66(SA): 1712.5MHz ~ 1777.5MHz NR Band n71(SA): 665.5MHz ~ 695.5MHz NR Band n77C/n77C-HPUE(SA): 3710MHz ~ 3970MHz
Uplink Modulations	WCDMA :QPSK LTE : QPSK, 16QAM, 64QAM 5G NR: DFT-s-OFDMA($\pi/2$ BPSK,QPSK,16QAM,64QAM,256QAM); CP-OFDMA(QPSK,16QAM,64QAM,256QAM)
Antenna Type	WWAN: Monopole antenna
EUT Stage	Production Unit

Note:

1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.
2. According to the information provided by the manufacturer, The difference between FE5NA0010, FE5NA0011 is as follows:

TA-code	L2/L5 GNSS	Band Difference
FE5NA0010	support	/
FE5NA0011	not support	BOM change: depopulated passive components from the GNSS RF front-end



2. MPE(Maximum Permissible Exposure) Assessment

2.1 Introduction

According to 47 CFR §2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitting antenna and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 cm separation requirement. The limits to be used for MPE evaluation are specified in §1.1310. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population/uncontrolled exposure.

2.2 RF Radiation Exposure Limits

According to 47 CFR §1.1310, the criteria listed in below table shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093.

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (min)
(A) Limits for Occupational / Controlled Exposures				
0.3 – 3.0	614	1.63	100	6
3.0 – 30	1842/f	4.89/f	900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	-	-	f/300	6
1500 – 100000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposures				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	-	-	f/1500	30
1500 – 100000	-	-	1.0	30

Limits for maximum permissible exposure (MPE)

Notes:

1. f = frequency in MHz
2. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided they are made aware of the potential for exposure.
3. General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



BUREAU
VERITAS

FCC RF Exposure Test Report



2.3 MPE Assessment Method

Calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations below. This equation is generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction.

$$\text{Power Density (S)} = \frac{PG}{4\pi R^2} = \frac{\text{EIRP}}{4\pi R^2}$$

Where

S = Power Density, unit in mW/cm²

P = Power input to the antenna, unit in mW

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna, unit in cm

EIRP = Effective isotropically radiated power

2.4 MPE Calculation for Standalone Operations

The manufacturer expects that the radiated component of this device will not close to the human body during normal usage and the warning statement was also stated in the user instruction. Since the transmitting antenna will be kept at least 20 cm away from the human body, the MPE level is calculated based on this condition and the result is listed in below table.



BUREAU
VERITAS

FCC RF Exposure Test Report



CALCULATION FOR MAXIMUM E.I.R.P

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Average EIRP (mW)	Power Density (mW/cm^2)	Limit (mW/cm^2)	Power Density / Limit	Result (PASS / FAIL)
WCDMA Band II	2.45	24	441.57	0.088	1.000	0.088	Pass
WCDMA Band IV	3.09	24	511.68	0.102	1.000	0.102	Pass
WCDMA Band V	0.58	24	287.08	0.057	0.551	0.103	Pass
LTE Band 2	2.45	24	441.57	0.088	1.000	0.088	Pass
LTE Band 4	3.09	24	511.68	0.102	1.000	0.102	Pass
LTE Band 5	0.58	24	287.08	0.057	0.550	0.104	Pass
LTE Band 7	1.69	24	370.68	0.074	1.000	0.074	Pass
LTE Band 12	-1.88	24	162.93	0.032	0.466	0.069	Pass
LTE Band 13	-1.88	24	162.93	0.032	0.520	0.062	Pass
LTE Band 14	-1.88	24	162.93	0.032	0.527	0.061	Pass
LTE Band 66	3.09	24	511.68	0.102	1.000	0.102	Pass
LTE Band 71	0.14	24	259.42	0.052	0.444	0.117	Pass
LTE Band CA_5B	0.58	24	287.08	0.057	0.550	0.104	Pass
LTE Band CA_7C	1.69	24	370.68	0.074	1.000	0.074	Pass
LTE Band CA_66B	3.09	24	511.68	0.102	1.000	0.102	Pass
LTE Band CA_66C	3.09	24	511.68	0.102	1.000	0.102	Pass
NR Band n2(NSA)	2.45	24	441.57	0.088	1.000	0.088	Pass
NR Band n5(NSA)	0.58	24	287.08	0.057	0.551	0.103	Pass
NR Band n25(SA)	4.84	24	765.60	0.152	1.000	0.152	Pass
NR Band n41/n41 HPUE(SA)	1.69	27	739.61	0.147	1.000	0.147	Pass
NR Band n66(SA)	3.09	24	511.68	0.102	1.000	0.102	Pass
NR Band n71(SA)	0.14	24	259.42	0.052	0.444	0.117	Pass
NR Band n77C/n77C-HPUE(SA)	1.5	27	707.95	0.141	1.000	0.141	Pass



CALCULATION MAX ANTENNA GAIN :

WCDMA

Band	Frequency (dBi)	Antenna Gain (dBi)	Conducted Tune-up Peak Power(dBm)	Limit EIRP (dBm)	Limit EIRP (W)	Power Density at 20cm (mW/cm^2)	limit (mW/cm^2)	Result (PASS / FAIL)
WCDMA Band II	1852.4	9	24	33.01	2	0.397	1.000	Pass
WCDMA Band IV	1712.4	6	24	30	1	0.199	1.000	Pass
WCDMA Band V	826.4	10.4	24	40.6	11.5	0.548	0.551	Pass

LTE

Band	Frequency (dBi)	Antenna Gain (dBi)	Conducted Tune-up Peak Power(dBm)	Limit EIRP (dBm)	Limit EIRP (W)	Power Density at 20cm (mW/cm^2)	limit (mW/cm^2)	Result (PASS / FAIL)
LTE Band 2	1850.7	9	24	33.01	2	0.397	1.000	Pass
LTE Band 4	1710.7	6	24	30	1	0.199	1.000	Pass
LTE Band 5	824.7	10.4	24	40.6	11.5	0.548	0.550	Pass
LTE Band 7	2502.5	9	24	33.01	2	0.397	1.000	Pass
LTE Band 12	699.7	9.6	24	36.92	4.92	0.456	0.466	Pass
LTE Band 13	779.5	10.1	24	36.92	4.92	0.512	0.520	Pass
LTE Band 14	790.5	10.2	24	36.92	4.92	0.524	0.527	Pass
LTE Band 66	1710.7	6	24	30	1	0.199	1.000	Pass
LTE Band 71	665.5	9.4	24	36.92	4.92	0.435	0.444	Pass
LTE Band CA_5B	825.6	10.4	24	40.6	11.5	0.548	0.550	Pass
LTE Band CA_7C	2505.5	9	24	33.01	2	0.397	1.000	Pass
LTE Band CA_66B	1712.5	6	24	30	1	0.199	1.000	Pass
LTE Band CA_66C	1713.3	6	24	30	1	0.199	1.000	Pass

5G NR

Band	Frequency (dBi)	Antenna Gain (dBi)	Conducted Tune-up Peak Power(dBm)	Limit EIRP (dBm)	Limit EIRP (W)	Power Density at 20cm (mW/cm^2)	limit (mW/cm^2)	Result (PASS / FAIL)
NR Band n2(NSA)	1852.5	9	24	33.01	2	0.397	1.000	Pass
NR Band n5(NSA)	826.5	10.4	24	40.6	11.5	0.548	0.551	Pass
NR Band n25(SA)	1852.5	9	24	33.01	2	0.397	1.000	Pass
NR Band n41/n41 HPUE(SA)	2506.02	6	27	33.01	2	0.199	1.000	Pass
NR Band n66(SA)	1712.5	6	24	30	1	0.199	1.000	Pass
NR Band n71(SA)	665.5	9.4	24	36.92	3	0.435	0.444	Pass
NR Band n77C/n77C-HPUE (SA)	3710	3	27	30	1	0.199	1.000	Pass



BUREAU
VERITAS

FCC RF Exposure Test Report



3. Information on the Testing Laboratories

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Add: No. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industry Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-8869-6566

Fax: 86-755-8869-6577

Email: customerservice.sw@bureauveritas.com

Web Site: www.bureauveritas.com

The road map of all our labs can be found in our web site also.

---END---