

BW	MCS Index	RB	RB Size	RB Offset	Low CH 650000	Mid CH 656000	High CH 662000	Max. Tune-up (dBm)
					Frequency 3750MHz	Frequency 3840MHz	Frequency 3930MHz	
100M	CP-OFDM QPSK	Outer	1	0	24.49	24.19	24.34	26
			1	272	24.59	24.37	24.47	26
			2	0	24.55	24.21	24.40	26
			2	271	24.59	24.33	24.51	26
			273	0	25.29	25.13	25.12	26
		Inner	1	1	25.79	25.63	25.77	27
			1	271	26.04	25.81	25.90	27
			137	68	25.81	25.66	25.70	27
	CP-OFDM 16QAM	Outer	1	0	24.42	24.28	24.33	26
			1	272	24.55	24.47	24.51	26
			2	0	24.47	24.21	24.31	26
			2	271	24.49	24.41	24.45	26
			273	0	25.26	24.98	25.14	26
		Inner	1	1	25.54	25.28	25.38	27
			1	271	25.64	25.47	25.52	27
			137	68	25.49	25.32	25.36	27
	CP-OFDM 64QAM	Outer	1	0	23.81	23.59	23.75	25
			1	272	23.94	23.78	23.75	25
			2	0	23.85	23.67	23.78	25
			2	271	23.94	23.82	23.82	25
			273	0	24.20	23.89	24.08	25
		Inner	1	1	23.81	23.68	23.71	25
			1	271	23.90	23.69	23.78	25
			137	68	24.18	24.00	24.12	25
	CP-OFDM 256QAM	Outer	1	0	23.77	23.54	23.64	25
			1	272	23.91	23.64	23.74	25
			2	0	23.88	23.62	23.78	25
			2	271	23.96	23.74	23.76	25
			273	0	23.87	23.66	23.68	25
		Inner	1	1	23.81	23.56	23.68	25
			1	271	23.88	23.59	23.71	25
			137	68	23.99	23.76	23.90	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647334	Mid CH 656000	High CH 664666	Max. Tune-up (dBm)
					Frequency 3710MHz	Frequency 3840MHz	Frequency 3970MHz	
20M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.94	24.61	24.79	26
			1	50	25.34	25.00	25.09	26
			2	0	25.01	24.78	24.82	26
			2	49	25.45	25.18	25.28	26
			50	0	26.76	26.47	26.62	27
		Inner	1	1	26.53	26.25	26.29	27
			1	49	26.69	26.52	26.66	27
			25	12	26.77	26.59	26.56	27
	DFT-s-OFDM QPSK	Outer	1	0	24.91	24.50	24.74	26
			1	50	25.36	25.11	25.21	26
			2	0	25.13	24.70	24.94	26
			2	49	25.34	25.08	25.20	26
			50	0	26.77	26.43	26.53	27
		Inner	1	1	26.46	26.09	26.18	27
			1	49	26.76	26.46	26.63	27
			25	12	26.77	26.43	26.49	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.99	24.60	24.82	26
			1	50	25.33	25.01	25.14	26
			2	0	24.97	24.59	24.71	26
			2	49	25.28	25.08	25.15	26
			50	0	25.85	25.46	25.72	27
		Inner	2	49	26.21	26.01	26.04	27
			25	12	26.58	26.22	26.47	27
			50	0	26.36	26.19	26.24	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.16	24.77	24.99	26
			1	50	25.39	25.00	25.19	26
			2	0	24.77	24.42	24.62	26
			2	49	24.95	24.75	24.67	26
			50	0	25.49	25.13	25.23	26
		Inner	1	1	24.97	24.72	24.78	26
			1	49	25.19	24.91	25.01	26
			25	12	24.97	24.72	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.85	23.46	23.64	25
			1	50	23.91	23.66	23.76	25
			2	0	23.90	23.59	23.71	25
			2	49	23.84	23.55	23.64	25
			50	0	23.94	23.63	23.79	25
		Inner	1	1	23.94	23.61	23.77	25
			1	49	24.01	23.67	23.87	25
			25	12	23.48	23.23	23.28	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647668	Mid CH 656000	High CH 664332	Max. Tune-up (dBm)
					Frequency 3715MHz	Frequency 3840MHz	Frequency 3965MHz	
30M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.91	24.65	24.75	26
			1	77	25.28	25.00	25.15	26
			2	0	25.03	24.76	24.81	26
			2	76	25.39	25.24	25.28	26
			75	0	26.78	26.50	26.63	27
		Inner	1	1	26.48	26.25	26.32	27
			1	76	26.69	26.55	26.70	27
			36	18	26.71	26.58	26.55	27
	DFT-s-OFDM QPSK	Outer	1	0	24.91	24.50	24.73	26
			1	77	25.36	25.09	25.18	26
			2	0	25.09	24.76	24.89	26
			2	76	25.37	25.04	25.24	26
			75	0	26.76	26.44	26.50	27
		Inner	1	1	26.42	26.08	26.21	27
			1	76	26.81	26.52	26.57	27
			36	18	26.73	26.37	26.51	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.05	24.62	24.86	26
			1	77	25.31	25.00	25.11	26
			2	0	24.97	24.58	24.74	26
			2	76	25.29	25.08	25.16	26
			75	0	25.79	25.50	25.68	27
		Inner	1	1	26.26	25.99	26.07	27
			1	76	26.58	26.23	26.43	27
			36	18	26.36	26.22	26.27	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.15	24.78	24.93	26
			1	77	25.33	25.06	25.22	26
			2	0	24.78	24.45	24.60	26
			2	76	24.94	24.69	24.74	26
			75	0	25.49	25.13	25.23	26
		Inner	1	1	24.97	24.72	24.78	26
			1	76	25.19	24.91	25.01	26
			36	18	24.97	24.72	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.85	23.46	23.64	25
			1	77	23.91	23.66	23.76	25
			2	0	23.90	23.59	23.71	25
			2	76	23.84	23.55	23.64	25
			75	0	23.94	23.63	23.79	25
		Inner	1	1	23.94	23.61	23.77	25
			1	76	24.00	23.69	23.86	25
			36	18	23.55	23.22	23.25	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648000	Mid CH 656000	High CH 664000	Max. Tune-up (dBm)
					Frequency 3720MHz	Frequency 3840MHz	Frequency 3960MHz	
40M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.93	24.59	24.80	26
			1	105	25.32	24.99	25.13	26
			2	0	25.06	24.77	24.84	26
			2	104	25.42	25.24	25.27	26
			100	0	26.80	26.50	26.63	27
		Inner	1	1	26.47	26.25	26.29	27
			1	104	26.72	26.57	26.71	27
			50	25	26.78	26.54	26.57	27
	DFT-s-OFDM QPSK	Outer	1	0	24.88	24.56	24.71	26
			1	105	25.42	25.12	25.20	26
			2	0	25.07	24.77	24.93	26
			2	104	25.38	25.07	25.17	26
			100	0	26.74	26.47	26.52	27
		Inner	1	1	26.43	26.08	26.22	27
			1	104	26.79	26.50	26.59	27
			50	25	26.71	26.40	26.55	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.98	24.66	24.82	26
			1	105	25.34	24.99	25.15	26
			2	0	24.91	24.60	24.69	26
			2	104	25.33	25.12	25.15	26
			100	0	25.79	25.53	25.71	27
		Inner	1	1	26.27	25.99	26.01	27
			1	104	26.59	26.28	26.40	27
			50	25	26.39	26.15	26.25	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.18	24.81	24.93	26
			1	105	25.36	24.99	25.20	26
			2	0	24.81	24.47	24.58	26
			2	104	24.91	24.75	24.68	26
			100	0	25.43	25.12	25.29	26
		Inner	1	1	24.95	24.68	24.79	26
			1	104	25.14	24.87	25.03	26
			50	25	24.95	24.75	24.82	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.78	23.47	23.67	25
			1	105	23.95	23.68	23.70	25
			2	0	23.83	23.62	23.72	25
			2	104	23.83	23.51	23.62	25
			100	0	23.94	23.63	23.80	25
		Inner	1	1	23.94	23.61	23.75	25
			1	104	23.96	23.70	23.86	25
			50	25	23.48	23.25	23.28	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648334	Mid CH 656000	High CH 663666	Max. Tune-up (dBm)
					Frequency 3725MHz	Frequency 3840MHz	Frequency 3955MHz	
50M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.92	24.60	24.76	26
			1	132	25.33	24.97	25.15	26
			2	0	25.02	24.73	24.85	26
			2	131	25.43	25.20	25.28	26
		Inner	128	0	26.74	26.54	26.59	27
			1	1	26.50	26.22	26.36	27
			1	131	26.70	26.58	26.67	27
			64	32	26.72	26.55	26.58	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.56	24.70	26
			1	132	25.42	25.07	25.24	26
			2	0	25.07	24.72	24.87	26
			2	131	25.36	25.10	25.19	26
		Inner	128	0	26.73	26.44	26.53	27
			1	1	26.46	26.11	26.19	27
			1	131	26.77	26.52	26.57	27
			64	32	26.76	26.40	26.53	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.98	24.66	24.82	26
			1	132	25.30	24.99	25.09	26
			2	0	24.97	24.60	24.68	26
			2	131	25.29	25.14	25.15	26
		Inner	128	0	25.85	25.49	25.65	27
			1	1	26.23	25.98	26.03	27
			1	131	26.58	26.25	26.41	27
			64	32	26.36	26.21	26.23	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.17	24.82	24.94	26
			1	132	25.33	25.02	25.16	26
			2	0	24.80	24.49	24.56	26
			2	131	24.91	24.70	24.70	26
		Inner	128	0	25.48	25.09	25.29	26
			1	1	24.96	24.67	24.83	26
			1	131	25.20	24.90	24.97	26
			64	32	24.96	24.69	24.82	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.83	23.42	23.67	25
			1	132	23.97	23.66	23.73	25
			2	0	23.85	23.55	23.72	25
			2	131	23.85	23.48	23.69	25
		Inner	128	0	23.90	23.64	23.76	25
			1	1	23.98	23.56	23.75	25
			1	131	23.97	23.67	23.86	25
			64	32	23.55	23.25	23.25	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648668	Mid CH 656000	High CH 663332	Max. Tune-up (dBm)
					Frequency 3730MHz	Frequency 3840MHz	Frequency 3950MHz	
60M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.91	24.65	24.75	26
			1	161	25.28	25.00	25.15	26
			2	0	25.03	24.76	24.81	26
			2	160	25.39	25.24	25.28	26
			162	0	26.78	26.50	26.63	27
		Inner	1	1	26.48	26.25	26.32	27
			1	160	26.69	26.55	26.70	27
			81	40	26.71	26.58	26.55	27
	DFT-s-OFDM QPSK	Outer	1	0	24.91	24.50	24.73	26
			1	161	25.36	25.09	25.18	26
			2	0	25.09	24.76	24.89	26
			2	160	25.37	25.04	25.24	26
			162	0	26.76	26.44	26.50	27
		Inner	1	1	26.42	26.08	26.21	27
			1	160	26.81	26.52	26.57	27
			81	40	26.73	26.37	26.51	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.05	24.62	24.86	26
			1	161	25.31	25.00	25.11	26
			2	0	24.97	24.58	24.74	26
			2	160	25.29	25.08	25.16	26
			162	0	25.79	25.50	25.68	27
		Inner	1	1	26.26	25.99	26.07	27
			1	160	26.58	26.23	26.43	27
			81	40	26.36	26.22	26.27	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.15	24.78	24.93	26
			1	161	25.33	25.06	25.22	26
			2	0	24.78	24.45	24.60	26
			2	160	24.94	24.69	24.74	26
			162	0	25.49	25.13	25.23	26
		Inner	1	1	24.97	24.72	24.78	26
			1	160	25.19	24.91	25.01	26
			81	40	24.97	24.72	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.85	23.46	23.64	25
			1	161	23.91	23.66	23.76	25
			2	0	23.90	23.59	23.71	25
			2	160	23.84	23.55	23.64	25
			162	0	23.94	23.63	23.79	25
		Inner	1	1	23.94	23.61	23.77	25
			1	160	24.00	23.69	23.86	25
			81	40	23.55	23.22	23.25	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649000	Mid CH 656000	High CH 663000	Max. Tune-up (dBm)
					Frequency 3735MHz	Frequency 3840MHz	Frequency 3945MHz	
70M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.94	24.61	24.79	26
			1	188	25.34	25.00	25.09	26
			2	0	25.01	24.78	24.82	26
			2	187	25.45	25.18	25.28	26
			180	0	26.76	26.47	26.62	27
		Inner	1	1	26.53	26.25	26.29	27
			1	187	26.69	26.52	26.66	27
			90	45	26.77	26.59	26.56	27
	DFT-s-OFDM QPSK	Outer	1	0	24.91	24.50	24.74	26
			1	188	25.36	25.11	25.21	26
			2	0	25.13	24.70	24.94	26
			2	187	25.34	25.08	25.20	26
			180	0	26.77	26.43	26.53	27
		Inner	1	1	26.46	26.09	26.18	27
			1	187	26.76	26.46	26.63	27
			90	45	26.77	26.43	26.49	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.99	24.60	24.82	26
			1	188	25.33	25.01	25.14	26
			2	0	24.97	24.59	24.71	26
			2	187	25.28	25.08	25.15	26
			180	0	25.85	25.53	25.69	27
		Inner	1	1	26.23	26.00	26.08	27
			1	187	26.59	26.28	26.43	27
			90	45	26.36	26.16	26.27	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.18	24.79	24.98	26
			1	188	25.38	25.06	25.18	26
			2	0	24.76	24.42	24.58	26
			2	187	24.93	24.71	24.73	26
			180	0	25.48	25.10	25.26	26
		Inner	1	1	24.95	24.67	24.82	26
			1	187	25.19	24.84	25.04	26
			90	45	24.95	24.73	24.83	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.84	23.41	23.64	25
			1	188	23.93	23.65	23.76	25
			2	0	23.90	23.61	23.66	25
			2	187	23.85	23.48	23.68	25
			180	0	23.90	23.62	23.73	25
		Inner	1	1	23.94	23.61	23.74	25
			1	187	23.96	23.70	23.86	25
			90	45	23.54	23.22	23.29	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649334	Mid CH 656000	High CH 662666	Max. Tune-up (dBm)
					Frequency 3740MHz	Frequency 3840MHz	Frequency 3940MHz	
80M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.92	24.60	24.76	26
			1	216	25.33	24.97	25.15	26
			2	0	25.02	24.73	24.85	26
			2	215	25.43	25.20	25.28	26
			216	0	26.74	26.54	26.59	27
		Inner	1	1	26.50	26.22	26.36	27
			1	215	26.70	26.58	26.67	27
			108	54	26.72	26.55	26.58	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.56	24.70	26
			1	216	25.42	25.07	25.24	26
			2	0	25.07	24.72	24.87	26
			2	215	25.36	25.10	25.19	26
			216	0	26.73	26.44	26.53	27
		Inner	1	1	26.42	26.09	26.18	27
			1	215	26.75	26.49	26.63	27
			108	54	26.70	26.43	26.51	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.98	24.67	24.86	26
			1	216	25.32	25.02	25.08	26
			2	0	24.91	24.65	24.74	26
			2	215	25.30	25.11	25.09	26
			216	0	25.81	25.52	25.70	27
		Inner	1	1	26.23	25.98	26.04	27
			1	215	26.53	26.25	26.46	27
			108	54	26.36	26.21	26.23	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.11	24.82	24.99	26
			1	216	25.37	25.02	25.16	26
			2	0	24.75	24.49	24.62	26
			2	215	24.91	24.72	24.71	26
			216	0	25.48	25.09	25.30	26
		Inner	1	1	24.93	24.71	24.79	26
			1	215	25.18	24.86	25.03	26
			108	54	25.01	24.70	24.83	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.80	23.40	23.67	25
			1	216	23.98	23.71	23.70	25
			2	0	23.86	23.55	23.68	25
			2	215	23.86	23.50	23.68	25
			216	0	23.93	23.66	23.74	25
		Inner	1	1	23.98	23.55	23.79	25
			1	215	23.95	23.71	23.83	25
			108	54	23.54	23.19	23.32	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649668	Mid CH 656000	High CH 662332	Max. Tune-up (dBm)
					Frequency 3745MHz	Frequency 3840MHz	Frequency 3935MHz	
90M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.96	24.63	24.73	26
			1	244	25.31	25.02	25.11	26
			2	0	25.05	24.80	24.82	26
			2	243	25.41	25.20	25.32	26
			240	0	26.81	26.53	26.59	27
		Inner	1	1	26.46	26.20	26.35	27
			1	243	26.75	26.56	26.69	27
			120	60	26.76	26.59	26.54	27
	DFT-s-OFDM QPSK	Outer	1	0	24.89	24.53	24.73	26
			1	244	25.38	25.13	25.23	26
			2	0	25.13	24.70	24.94	26
			2	243	25.34	25.08	25.20	26
			240	0	26.77	26.43	26.53	27
		Inner	1	1	26.47	26.11	26.15	27
			1	243	26.76	26.51	26.61	27
			120	60	26.76	26.38	26.52	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.00	24.60	24.86	26
			1	244	25.35	25.05	25.08	26
			2	0	24.92	24.58	24.70	26
			2	243	25.32	25.15	25.13	26
			240	0	25.85	25.46	25.72	27
		Inner	1	1	26.21	26.01	26.04	27
			1	243	26.58	26.22	26.47	27
			120	60	26.36	26.19	26.24	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.16	24.77	24.99	26
			1	244	25.39	25.00	25.19	26
			2	0	24.77	24.42	24.62	26
			2	243	24.95	24.75	24.67	26
			240	0	25.43	25.09	25.25	26
		Inner	1	1	24.98	24.69	24.82	26
			1	243	25.19	24.85	25.00	26
			120	60	24.97	24.69	24.86	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.84	23.40	23.68	25
			1	244	23.91	23.69	23.73	25
			2	0	23.89	23.55	23.73	25
			2	243	23.79	23.52	23.65	25
			240	0	23.95	23.62	23.79	25
		Inner	1	1	23.98	23.56	23.75	25
			1	243	23.97	23.67	23.86	25
			120	60	23.55	23.25	23.25	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 650000	Mid CH 656000	High CH 662000	Max. Tune-up (dBm)
					Frequency 3750MHz	Frequency 3840MHz	Frequency 3930MHz	
100M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.97	24.67	24.81	26
			1	272	25.35	25.05	25.17	26
			2	0	25.07	24.81	24.86	26
			2	271	25.47	25.25	25.33	26
			270	0	26.82	26.55	26.64	27
		Inner	1	1	26.54	26.27	26.37	27
			1	271	26.76	26.60	26.72	27
			135	67	26.79	26.60	26.60	27
	DFT-s-OFDM QPSK	Outer	1	0	24.93	24.58	24.75	26
			1	272	25.44	25.15	25.26	26
			2	0	25.15	24.78	24.95	26
			2	271	25.42	25.12	25.25	26
			270	0	26.80	26.49	26.55	27
		Inner	1	1	26.48	26.16	26.23	27
			1	271	26.82	26.54	26.65	27
			135	67	26.78	26.45	26.57	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.06	24.68	24.88	26
			1	272	25.36	25.07	25.16	26
			2	0	24.99	24.66	24.76	26
			2	271	25.34	25.16	25.17	26
			270	0	25.87	25.54	25.73	27
		Inner	1	1	26.29	26.05	26.09	27
			1	271	26.60	26.30	26.48	27
			135	67	26.44	26.23	26.29	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.19	24.83	25.01	26
			1	272	25.41	25.07	25.24	26
			2	0	24.83	24.50	24.64	26
			2	271	24.96	24.77	24.75	26
			270	0	25.50	25.17	25.31	26
		Inner	1	1	25.01	24.75	24.84	26
			1	271	25.21	24.92	25.05	26
			135	67	25.03	24.77	24.88	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.86	23.48	23.69	25
			1	272	23.99	23.73	23.78	25
			2	0	23.91	23.63	23.74	25
			2	271	23.87	23.56	23.70	25
			270	0	23.98	23.68	23.81	25
		Inner	1	1	24.00	23.63	23.80	25
			1	271	24.03	23.75	23.88	25
			135	67	23.56	23.27	23.33	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647334	Mid CH 656000	High CH 664666	Max. Tune-up (dBm)
					Frequency 3710MHz	Frequency 3840MHz	Frequency 3970MHz	
20M	CP-OFDM QPSK	Outer	1	0	24.52	24.14	24.26	26
			1	50	24.62	24.31	24.38	26
			2	0	24.49	24.25	24.34	26
			2	49	24.59	24.27	24.53	26
			51	0	25.28	25.05	25.11	26
		Inner	1	1	25.77	25.59	25.69	27
			1	49	26.02	25.76	25.86	27
			25	12	25.83	25.69	25.62	27
	CP-OFDM 16QAM	Outer	1	0	24.40	24.18	24.33	26
			1	50	24.53	24.36	24.47	26
			2	0	24.41	24.14	24.33	26
			2	49	24.46	24.32	24.40	26
			51	0	25.20	24.93	25.09	26
		Inner	1	1	25.55	25.21	25.32	27
			1	49	25.57	25.36	25.54	27
			25	12	25.52	25.26	25.28	27
	CP-OFDM 64QAM	Outer	1	0	23.70	23.55	23.65	25
			1	50	23.93	23.69	23.77	25
			2	0	23.84	23.63	23.70	25
			2	49	23.89	23.71	23.83	25
			51	0	24.12	23.87	24.04	25
		Inner	1	1	23.79	23.62	23.72	25
			1	49	23.86	23.57	23.75	25
			25	12	24.09	24.02	24.02	25
	CP-OFDM 256QAM	Outer	1	0	23.71	23.48	23.65	25
			1	50	23.88	23.58	23.70	25
			2	0	23.76	23.55	23.76	25
			2	49	23.92	23.77	23.67	25
			51	0	23.79	23.63	23.66	25
		Inner	1	1	23.78	23.56	23.60	25
			1	49	23.79	23.63	23.67	25
			25	12	23.94	23.73	23.86	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647668	Mid CH 656000	High CH 664332	Max. Tune-up (dBm)
					Frequency 3715MHz	Frequency 3840MHz	Frequency 3965MHz	
30M	CP-OFDM QPSK	Outer	1	0	24.49	24.18	24.22	26
			1	77	24.56	24.31	24.44	26
			2	0	24.51	24.23	24.33	26
			2	76	24.53	24.33	24.53	26
			78	0	25.30	25.08	25.12	26
		Inner	1	1	25.72	25.59	25.72	27
			1	76	26.02	25.79	25.90	27
			39	19	25.77	25.68	25.61	27
	CP-OFDM 16QAM	Outer	1	0	24.40	24.18	24.32	26
			1	77	24.53	24.34	24.44	26
			2	0	24.37	24.20	24.28	26
			2	76	24.49	24.28	24.44	26
			78	0	25.19	24.94	25.06	26
		Inner	1	1	25.51	25.20	25.35	27
			1	76	25.62	25.42	25.48	27
			39	19	25.48	25.20	25.30	27
	CP-OFDM 64QAM	Outer	1	0	23.76	23.57	23.69	25
			1	77	23.91	23.68	23.74	25
			2	0	23.84	23.62	23.73	25
			2	76	23.90	23.71	23.84	25
			78	0	24.06	23.91	24.00	25
		Inner	1	1	23.84	23.60	23.75	25
			1	76	23.86	23.58	23.71	25
			39	19	24.09	24.05	24.05	25
	CP-OFDM 256QAM	Outer	1	0	23.70	23.49	23.59	25
			1	77	23.82	23.64	23.73	25
			2	0	23.77	23.58	23.74	25
			2	76	23.91	23.71	23.74	25
			78	0	23.79	23.63	23.66	25
		Inner	1	1	23.78	23.56	23.60	25
			1	76	23.79	23.63	23.67	25
			39	19	23.94	23.73	23.86	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648000	Mid CH 656000	High CH 664000	Max. Tune-up (dBm)
					Frequency 3720MHz	Frequency 3840MHz	Frequency 3960MHz	
40M	CP-OFDM QPSK	Outer	1	0	24.51	24.12	24.27	26
			1	105	24.60	24.30	24.42	26
			2	0	24.54	24.24	24.36	26
			2	104	24.56	24.33	24.52	26
			106	0	25.32	25.08	25.12	26
		Inner	1	1	25.71	25.59	25.69	27
			1	104	26.05	25.81	25.91	27
			53	26	25.84	25.64	25.63	27
	CP-OFDM 16QAM	Outer	1	0	24.37	24.24	24.30	26
			1	105	24.59	24.37	24.46	26
			2	0	24.35	24.21	24.32	26
			2	104	24.50	24.31	24.37	26
			106	0	25.17	24.97	25.08	26
		Inner	1	1	25.52	25.20	25.36	27
			1	104	25.60	25.40	25.50	27
			53	26	25.46	25.23	25.34	27
	CP-OFDM 64QAM	Outer	1	0	23.69	23.61	23.65	25
			1	105	23.94	23.67	23.78	25
			2	0	23.78	23.64	23.68	25
			2	104	23.94	23.75	23.83	25
			106	0	24.06	23.94	24.03	25
		Inner	1	1	23.85	23.60	23.69	25
			1	104	23.87	23.63	23.68	25
			53	26	24.12	23.98	24.03	25
	CP-OFDM 256QAM	Outer	1	0	23.73	23.52	23.59	25
			1	105	23.85	23.57	23.71	25
			2	0	23.80	23.60	23.72	25
			2	104	23.88	23.77	23.68	25
			106	0	23.73	23.62	23.72	25
		Inner	1	1	23.76	23.52	23.61	25
			1	104	23.74	23.59	23.69	25
			53	26	23.92	23.76	23.81	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648334	Mid CH 656000	High CH 663666	Max. Tune-up (dBm)
					Frequency 3725MHz	Frequency 3840MHz	Frequency 3955MHz	
50M	CP-OFDM QPSK	Outer	1	0	24.50	24.13	24.23	26
			1	132	24.61	24.28	24.44	26
			2	0	24.50	24.20	24.37	26
			2	131	24.57	24.29	24.53	26
			133	0	25.26	25.12	25.08	26
		Inner	1	1	25.74	25.56	25.76	27
			1	131	26.03	25.82	25.87	27
			67	33	25.78	25.65	25.64	27
	CP-OFDM 16QAM	Outer	1	0	24.34	24.24	24.29	26
			1	132	24.59	24.32	24.50	26
			2	0	24.35	24.16	24.26	26
			2	131	24.48	24.34	24.39	26
			133	0	25.16	24.94	25.09	26
		Inner	1	1	25.55	25.23	25.33	27
			1	131	25.58	25.42	25.48	27
			67	33	25.51	25.23	25.32	27
	CP-OFDM 64QAM	Outer	1	0	23.69	23.61	23.65	25
			1	132	23.90	23.67	23.72	25
			2	0	23.84	23.64	23.67	25
			2	131	23.90	23.77	23.83	25
			133	0	24.12	23.90	23.97	25
		Inner	1	1	23.81	23.59	23.71	25
			1	131	23.86	23.60	23.69	25
			67	33	24.09	24.04	24.01	25
	CP-OFDM 256QAM	Outer	1	0	23.72	23.53	23.60	25
			1	132	23.82	23.60	23.67	25
			2	0	23.79	23.62	23.70	25
			2	131	23.88	23.72	23.70	25
			133	0	23.78	23.59	23.72	25
		Inner	1	1	23.77	23.51	23.65	25
			1	131	23.80	23.62	23.63	25
			67	33	23.93	23.70	23.81	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648668	Mid CH 656000	High CH 663332	Max. Tune-up (dBm)
					Frequency 3730MHz	Frequency 3840MHz	Frequency 3950MHz	
60M	CP-OFDM QPSK	Outer	1	0	24.49	24.18	24.22	26
			1	161	24.56	24.31	24.44	26
			2	0	24.51	24.23	24.33	26
			2	160	24.53	24.33	24.53	26
			162	0	25.30	25.08	25.12	26
		Inner	1	1	25.72	25.59	25.72	27
			1	160	26.02	25.79	25.90	27
			81	40	25.77	25.68	25.61	27
	CP-OFDM 16QAM	Outer	1	0	24.40	24.18	24.32	26
			1	161	24.53	24.34	24.44	26
			2	0	24.37	24.20	24.28	26
			2	160	24.49	24.28	24.44	26
			162	0	25.19	24.94	25.06	26
		Inner	1	1	25.51	25.20	25.35	27
			1	160	25.62	25.42	25.48	27
			81	40	25.48	25.20	25.30	27
	CP-OFDM 64QAM	Outer	1	0	23.76	23.57	23.69	25
			1	161	23.91	23.68	23.74	25
			2	0	23.84	23.62	23.73	25
			2	160	23.90	23.71	23.84	25
			162	0	24.06	23.91	24.00	25
		Inner	1	1	23.84	23.60	23.75	25
			1	160	23.86	23.58	23.71	25
			81	40	24.09	24.05	24.05	25
	CP-OFDM 256QAM	Outer	1	0	23.70	23.49	23.59	25
			1	161	23.82	23.64	23.73	25
			2	0	23.77	23.58	23.74	25
			2	160	23.91	23.71	23.74	25
			162	0	23.79	23.63	23.66	25
		Inner	1	1	23.78	23.56	23.60	25
			1	160	23.79	23.63	23.67	25
			81	40	23.94	23.73	23.86	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649000	Mid CH 656000	High CH 663000	Max. Tune-up (dBm)
					Frequency 3735MHz	Frequency 3840MHz	Frequency 3945MHz	
70M	CP-OFDM QPSK	Outer	1	0	24.52	24.14	24.26	26
			1	188	24.62	24.31	24.38	26
			2	0	24.49	24.25	24.34	26
			2	187	24.59	24.27	24.53	26
			189	0	25.28	25.05	25.11	26
		Inner	1	1	25.77	25.59	25.69	27
			1	187	26.02	25.76	25.86	27
			95	47	25.83	25.69	25.62	27
	CP-OFDM 16QAM	Outer	1	0	24.40	24.18	24.33	26
			1	188	24.53	24.36	24.47	26
			2	0	24.41	24.14	24.33	26
			2	187	24.46	24.32	24.40	26
			189	0	25.20	24.93	25.09	26
		Inner	1	1	25.55	25.21	25.32	27
			1	187	25.57	25.36	25.54	27
			95	47	25.52	25.26	25.28	27
	CP-OFDM 64QAM	Outer	1	0	23.70	23.55	23.65	25
			1	188	23.93	23.69	23.77	25
			2	0	23.84	23.63	23.70	25
			2	187	23.89	23.71	23.83	25
			189	0	24.12	23.94	24.01	25
		Inner	1	1	23.81	23.61	23.76	25
			1	187	23.87	23.63	23.71	25
			95	47	24.09	23.99	24.05	25
	CP-OFDM 256QAM	Outer	1	0	23.73	23.50	23.64	25
			1	188	23.87	23.64	23.69	25
			2	0	23.75	23.55	23.72	25
			2	187	23.90	23.73	23.73	25
			189	0	23.78	23.60	23.69	25
		Inner	1	1	23.76	23.51	23.64	25
			1	187	23.79	23.56	23.70	25
			95	47	23.92	23.74	23.82	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649334	Mid CH 656000	High CH 662666	Max. Tune-up (dBm)
					Frequency 3740MHz	Frequency 3840MHz	Frequency 3940MHz	
80M	CP-OFDM QPSK	Outer	1	0	24.50	24.13	24.23	26
			1	216	24.61	24.28	24.44	26
			2	0	24.50	24.20	24.37	26
			2	215	24.57	24.29	24.53	26
			217	0	25.26	25.12	25.08	26
		Inner	1	1	25.74	25.56	25.76	27
			1	215	26.03	25.82	25.87	27
			109	54	25.78	25.65	25.64	27
	CP-OFDM 16QAM	Outer	1	0	24.34	24.24	24.29	26
			1	216	24.59	24.32	24.50	26
			2	0	24.35	24.16	24.26	26
			2	215	24.48	24.34	24.39	26
			217	0	25.16	24.94	25.09	26
		Inner	1	1	25.51	25.21	25.32	27
			1	215	25.56	25.39	25.54	27
			109	54	25.45	25.26	25.30	27
	CP-OFDM 64QAM	Outer	1	0	23.69	23.62	23.69	25
			1	216	23.92	23.70	23.71	25
			2	0	23.78	23.69	23.73	25
			2	215	23.91	23.74	23.77	25
			217	0	24.08	23.93	24.02	25
		Inner	1	1	23.81	23.59	23.72	25
			1	215	23.81	23.60	23.74	25
			109	54	24.09	24.04	24.01	25
	CP-OFDM 256QAM	Outer	1	0	23.66	23.53	23.65	25
			1	216	23.86	23.60	23.67	25
			2	0	23.74	23.62	23.76	25
			2	215	23.88	23.74	23.71	25
			217	0	23.78	23.59	23.73	25
		Inner	1	1	23.74	23.55	23.61	25
			1	215	23.78	23.58	23.69	25
			109	54	23.98	23.71	23.82	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649668	Mid CH 656000	High CH 662332	Max. Tune-up (dBm)
					Frequency 3745MHz	Frequency 3840MHz	Frequency 3935MHz	
90M	CP-OFDM QPSK	Outer	1	0	24.54	24.16	24.20	26
			1	244	24.59	24.33	24.40	26
			2	0	24.53	24.27	24.34	26
			2	243	24.55	24.29	24.57	26
			245	0	25.33	25.11	25.08	26
		Inner	1	1	25.70	25.54	25.75	27
			1	243	26.08	25.80	25.89	27
			123	61	25.82	25.69	25.60	27
	CP-OFDM 16QAM	Outer	1	0	24.38	24.21	24.32	26
			1	244	24.55	24.38	24.49	26
			2	0	24.41	24.14	24.33	26
			2	243	24.46	24.32	24.40	26
			245	0	25.20	24.93	25.09	26
		Inner	1	1	25.56	25.23	25.29	27
			1	243	25.57	25.41	25.52	27
			123	61	25.51	25.21	25.31	27
	CP-OFDM 64QAM	Outer	1	0	23.71	23.55	23.69	25
			1	244	23.95	23.73	23.71	25
			2	0	23.79	23.62	23.69	25
			2	243	23.93	23.78	23.81	25
			245	0	24.12	23.87	24.04	25
		Inner	1	1	23.79	23.62	23.72	25
			1	243	23.86	23.57	23.75	25
			123	61	24.09	24.02	24.02	25
	CP-OFDM 256QAM	Outer	1	0	23.71	23.48	23.65	25
			1	244	23.88	23.58	23.70	25
			2	0	23.76	23.55	23.76	25
			2	243	23.92	23.77	23.67	25
			245	0	23.73	23.59	23.68	25
		Inner	1	1	23.79	23.53	23.64	25
			1	243	23.79	23.57	23.66	25
			123	61	23.94	23.70	23.85	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 650000	Mid CH 656000	High CH 662000	Max. Tune-up (dBm)
					Frequency 3750MHz	Frequency 3840MHz	Frequency 3930MHz	
100M	CP-OFDM QPSK	Outer	1	0	24.55	24.20	24.28	26
			1	272	24.63	24.36	24.46	26
			2	0	24.55	24.28	24.38	26
			2	271	24.61	24.34	24.58	26
			273	0	25.34	25.13	25.13	26
		Inner	1	1	25.78	25.61	25.77	27
			1	271	26.09	25.84	25.92	27
			137	68	25.85	25.70	25.66	27
	CP-OFDM 16QAM	Outer	1	0	24.42	24.26	24.34	26
			1	272	24.61	24.40	24.52	26
			2	0	24.43	24.22	24.34	26
			2	271	24.54	24.36	24.45	26
			273	0	25.23	24.99	25.11	26
		Inner	1	1	25.57	25.28	25.37	27
			1	271	25.63	25.44	25.56	27
			137	68	25.53	25.28	25.36	27
	CP-OFDM 64QAM	Outer	1	0	23.77	23.63	23.71	25
			1	272	23.96	23.75	23.79	25
			2	0	23.86	23.70	23.75	25
			2	271	23.95	23.79	23.85	25
			273	0	24.14	23.95	24.05	25
		Inner	1	1	23.87	23.66	23.77	25
			1	271	23.88	23.65	23.76	25
			137	68	24.17	24.06	24.07	25
	CP-OFDM 256QAM	Outer	1	0	23.74	23.54	23.67	25
			1	272	23.90	23.65	23.75	25
			2	0	23.82	23.63	23.78	25
			2	271	23.93	23.79	23.75	25
			273	0	23.80	23.67	23.74	25
		Inner	1	1	23.82	23.59	23.66	25
			1	271	23.81	23.64	23.71	25
			137	68	24.00	23.78	23.87	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647334	Mid CH 656000	High CH 664666	Max. Tune-up (dBm)
					Frequency 3710MHz	Frequency 3840MHz	Frequency 3970MHz	
20M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.90	24.67	24.75	26
			1	50	25.32	25.03	25.08	26
			2	0	24.99	24.76	24.82	26
			2	49	25.46	25.14	25.31	26
			50	0	26.72	26.50	26.57	27
		Inner	1	1	26.51	26.26	26.32	27
			1	49	26.72	26.52	26.60	27
			25	12	26.83	26.53	26.60	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.54	24.71	26
			1	50	25.36	25.11	25.21	26
			2	0	25.13	24.70	24.94	26
			2	49	25.34	25.08	25.20	26
			50	0	26.77	26.43	26.53	27
		Inner	1	1	26.44	26.09	26.18	27
			1	49	26.74	26.46	26.63	27
			25	12	26.80	26.43	26.49	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.95	24.60	24.82	26
			1	50	25.36	25.01	25.14	26
			2	0	24.93	24.60	24.71	26
			2	49	25.34	25.01	25.19	26
			50	0	25.87	25.43	25.72	27
		Inner	2	49	26.21	26.01	26.04	27
			25	12	26.63	26.26	26.45	27
			50	0	26.38	26.15	26.25	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.17	24.83	24.96	26
			1	50	25.36	25.01	25.18	26
			2	0	24.80	24.43	24.64	26
			2	49	25.00	24.75	24.66	26
			50	0	25.49	25.13	25.22	26
		Inner	1	1	24.97	24.72	24.80	26
			1	49	25.24	24.88	25.02	26
			25	12	24.97	24.70	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.84	23.48	23.64	25
			1	50	23.98	23.67	23.76	25
			2	0	23.90	23.58	23.73	25
			2	49	23.87	23.56	23.60	25
			50	0	23.93	23.60	23.81	25
		Inner	1	1	23.95	23.67	23.70	25
			1	49	24.04	23.66	23.88	25
			25	12	23.49	23.21	23.29	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 647668	Mid CH 656000	High CH 664332	Max. Tune-up (dBm)
					Frequency 3715MHz	Frequency 3840MHz	Frequency 3965MHz	
30M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.87	24.71	24.71	26
			1	77	25.26	25.03	25.14	26
			2	0	25.01	24.74	24.81	26
			2	76	25.40	25.20	25.31	26
			75	0	26.74	26.53	26.58	27
		Inner	1	1	26.46	26.26	26.35	27
			1	76	26.72	26.55	26.64	27
			36	18	26.77	26.52	26.59	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.54	24.70	26
			1	77	25.36	25.09	25.18	26
			2	0	25.09	24.76	24.89	26
			2	76	25.37	25.04	25.24	26
			75	0	26.76	26.44	26.50	27
		Inner	1	1	26.40	26.08	26.21	27
			1	76	26.79	26.52	26.57	27
			36	18	26.76	26.37	26.51	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.01	24.62	24.86	26
			1	77	25.34	25.00	25.11	26
			2	0	24.93	24.59	24.74	26
			2	76	25.35	25.01	25.20	26
			75	0	25.81	25.47	25.68	27
		Inner	1	1	26.26	25.99	26.07	27
			1	76	26.63	26.27	26.41	27
			36	18	26.38	26.18	26.28	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.16	24.84	24.90	26
			1	77	25.30	25.07	25.21	26
			2	0	24.81	24.46	24.62	26
			2	76	24.99	24.69	24.73	26
			75	0	25.49	25.13	25.22	26
		Inner	1	1	24.97	24.72	24.80	26
			1	76	25.24	24.88	25.02	26
			36	18	24.97	24.70	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.84	23.48	23.64	25
			1	77	23.98	23.67	23.76	25
			2	0	23.90	23.58	23.73	25
			2	76	23.87	23.56	23.60	25
			75	0	23.93	23.60	23.81	25
		Inner	1	1	23.95	23.67	23.70	25
			1	76	24.03	23.68	23.87	25
			36	18	23.56	23.20	23.26	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648000	Mid CH 656000	High CH 664000	Max. Tune-up (dBm)
					Frequency 3720MHz	Frequency 3840MHz	Frequency 3960MHz	
40M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.89	24.65	24.76	26
			1	105	25.30	25.02	25.12	26
			2	0	25.04	24.75	24.84	26
			2	104	25.43	25.20	25.30	26
			100	0	26.76	26.53	26.58	27
		Inner	1	1	26.45	26.26	26.32	27
			1	104	26.75	26.57	26.65	27
			50	25	26.84	26.48	26.61	27
	DFT-s-OFDM QPSK	Outer	1	0	24.82	24.60	24.68	26
			1	105	25.42	25.12	25.20	26
			2	0	25.07	24.77	24.93	26
			2	104	25.38	25.07	25.17	26
			100	0	26.74	26.47	26.52	27
		Inner	1	1	26.41	26.08	26.22	27
			1	104	26.77	26.50	26.59	27
			50	25	26.74	26.40	26.55	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.94	24.66	24.82	26
			1	105	25.37	24.99	25.15	26
			2	0	24.87	24.61	24.69	26
			2	104	25.39	25.05	25.19	26
			100	0	25.81	25.50	25.71	27
		Inner	1	1	26.27	25.99	26.01	27
			1	104	26.64	26.32	26.38	27
			50	25	26.41	26.11	26.26	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.19	24.87	24.90	26
			1	105	25.33	25.00	25.19	26
			2	0	24.84	24.48	24.60	26
			2	104	24.96	24.75	24.67	26
			100	0	25.43	25.12	25.28	26
		Inner	1	1	24.95	24.68	24.81	26
			1	104	25.19	24.84	25.04	26
			50	25	24.95	24.73	24.82	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.77	23.49	23.67	25
			1	105	24.02	23.69	23.70	25
			2	0	23.83	23.61	23.74	25
			2	104	23.86	23.52	23.58	25
			100	0	23.93	23.60	23.82	25
		Inner	1	1	23.95	23.67	23.68	25
			1	104	23.99	23.69	23.87	25
			50	25	23.49	23.23	23.29	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648334	Mid CH 656000	High CH 663666	Max. Tune-up (dBm)
					Frequency 3725MHz	Frequency 3840MHz	Frequency 3955MHz	
50M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.88	24.66	24.72	26
			1	132	25.31	25.00	25.14	26
			2	0	25.00	24.71	24.85	26
			2	131	25.44	25.16	25.31	26
			128	0	26.70	26.57	26.54	27
		Inner	1	1	26.48	26.23	26.39	27
			1	131	26.73	26.58	26.61	27
			64	32	26.78	26.49	26.62	27
	DFT-s-OFDM QPSK	Outer	1	0	24.79	24.60	24.67	26
			1	132	25.42	25.07	25.24	26
			2	0	25.07	24.72	24.87	26
			2	131	25.36	25.10	25.19	26
			128	0	26.73	26.44	26.53	27
		Inner	1	1	26.44	26.11	26.19	27
			1	131	26.75	26.52	26.57	27
			64	32	26.79	26.40	26.53	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.94	24.66	24.82	26
			1	132	25.33	24.99	25.09	26
			2	0	24.93	24.61	24.68	26
			2	131	25.35	25.07	25.19	26
			128	0	25.87	25.46	25.65	27
		Inner	1	1	26.23	25.98	26.03	27
			1	131	26.63	26.29	26.39	27
			64	32	26.38	26.17	26.24	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.18	24.88	24.91	26
			1	132	25.30	25.03	25.15	26
			2	0	24.83	24.50	24.58	26
			2	131	24.96	24.70	24.69	26
			128	0	25.48	25.09	25.28	26
		Inner	1	1	24.96	24.67	24.85	26
			1	131	25.25	24.87	24.98	26
			64	32	24.96	24.67	24.82	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.82	23.44	23.67	25
			1	132	24.04	23.67	23.73	25
			2	0	23.85	23.54	23.74	25
			2	131	23.88	23.49	23.65	25
			128	0	23.89	23.61	23.78	25
		Inner	1	1	23.99	23.62	23.68	25
			1	131	24.00	23.66	23.87	25
			64	32	23.56	23.23	23.26	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 648668	Mid CH 656000	High CH 663332	Max. Tune-up (dBm)
					Frequency 3730MHz	Frequency 3840MHz	Frequency 3950MHz	
60M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.87	24.71	24.71	26
			1	161	25.26	25.03	25.14	26
			2	0	25.01	24.74	24.81	26
			2	160	25.40	25.20	25.31	26
			162	0	26.74	26.53	26.58	27
		Inner	1	1	26.46	26.26	26.35	27
			1	160	26.72	26.55	26.64	27
			81	40	26.77	26.52	26.59	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.54	24.70	26
			1	161	25.36	25.09	25.18	26
			2	0	25.09	24.76	24.89	26
			2	160	25.37	25.04	25.24	26
			162	0	26.76	26.44	26.50	27
		Inner	1	1	26.40	26.08	26.21	27
			1	160	26.79	26.52	26.57	27
			81	40	26.76	26.37	26.51	27
	DFT-s-OFDM 16QAM	Outer	1	0	25.01	24.62	24.86	26
			1	161	25.34	25.00	25.11	26
			2	0	24.93	24.59	24.74	26
			2	160	25.35	25.01	25.20	26
			162	0	25.81	25.47	25.68	27
		Inner	1	1	26.26	25.99	26.07	27
			1	160	26.63	26.27	26.41	27
			81	40	26.38	26.18	26.28	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.16	24.84	24.90	26
			1	161	25.30	25.07	25.21	26
			2	0	24.81	24.46	24.62	26
			2	160	24.99	24.69	24.73	26
			162	0	25.49	25.13	25.22	26
		Inner	1	1	24.97	24.72	24.80	26
			1	160	25.24	24.88	25.02	26
			81	40	24.97	24.70	24.87	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.84	23.48	23.64	25
			1	161	23.98	23.67	23.76	25
			2	0	23.90	23.58	23.73	25
			2	160	23.87	23.56	23.60	25
			162	0	23.93	23.60	23.81	25
		Inner	1	1	23.95	23.67	23.70	25
			1	160	24.03	23.68	23.87	25
			81	40	23.56	23.20	23.26	25

BW	MCS Index	RB	RB Size	RB Offset	Low CH 649000	Mid CH 656000	High CH 663000	Max. Tune-up (dBm)
					Frequency 3735MHz	Frequency 3840MHz	Frequency 3945MHz	
70M	DFT-s-OFDM Pi/2 BPSK	Outer	1	0	24.90	24.67	24.75	26
			1	188	25.32	25.03	25.08	26
			2	0	24.99	24.76	24.82	26
			2	187	25.46	25.14	25.31	26
			180	0	26.72	26.50	26.57	27
		Inner	1	1	26.51	26.26	26.32	27
			1	187	26.72	26.52	26.60	27
			90	45	26.83	26.53	26.60	27
	DFT-s-OFDM QPSK	Outer	1	0	24.85	24.54	24.71	26
			1	188	25.36	25.11	25.21	26
			2	0	25.13	24.70	24.94	26
			2	187	25.34	25.08	25.20	26
			180	0	26.77	26.43	26.53	27
		Inner	1	1	26.44	26.09	26.18	27
			1	187	26.74	26.46	26.63	27
			90	45	26.80	26.43	26.49	27
	DFT-s-OFDM 16QAM	Outer	1	0	24.95	24.60	24.82	26
			1	188	25.36	25.01	25.14	26
			2	0	24.93	24.60	24.71	26
			2	187	25.34	25.01	25.19	26
			180	0	25.87	25.50	25.69	27
		Inner	1	1	26.23	26.00	26.08	27
			1	187	26.64	26.32	26.41	27
			90	45	26.38	26.12	26.28	27
	DFT-s-OFDM 64QAM	Outer	1	0	25.19	24.85	24.95	26
			1	188	25.35	25.07	25.17	26
			2	0	24.79	24.43	24.60	26
			2	187	24.98	24.71	24.72	26
			180	0	25.48	25.10	25.25	26
		Inner	1	1	24.95	24.67	24.84	26
			1	187	25.24	24.81	25.05	26
			90	45	24.95	24.71	24.83	26
	DFT-s-OFDM 256QAM	Outer	1	0	23.83	23.43	23.64	25
			1	188	24.00	23.66	23.76	25
			2	0	23.90	23.60	23.68	25
			2	187	23.88	23.49	23.64	25
			180	0	23.89	23.59	23.75	25
		Inner	1	1	23.95	23.67	23.67	25
			1	187	23.99	23.69	23.87	25
			90	45	23.55	23.20	23.30	25