




BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH376500


MODE	TX channel 376500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,831.500	-50.69	-13.00	37.69	23.59	H	220.2	2
5	6,842.000	-45.80	-13.00	32.80	30.45	H	212.4	1



MODE	TX channel 376500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,874.500	-50.54	-13.00	37.54	23.71	V	0	2
5	6,830.000	-45.41	-13.00	32.41	30.44	V	0	2



CH381500


MODE	TX channel 381500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,680.000	-52.46	-13.00	39.46	22.50	H	210.4	2
5	6,840.500	-45.44	-13.00	32.44	30.44	H	202.5	1



MODE	TX channel 381500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,852.500	-50.50	-13.00	37.50	23.83	V	149.7	1
5	6,813.500	-45.60	-13.00	32.60	30.43	V	0	2






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 20MHz / QPSK


MODE	TX channel 376500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,676.000	-52.18	-13.00	39.18	22.51	H	1.4	2
5	6,837.000	-46.44	-13.00	33.44	30.41	H	146.7	2



MODE	TX channel 376500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
4	3,858.500	-50.78	-13.00	37.78	23.93	V	149.7	1
5	6,768.500	-45.58	-13.00	32.58	30.54	V	0	2




5G_NR41-HUPE:

CHANNEL BANDWIDTH: 20MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-51.02	-61.00	-25.00	-26.02	9.98	Peak	Horizontal
2 PP	7778.970	-50.62	-64.06	-25.00	-25.62	13.44	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-50.58	-61.02	-25.00	-25.58	10.44	Peak	Vertical
2 PP	7778.970	-48.47	-63.58	-25.00	-23.47	15.11	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 30MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	5186.000	-49.53	-59.51	-25.00	-24.53	9.98	Peak	Horizontal
2	7778.970	-50.10	-63.54	-25.00	-25.10	13.44	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-50.59	-61.03	-25.00	-25.59	10.44	Peak	Vertical
2 PP	7778.970	-49.28	-64.39	-25.00	-24.28	15.11	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 40MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.980	-51.06	-61.04	-25.00	-26.06	9.98	Peak	Horizontal
2 PP	7786.000	-49.48	-62.97	-25.00	-24.48	13.49	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-50.58	-61.02	-25.00	-25.58	10.44	Peak	Vertical
2 PP	7778.970	-48.38	-63.49	-25.00	-23.38	15.11	Peak	Vertical





BUREAU
VERITAS


Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 50MHz / QPSK

CH 504204


MODE	TX channel 504204	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 5030.000	-51.25	-60.99	-25.00	-26.25	9.74	Peak	Horizontal
2	7563.060	-52.06	-63.94	-25.00	-27.06	11.88	Peak	Horizontal



MODE	TX channel 504204	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5030.000	-50.71	-61.01	-25.00	-25.71	10.30	Peak	Vertical
2 PP	7563.060	-49.95	-64.74	-25.00	-24.95	14.79	Peak	Vertical



CH 518598

MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	5186.000	-50.15	-60.13	-25.00	-25.15	9.98	Peak	Horizontal
2	7778.970	-50.95	-64.39	-25.00	-25.95	13.44	Peak	Horizontal






Test Report No.: W7L-220214W001RF06

MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.970	-49.89	-60.33	-25.00	-24.89	10.44	Peak	Vertical
2	PP 7786.000	-47.98	-63.10	-25.00	-22.98	15.12	Peak	Vertical



CH 532998


MODE	TX channel 532998	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5342.000	-51.28	-61.51	-25.00	-26.28	10.23	Peak	Horizontal
2 PP	7994.970	-48.16	-63.17	-25.00	-23.16	15.01	Peak	Horizontal



MODE	TX channel 532998	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5342.000	-50.50	-61.08	-25.00	-25.50	10.58	Peak	Vertical
2 PP	7994.970	-48.86	-64.29	-25.00	-23.86	15.43	Peak	Vertical



CHANNEL BANDWIDTH: 60MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.980	-51.25	-61.23	-25.00	-26.25	9.98	Peak	Horizontal
2 PP	7786.000	-50.00	-63.49	-25.00	-25.00	13.49	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-50.10	-60.54	-25.00	-25.10	10.44	Peak	Vertical
2 PP	7778.970	-48.66	-63.77	-25.00	-23.66	15.11	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 80MHz / QPSK

MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-51.25	-61.23	-25.00	-26.25	9.98	Peak	Horizontal
2 PP	7778.970	-50.75	-64.19	-25.00	-25.75	13.44	Peak	Horizontal






Test Report No.: W7L-220214W001RF06

MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.980	-50.63	-61.07	-25.00	-25.63	10.44	Peak	Vertical
2 PP	7786.000	-48.95	-64.07	-25.00	-23.95	15.12	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 90MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.980	-51.37	-61.35	-25.00	-26.37	9.98	Peak	Horizontal
2 PP	7786.000	-50.12	-63.61	-25.00	-25.12	13.49	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-50.67	-61.11	-25.00	-25.67	10.44	Peak	Vertical
2 PP	7778.970	-48.96	-64.07	-25.00	-23.96	15.11	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 100MHz / QPSK


MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5186.000	-51.27	-61.25	-25.00	-26.27	9.98	Peak	Horizontal
2 PP	7778.970	-50.07	-63.51	-25.00	-25.07	13.44	Peak	Horizontal



MODE	TX channel 518598	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	5185.980	-50.66	-61.10	-25.00	-25.66	10.44	Peak	Vertical
2 PP	7786.000	-48.53	-63.65	-25.00	-23.53	15.12	Peak	Vertical




5G NR66:

CHANNEL BANDWIDTH: 5MHz / QPSK

CH342500


MODE	TX channel 342500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3418.000	-48.08	-56.67	-13.00	-35.08	8.59	Peak	Horizontal
2	5137.500	-49.41	-58.35	-13.00	-36.41	8.94	Peak	Horizontal



MODE	TX channel 342500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3418.000	-47.61	-56.72	-13.00	-34.61	9.11	Peak	Vertical
2		5137.500	-48.82	-58.67	-13.00	-35.82	9.85	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH349000


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-44.85	-53.42	-13.00	-31.85	8.57	Peak	Horizontal
2	5235.000	-49.32	-58.55	-13.00	-36.32	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-40.65	-49.84	-13.00	-27.65	9.19	Peak	Vertical
2	5235.000	-47.35	-57.16	-13.00	-34.35	9.81	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH355500


MODE	TX channel 355500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3548.000	-41.58	-50.20	-13.00	-28.58	8.62	Peak	Horizontal
2	5332.500	-48.13	-57.65	-13.00	-35.13	9.52	Peak	Horizontal



MODE	TX channel 355500	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3548.000	-42.20	-51.41	-13.00	-29.20	9.21	Peak	Vertical
2	5332.500	-48.54	-58.31	-13.00	-35.54	9.77	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 10MHz / QPSK


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-43.42	-51.99	-13.00	-30.42	8.57	Peak	Horizontal
2	5235.000	-49.10	-58.33	-13.00	-36.10	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-44.08	-53.27	-13.00	-31.08	9.19	Peak	Vertical
2	5235.000	-49.09	-58.90	-13.00	-36.09	9.81	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 15MHz / QPSK


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

		Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
		MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP	3496.000	-44.83	-53.40	-13.00	-31.83	8.57	Peak	Horizontal
2		5235.000	-49.10	-58.33	-13.00	-36.10	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-42.73	-51.92	-13.00	-29.73	9.19	Peak	Vertical
2	5235.000	-48.75	-58.56	-13.00	-35.75	9.81	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 20MHz / QPSK

CH34900


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-43.33	-51.90	-13.00	-30.33	8.57	Peak	Horizontal
2	5235.000	-48.99	-58.22	-13.00	-35.99	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-41.01	-50.20	-13.00	-28.01	9.19	Peak	Vertical
2	5235.000	-47.88	-57.69	-13.00	-34.88	9.81	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 30MHz / QPSK


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3496.000	-42.64	-51.21	-13.00	-29.64	8.57	Peak	Horizontal
2	5235.000	-47.88	-57.11	-13.00	-34.88	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1 PP	3496.000	-42.15	-51.34	-13.00	-29.15	9.19	Peak	Vertical
2	5235.000	-49.27	-59.08	-13.00	-36.27	9.81	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 40MHz / QPSK


MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3496.000	-43.89	-52.46	-13.00	-30.89	8.57	Peak	Horizontal
2	5235.000	-49.38	-58.61	-13.00	-36.38	9.23	Peak	Horizontal



MODE	TX channel 349000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 3496.000	-44.40	-53.59	-13.00	-31.40	9.19	Peak	Vertical
2	5235.000	-47.93	-57.74	-13.00	-34.93	9.81	Peak	Vertical




5G NR71:

CHANNEL BANDWIDTH: 5MHz / QPSK


MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,033.000	-51.30	-13.00	38.30	20.99	H	0	2
5	6,868.500	-45.74	-13.00	32.74	30.61	H	155.6	2



MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,046.000	-51.09	-13.00	38.09	20.69	V	360	1
5	6,896.000	-45.45	-13.00	32.45	30.83	V	204.3	1





BUREAU
VERITAS


Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 10MHz / QPSK

CH1336000


MODE	TX channel 133600	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,051.000	-51.49	-13.00	38.49	20.60	H	50.2	1
5	6,852.000	-46.36	-13.00	33.36	30.51	H	0.1	1



MODE	TX channel 133600	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,010.000	-50.16	-13.00	37.16	21.78	V	359.9	1
5	6,887.000	-45.42	-13.00	32.42	30.82	V	155.5	2






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH1361000


MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,022.500	-50.78	-13.00	37.78	21.26	H	0.1	1
5	6,842.500	-46.13	-13.00	33.13	30.45	H	157.4	2



MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,010.500	-50.04	-13.00	37.04	21.78	V	48.4	1
5	6,803.500	-44.91	-13.00	31.91	30.46	V	360	1






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH1386000


MODE	TX channel 138600	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,046.500	-51.42	-13.00	38.42	20.63	H	359.9	1
5	6,839.000	-44.60	-13.00	31.60	30.43	H	0.1	1



MODE	TX channel 138600	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,022.500	-50.23	-13.00	37.23	21.65	V	36.4	2
5	6,815.000	-45.57	-13.00	32.57	30.43	V	0	2






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 15MHz / QPSK


MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,020.500	-50.62	-13.00	37.62	21.27	H	0.1	1
5	6,827.500	-45.89	-13.00	32.89	30.35	H	359.8	1



MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,056.500	-50.69	-13.00	37.69	20.73	V	322.6	1
5	6,811.000	-45.84	-13.00	32.84	30.44	V	157.4	2






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 20MHz / QPSK


MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,030.500	-51.60	-13.00	38.60	21.07	H	310.6	2
5	6,801.000	-45.73	-13.00	32.73	30.36	H	359.9	2



MODE	TX channel 136100	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

Rg	Frequency [MHz]	PK+ Level [dBm]	PK+ Limit [dBm]	PK+ Margin [dB]	Correction [dB]	Polarization	Azimuth [deg]	Antenna Height [m]
2	2,022.500	-51.01	-13.00	38.01	21.65	V	0	2
5	6,777.500	-45.86	-13.00	32.86	30.52	V	0	2





Test Report No.: W7L-220214W001RF06


5G NR77 C HUPE:

CHANNEL BANDWIDTH: 20MHz / QPSK

CH647334


MODE	TX channel 647334	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7420.000	-52.62	-64.17	-13.00	-39.62	11.55	Peak	Horizontal
2	PP11140.000	-45.96	-66.11	-13.00	-32.96	20.15	Peak	Horizontal



MODE	TX channel 647334	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7420.000	-48.57	-62.95	-13.00	-35.57	14.38	Peak	Vertical
2	PP11130.000	-46.45	-66.01	-13.00	-33.45	19.56	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH656000


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7680.000	-51.87	-64.59	-13.00	-38.87	12.72	Peak	Horizontal
2	PP11530.000	-44.94	-65.63	-13.00	-31.94	20.69	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-49.71	-64.68	-13.00	-36.71	14.97	Peak	Vertical
2	PP11520.000	-48.71	-66.36	-13.00	-35.71	17.65	Peak	Vertical






BUREAU
VERITAS

Test Report No.: W7L-220214W001RF06

CH664666


MODE	TX channel 664666	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7942.000	-48.93	-63.56	-13.00	-35.93	14.63	Peak	Horizontal
2	PP11910.000	-43.08	-64.33	-13.00	-30.08	21.25	Peak	Horizontal



MODE	TX channel 664666	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7940.000	-48.62	-63.97	-13.00	-35.62	15.35	Peak	Vertical
2	PP11920.000	-46.23	-65.45	-13.00	-33.23	19.22	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 30MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-51.50	-64.24	-13.00	-38.50	12.74	Peak	Horizontal
2	PP11520.000	-45.40	-66.07	-13.00	-32.40	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 7680.000	-49.48	-64.44	-13.00	-36.48	14.96	Peak	Vertical
2	11530.000	-50.07	-67.76	-13.00	-37.07	17.69	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 40MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7680.000	-52.20	-64.92	-13.00	-39.20	12.72	Peak	Horizontal
2	PP11530.000	-46.51	-67.20	-13.00	-33.51	20.69	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-49.63	-64.60	-13.00	-36.63	14.97	Peak	Vertical
2	PP11520.000	-49.37	-67.02	-13.00	-36.37	17.65	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 50MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-52.36	-65.10	-13.00	-39.36	12.74	Peak	Horizontal
2	PP11520.000	-45.74	-66.41	-13.00	-32.74	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7680.000	-48.66	-63.62	-13.00	-35.66	14.96	Peak	Vertical
2	PP11530.000	-48.23	-65.92	-13.00	-35.23	17.69	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 60MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-51.93	-64.67	-13.00	-38.93	12.74	Peak	Horizontal
2	PP11520.000	-45.90	-66.57	-13.00	-32.90	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			


	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	PP 7682.000	-49.35	-64.32	-13.00	-36.35	14.97	Peak	Vertical
2	11520.000	-49.38	-67.03	-13.00	-36.38	17.65	Peak	Vertical



CHANNEL BANDWIDTH: 70MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-50.18	-62.92	-13.00	-37.18	12.74	Peak	Horizontal
2	PP11520.000	-46.01	-66.68	-13.00	-33.01	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-49.78	-64.75	-13.00	-36.78	14.97	Peak	Vertical
2	PP11520.000	-48.60	-66.25	-13.00	-35.60	17.65	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 80MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-51.90	-64.64	-13.00	-38.90	12.74	Peak	Horizontal
2	PP11520.000	-46.29	-66.96	-13.00	-33.29	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-48.75	-63.72	-13.00	-35.75	14.97	Peak	Vertical
2	PP11520.000	-47.97	-65.62	-13.00	-34.97	17.65	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 90MHz / QPSK


MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-51.90	-64.64	-13.00	-38.90	12.74	Peak	Horizontal
2	PP11520.000	-45.77	-66.44	-13.00	-32.77	20.67	Peak	Horizontal



MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-49.65	-64.62	-13.00	-36.65	14.97	Peak	Vertical
2	PP11520.000	-49.19	-66.84	-13.00	-36.19	17.65	Peak	Vertical






Test Report No.: W7L-220214W001RF06

CHANNEL BANDWIDTH: 100MHz / QPSK

MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: HORIZONTAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-51.09	-63.83	-13.00	-38.09	12.74	Peak	Horizontal
2	PP11520.000	-45.22	-65.89	-13.00	-32.22	20.67	Peak	Horizontal






Test Report No.: W7L-220214W001RF06

MODE	TX channel 656000	FREQUENCY RANGE	Above 1000MHz
ENVIRONMENTAL CONDITIONS	23deg. C, 70%RH	INPUT POWER	EUT 4.0V
TESTED BY	Jace Hu		
ANTENNA POLARITY & TEST DISTANCE: VERTICAL AT 3 M			

	Freq	Level	Read Level	Limit Line	Over Limit	Factor	Remark	Pol/Phase
	MHz	dBm/m	dBm	dBm/m	dB	dB/m		
1	7682.000	-49.42	-64.39	-13.00	-36.42	14.97	Peak	Vertical
2	PP11520.000	-48.99	-66.64	-13.00	-35.99	17.65	Peak	Vertical




3.7 PEAK TO AVERAGE RATIO

3.7.1 LIMITS OF PEAK TO AVERAGE RATIO MEASUREMENT

In measuring transmissions in this band using an average power technique, the peak to-average ratio (PAR) of the transmission may not exceed 13 dB

3.7.2 TEST SETUP



3.7.3 TEST PROCEDURES

1. Set resolution/measurement bandwidth $\geq$ signal's occupied bandwidth;
2. Set the number of counts to a value that stabilizes the measured CCDF curve;
3. Record the maximum PAPR level associated with a probability of 0.1%.



Test Report No.: W7L-220214W001RF06

3.7.4 TEST RESULTS

Please Refer to Appendix F Of this test report.



Test Report No.: W7L-220214W001RF06

4 INFORMATION ON THE TESTING LABORATORIES

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO. LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Shenzhen EMC/RF Lab:

Tel: +86-755-88696566

Fax: +86-755-88696577

Email: customerservice.sw@bureauveritas.com

Web Site: www.adt.com.tw

The address and road map of all our labs can be found in our web site also.



Test Report No.: W7L-220214W001RF06

5 MODIFICATIONS RECORDERS FOR ENGINEERING CHANGES TO THE EUT BY THE LAB

No any modifications are made to the EUT by the lab during the test.

NOTE: APPENDIX F is another word.

---END---