



FCC RADIO TEST REPORT

FCC ID : LHJ-LNADFW
Equipment : LNADFW
Brand Name : Continental Automotive Systems
Model Name : LNADFW
Applicant : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Manufacturer : Continental Automotive Systems, Inc.
21440 W Lake Cook Rd., Deer Park, IL 60010, USA
Standard : FCC Part 15 Subpart C §15.247

The product was received on Aug. 30, 2024 and testing was performed from Oct. 07, 2024 to Oct. 25, 2024. We, Sporton International Inc. Wensan Laboratory, would like to declare that the tested sample has been evaluated in accordance with the test procedures and has been in compliance with the applicable technical standards.

The test results in this report apply exclusively to the tested model / sample. Without written approval from Sporton International Inc. Wensan Laboratory, the test report shall not be reproduced except in full.

Approved by: Louis Wu

Sportun International Inc. Wensan Laboratory

No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.)



Table of Contents

| | |
|--|-----------|
| History of this test report..... | 3 |
| Summary of Test Result..... | 4 |
| 1 General Description | 5 |
| 1.1 Product Feature of Equipment Under Test..... | 5 |
| 1.2 Product Specification of Equipment Under Test..... | 5 |
| 1.3 Modification of EUT | 5 |
| 1.4 Testing Location | 6 |
| 1.5 Applicable Standards..... | 6 |
| 2 Test Configuration of Equipment Under Test | 7 |
| 2.1 Carrier Frequency and Channel | 7 |
| 2.2 Test Mode | 7 |
| 2.3 Connection Diagram of Test System..... | 8 |
| 2.4 Support Unit used in test configuration and system | 8 |
| 2.5 EUT Operation Test Setup | 8 |
| 2.6 Measurement Results Explanation Example..... | 9 |
| 3 Test Result | 10 |
| 3.1 6dB and 99% Bandwidth Measurement | 10 |
| 3.2 Output Power Measurement..... | 11 |
| 3.3 Power Spectral Density Measurement | 12 |
| 3.4 Conducted Band Edges and Spurious Emission Measurement | 13 |
| 3.5 Radiated Band Edges and Spurious Emission Measurement | 14 |
| 3.6 Antenna Requirements | 18 |
| 4 List of Measuring Equipment..... | 19 |
| 5 Measurement Uncertainty | 20 |
| Appendix A. Conducted Test Results | |
| Appendix B. Radiated Spurious Emission Test Data | |
| Appendix C. Duty Cycle Plots | |
| Appendix D. Setup Photographs | |



History of this test report



Summary of Test Result

| Report Clause | Ref Std. Clause | Test Items | Result (PASS/FAIL) | Remark |
|---------------|-----------------|--|--------------------|--|
| 3.1 | 15.247(a)(2) | 6dB Bandwidth | Pass | - |
| 3.1 | 2.1049 | 99% Occupied Bandwidth | Pass | - |
| 3.2 | 15.247(b) | Power Output Measurement | Pass | - |
| 3.3 | 15.247(e) | Power Spectral Density | Pass | - |
| 3.4 | 15.247(d) | Conducted Band Edges | Pass | - |
| | | Conducted Spurious Emission | Pass | - |
| 3.5 | 15.247(d) | Radiated Band Edges and Radiated Spurious Emission | Pass | 2.70 dB under the limit at 4924.00 MHz |
| - | 15.207 | AC Conducted Emission | Not Required | - |
| 3.6 | 15.203 | Antenna Requirement | Pass | - |

Note: Not required means after assessing, test items are not necessary to carry out.

Conformity Assessment Condition:

1. The test results (PASS/FAIL) with all measurement uncertainty excluded are presented against the regulation limits or in accordance with the requirements stipulated by the applicant/manufacturer who shall bear all the risks of non-compliance that may potentially occur if measurement uncertainty is taken into account.
2. The measurement uncertainty please refer to each test result in the section "Measurement Uncertainty".

Disclaimer:

The product specifications of the EUT presented in the test report that may affect the test assessments are declared by the manufacturer who shall take full responsibility for the authenticity.

Reviewed by: Yun Huang

Report Producer: Mila Chen



1 General Description

1.1 Product Feature of Equipment Under Test

| Product Feature | |
|--|---|
| Equipment | LNADVV |
| Brand Name | Continental Automotive Systems |
| Model Name | LNADVV |
| FCC ID | LHJ-LNADVV |
| Installed into the Host | Equipment name: StrLnk2 Brand name: Continental Automotive Systems Model name: LNADVV |
| EUT supports Radios application | WCDMA/HSPA/LTE/GNSS WLAN 11b/g/n HT20 WLAN 11a/n HT20/HT40 |
| EUT Stage | Identical Prototype |

1.2 Product Specification of Equipment Under Test

| Product Specification is subject to this standard | |
|---|---|
| Tx/Rx Frequency Range | 2402 MHz ~ 2480 MHz |
| Maximum Output Power to Antenna | 802.11b : 20.97 dBm / 0.1250 W 802.11g : 15.77 dBm / 0.0378 W 802.11n HT20 : 16.67 dBm / 0.0465 W |
| 99% Occupied Bandwidth | 802.11b: 14.94 MHz 802.11g: 17.32 MHz 802.11n HT20 : 18.48 MHz |
| Antenna Type / Gain | PCB Antenna with gain 3.38361 dBi |
| Type of Modulation | 802.11b : DSSS (DBPSK / DQPSK / CCK) 802.11g/n : OFDM (BPSK / QPSK / 16QAM / 64QAM) |

Remark: The EUT's information above is declared by manufacturer. Please refer to Disclaimer in report summary.

1.3 Modification of EUT

No modifications made to the EUT during the testing.



1.4 Testing Location

| | |
|---------------------------|--|
| Test Site | Sportun International Inc. Wensan Laboratory |
| Test Site Location | No.58, Aly. 75, Ln. 564, Wenhua 3rd, Rd., Guishan Dist., Taoyuan City 333010, Taiwan (R.O.C.) TEL: +886-3-327-0868 FAX: +886-3-327-0855 |
| Test Site No. | Sportun Site No. TH05-HY, 03CH11-HY |

Note: The test site complies with ANSI C63.4 2014 requirement.

FCC designation No.: TW3786

1.5 Applicable Standards

According to the specifications declared by the manufacturer, the EUT must comply with the requirements of the following standards:

- ♦ FCC Part 15 Subpart C §15.247
- ♦ FCC KDB Publication No. 558074 D01 15.247 Meas Guidance v05r02
- ♦ FCC KDB 414788 D01 Radiated Test Site v01r01.
- ♦ ANSI C63.10-2013

Remark:

1. All the test items were validated and recorded in accordance with the standards without any modification during the testing.
2. The TAF code is not including all the FCC KDB listed without accreditation.
3. This EUT has also been tested and complied with the requirements of FCC Part 15, Subpart B, recorded in a separate test report.



2 Test Configuration of Equipment Under Test

The EUT has been associated with peripherals and configuration operated in a manner tended to maximize its emission characteristics in a typical application. Frequency range investigated: radiation emission (9 kHz to the 10th harmonic of the highest fundamental frequency or to 40 GHz, whichever is lower). For radiated measurement, the measured emission level of the EUT was maximized by rotating the EUT on a turntable, adjusting the orientation of the EUT and EUT antenna in three orthogonal axis (X: flat, Y: portrait, Z: landscape), and adjusting the measurement antenna orientation, following C63.10 exploratory test procedures and only the worst case emissions were reported in this report.

2.1 Carrier Frequency and Channel

| Frequency Band | Channel | Freq. (MHz) | Channel | Freq. (MHz) |
|-----------------|---------|----------------|---------|----------------|
| 2400-2483.5 MHz | 1 | 2412 | 7 | 2442 |
| | 2 | 2417 | 8 | 2447 |
| | 3 | 2422 | 9 | 2452 |
| | 4 | 2427 | 10 | 2457 |
| | 5 | 2432 | 11 | 2462 |
| | 6 | 2437 | | |

2.2 Test Mode


The final test modes include the worst data rates for each modulation shown in the table below.

| Modulation | Data Rate | | |
|--------------|-----------|--|--|
| 802.11b | 1 Mbps | | |
| 802.11g | 6 Mbps | | |
| 802.11n HT20 | MCS0 | | |

| Ch. # | 2400-2483.5 MHz | | |
|--------|-----------------|---------|--------------|
| | 802.11b | 802.11g | 802.11n HT20 |
| Low | 01 | 01 | 01 |
| Middle | 06 | 06 | 06 |
| High | 11 | 11 | 11 |

Remark: For radiation spurious emission, the modulation and the data rate picked for testing are determined by the Max. RF conducted power.

2.3 Connection Diagram of Test System



2.4 Support Unit used in test configuration and system

| Item | Equipment | Brand Name | Model Name | FCC ID | Data Cable | Power Cord |
|------|-----------------|-------------|---------------|--------|------------|--|
| 1. | Notebook | DELL | Latitude 3400 | NA | N/A | AC I/P: Unshielded, 1.2 m DC O/P: Shielded, 1.8 m |
| 2. | TP LoadBox | Continental | Subaru T19 | N/A | N/A | N/A |
| 3. | DC Power Supply | GW Insteck | GPE-2323 | N/A | N/A | N/A |

2.5 EUT Operation Test Setup

The RF test items, utility “QRCT v3.0.277.0” was installed in Notebook which was programmed in order to make the EUT get into the engineering modes to provide channel selection, power level, data rate and the application type and for continuous transmitting signals.



2.6 Measurement Results Explanation Example

For all conducted test items:

The offset level is set in the spectrum analyzer to compensate the RF cable loss and attenuator factor between EUT conducted output port and spectrum analyzer. With the offset compensation, the spectrum analyzer reading level is exactly the EUT RF output level.

Example:

The spectrum analyzer offset is derived from RF cable loss and attenuator factor.

Offset = RF cable loss + attenuator factor.

Following shows an offset computation example with cable loss 4.2 dB and 10 dB attenuator.

Offset(dB) = RF cable loss(dB) + attenuator factor(dB).

= 4.2 + 10 = 14.2 (dB)

3 Test Result

3.1 6dB and 99% Bandwidth Measurement

3.1.1 Limit of 6dB and 99% Bandwidth

The minimum 6 dB bandwidth shall be at least 500 kHz.


3.1.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.1.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 6.9.3 (OBW) and 11.8.1 (6dB BW).
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6 dB bandwidth must be greater than 500 kHz.
5. For 99% Bandwidth Measurement, the spectrum analyzer's resolution bandwidth (RBW) is set 1-5% of the emission bandwidth and set the Video bandwidth (VBW) $\geq 3 * \text{RBW}$.
6. Measure and record the results in the test report.

3.1.4 Test Setup



3.1.5 Test Result of 6dB and 99% Occupied Bandwidth

Please refer to Appendix A.

3.2 Output Power Measurement

3.2.1 Limit of Output Power

For systems using digital modulation in the 2400-2483.5 MHz, the limit for output power is 30 dBm. If transmitting antenna with directional gain greater than 6 dBi is used, the peak output power from the intentional radiator shall be reduced below the above stated value by the amount in dB that the directional gain of the antenna exceeds 6 dBi. In case of point-to-point operation, the limit has to be reduced by 1 dB for every 3 dB that the directional gain of the antenna exceeds 6 dBi.


3.2.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.2.3 Test Procedures

1. For Average Power, the testing follows ANSI C63.10 Section 11.9.2.3.2 Method AVGPM-G
2. The RF output of EUT is connected to the power meter by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Measure the conducted output power and record the results in the test report.

3.2.4 Test Setup



3.2.5 Test Result of Average Output Power

Please refer to Appendix A.

3.3 Power Spectral Density Measurement

3.3.1 Limit of Power Spectral Density

The peak power spectral density shall not be greater than 8 dBm in any 3 kHz band at any time interval of continuous transmission.


3.3.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.3.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.10.2 Method PKPSD.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 3 kHz. Video bandwidth VBW = 10 kHz In order to make an accurate measurement, set the span to 1.5 times DTS Channel Bandwidth. (6dB BW)
5. Detector = peak, Sweep time = auto couple, Trace mode = max hold, Allow trace to fully stabilize. Use the peak marker function to determine the maximum power level.
6. Measure and record the results in the test report.

3.3.4 Test Setup



3.3.5 Test Result of Power Spectral Density

Please refer to Appendix A.

3.4 Conducted Band Edges and Spurious Emission Measurement

3.4.1 Limit of Conducted Band Edges and Spurious Emission Measurement

In any 100 kHz bandwidth outside of the authorized frequency band, the emissions which fall in the non-restricted bands shall be attenuated at least 20 dB / 30dB relative to the maximum PSD level in 100 kHz by RF conducted measurement.


3.4.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.4.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.11.3 Emission level measurement.
2. The RF output of EUT is connected to the spectrum analyzer by RF cable and attenuator. The path loss is compensated to the results for each measurement.
3. Set the maximum power setting and enable the EUT to transmit continuously.
4. Set RBW = 100 kHz, VBW=300 kHz, Peak Detector. Unwanted Emissions measured in any 100 kHz bandwidth outside of the authorized frequency band shall be attenuated by at least 20 dB relative to the maximum in-band peak PSD level in 100 kHz when maximum peak conducted output power procedure is used. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, the attenuation required under this paragraph shall be 30 dB instead of 20 dB per 15.247(d).
5. Measure and record the results in the test report.
6. The RF fundamental frequency should be excluded against the limit line in the operating frequency band.

3.4.4 Test Setup



3.4.5 Test Result of Conducted Band Edges and Spurious Emission

Please refer to Appendix A.



3.5 Radiated Band Edges and Spurious Emission Measurement

3.5.1 Limit of Radiated band edge and Spurious Emission Measurement

In any 100 kHz bandwidth outside the intentional radiator frequency band, all harmonics/spurious must be at least 20 dB below the highest emission level within the authorized band. If the output power of this device is measured by spectrum analyzer, the attenuation under this paragraph shall be 30 dB instead of 20 dB. In addition, radiated emissions which fall in the restricted bands must also comply with the limits as below.

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|--------------------|--------------------------------------|----------------------------------|
| 0.009 – 0.490 | 2400/F(kHz) | 300 |
| 0.490 – 1.705 | 24000/F(kHz) | 30 |
| 1.705 – 30.0 | 30 | 30 |
| 30 – 88 | 100 | 3 |
| 88 – 216 | 150 | 3 |
| 216 - 960 | 200 | 3 |
| Above 960 | 500 | 3 |

3.5.2 Measuring Instruments

Please refer to the measuring equipment list in this test report.

3.5.3 Test Procedures

1. The testing follows the ANSI C63.10 Section 11.12.1 Radiated emission measurements.
2. The EUT is arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level.
3. The EUT is placed on a turntable with 0.8 meter for frequency below 1 GHz and 1.5 meter for frequency above 1 GHz respectively above ground.
4. The EUT is set 3 meters away from the receiving antenna, which is mounted on the top of a variable height antenna tower.
5. Corrected Reading: Antenna Factor + Cable Loss + Read Level - Preamp Factor = Level
6. Radiated testing below 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading. When there is no suspected emission found and the emission level is with at least 6 dB margin against QP limit line, the position is marked as “-”.


7. Radiated testing above 1 GHz is performed by adjusting the antenna tower from 1 m to 4 m and by rotating the turn table from 0 degree to 360 degrees to find the peak maximum hold reading for scanning all frequencies. When there is no suspected emission found and the harmonic emission level is with at least 6 dB margin against average limit line, the position is marked as “_”.
8. Use the following spectrum analyzer settings:
 - (1) Span shall wide enough to fully capture the emission being measured;
 - (2) Set RBW = 100 kHz for $f < 1$ GHz; VBW \geq RBW; Sweep = auto; Detector function = peak; Trace = max hold;
 - (3) Set RBW = 1 MHz, VBW= 3 MHz for $f \geq 1$ GHz for peak measurement.

For average measurement:


 - VBW = 10 Hz, when duty cycle is no less than 98 percent.
 - VBW $\geq 1/T$, when duty cycle is less than 98 percent where T is the minimum transmission duration over which the transmitter is on and is transmitting at its maximum power control level for the tested mode of operation.

3.5.4 Test Setup


For radiated emissions below 30MHz




For radiated emissions from 30MHz to 1GHz



For radiated test from 1GHz to 18GHz



For radiated test above 18GHz





3.5.5 Test Results of Radiated Spurious Emissions (9kHz ~ 30MHz)

The low frequency, which starts from 9 kHz to 30 MHz, is pre-scanned and the result which is 20 dB lower than the limit line is not reported.

There is adequate comparison measurement of both open-field test site and alternative test site - semi-Anechoic chamber according to 414788 D01 Radiated Test Site v01r01, and the result comes out very similar.

3.5.6 Test Result of Radiated Spurious at Band Edges

Please refer to Appendix B.

3.5.7 Duty Cycle

Please refer to Appendix C.

3.5.8 Test Result of Radiated Spurious Emission (30MHz ~ 10th Harmonic)

Please refer to Appendix B.



3.6 Antenna Requirements

3.6.1 Standard Applicable

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited. This requirement does not apply to carrier current devices or to devices operated under the provisions of § 15.211, 15.213, 15.217, 15.219, 15.221, or § 15.236. Further, this requirement does not apply to intentional radiators that must be professionally installed, such as perimeter protection systems and some field disturbance sensors, or to other intentional radiators which, in accordance with § 15.31(d), must be measured at the installation site. However, the installer shall be responsible for ensuring that the proper antenna is employed so that the limits in this part are not exceeded.

3.6.2 Antenna Anti-Replacement Construction

Antenna permanently attached.



4 List of Measuring Equipment

| Instrument | Brand Name | Model No. | Serial No. | Characteristics | Calibration Date | Test Date | Due Date | Remark |
|--------------------------|-----------------|-----------------------------|-------------------------|-------------------------------|------------------|-----------------------------|---------------|-----------------------|
| Hygrometer | TECPHEL | DTM-303A | TP201996 | N/A | Nov. 07, 2023 | Oct. 07, 2024~Oct. 25, 2024 | Nov. 06, 2024 | Conducted (TH05-HY) |
| Power Sensor | DARE | RPR3006W | 15I00041SNO 10 (NO:248) | 10MHz~6GHz | Jan. 10, 2024 | Oct. 07, 2024~Oct. 25, 2024 | Jan. 09, 2025 | Conducted (TH05-HY) |
| Signal Analyzer | Rohde & Schwarz | FSV3044 | 101466 | 10HZ~44GHZ | Jan. 24, 2024 | Oct. 07, 2024~Oct. 25, 2024 | Jan. 23, 2025 | Conducted (TH05-HY) |
| Switch Control Mainframe | Burgeon | ETF-058 | EC1300484 (BOX3) | N/A | May 20, 2024 | Oct. 07, 2024~Oct. 25, 2024 | May 19, 2025 | Conducted (TH05-HY) |
| Software | Sportun | BTWIFI_Final_version_240513 | N/A | Conducted Other Test Item | N/A | Oct. 07, 2024~Oct. 25, 2024 | N/A | Conducted (TH05-HY) |
| Bilog Antenna | TESEQ | CBL 6111D & N-6-06 | 35414 & AT-N0602 | 30MHz~1GHz | Oct. 05, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Oct. 04, 2025 | Radiation (03CH11-HY) |
| Horn Antenna | SCHWARZBECK | BBHA 9120 D | 9120D-01620 | 1GHz~18GHz | Aug. 28, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Aug. 27, 2025 | Radiation (03CH11-HY) |
| SHF-EHF Horn Antenna | SCHWARZBECK | BBHA 9170 | 00993 | 18GHz~40GHz | Nov. 24, 2023 | Oct. 15, 2024~Oct. 22, 2024 | Nov. 23, 2024 | Radiation (03CH11-HY) |
| Amplifier | SONOMA | 310N | 187312 | 9kHz~1GHz | Dec. 08, 2023 | Oct. 15, 2024~Oct. 22, 2024 | Dec. 07, 2024 | Radiation (03CH11-HY) |
| Preamplifier | Keysight | 83017A | MY53270080 | 1GHz~26.5GHz | Mar. 25, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Mar. 24, 2025 | Radiation (03CH11-HY) |
| Preamplifier | Jet-Power | JPA0118-55-303 | 17100018000 55007 | 1GHz~18GHz | Jun. 13, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Jun. 12, 2025 | Radiation (03CH11-HY) |
| Preamplifier | EMEC | EM18G40G | 060715 | 18GHz~40GHz | Dec. 07, 2023 | Oct. 15, 2024~Oct. 22, 2024 | Dec. 06, 2024 | Radiation (03CH11-HY) |
| Spectrum Analyzer | Keysight | N9010A | MY54200486 | 10Hz~44GHz | Oct. 14, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Oct. 13, 2025 | Radiation (03CH11-HY) |
| EMI Test Receiver | Keysight | N9038A(MXE) | MY55420170 | 20MHz~8.4GHz | Jul. 19, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Jul. 18, 2025 | Radiation (03CH11-HY) |
| Controller | EMEC | EM 1000 | N/A | Control Turn table & Ant Mast | N/A | Oct. 15, 2024~Oct. 22, 2024 | N/A | Radiation (03CH11-HY) |
| Antenna Mast | EMEC | AM-BS-4500-B | N/A | 1~4m | N/A | Oct. 15, 2024~Oct. 22, 2024 | N/A | Radiation (03CH11-HY) |
| Turn Table | EMEC | TT 2000 | N/A | 0~360 Degree | N/A | Oct. 15, 2024~Oct. 22, 2024 | N/A | Radiation (03CH11-HY) |
| Software | Audix | E3 6.2009-8-24 | RK-001053 | N/A | N/A | Oct. 15, 2024~Oct. 22, 2024 | N/A | Radiation (03CH11-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | 804013/2 | 30M~40G | May 23, 2024 | Oct. 15, 2024~Oct. 22, 2024 | May 22, 2025 | Radiation (03CH11-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | MY2859/2 | 30MHz~40GHz | Mar. 06, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Mar. 05, 2025 | Radiation (03CH11-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | 803951/2 | 9K~30M | Mar. 06, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Mar. 05, 2025 | Radiation (03CH11-HY) |
| RF Cable | HUBER + SUHNER | SUCOFLEX 102 | 803951/2 | 30M~40G | Mar. 06, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Mar. 05, 2025 | Radiation (03CH11-HY) |
| Attenuator | HONOVA | 5910 SMA-50-005 | 0028 | N/A | Jul. 09, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Jul. 08, 2025 | Radiation (03CH11-HY) |
| Filter | Wainwright | WHKX12-2700-3000-18000-60SS | SN3 | 3GHz High Pass Filter | Sep. 10, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Sep. 09, 2025 | Radiation (03CH11-HY) |
| Filter | Wainwright | WLK4-1000-1530-8000-40SS | SN11 | 1.53GHz Low Pass Filter | Sep. 10, 2024 | Oct. 15, 2024~Oct. 22, 2024 | Sep. 09, 2025 | Radiation (03CH11-HY) |
| Hygrometer | TECPHEL | DTM-303B | TP140325 | N/A | Dec. 08, 2023 | Oct. 15, 2024~Oct. 22, 2024 | Dec. 07, 2024 | Radiation (03CH11-HY) |



5 Measurement Uncertainty

Uncertainty of Radiated Emission Measurement (30 MHz ~ 1000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$) | 6.4 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (1000 MHz ~ 6000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$) | 5.1 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (6000 MHz ~ 18000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$) | 5.3 dB |
|---|--------|

Uncertainty of Radiated Emission Measurement (18000 MHz ~ 40000 MHz)

| | |
|---|--------|
| Measuring Uncertainty for a Level of Confidence of 95% ($U = 2U_{c(y)}$) | 5.3 dB |
|---|--------|

Appendix A. Test Result of Conducted Test Items

| | | | | |
|----------------|------------------------|--------------------|-------|----|
| Test Engineer: | Benny Ku and Derek Hsu | Temperature: | 21~25 | °C |
| Test Date: | 2024/10/07~2024/10/25 | Relative Humidity: | 51~54 | % |

TEST RESULTS DATA
6dB and 99% Occupied Bandwidth

| 2.4GHz Band Single Antenna | | | | | | | | | | |
|----------------------------|-----------|-----------------|-----|-------------|-----------------------|------|--------------|------|--------------------|-----------|
| Mod. | Data Rate | N _{TX} | CH. | Freq. (MHz) | 99% Occupied BW (MHz) | | 6dB BW (MHz) | | 6dB BW Limit (MHz) | Pass/Fail |
| | | | | | Ant1 | Ant2 | Ant1 | Ant2 | | |
| 11b | 1Mbps | 1 | 1 | 2412 | 13.96 | - | 10.06 | - | 0.50 | Pass |
| 11b | 1Mbps | 1 | 6 | 2437 | 14.94 | - | 10.07 | - | 0.50 | Pass |
| 11b | 1Mbps | 1 | 11 | 2462 | 13.78 | - | 10.04 | - | 0.50 | Pass |
| 11g | 6Mbps | 1 | 1 | 2412 | 16.92 | - | 16.08 | - | 0.50 | Pass |
| 11g | 6Mbps | 1 | 6 | 2437 | 17.32 | - | 16.32 | - | 0.50 | Pass |
| 11g | 6Mbps | 1 | 11 | 2462 | 16.72 | - | 16.29 | - | 0.50 | Pass |
| HT20 | MCS0 | 1 | 1 | 2412 | 18.05 | - | 17.17 | - | 0.50 | Pass |
| HT20 | MCS0 | 1 | 6 | 2437 | 18.48 | - | 17.31 | - | 0.50 | Pass |
| HT20 | MCS0 | 1 | 11 | 2462 | 17.84 | - | 16.93 | - | 0.50 | Pass |

TEST RESULTS DATA
Average Output Power


| 2.4GHz Band Single Antenna | | | | | | | | | | | | | | | | |
|----------------------------|-----------|-----|-----|-------------|-------------------------------|------|-------|-----------------------------|---------|----------|-------|------------------|-------|------------------------|------|------------|
| Mod. | Data Rate | NTX | CH. | Freq. (MHz) | Average Conducted Power (dBm) | | | Conducted Power Limit (dBm) | | DG (dBi) | | EIRP Power (dBm) | | EIRP Power Limit (dBm) | | Pass /Fail |
| | | | | | Ant1 | Ant2 | SUM | Ant1 | Ant2 | Ant1 | Ant2 | Ant1 | Ant2 | Ant1 | Ant2 | |
| 11b | 1Mbps | 1 | 1 | 2412 | 19.37 | - | 30.00 | - | 3.38361 | - | 22.75 | - | 36.00 | - | Pass | |
| 11b | 1Mbps | 1 | 6 | 2437 | 19.37 | - | | - | 3.38361 | - | 22.75 | - | 36.00 | - | Pass | |
| 11b | 1Mbps | 1 | 11 | 2462 | 20.97 | - | | - | 3.38361 | - | 24.35 | - | 36.00 | - | Pass | |
| 11g | 6Mbps | 1 | 1 | 2412 | 14.67 | - | | - | 3.38361 | - | 18.05 | - | 36.00 | - | Pass | |
| 11g | 6Mbps | 1 | 6 | 2437 | 14.97 | - | | - | 3.38361 | - | 18.35 | - | 36.00 | - | Pass | |
| 11g | 6Mbps | 1 | 11 | 2462 | 15.77 | - | | - | 3.38361 | - | 19.15 | - | 36.00 | - | Pass | |
| HT20 | MCS0 | 1 | 1 | 2412 | 16.07 | - | | - | 3.38361 | - | 19.45 | - | 36.00 | - | Pass | |
| HT20 | MCS0 | 1 | 6 | 2437 | 15.77 | - | | - | 3.38361 | - | 19.15 | - | 36.00 | - | Pass | |
| HT20 | MCS0 | 1 | 11 | 2462 | 16.67 | - | | | 3.38361 | - | 20.05 | - | 36.00 | - | Pass | |

Note: Measured power (dBm) has offset with cable loss.


TEST RESULTS DATA
Peak Power Spectral Density

| 2.4GHz Band Single Antenna | | | | | | | | | | | | |
|----------------------------|-----------|-----|-----|-------------|---------------------|------|--------------|----------|------|---------------------------|------|-----------|
| Mod. | Data Rate | NTX | CH. | Freq. (MHz) | Peak PSD (dBm/3kHz) | | | DG (dBi) | | Peak PSD Limit (dBm/3kHz) | | Pass/Fail |
| | | | | | Ant1 | Ant2 | Worse + 3.01 | Ant1 | Ant2 | Ant1 | Ant2 | |
| 11b | 1Mbps | 1 | 1 | 2412 | -5.23 | - | 3.38361 | - | 8.00 | - | Pass | |
| 11b | 1Mbps | 1 | 6 | 2437 | -5.18 | - | | - | 8.00 | - | Pass | |
| 11b | 1Mbps | 1 | 11 | 2462 | -3.18 | - | | - | 8.00 | - | Pass | |
| 11g | 6Mbps | 1 | 1 | 2412 | -10.66 | - | | - | 8.00 | - | Pass | |
| 11g | 6Mbps | 1 | 6 | 2437 | -9.30 | - | | - | 8.00 | - | Pass | |
| 11g | 6Mbps | 1 | 11 | 2462 | -7.31 | - | | - | 8.00 | - | Pass | |
| HT20 | MCS0 | 1 | 1 | 2412 | -9.90 | - | | - | 8.00 | - | Pass | |
| HT20 | MCS0 | 1 | 6 | 2437 | -9.48 | - | | - | 8.00 | - | Pass | |
| HT20 | MCS0 | 1 | 11 | 2462 | -7.93 | - | | - | 8.00 | - | Pass | |

Measured power density (dBm) has offset with cable loss.

6dB and 99% Occupied Bandwidth
<802.11b>



Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

<802.11g>


Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.




<802.11n HT20>




Note: The occupied channel bandwidth is maintained within the band of operation for all of the modulations.

Power Spectral Density(dBm/3kHz)

<802.11b>




<802.11g>






<802.11n HT20>



**Band Edges and Spurious Emission**

Number of TX = 1, Ant. 1 (Measured)


| | |
|---------------------|-------------------|
| Test Mode : 802.11b | Test Channel : 01 |
|---------------------|-------------------|





Test Mode : 802.11b


Test Channel : 06





Test Mode : 802.11b


Test Channel : 11





Test Mode : 802.11g


Test Channel : 01





Test Mode : 802.11g


Test Channel : 06





Test Mode : 802.11g


Test Channel : 11





Test Mode : 802.11n HT20


Test Channel : 01





Test Mode : 802.11n HT20


Test Channel : 06





Test Mode : 802.11n HT20

Test Channel : 11





Appendix B. Radiated Spurious Emission Test Data

| | | | |
|------------------------|-------------------------------------|----------------------------|-------------|
| Test Engineer : | Kevin Hsu, Fu Chen, and Troye Hsieh | Temperature : | 20.1~21.9°C |
| | | Relative Humidity : | 54.3~68.7% |

Note symbol

| | |
|----|-----------------------|
| -L | Low channel location |
| -R | High channel location |

B1. Radiated Spurious Emission Test Modes

| Mode | Band (MHz) | Antenna | Modulation | Channel | Frequency | Data Rate | RU | Remark |
|---------|-------------|---------|--------------|---------|-----------|-----------|----|--------|
| Mode 1 | 2400-2483.5 | SISO | 802.11b | 01 | 2412 | 1Mbps | - | - |
| Mode 2 | 2400-2483.5 | SISO | 802.11b | 06 | 2437 | 1Mbps | - | - |
| Mode 3 | 2400-2483.5 | SISO | 802.11b | 11 | 2462 | 1Mbps | - | - |
| Mode 4 | 2400-2483.5 | SISO | 802.11g | 01 | 2412 | 6Mbps | - | - |
| Mode 5 | 2400-2483.5 | SISO | 802.11g | 06 | 2437 | 6Mbps | - | - |
| Mode 6 | 2400-2483.5 | SISO | 802.11g | 11 | 2462 | 6Mbps | - | - |
| Mode 7 | 2400-2483.5 | SISO | 802.11n HT20 | 01 | 2412 | MCS0 | - | - |
| Mode 8 | 2400-2483.5 | SISO | 802.11n HT20 | 06 | 2437 | MCS0 | - | - |
| Mode 9 | 2400-2483.5 | SISO | 802.11n HT20 | 11 | 2462 | MCS0 | - | - |
| Mode 10 | 2400-2483.5 | SISO | 802.11b | 11 | 2462 | 1Mbps | - | SHF |
| Mode 11 | 2400-2483.5 | SISO | 802.11b | 11 | 2462 | 1Mbps | - | LF |



B2. Summary of each worse mode


| Mode | Modulation | Ch. | Freq. (MHz) | Level (dBuV/m) | Limit (dBuV/m) | Margin (dB) | Pol. | Peak Avg. | Result | RU | Remark |
|------|--------------|-----|----------------|-------------------|-------------------|----------------|------|--------------|--------|----|-----------|
| 1 | 802.11b | 01 | 2389.95 | 44.60 | 54.00 | -9.40 | H | Avg. | Pass | - | Band Edge |
| | 802.11b | 01 | 4824.00 | 43.47 | 54.00 | -10.53 | H | Avg. | Pass | - | Harmonic |
| 2 | 802.11b | 06 | 2483.56 | 45.29 | 54.00 | -8.71 | H | Avg. | Pass | - | Band Edge |
| | 802.11b | 06 | 4874.00 | 47.39 | 54.00 | -6.61 | H | Avg. | Pass | - | Harmonic |
| 3 | 802.11b | 11 | 2483.55 | 46.11 | 54.00 | -7.89 | H | Avg. | Pass | - | Band Edge |
| | 802.11b | 11 | 4924.00 | 51.30 | 54.00 | -2.70 | H | Avg. | Pass | - | Harmonic |
| 4 | 802.11g | 01 | 2389.95 | 46.27 | 54.00 | -7.73 | H | Avg. | Pass | - | Band Edge |
| | 802.11g | 01 | 4824.00 | 40.06 | 74.00 | -33.94 | H | Peak | Pass | - | Harmonic |
| 5 | 802.11g | 06 | 2483.68 | 43.14 | 54.00 | -10.86 | H | Avg. | Pass | - | Band Edge |
| | 802.11g | 06 | 7311.00 | 42.24 | 74.00 | -31.76 | H | Peak | Pass | - | Harmonic |
| 6 | 802.11g | 11 | 2483.51 | 46.29 | 54 | -7.71 | H | Avg. | Pass | - | Band Edge |
| | 802.11g | 11 | 7386.00 | 42.22 | 74.00 | -31.78 | H | Peak | Pass | - | Harmonic |
| 7 | 802.11n HT20 | 01 | 2389.95 | 48.38 | 54.00 | -5.62 | H | Avg. | Pass | - | Band Edge |
| | 802.11n HT20 | 01 | 4824.00 | 40.92 | 74.00 | -33.09 | V | Peak | Pass | - | Harmonic |
| 8 | 802.11n HT20 | 06 | 2483.56 | 43.80 | 54.00 | -10.20 | H | Avg. | Pass | - | Band Edge |
| | 802.11n HT20 | 06 | 7311.00 | 43.48 | 74.00 | -30.52 | V | Peak | Pass | - | Harmonic |
| 9 | 802.11n HT20 | 11 | 2483.51 | 48.33 | 54.00 | -5.67 | H | Avg. | Pass | - | Band Edge |
| | 802.11n HT20 | 11 | 7386.00 | 43.18 | 74.00 | -30.82 | H | Peak | Pass | - | Harmonic |
| 10 | 802.11b | 11 | 25576.00 | 41.58 | 68.20 | -26.62 | H | Peak | Pass | - | SHF |
| 11 | 802.11b | 11 | 959.26 | 32.78 | 46.00 | -13.22 | H | Peak | Pass | - | LF |









| Mode | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-------------|--------|--------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|-------|--------|-------|-------|-------|-------|-----------------|---|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|--------|-------|-------|-------|-----------------|--------------|
| | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH01_2412MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak | <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.69</td><td>55.47</td><td>74.00</td><td>-18.53</td><td>44.70</td><td>27.38</td><td>6.78</td><td>33.34</td><td>10.03</td><td>201 132 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.69 | 55.47 | 74.00 | -18.53 | 44.70 | 27.38 | 6.78 | 33.34 | 10.03 | 201 132 PEAK | <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2412.00</td><td>111.09</td><td>-----</td><td>-----</td><td>100.13</td><td>27.44</td><td>6.81</td><td>33.32</td><td>10.03</td><td>201 132 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 111.09 | ----- | ----- | 100.13 | 27.44 | 6.81 | 33.32 | 10.03 | 201 132 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.69 | 55.47 | 74.00 | -18.53 | 44.70 | 27.38 | 6.78 | 33.34 | 10.03 | 201 132 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 111.09 | ----- | ----- | 100.13 | 27.44 | 6.81 | 33.32 | 10.03 | 201 132 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.95</td><td>44.60</td><td>54.00</td><td>-9.40</td><td>33.83</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>201 132 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.95 | 44.60 | 54.00 | -9.40 | 33.83 | 27.30 | 6.78 | 33.34 | 10.03 | 201 132 AVERAGE | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2412.00</td><td>108.21</td><td>-----</td><td>-----</td><td>97.25</td><td>27.44</td><td>6.81</td><td>33.32</td><td>10.03</td><td>201 132 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 108.21 | ----- | ----- | 97.25 | 27.44 | 6.81 | 33.32 | 10.03 | 201 132 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.95 | 44.60 | 54.00 | -9.40 | 33.83 | 27.30 | 6.78 | 33.34 | 10.03 | 201 132 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 108.21 | ----- | ----- | 97.25 | 27.44 | 6.81 | 33.32 | 10.03 | 201 132 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |







| Mode | 1 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|---|-------------|--------------|-------------|--------|--------|--------|-------|--------|-----------------|--------|-------|-------------|--------------|--------------|-------------|--------|--|--|--|---|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|--|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|-------|-------------|--------------|--------------|-------------|--------|--|--|--|---|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH01_2412MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak | <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> </thead> <tbody> <tr> <td>1</td><td>2389.95</td><td>53.70</td><td>74.00</td><td>-20.30</td><td>42.93</td><td>27.38</td><td>6.78</td><td>33.34</td><td>10.03</td><td>400 195 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | 1 | 2389.95 | 53.70 | 74.00 | -20.30 | 42.93 | 27.38 | 6.78 | 33.34 | 10.03 | 400 195 PEAK | <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> </thead> <tbody> <tr> <td>1</td><td>2412.00</td><td>106.31</td><td>-----</td><td>-----</td><td>95.35</td><td>27.44</td><td>6.81</td><td>33.32</td><td>10.03</td><td>400 195 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | 1 | 2412.00 | 106.31 | ----- | ----- | 95.35 | 27.44 | 6.81 | 33.32 | 10.03 | 400 195 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2389.95 | 53.70 | 74.00 | -20.30 | 42.93 | 27.38 | 6.78 | 33.34 | 10.03 | 400 195 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2412.00 | 106.31 | ----- | ----- | 95.35 | 27.44 | 6.81 | 33.32 | 10.03 | 400 195 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> </thead> <tbody> <tr> <td>1</td><td>2389.95</td><td>42.89</td><td>54.00</td><td>-11.11</td><td>32.12</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>400 195 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | 1 | 2389.95 | 42.89 | 54.00 | -11.11 | 32.12 | 27.30 | 6.78 | 33.34 | 10.03 | 400 195 AVERAGE | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> </thead> <tbody> <tr> <td>1</td><td>2412.00</td><td>102.91</td><td>-----</td><td>-----</td><td>91.95</td><td>27.44</td><td>6.81</td><td>33.32</td><td>10.03</td><td>400 195 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | 1 | 2412.00 | 102.91 | ----- | ----- | 91.95 | 27.44 | 6.81 | 33.32 | 10.03 | 400 195 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2389.95 | 42.89 | 54.00 | -11.11 | 32.12 | 27.30 | 6.78 | 33.34 | 10.03 | 400 195 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2412.00 | 102.91 | ----- | ----- | 91.95 | 27.44 | 6.81 | 33.32 | 10.03 | 400 195 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |







| | | |
|--------|--|---|
| Mode | 1 | |
| | Harmonic | |
| | 2400-2483.5_802.11b_CH01_2412MHz | |
| ANT | SISO | |
| Pol. | Horizontal | Vertical |
| 14.47G |  |  |
| ~14.5G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p>  | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p>  |
| 17.7G | | |
| ~18G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p>  | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p>  |



| Mode | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-------------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|---|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | Band Edge - L | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2317.37</td><td>53.57</td><td>74.00</td><td>-20.43</td><td>43.01</td><td>27.20</td><td>6.73</td><td>33.38</td><td>10.01</td><td>170 133 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2317.37 | 53.57 | 74.00 | -20.43 | 43.01 | 27.20 | 6.73 | 33.38 | 10.01 | 170 133 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2437.00</td><td>109.61</td><td>-----</td><td>-----</td><td>98.44</td><td>27.60</td><td>6.85</td><td>33.31</td><td>10.03</td><td>170 133 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 109.61 | ----- | ----- | 98.44 | 27.60 | 6.85 | 33.31 | 10.03 | 170 133 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2317.37 | 53.57 | 74.00 | -20.43 | 43.01 | 27.20 | 6.73 | 33.38 | 10.01 | 170 133 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 109.61 | ----- | ----- | 98.44 | 27.60 | 6.85 | 33.31 | 10.03 | 170 133 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2389.88</td><td>43.21</td><td>54.00</td><td>-10.79</td><td>32.44</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>170 133 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.88 | 43.21 | 54.00 | -10.79 | 32.44 | 27.30 | 6.78 | 33.34 | 10.03 | 170 133 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2437.00</td><td>106.63</td><td>-----</td><td>-----</td><td>95.46</td><td>27.60</td><td>6.85</td><td>33.31</td><td>10.03</td><td>170 133 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 106.63 | ----- | ----- | 95.46 | 27.60 | 6.85 | 33.31 | 10.03 | 170 133 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.88 | 43.21 | 54.00 | -10.79 | 32.44 | 27.30 | 6.78 | 33.34 | 10.03 | 170 133 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 106.63 | ----- | ----- | 95.46 | 27.60 | 6.85 | 33.31 | 10.03 | 170 133 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |




| Mode | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------|--|-------------|--------|--------|--------|--------|--------|-------|-----------------|------|--------|------|-------|-------------|-------|--------|------|--------|--------|------|--------|---|-----|--------|--------|----|------|------|----|----|--------|---------|-------|-------|--------|-------|-------|------|-------|-------|-----------------|-------|
| | Band Edge - R | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>2483.87</td><td>56.14</td><td>74.00</td><td>-17.88</td><td>44.64</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>170 133 PEAK</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 2483.87 | 56.14 | 74.00 | -17.88 | 44.64 | 27.84 | 6.91 | 33.28 | 10.03 | 170 133 PEAK | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.87 | 56.14 | 74.00 | -17.88 | 44.64 | 27.84 | 6.91 | 33.28 | 10.03 | 170 133 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Avg. |  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>2483.56</td><td>45.29</td><td>54.00</td><td>-8.71</td><td>33.79</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>170 133 AVERAGE</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 2483.56 | 45.29 | 54.00 | -8.71 | 33.79 | 27.84 | 6.91 | 33.28 | 10.03 | 170 133 AVERAGE | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.56 | 45.29 | 54.00 | -8.71 | 33.79 | 27.84 | 6.91 | 33.28 | 10.03 | 170 133 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |









| Mode | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|-------------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|---|--|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | Band Edge - L | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak | <p>Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2372.99</td><td>53.89</td><td>74.00</td><td>-20.11</td><td>43.25</td><td>27.28</td><td>6.77</td><td>33.35</td><td>10.02</td><td>383 196 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2372.99 | 53.89 | 74.00 | -20.11 | 43.25 | 27.28 | 6.77 | 33.35 | 10.02 | 383 196 PEAK | <p>Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2437.00</td><td>105.03</td><td>-----</td><td>-----</td><td>93.87</td><td>27.60</td><td>6.84</td><td>33.31</td><td>10.03</td><td>383 196 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 105.03 | ----- | ----- | 93.87 | 27.60 | 6.84 | 33.31 | 10.03 | 383 196 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2372.99 | 53.89 | 74.00 | -20.11 | 43.25 | 27.28 | 6.77 | 33.35 | 10.02 | 383 196 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 105.03 | ----- | ----- | 93.87 | 27.60 | 6.84 | 33.31 | 10.03 | 383 196 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| <p>Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.88</td><td>42.05</td><td>54.00</td><td>-11.95</td><td>31.28</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>383 196 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.88 | 42.05 | 54.00 | -11.95 | 31.28 | 27.30 | 6.78 | 33.34 | 10.03 | 383 196 AVERAGE | <p>Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240828 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2437.00</td><td>101.90</td><td>-----</td><td>-----</td><td>90.73</td><td>27.60</td><td>6.85</td><td>33.31</td><td>10.03</td><td>383 196 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 101.90 | ----- | ----- | 90.73 | 27.60 | 6.85 | 33.31 | 10.03 | 383 196 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.88 | 42.05 | 54.00 | -11.95 | 31.28 | 27.30 | 6.78 | 33.34 | 10.03 | 383 196 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 101.90 | ----- | ----- | 90.73 | 27.60 | 6.85 | 33.31 | 10.03 | 383 196 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |







| Mode | 2 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------|---|-------------|--------|--------|--------|--------|--------|-------|-----------------------|------|--------|------|-------|-------------|-------|--------|------|--------|--------|------|--------|---|-----|--------|--------|----|------|------|----|----|--------|---|---------|-------|-------|--------|-------|-------|------|-------|-----------------------|-------|
| | Band Edge - R | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak | <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SFT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2486.33</td><td>54.51</td><td>74.00</td><td>-19.49</td><td>42.98</td><td>27.86</td><td>6.92</td><td>33.28</td><td>10.03 383 196 PEAK</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 1 | 2486.33 | 54.51 | 74.00 | -19.49 | 42.98 | 27.86 | 6.92 | 33.28 | 10.03 383 196 PEAK | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2486.33 | 54.51 | 74.00 | -19.49 | 42.98 | 27.86 | 6.92 | 33.28 | 10.03 383 196 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SFT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2483.56</td><td>42.90</td><td>54.00</td><td>-11.10</td><td>31.40</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03 383 196 AVERAGE</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 1 | 2483.56 | 42.90 | 54.00 | -11.10 | 31.40 | 27.84 | 6.91 | 33.28 | 10.03 383 196 AVERAGE | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2483.56 | 42.90 | 54.00 | -11.10 | 31.40 | 27.84 | 6.91 | 33.28 | 10.03 383 196 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |










| | | |
|--------|---|--|
| Mode | 2 | |
| | Harmonic | |
| | 2400-2483.5_802.11b_CH06_2437MHz | |
| ANT | SISO | |
| Pol. | Horizontal | Vertical |
| 14.47G |  |  |
| ~14.5G |  |  |
| Avg. | Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL | Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL |
| 17.7G |  |  |
| ~18G |  |  |
| Avg. | Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL | Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL |









| Mode | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|--|--------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|-------|--------|-------|-------|-------|-------|-----------------|--|--|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-------------|----------|
| | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH11_2462MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2483.51</td><td>58.16</td><td>74.00</td><td>-15.84</td><td>46.66</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>195 131 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2483.51 | 58.16 | 74.00 | -15.84 | 46.66 | 27.84 | 6.91 | 33.28 | 10.03 | 195 131 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2462.00</td><td>110.97</td><td>-----</td><td>99.75</td><td>27.60</td><td>6.88</td><td>33.29</td><td>10.03</td><td>195</td><td>131 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2462.00 | 110.97 | ----- | 99.75 | 27.60 | 6.88 | 33.29 | 10.03 | 195 | 131 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.51 | 58.16 | 74.00 | -15.84 | 46.66 | 27.84 | 6.91 | 33.28 | 10.03 | 195 131 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2462.00 | 110.97 | ----- | 99.75 | 27.60 | 6.88 | 33.29 | 10.03 | 195 | 131 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2483.55</td><td>46.11</td><td>54.00</td><td>-7.89</td><td>34.61</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>195 131 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2483.55 | 46.11 | 54.00 | -7.89 | 34.61 | 27.84 | 6.91 | 33.28 | 10.03 | 195 131 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2462.00</td><td>107.78</td><td>-----</td><td>96.56</td><td>27.60</td><td>6.88</td><td>33.29</td><td>10.03</td><td>195</td><td>131 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2462.00 | 107.78 | ----- | 96.56 | 27.60 | 6.88 | 33.29 | 10.03 | 195 | 131 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.55 | 46.11 | 54.00 | -7.89 | 34.61 | 27.84 | 6.91 | 33.28 | 10.03 | 195 131 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2462.00 | 107.78 | ----- | 96.56 | 27.60 | 6.88 | 33.29 | 10.03 | 195 | 131 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| Mode | 3 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|-------------|--------------|-------------|--------|--------|--------|-------|-------------|--------|--------|-------|-------------|--------------|--------------|-------------|--------|--|--|--|-----|--------|--------|--------|------|------|------|----|----|-----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-------|--|--|--|--|--|--|--|-----|-------------|---|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|-------|-------------|--------------|--------------|-------------|--------|--|--|--|-----|--------|--------|--------|------|------|------|----|----|-----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-------|--|--|--|--|--|--|--|-----|-------------|----------|
| | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11b_CH11_2462MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 9120D_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2483.70</td><td>54.78</td><td>74.00</td><td>-19.22</td><td>43.28</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td></tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>377</td><td>194 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 1 | 2483.70 | 54.78 | 74.00 | -19.22 | 43.28 | 27.84 | 6.91 | 33.28 | 10.03 | | | | | | | | | 377 | 194 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 9120D_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2462.00</td><td>104.89</td><td>-----</td><td>-----</td><td>93.67</td><td>27.60</td><td>6.88</td><td>33.29</td><td>10.03</td></tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>377</td><td>194 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 1 | 2462.00 | 104.89 | ----- | ----- | 93.67 | 27.60 | 6.88 | 33.29 | 10.03 | | | | | | | | | 377 | 194 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2483.70 | 54.78 | 74.00 | -19.22 | 43.28 | 27.84 | 6.91 | 33.28 | 10.03 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 377 | 194 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2462.00 | 104.89 | ----- | ----- | 93.67 | 27.60 | 6.88 | 33.29 | 10.03 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 377 | 194 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 9120D_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2483.51</td><td>43.68</td><td>54.00</td><td>-10.32</td><td>32.18</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td></tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>377</td><td>194 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 1 | 2483.51 | 43.68 | 54.00 | -10.32 | 32.18 | 27.84 | 6.91 | 33.28 | 10.03 | | | | | | | | | 377 | 194 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 9120D_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>Freq</th><th>Level</th><th>Line Margin</th><th>Level Factor</th><th>Loss Factor</th><th>Factor</th><th></th><th></th><th></th><th></th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>1</td><td>2462.00</td><td>101.27</td><td>-----</td><td>-----</td><td>90.05</td><td>27.60</td><td>6.88</td><td>33.29</td><td>10.03</td></tr> <tr> <td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td>377</td><td>194 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 1 | 2462.00 | 101.27 | ----- | ----- | 90.05 | 27.60 | 6.88 | 33.29 | 10.03 | | | | | | | | | 377 | 194 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2483.51 | 43.68 | 54.00 | -10.32 | 32.18 | 27.84 | 6.91 | 33.28 | 10.03 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 377 | 194 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level Factor | Loss Factor | Factor | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2462.00 | 101.27 | ----- | ----- | 90.05 | 27.60 | 6.88 | 33.29 | 10.03 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | | | | | | | | 377 | 194 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |













| | | |
|--------|--|---|
| Mode | 3 | |
| | Harmonic | |
| | 2400-2483.5_802.11b_CH11_2462MHz | |
| ANT | SISO | |
| Pol. | Horizontal | Vertical |
| 14.47G |  |  |
| ~14.5G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p>  | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p>  |
| 17.7G | | |
| ~18G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p>  | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p>  |




4





| Mode | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------|---|--------|--------|-------|--------|------|-------|--------|-----------------|------|------|--------|-----|--------|--------|----|------|------|----|----|----|-----|---------|--------|-------|--------|-------|-------|------|-------|-------|-----------------|
| | 2400-2483.5_802.11g_CH01_2412MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | Horizontal | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal  Site : 03CH11-HY Condition: PEAK_8E_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SW:Auto <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.95</td><td>59.67</td><td>74.00</td><td>-14.33</td><td>48.90</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>228 126 PEAK</td></tr> </tbody> </table> | | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.95 | 59.67 | 74.00 | -14.33 | 48.90 | 27.30 | 6.78 | 33.34 | 10.03 | 228 126 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.95 | 59.67 | 74.00 | -14.33 | 48.90 | 27.30 | 6.78 | 33.34 | 10.03 | 228 126 PEAK | | | | | | | | | | | | | | | | | | | | | | | |
| Peak | Fundamental  Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SW:Auto <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2412.00</td><td>108.86</td><td>-----</td><td>-----</td><td>97.88</td><td>27.46</td><td>6.81</td><td>33.32</td><td>10.03</td><td>228 126 PEAK</td></tr> </tbody> </table> | | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 108.86 | ----- | ----- | 97.88 | 27.46 | 6.81 | 33.32 | 10.03 | 228 126 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 108.86 | ----- | ----- | 97.88 | 27.46 | 6.81 | 33.32 | 10.03 | 228 126 PEAK | | | | | | | | | | | | | | | | | | | | | | | |
| Avg. |  Site : 03CH11-HY Condition: AVG_8E_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SW:Auto <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.95</td><td>46.27</td><td>54.00</td><td>-7.73</td><td>35.50</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>228 126 AVERAGE</td></tr> </tbody> </table> | | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.95 | 46.27 | 54.00 | -7.73 | 35.50 | 27.30 | 6.78 | 33.34 | 10.03 | 228 126 AVERAGE |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.95 | 46.27 | 54.00 | -7.73 | 35.50 | 27.30 | 6.78 | 33.34 | 10.03 | 228 126 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | |
| |  Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SW:Auto <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2412.00</td><td>101.77</td><td>-----</td><td>-----</td><td>99.76</td><td>27.48</td><td>6.82</td><td>33.32</td><td>10.03</td><td>228 126 AVERAGE</td></tr> </tbody> </table> | | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 101.77 | ----- | ----- | 99.76 | 27.48 | 6.82 | 33.32 | 10.03 | 228 126 AVERAGE |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 101.77 | ----- | ----- | 99.76 | 27.48 | 6.82 | 33.32 | 10.03 | 228 126 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | |







| Mode | Band Edge | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|--------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|--|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | 2400-2483.5_802.11g_CH01_2412MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | Vertical | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2389.95</td><td>56.46</td><td>74.00</td><td>-17.54</td><td>45.69</td><td>27.38</td><td>6.78</td><td>33.34</td><td>10.03</td><td>400 190 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.95 | 56.46 | 74.00 | -17.54 | 45.69 | 27.38 | 6.78 | 33.34 | 10.03 | 400 190 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2412.00</td><td>103.92</td><td>-----</td><td>-----</td><td>92.94</td><td>27.46</td><td>6.81</td><td>33.32</td><td>10.03</td><td>400 190 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 103.92 | ----- | ----- | 92.94 | 27.46 | 6.81 | 33.32 | 10.03 | 400 190 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.95 | 56.46 | 74.00 | -17.54 | 45.69 | 27.38 | 6.78 | 33.34 | 10.03 | 400 190 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 103.92 | ----- | ----- | 92.94 | 27.46 | 6.81 | 33.32 | 10.03 | 400 190 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2389.95</td><td>43.76</td><td>54.00</td><td>-10.24</td><td>32.99</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>400 190 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.95 | 43.76 | 54.00 | -10.24 | 32.99 | 27.30 | 6.78 | 33.34 | 10.03 | 400 190 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2412.00</td><td>96.55</td><td>-----</td><td>-----</td><td>85.57</td><td>27.46</td><td>6.81</td><td>33.32</td><td>10.03</td><td>400 190 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2412.00 | 96.55 | ----- | ----- | 85.57 | 27.46 | 6.81 | 33.32 | 10.03 | 400 190 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.95 | 43.76 | 54.00 | -10.24 | 32.99 | 27.30 | 6.78 | 33.34 | 10.03 | 400 190 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2412.00 | 96.55 | ----- | ----- | 85.57 | 27.46 | 6.81 | 33.32 | 10.03 | 400 190 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |







| | | |
|--------|---|--|
| Mode | 4 | |
| | Harmonic | |
| | 2400-2483.5_802.11g_CH01_2412MHz | |
| ANT | SISO | |
| Pol. | Horizontal | Vertical |
| 14.47G |  |  |
| ~14.5G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p> | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p> |
| 17.7G |  |  |
| ~18G | | |
| Avg. | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL</p> | <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 VERTICAL</p> |







| Mode | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---|---|-------------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|--|---|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | Band Edge - L | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11g_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2378.33</td><td>53.05</td><td>74.00</td><td>-20.95</td><td>42.41</td><td>27.28</td><td>6.77</td><td>33.35</td><td>10.02</td><td>100 118 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2378.33 | 53.05 | 74.00 | -20.95 | 42.41 | 27.28 | 6.77 | 33.35 | 10.02 | 100 118 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2437.00</td><td>106.00</td><td>-----</td><td>-----</td><td>95.62</td><td>27.60</td><td>6.85</td><td>33.30</td><td>10.03</td><td>100 118 PEAK</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 106.00 | ----- | ----- | 95.62 | 27.60 | 6.85 | 33.30 | 10.03 | 100 118 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2378.33 | 53.05 | 74.00 | -20.95 | 42.41 | 27.28 | 6.77 | 33.35 | 10.02 | 100 118 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 106.00 | ----- | ----- | 95.62 | 27.60 | 6.85 | 33.30 | 10.03 | 100 118 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2389.76</td><td>41.99</td><td>54.00</td><td>-12.01</td><td>31.22</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>100 118 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.76 | 41.99 | 54.00 | -12.01 | 31.22 | 27.30 | 6.78 | 33.34 | 10.03 | 100 118 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th> </tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th> </tr> </thead> <tbody> <tr> <td>2437.00</td><td>98.45</td><td>-----</td><td>-----</td><td>87.27</td><td>27.60</td><td>6.85</td><td>33.30</td><td>10.03</td><td>100 118 AVERAGE</td> </tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 98.45 | ----- | ----- | 87.27 | 27.60 | 6.85 | 33.30 | 10.03 | 100 118 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.76 | 41.99 | 54.00 | -12.01 | 31.22 | 27.30 | 6.78 | 33.34 | 10.03 | 100 118 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 98.45 | ----- | ----- | 87.27 | 27.60 | 6.85 | 33.30 | 10.03 | 100 118 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |





| Mode | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|------|--|-------------|--------|--------|--------|--------|--------|-------|-------------------|------|--------|------|-------|-------------|-------|--------|------|--------|--------|------|--------|---|-----|--------|--------|----|------|------|----|----|--------|---|---------|-------|-------|--------|-------|-------|------|-------|-------------------|-------|
| | Band Edge - R | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11g_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Horizontal | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2486.77</td><td>54.74</td><td>74.00</td><td>-19.26</td><td>43.20</td><td>27.87</td><td>6.92</td><td>33.28</td><td>10.03 118 PEAK</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 1 | 2486.77 | 54.74 | 74.00 | -19.26 | 43.20 | 27.87 | 6.92 | 33.28 | 10.03 118 PEAK | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2486.77 | 54.74 | 74.00 | -19.26 | 43.20 | 27.87 | 6.92 | 33.28 | 10.03 118 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Avg. |  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240828 HORIZONTAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>1</td><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>1</td><td>2483.68</td><td>43.14</td><td>54.00</td><td>-10.86</td><td>31.64</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03 118 AVERAGE</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | 1 | 2483.68 | 43.14 | 54.00 | -10.86 | 31.64 | 27.84 | 6.91 | 33.28 | 10.03 118 AVERAGE | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 1 | 2483.68 | 43.14 | 54.00 | -10.86 | 31.64 | 27.84 | 6.91 | 33.28 | 10.03 118 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| Mode | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|--|--|-------------|--------|-------|--------|--------|--------|-------|-----------------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|-------|--------|--------|-------|-------|-------|-------|-----------------|---|--|-------|-------|------|-------|--------|--------|------|------|--------|--------|--------|--------|--------|------|------|------|----|----|-----|---------|---------|--------|-------|-------|-------|-------|-------|-------|-----------------|--------------|
| | Band Edge - L | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11g_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2388.36</td><td>53.33</td><td>74.00</td><td>-20.67</td><td>42.58</td><td>27.28</td><td>6.78</td><td>33.34</td><td>10.03</td><td>300 209 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2388.36 | 53.33 | 74.00 | -20.67 | 42.58 | 27.28 | 6.78 | 33.34 | 10.03 | 300 209 PEAK |  <p>Site : 03CH11-HY Condition: PEAK_74 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2437.00</td><td>101.37</td><td>-----</td><td>-----</td><td>90.19</td><td>27.60</td><td>6.85</td><td>33.30</td><td>10.03</td><td>300 209 PEAK</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 101.37 | ----- | ----- | 90.19 | 27.60 | 6.85 | 33.30 | 10.03 | 300 209 PEAK |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2388.36 | 53.33 | 74.00 | -20.67 | 42.58 | 27.28 | 6.78 | 33.34 | 10.03 | 300 209 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 101.37 | ----- | ----- | 90.19 | 27.60 | 6.85 | 33.30 | 10.03 | 300 209 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2389.88</td><td>41.70</td><td>54.00</td><td>-12.30</td><td>30.93</td><td>27.30</td><td>6.78</td><td>33.34</td><td>10.03</td><td>300 209 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2389.88 | 41.70 | 54.00 | -12.30 | 30.93 | 27.30 | 6.78 | 33.34 | 10.03 | 300 209 AVERAGE |  <p>Site : 03CH11-HY Condition: AVG_54 3m 91200_01620_240028 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SWT:Auto</p> <table border="1"> <thead> <tr> <th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr> <tr> <th>MHz</th><th>dBuV/m</th><th>dBuV/m</th><th>dB</th><th>dBuV</th><th>dB/m</th><th>dB</th><th>dB</th><th>cm</th><th>deg</th></tr> </thead> <tbody> <tr> <td>2437.00</td><td>93.96</td><td>-----</td><td>-----</td><td>82.79</td><td>27.60</td><td>6.85</td><td>33.31</td><td>10.03</td><td>300 209 AVERAGE</td></tr> </tbody> </table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | 2437.00 | 93.96 | ----- | ----- | 82.79 | 27.60 | 6.85 | 33.31 | 10.03 | 300 209 AVERAGE | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2389.88 | 41.70 | 54.00 | -12.30 | 30.93 | 27.30 | 6.78 | 33.34 | 10.03 | 300 209 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | cm | deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2437.00 | 93.96 | ----- | ----- | 82.79 | 27.60 | 6.85 | 33.31 | 10.03 | 300 209 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |



| Mode | 5 | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
|---------|---|-------------|--------|--------|--------|--------|--------|-------|-----------------|------|--------|------|-------|-------------|-------|--------|------|--------|--------|------|--------|-----|--------|--------|----|------|------|----|----|----|--------|---------|-------|-------|--------|-------|-------|------|-------|-------|-----------------|-------|
| | Band Edge - R | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| | 2400-2483.5_802.11g_CH06_2437MHz | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| ANT | SISO | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Pol. | Vertical | Fundamental | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Peak |  <p>Site : 03CH11-HY Condition: PEAK_BE_74 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:3000.000kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>2483.87</td><td>53.94</td><td>74.00</td><td>-20.06</td><td>42.44</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>300 209 PEAK</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | dB | cm deg | 2483.87 | 53.94 | 74.00 | -20.06 | 42.44 | 27.84 | 6.91 | 33.28 | 10.03 | 300 209 PEAK | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.87 | 53.94 | 74.00 | -20.06 | 42.44 | 27.84 | 6.91 | 33.28 | 10.03 | 300 209 PEAK | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Avg. |  <p>Site : 03CH11-HY Condition: AVG_BE_54 3m 91200_01620_240828 VERTICAL : RBW:1000.000kHz VBW:0.010kHz SMT:Auto</p> <table><thead><tr><th>Freq</th><th>Limit</th><th>Read</th><th>Ant</th><th>Cable</th><th>Preamp</th><th>Aux</th><th>APos</th><th>TPos</th><th>Remark</th></tr><tr><th>Freq</th><th>Level</th><th>Line Margin</th><th>Level</th><th>Factor</th><th>Loss</th><th>Factor</th><th>Factor</th><th>TPos</th><th>Remark</th></tr></thead><tbody><tr><td>MHz</td><td>dBuV/m</td><td>dBuV/m</td><td>dB</td><td>dBuV</td><td>dB/m</td><td>dB</td><td>dB</td><td>dB</td><td>cm deg</td></tr><tr><td>2483.87</td><td>42.52</td><td>54.00</td><td>-11.48</td><td>31.02</td><td>27.84</td><td>6.91</td><td>33.28</td><td>10.03</td><td>300 209 AVERAGE</td></tr></tbody></table> | Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | dB | cm deg | 2483.87 | 42.52 | 54.00 | -11.48 | 31.02 | 27.84 | 6.91 | 33.28 | 10.03 | 300 209 AVERAGE | Blank |
| Freq | Limit | Read | Ant | Cable | Preamp | Aux | APos | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| Freq | Level | Line Margin | Level | Factor | Loss | Factor | Factor | TPos | Remark | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| MHz | dBuV/m | dBuV/m | dB | dBuV | dB/m | dB | dB | dB | cm deg | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |
| 2483.87 | 42.52 | 54.00 | -11.48 | 31.02 | 27.84 | 6.91 | 33.28 | 10.03 | 300 209 AVERAGE | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | | |