

RF Exposure Report

Report No.: SA191119C05

FCC ID: LHJ-STRLNK2P

Test Model: StrLnk2P

Received Date: Nov. 19, 2019

Date of Evaluation: Dec. 09, 2019

Issued Date: Dec. 26, 2019

Applicant: Continental Automotive Systems, Inc.

Address: 21440 West Lake Cook Road Deer Park, IL 60010 United States

Issued By: Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch
Lin Kou Laboratories

Lab Address: No. 47-2, 14th Ling, Chia Pau Vil., Lin Kou Dist., New Taipei City, Taiwan

Test Location: No. 19, Hwa Ya 2nd Rd., Wen Hwa Vil., Kwei Shan Dist., Taoyuan City
33383, TAIWAN

FCC Registration /
Designation Number: 788550 / TW0003



This report is for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence, provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents. Unless specific mention, the uncertainty of measurement has been explicitly taken into account to declare the compliance or non-compliance to the specification. The report must not be used by the client to claim product certification, approval, or endorsement by TAF or any government agencies.

Table of Contents

Release Control Record	3
1 Certificate of Conformity	4
2 RF Exposure	5
2.1 Limits for Maximum Permissible Exposure (MPE)	5
2.2 MPE Calculation Formula	5
2.3 Classification	5
2.4 Calculation Result of Maximum Conducted Power	6

Release Control Record

Issue No.	Description	Date Issued
SA191119C05	Original Release	Dec. 26, 2019

1 Certificate of Conformity

Product: TCU (Telematics Control Unit)

Brand: Continental

Test Model: StrLnk2P

Sample Status: Identical Prototype

Applicant: Continental Automotive Systems, Inc.

Date of Evaluation: Dec. 09, 2019

Standards: FCC Part 2 (Section 2.1091)

References Test Guidance : KDB 447498 D01 General RF Exposure Guidance v06
IEEE C95.3 -2002

The above equipment has been tested by **Bureau Veritas Consumer Products Services (H.K.) Ltd., Taoyuan Branch**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's RF characteristics under the conditions specified in this report.



Prepared by : _____, **Date:** _____
Lena Wang / Specialist



Approved by : _____, **Date:** _____
Dylan Chiou / Project Engineer

2 RF Exposure

2.1 Limits for Maximum Permissible Exposure (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (minutes)
Limits For General Population / Uncontrolled Exposure				
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f ²)*	30
30-300	27.5	0.073	0.2	30
300-1500	...	...	f/1500	30
1500-100,000	...	...	1.0	30

f = Frequency in MHz ; *Plane-wave equivalent power density

2.2 MPE Calculation Formula

$$P_d = (P_{out} \cdot G) / (4 \cdot \pi \cdot r^2)$$

where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

r = distance between observation point and center of the radiator in cm

2.3 Classification

The antenna of this product, under normal use condition, is at least 25cm away from the body of the user.
So, this device is classified as **Mobile Device**.

2.4 Calculation Result of Maximum Conducted Power

Band	Frequency Band (MHz)	Output Power ERP / EIRP (dBm)	Output Power ERP / EIRP (mW)	Distance (cm)	Power Density (mW/cm ²)	Limit (mW/cm ²)
GSM850	824-849	27.78	599.791	25	0.076	0.55
PCS1900	1850-1910	31.51	1415.794	25	0.180	1.00
WCDMA II	1850-1910	24.05	254.097	25	0.032	1.00
WCDMA IV	1710-1755	24.34	271.644	25	0.035	1.00
WCDMA V	824-849	22.48	177.011	25	0.023	0.55
LTE 2	1850-1910	25.41	347.536	25	0.024	1.00
LTE 4	1710-1755	25.40	346.737	25	0.044	1.00
LTE 5	824-849	23.41	219.280	25	0.028	0.55
LTE 7	2500-2570	25.45	350.752	25	0.045	1.00
LTE 12	699-716	23.71	234.963	25	0.030	0.47
WLAN	2412-2462	26.56	452.898	25	0.058	1.00
	5180-5240	17.15	51.88	25	0.007	1.00
	5745-5825	18.39	69.024	25	0.009	1.00

Note:

1. Determining compliance based on the results of the compliance measurement, not taking into account measurement instrumentation uncertainty.

Conclusion:

The formula of calculated the MPE is:

$$CPD1 / LPD1 + CPD2 / LPD2 + \dots \text{etc.} < 1$$

CPD = Calculation power density

LPD = Limit of power density

$$WWAN + WLAN 2.4GHz = 0.180 / 1 + 0.58/1 = 0.76$$

$$WWAN + WLAN 5GHz = 0.180 / 1 + 0.009/1 = 0.189$$

Therefore the maximum calculations of above situations are less than the “1” limit.

--- END ---