
## **RF Exposure**

# **Test Setup Configuration**



#### Note

- The RF exposure test is performed in the shield room.The test distance is between the edge of the charger and the geometric centre of probe.

## **Test Equipment List**

Name of instrument	Model	Manufacturer	Cal. Date	<b>Due Date</b>
MAGNETIC FIELD HITESTER	3470	Hioki	25-Jun-11	25-Jun-13

Test Date: 29 September, 2012

#### **Reference Limit:**

# Environmental evaluation and exposure limit according to FCC CFR 47 part 1, 1.1307(c) and (d), 1.1310

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric field strength (V/m)	Magnetic Field Strength (A/m)	Power Density	Average Time (minutes)		
(A) Limits for Occupational/Controlled Exposure						
0.3 – 3.0	614	1.63	(100)*	6		
(B) Limits for General Population/Uncontrolled Exposure						
0.3 – 1.34	614	1.63	(100)*	30		

Note: \* = Plane wave equivalent power density

**Test Mode:** Normal Operation (Transmit with Charging Mode)

**Test Result:** 

#### H-Field Strength at 10 cm from the edges surrounding the EUT

Frequency Range (MHz)	Probe Position A (A/m)	Probe Position B (A/m)	Probe Position C (A/m)	Probe Position D (A/m)	Limits (A/m)
0.115 ~ 0.205	0.010	0.008	0.009	0.018	1.63

#### E-Field Strength (calculated) at 10 cm from the edges surrounding the EUT

Frequency Range (MHz)	Probe Position A (V/m)	Probe Position B (V/m)	Probe Position C (V/m)	Probe Position D (V/m)	Limits (V/m)
0.115 ~ 0.205	3.77	3.016	3.393	6.786	614

Note:

The maximum E-field Strength at 3m is 70.7dBuv/m, According to FCC KDB 412172 D01:

The EIRP =  $(FS*D)^2 / 30 = -24.5 dBm$