

FCC Part 15C Compliance Test Report

Test Report no.:	FCC15C_RM-696_14.docx	Date of Report:	18-Jul-2011
Number of pages:	20	Customer's Contact person:	Timo Peltola
Testing laboratory:	TCC Nokia Tampere Laboratory P.O. Box 68 Sinitaival 5 FIN-33720 TAMPERE, FINLAND Tel. +358 (0) 7180 46800 Fax. +358 (0) 7180 46880	Customer:	Nokia Corporation P.O. Box 50 Elektroniikkatie 10 FIN-90571 OULU, FINLAND Tel. +358 (0) 7180 08000 Fax. +358 (0) 7180 47222
FCC listing no.:	94436		
IC recognition no.:	661AK-1		
Tested devices/ accessories:	Phone RM-696 / Battery BV-5JW, AC charger AC-16E, Data cable CA-185CD, Headset WH-901		
FCC ID:	LJPK	IC:	-
Supplement reports:	-		
Testing has been carried out in accordance with:	CFR 47, FCC rules Part 15 Subpart C, ANSI C63.4 (2003), Public Notice DA 00-705, DTS procedures KDB 558074, IC standards RSS-GEN (Issue 3, December 2010) and RSS-210 (Issue 8, December 2010). Deviations, modifications or clarifications (if any) to above mentioned documents are written in each section under "Test method and limit".		
Documentation:	The test report must always be reproduced in full; reproduction of an excerpt only is subject to written approval of the testing laboratory. The documentation of the testing performed on the tested devices is archived for 15 years at TCC Nokia.		
Test Results:	The EUT complies with the requirements in respect of all parameters subject to the test. The test results relate only to devices specified in this document.		
Date and signature for the contents:			

Kalle Hannila, Engineer , EMC

1. Summary for FCC Part 15C Compliance Test Report

Date of receipt	27-May-2011
Testing completed	14-Jun-2011
The customer's contact person	Timo Peltola
Test Plan referred to	T:\Projects\RM-696\TestPlan\RS_testplan_RM-696.xls
Notes	-
Document name	FCC15C_RM-696_14.docx

1.1. EUT and Accessory Information

The EUT is a 9-band (GSM850/900/1800/1900 and WCDMA Band I/II(1900)/IV(1700)/V(850)/VIII) mobile phone with GPRS, EGPRS, Bluetooth and WLAN. Bluetooth and WLAN are tested with maximum rated TX power.

Product	Type	SN	HW	MV	SW	DUT
Phone	RM-696	004402135480402	1501	-	V 0.2011.21-5 TA_RM680	42578
Phone	RM-696	004402135480758	1501	-	V 0.2011.21-5 TA_RM680	42570
Battery	BV-5JW	-	00-04A	-	-	-
AC charger	AC-16E	4090491166580400077;0675491	0.31	0.3	-	42572
Data cable	CA-185CD	-	-	-	-	42575
Headset	WH-901	-	3.2	4.0	-	42576

1.2. Summary of Test Results

WLAN:

Section in CFR 47	Section in RSS-GEN or RSS-210	Name of the test	Result
15.247(b)(1)	A8.4 (4)	Conducted peak output power	PASSED
15.247(d)	A8.5	Band edge compliance of RF emissions	NP
15.247(d)	A8.5	Spurious RF conducted emissions	PASSED
15.247(d), 15.209	A8.5	Spurious radiated emissions	NP
15.207	7.2.2	AC powerline conducted emissions	PASSED
15.247(a)(2)	A8.2 (a)	6 dB bandwidth	PASSED
15.247(e)	A8.2 (b)	Power spectral density	PASSED

PASSED

FAILED

NP

The EUT complies with the essential requirements in the standard.

The EUT does not comply with the essential requirements in the standard.


The test was not performed by the TCC Nokia Tampere Laboratory.

CONTENTS


1. Summary for FCC Part 15C Compliance Test Report	2
1.1. EUT and Accessory Information	2
1.2. Summary of Test Results	2
2. Test setups	4
2.1. Conducted RF test setup	4
2.2. Conducted RF test setup for spurious conducted emissions	4
2.3. AC powerline conducted emissions test setup	4
2.4. Radiated test setup	5
4. Conducted peak output power (FCC §15.247(b)(1)), RSS-210 A8.4 (4)	6
4.1. Test method and limit	6
4.2. WLAN Test results	7
5. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5).....	9
5.1. Test method and limit	9
5.2. WLAN Test results	10
6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2).....	11
6.1. Test method and limit	11
6.2. WLAN Test results	12
7. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (a)).....	13
7.1. Test method and limit	13
7.2. WLAN test results	14
8. Power spectral density (FCC §15.247(e)), RSS-210 A8.2 (b))	16
8.1. Test method and limit	16
8.2. WLAN test results	17
9. Test Equipment	19
9.1. Conducted measurements	19
9.2. Radiated measurements	19

2. Test setups


2.1. Conducted RF test setup




2.2. Conducted RF test setup for spurious conducted emissions



2.3. AC powerline conducted emissions test setup



2.4. Radiated test setup



4. Conducted peak output power (FCC §15.247(b)(1)), RSS-210 A8.4 (4)

EUT with DUT number	RM-696 DUT 42578
Accessories with DUT numbers	BV-5JW DUT-
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 58 / 99.8
Date of measurements	30-May-2011
Measured by	Jari Jantunen

4.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for conducted peak output power measurements


Frequency range [MHz]	Limit [W]	Limit [dBm]
5725 – 5850	≤ 1	≤ 30

4.2. WLAN Test results

4.2.1 OFDM mode, BPSK modulation, n-6.5 Mbps data rate

Channel / f_c [MHz]	P [dBm]	P [W]	Result
165 / 5825	21.83	0.152	PASSED

Channel 165 / 5825 MHz




Date: 30.MAY.2011 11:05:14

4.2.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f_c [MHz]	P [dBm]	P [W]	Result
165 / 5825	22.05	0.160	PASSED

Channel 165 / 5825 MHz



Date: 30.MAY.2011 11:09:42

5. Spurious RF conducted emissions (FCC §15.247(d), RSS-210 A8.5)

EUT with DUT number	RM-696 DUT 42578
Accessories with DUT numbers	BV-5JW DUT-
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 58 / 99.8
Date of measurements	30-May-2011
Measured by	Jari Jantunen

5.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.


Limits for spurious RF conducted emissions measurements

Frequency range [MHz]	Limit [dBc]
1 – 40000	≤ -20

5.2. WLAN Test results

5.2.1 OFDM mode, BPSK modulation, n-6.5 Mbps data rate

Channel 165 / 5825 MHz




Date: 30.MAY.2011 14:48:17

Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
28435.571	32.69	PASSED
32200.281	32.10	PASSED
32921.182	30.64	PASSED

5.2.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel 165 / 5825 MHz



Date: 30.MAY.2011 14:44:00

Peak (RBW: 100 kHz, VBW: 100 kHz)

Frequency [MHz]	P [dBc]	Result
28035.070	33.26	PASSED
32120.180	31.38	PASSED
33001.283	30.25	PASSED

6. AC powerline conducted emissions (FCC §15.207, RSS-GEN 7.2.2)

EUT with DUT number	RM-696 DUT 42570
Accessories with DUT numbers	BV-5JW DUT- , AC-16E DUT 42572, CA-185CD DUT 42575, WH-901 DUT 42576
Operation Voltage [V] / [Hz]	115 / 60
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	20 / 50 / 98.8
Date of measurements	14-Jun-2011
Measured by	Jari Jantunen

6.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-GEN as follows:

The EUT is placed on a wooden table 80 cm above the reference groundplane.

The EUT is connected via LISN to a test power supply.

The measurement results are obtained as described below:

$$U [dB\mu V] = U_{RX} + A_{TOT}$$

Where U_{RX} is receiver reading and A_{TOT} is total correction factor including cable and pulse limiter attenuations.


CISPR 22 Class B limits

Frequency range [MHz]	Quasi peak limit [dBμV]	Average limit [dBμV]
0.15 - 0.5	66 - 56	56 - 46
0.5 - 5	56	46
5 - 30	60	50

6.2. WLAN Test results

6.2.1 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel 165 / 5825 MHz



Quasi peak

Frequency [MHz]	Level [dBμV]	IF-BW[kHz]	Line	Margin	Result
0.235	43.16	10	N	19.07	PASSED
0.5	36.19	10	L1	19.8	PASSED
0.99	32.82	10	L1	23.2	PASSED
1.09	33	10	L1	23	PASSED
1.375	32.92	10	L1	23.1	PASSED
1.48	33.83	10	L1	22.2	PASSED

Average

Frequency [MHz]	Level [dBμV]	IF-BW[kHz]	Line	Margin	Result
0.195	38.23	10	N	15.62	PASSED
0.225	37.35	10	N	15.23	PASSED
0.25	36.34	10	N	15.46	PASSED
0.515	30.79	10	N	15.2	PASSED
2.625	32.45	10	L1	13.6	PASSED
15.89	37.12	10	L1	12.9	PASSED

7. 6 dB bandwidth (FCC §15.247(a)(2), RSS-210 A8.2 (a))

EUT with DUT number	RM-696 DUT 42578
Accessories with DUT numbers	BV-5JW DUT-
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 58 / 99.8
Date of measurements	30-May-2011
Measured by	Jari Jantunen

7.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for 6 dB bandwidth measurements


Limit [kHz]
≥ 500

7.2. WLAN test results

7.2.1 OFDM mode, BPSK modulation, n-6.5 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
165 / 5825	17388	PASSED

Channel 165 / 5825 MHz




Date: 30.MAY.2011 11:24:47

7.2.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f _c [MHz]	6 dB bandwidth [kHz]	Result
165 / 5825	16186	PASSED

Channel 165 / 5825 MHz



Date: 30.MAY.2011 11:22:47

8. Power spectral density (FCC §15.247(e)), RSS-210 A8.2 (b))

EUT with DUT number	RM-696 DUT 42578
Accessories with DUT numbers	BV-5JW DUT-
Operation Voltage [V] / [Hz]	Nominal
Result	PASSED
Remarks	-
Temp [°C] / Humidity [%RH] / Air Pressure [kPa]	22 / 58 / 99.8
Date of measurements	30-May-2011
Measured by	Jari Jantunen

8.1. Test method and limit

The measurement is made according to DTS procedures KDB 558074 and IC standard RSS-210.

Limits for power spectral density measurements


Limit [dBm] @ 3 kHz
≤ 8

8.2. WLAN test results

8.2.1 OFDM mode, BPSK modulation, n-6.5 Mbps data rate

Channel / f _c [MHz]	P [dBm]	Result
165 / 5825	-7.83	PASSED

Channel 165 / 5825 MHz




Date: 30.MAY.2011 11:43:56

8.2.2 OFDM mode, BPSK modulation, 6 Mbps data rate

Channel / f _c [MHz]	P [dBm]	Result
165/ 5825	-8.16	PASSED

Channel 165 / 5825 MHz



Date: 30.MAY.2011 11:56:35

9. Test Equipment

9.1. Conducted measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38112	Power supply	6632A	Agilent	22/24/27, 15C
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
OM0631 2	Signal Generator	E4422B	Agilent	22/24
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM30600	Impulse limiter	ESH3-Z2	R&S	15C, 15B
TM26490	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM26491	LISN 50 µH	ESH3-Z5	R&S	15C, 15B
TM37610	Spectrum Analyzer	FSU26	R&S	22/24/27, 15C
-	Test Receiver	ESI40	R&S	15C
TM22806	Battery	BAT 20/E	Fiskars	15C, 15B
TM22805	UPS	PS 20/1.2	Fiskars	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
-	Temperature test chamber	VT 4002	Vötsch	22/24
2058	Receiver	ESPC	R&S	15C, 15B
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
2002	Communication Tester	CMU200	R&S	22/24/27
2009	LISN 50 µH	ENV216	R&S	15C, 15B
2010	LISN 50 µH	ENV216	R&S	15C, 15B
2012	Power splitter	11667B	Agilent	22/24/27, 15C
2013	Attenuator	8493C	Agilent	22/24/27, 15C
2014	Attenuator	8493C	Agilent	22/24/27, 15C

9.2. Radiated measurements

Eq. No	Equipment	Type	Manufacturer	Used in
TM38114	Power supply	6632A	Agilent	22/24/27, 15C, 15B
TM38631	Signal Generator	83640L	Agilent	22/24/27, 15C, 15B
TM38323	Preamplifier	PA-02 18-26 GHz	EMC Automation	22/24/27, 15C, 15B
-	Antenna	BBHA 9120 D	Schwarzbeck	22/24/27, 15C
TM26497	Antenna	3115	Emco	22/24/27, 15C, 15B
TM37678	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM37773	Communication Tester	CMU200	R&S	22/24/27, 15C, 15B
TM38845	Receiver	ESIB 26	R&S	22/24/27, 15C, 15B
-	Antenna	HL562	R&S	22/24/27, 15C, 15B
TM26500	Turntable	DS412	Deisel	22/24/27, 15C, 15B
TM30642	Mast/turntable controller	HD-100	Deisel	22/24/27, 15C, 15B
TM38990	Remote switching module	RSM1	EMC Automation	22/24/27, 15C, 15B
TM38341	System interface	SI-300	EMC Automation	22/24/27, 15C, 15B
-	Mini mast	2075-2	ETS Lindgren	22/24/27, 15C, 15B
TM38843	Mini mast	2075	Emco	22/24/27, 15C, 15B
TM38842	Controller	2090	Emco	22/24/27, 15C, 15B
TM39158	Antenna	3116	Emco	22/24/27, 15C, 15B
TM30643	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
TM30644	LISN 50 µH	LISN-5-20-2	FCC	22/24/27, 15C, 15B
-	Temperature and humidity logger	175-H2	Testo	22/24/27, 15C, 15B

Eq. No	Equipment	Type	Manufacturer	Used in
-	Air pressure and temperature logger	635-2	Testo	22/24/27, 15C, 15B
-	Air pressure sensor	0638-1835	Testo	22/24/27, 15C, 15B
TM39180	Laser distance meter	Disto Pro	Leica	22/24/27, 15C, 15B
TM37523	Preamplifier	AMF-4D-10M-3G-25-20P	Miteq	22/24/27, 15C, 15B
-	Preamplifier	AFS4-00100300-20-23P6	Miteq	15C
TM37498	Preamplifier	AMF-5D-020180-26-10P	Miteq	22/24/27, 15C, 15B
TM30599	Semi anechoic chambre	UNKNOWN	TDK	22/24/27, 15C, 15B
TM22638	Power supply	OL63743-901	Torqueleader	22/24/27, 15C, 15B
TM38066	High pass filter	4HC3000/18000-3-KK	Trilithic	22/24/27, 15C, 15B
TM26511	Tunable notch filter	WRCA870/	Wainwright	27
TM38215	Band reject filter	WRCD 1920/1980-1918/1982-40/20	Wainwright UMTS	27
TM38214	Band reject filter	WRCT 2402/2480-2400/2483.5-30/	Wainwright ISM	15C
-	Band reject filter	WRCG1877/1883-1870/1890-40/6EE	Wainwright	27
-	Band reject filter	WRCG1729.4/1735.4-1722.4/1742.4-40/6SS	Wainwright	27
-	Band reject filter	WRCG832/838-825/848-40/5SS	Wainwright	27
TM23892	Controller	G-1000SDX	Yaesu	22/24/27
2001	Bluetooth tester	CBT	R&S	22/24/27, 15C, 15B
-	Antenna	SBA 9113	Schwarzbeck	22/24/27
6023	Antenna	VUBA 9117	Schwarzbeck	22/24/27, 15C