



**M. Flom Associates, Inc. - Global Compliance Center**

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

Date: January 18, 2000

Federal Communications Commission  
Via: Electronic Filing

Attention: Authorization & Evaluation Division

Applicant: Nokia Mobile Phones  
Equipment: 8890, Type NSB-6NX  
FCC ID: LJPNSB-6NX  
FCC Rules: 24, Confidentiality

Gentlemen:

On behalf of the Applicant, enclosed please find Application Form 731, Engineering Test Report and all pertinent documentation, the whole for approval of the referenced equipment as shown.

Filing fees are attached.

We trust the same is in order. Should you need any further information, kindly contact the writer who is authorized to act as agent.

Sincerely yours,

A handwritten signature in black ink, appearing to read 'M. Flom, P. Eng.' The signature is fluid and cursive, with a horizontal line underneath it.

Morton Flom, P. Eng.

enclosure(s)  
cc: Applicant  
MF/cvr

LIST OF EXHIBITS  
(FCC CERTIFICATION (PCS TRANSMITTERS) - REVISED 9/28/98)

APPLICANT: Nokia Mobile Phones

FCC ID: LJPNSB-6NX

BY APPLICANT:

1. LETTER OF AUTHORIZATION
2. IDENTIFICATION DRAWINGS, 2.1033(c)(11)
  - ID LABEL
  - LOCATION OF LABEL
  - COMPLIANCE STATEMENT
  - LOCATION OF COMPLIANCE STATEMENT
3. PHOTOGRAPHS, 2.1033(c)(12)
4. CONFIDENTIALITY REQUEST: 0.457 and 0.459
5. DOCUMENTATION: 2.1033(c)
  - (3) USER MANUAL
  - (9) TUNE UP INFO
  - (10) SCHEMATIC DIAGRAM
  - (10) CIRCUIT DESCRIPTION

BY M.F.A. INC.

- A. TESTIMONIAL & STATEMENT OF CERTIFICATION
- B. STATEMENT OF QUALIFICATIONS



**M. Flom Associates, Inc. - Global Compliance Center**

3356 North San Marcos Place, Suite 107, Chandler, Arizona 85225-7176

www.mflom.com general@mflom.com (480) 926-3100, FAX: 926-3598

---

Sub-part  
2.1033(c):

EQUIPMENT IDENTIFICATION

FCC ID: LJPNSB-6NX

Serial No. of unit tested: 001004300146801

MFA No.: s00574

NAMEPLATE DRAWING

ATTACHED, EXHIBIT 1.

LOCATION

AS PER LABEL DRAWING(S)

DATE OF REPORT

January 18, 2000

SUPERVISED BY:

A handwritten signature in black ink, appearing to read 'M. Flom, P. Eng.' The signature is fluid and cursive, with 'M. Flom' on the top line and 'P. Eng.' on the bottom line.

Morton Flom, P. Eng.

THE APPLICANT HAS BEEN CAUTIONED AS TO THE FOLLOWING:

15.21 INFORMATION TO USER.

The users manual or instruction manual for an intentional radiator shall caution the user that changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

15.27(a) SPECIAL ACCESSORIES.

Equipment marketed to a consumer must be capable of complying with the necessary regulations in the configuration in which the equipment is marketed. Where special accessories, such as shielded cables and/or special connectors are required to enable an unintentional or intentional radiator to comply with the emission limits in this part, the equipment must be marketed with, i.e. shipped and sold with, those special accessories. However, in lieu of shipping or packaging the special accessories with the unintentional or intentional radiator, the responsible party may employ other methods of ensuring that the special accessories are provided to the consumer, without additional charge.

Information detailing any alternative method used to supply the special accessories for a grant of equipment authorization or retained in the verification records, as appropriate. The party responsible for the equipment, as detailed in § 2.909 of this chapter, shall ensure that these special accessories are provided with the equipment. The instruction manual for such devices shall include appropriate instructions on the first page of text concerned with the installation of the device that these special accessories must be used with the device. It is the responsibility of the user to use the needed special accessories supplied with the equipment.

TABLE OF CONTENTS

<u>RULE</u>	<u>DESCRIPTION</u>	<u>PAGE</u>
	Test Report	1
2.1033(c)	General Information Required	1
2.1033(c)(14)	Rule Summary	5
	Standard Test Conditions and Engineering Practices	6
2.1046(a), 24.232(b)		
	Carrier Output Power (Radiated)	7
2.1051, 2.1049(c), 24, 24.238(b)		
	Transmitter Conducted Measurements	9
2.1053(a)	Transmitter Radiated Measurements	14
2.1055(a)(1), 24.235		
	Frequency Stability (Temperature Variation)	17
2.1055(b)(1)	Frequency Stability (Voltage Variation)	20
2.202(g)	Necessary Bandwidth and Emission Bandwidth	21

PAGE NO.

1 of 21.

*Required information per ISO/IEC Guide 25-1990, paragraph 13.2:*

a)

TEST REPORT

b) Laboratory:  
(FCC: 31040/SIT)  
(Canada: IC 2044) M. Flom Associates, Inc.  
3356 N. San Marcos Place, Suite 107  
Chandler, AZ 85224

c) Report Number: d0010040

d) Client: Nokia Mobile Phones  
Elektroniikkatie 10  
Fin-90570  
Oulu, Finland

e) Identification:  
Description: 8890, Type NSB-6NX  
FCC ID: LJPNSB-6NX  
PCS Band GSM Hand Held Transceiver

f) EUT Condition: Not required unless specified in individual tests.

g) Report Date: January 18, 2000  
EUT Received: December 9, 1999

h, j, k): As indicated in individual tests.

i) Sampling method: No sampling procedure used.

l) Uncertainty: In accordance with MFA internal quality manual.

m) Supervised by:

  
Morton Flom, P. Eng.

n) Results: The results presented in this report relate only to the item tested.

o) Reproduction: This report must not be reproduced, except in full, without written permission from this laboratory.

Accessories used: ACP-7U Charger  
ACP-8U Multi-voltage switching charger  
LHC-9 Cigarette Lighter Charger  
DCV-1 Desktop Stand with 1 Slot  
HDC-5 Headset  
LPS-3 Loopset  
HHC-4 Holster  
PPH-1 Plug & Play handsfree  
CARK-119

PAGE NO.

1 of 21.

LIST OF GENERAL INFORMATION REQUIRED FOR CERTIFICATIONIN ACCORDANCE WITH FCC RULES AND REGULATIONS,  
VOLUME II, PART 2 AND TO

24, Confidentiality

Sub-part 2.1033(c)(1): NAME AND ADDRESS OF APPLICANT:Nokia Mobile Phones  
Elektroniikkatie 10  
Fin-90570  
Oulu, FinlandMANUFACTURER:Nokia tmc Ltd.  
Yangduck-Dong 973-6  
Hwe won-Ku, Masan, Korea(c)(2): FCC ID: LJPNSB-6NXMODEL NO: 8890, Type NSB-6NX(c)(3): INSTRUCTION MANUAL(S):

PLEASE SEE ATTACHED EXHIBITS

(c)(4): TYPE OF EMISSION: 256KGXW(c)(5): FREQUENCY RANGE, MHz: 1850 to 1910(c)(6): POWER RATING, Watts: 1.25  
Switchable                     Variable                    N/A

GRANT NOTE: BC The output power is continuously variable from the value listed in this entry to 5%-10% of the value listed.

(c)(7): MAXIMUM POWER RATING, Watts: 2

PAGE NO.

3 of 21.

Subpart 2.1033 (continued)

(c)(8): VOLTAGES & CURRENTS IN ALL ELEMENTS IN FINAL R. F. STAGE, INCLUDING FINAL TRANSISTOR OR SOLID STATE DEVICE:

COLLECTOR CURRENT, A	= per manual
COLLECTOR VOLTAGE, Vdc	= per manual
SUPPLY VOLTAGE, Vdc	= 3.6

(c)(9): TUNE-UP PROCEDURE:

PLEASE SEE ATTACHED EXHIBITS

(c)(10): CIRCUIT DIAGRAM/CIRCUIT DESCRIPTION:

Including description of circuitry & devices provided for determining and stabilizing frequency, for suppression of spurious radiation, for limiting modulation and limiting power.

PLEASE SEE ATTACHED EXHIBITS

(c)(11): LABEL INFORMATION:

PLEASE SEE ATTACHED EXHIBITS

(c)(12): PHOTOGRAPHS:

PLEASE SEE ATTACHED EXHIBITS

(c)(13): DIGITAL MODULATION DESCRIPTION:

       ATTACHED EXHIBITS  
X N/A

(c)(14): TEST AND MEASUREMENT DATA:

FOLLOWS

PAGE NO.

4 of 21.

M. Flom Associates, Inc. is accredited by the American Association for Laboratory Accreditation (A2LA) as shown in the scope below.



THE AMERICAN  
ASSOCIATION  
FOR LABORATORY  
ACCREDITATION

### ACCREDITED LABORATORY

A2LA has accredited

**M. FLOM ASSOCIATES, INC.**

**Chandler, AZ**

for technical competence in the field of

#### Electrical (EMC) Testing

The accreditation covers the specific tests and types of tests listed on the agreed scope of accreditation. This laboratory meets the requirements of ISO/IEC Guide 25-1990 "General Requirements for the Competence of Calibration and Testing Laboratories" (equivalent to relevant requirements of the ISO 9000 series of standards) and any additional program requirements in the identified field of testing.

Presented this 24<sup>th</sup> day of November, 1998.



*Pete Flom*  
President  
For the Accreditation Council  
Certificate Number 1008.01  
Valid to December 31, 2000

For tests or types of tests to which this accreditation applies, please refer to the laboratory's Electrical (EMC) Scope of Accreditation



American Association for Laboratory Accreditation

#### SCOPE OF ACCREDITATION TO ISO/IEC GUIDE 25-1990 AND EN 45001

M. FLOM ASSOCIATES, INC.  
Electronic Testing Laboratory  
3356 North San Marcos Place, Suite 107  
Chandler, AZ 85224-1571  
Morton Flom Phone: 602 926 3100

#### ELECTRICAL (EMC)

Valid to: December 31, 2000

Certificate Number: 1008-01

In recognition of the successful completion of the A2LA evaluation process, accreditation is granted to this laboratory to perform the following electromagnetic compatibility tests:

Tests	Standard(s)
RF Emissions	FCC Part 15 (Subparts B and C) using ANSI C63.4-1992; CISPR 11; CISPR 13; CISPR 14; CISPR 22; EN 55011; EN 55013; EN 55014; EN 55022; EN 50081-1; EN 50081-2; FCC Part 18; ICES-003; AS/NZS 1044; AS/NZS 1053; AS/NZS 3548; AS/NZS 4251.1
RF Immunity	EN 50082-1; EN 50082-2; AS/NZS 4251.1
Radiated Susceptibility	EN 61000-4-3; ENV 50140; ENV 50204; IEC 1000-4-3; IEC 801-3
ESD	EN 61000-4-2; IEC 1000-4-2; IEC 801-2
EFT	EN 61000-4-4; IEC 1000-4-4; IEC 801-4
Surge	EN 61000-4-5; ENV 50142; IEC 1000-4-5; IEC 801-5
47 CFR (FCC)	2, 21, 22, 23, 24, 74, 80, 87, 90, 95, 97

*Pete Flom*

5301 Buckeystown Pike, Suite 350 • Frederick, MD 21704-8307 • Phone: 301 644 3200 • Fax: 301 662 2974



"This laboratory is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this report have been determined in accordance with the laboratory's terms of accreditation unless stated otherwise in the report."

Should this report contain any data for tests for which we are not accredited, or which have been undertaken by a subcontractor that is not A2LA accredited, such data would not be covered by this laboratory's A2LA accreditation.

PAGE NO.

5 of 21.

Sub-part

2.1033(c)(14):TEST AND MEASUREMENT DATA

All tests and measurement data shown were performed in accordance with FCC Rules and Regulations, Volume II; Part 2, Sub-part J, Sections 2.947, 2.1033(c), 2.1041, 2.1046, 2.1047, 2.1079, 2.1051, 2.1053, 2.1055, 2.1057 and the following individual Parts:

- \_\_\_\_ 21 - Domestic Public Fixed Radio Services
- \_\_\_\_ 22 - Public Mobile Services
- \_\_\_\_ 22 Subpart H - Cellular Radiotelephone Service
- \_\_\_\_ 22.901(d) - Alternative technologies and auxiliary services
- \_\_\_\_ 23 - International Fixed Public Radiocommunication services
- x 24 - Personal Communications Services
- \_\_\_\_ 74 Subpart H - Low Power Auxiliary Stations
- \_\_\_\_ 80 - Stations in the Maritime Services
- \_\_\_\_ 80 Subpart E - General Technical Standards
- \_\_\_\_ 80 Subpart F - Equipment Authorization for Compulsory Ships
- \_\_\_\_ 80 Subpart K - Private Coast Stations and Marine Utility Stations
- \_\_\_\_ 80 Subpart S - Compulsory Radiotelephone Installations for Small Passenger Boats
- \_\_\_\_ 80 Subpart T - Radiotelephone Installation Required for Vessels on the Great Lakes
- \_\_\_\_ 80 Subpart U - Radiotelephone Installations Required by the Bridge-to-Bridge Act
- \_\_\_\_ 80 Subpart V - Emergency Position Indicating Radiobeacons (EPIRB'S)
- \_\_\_\_ 80 Subpart W - Global Maritime Distress and Safety System (GMDSS)
- \_\_\_\_ 80 Subpart X - Voluntary Radio Installations
- \_\_\_\_ 87 - Aviation Services
- \_\_\_\_ 90 - Private Land Mobile Radio Services
- \_\_\_\_ 94 - Private Operational-Fixed Microwave Service
- \_\_\_\_ 95 Subpart A - General Mobile Radio Service (GMRS)
- \_\_\_\_ 95 Subpart C - Radio Control (R/C) Radio Service
- \_\_\_\_ 95 Subpart D - Citizens Band (CB) Radio Service
- \_\_\_\_ 95 Subpart E - Family Radio Service
- \_\_\_\_ 95 Subpart F - Interactive Video and Data Service (IVDS)
- \_\_\_\_ 97 - Amateur Radio Service
- \_\_\_\_ 101 - Fixed Microwave Services

PAGE NO.

6 of 21.

STANDARD TEST CONDITIONS  
and  
ENGINEERING PRACTICES

Except as noted herein, the following conditions and procedures were observed during the testing:

In accordance with ANSI C63.4-1992, section 6.1.9, and unless otherwise indicated in the specific measurement results, the ambient temperature of the actual EUT was maintained within the range of 10° to 40°C (50° to 104 °F) unless the particular equipment requirements specify testing over a different temperature range. Also, unless otherwise indicated, the humidity levels were in the range of 10% to 90% relative humidity.

Prior to testing, the EUT was tuned up in accordance with the manufacturer's alignment procedures. All external gain controls were maintained at the position of maximum and/or optimum gain throughout the testing.

Measurement results, unless otherwise noted, are worst case measurements.

FOR PCS EQUIPMENT:

Pursuant to Section 24.51(d), the EUT complies with IEEE C95.1-1991, "IEEE Standards for Safety Levels with Respect to Human Exposure to Radio Frequency Electromagnetic Fields, 3 kHz to 300 GHz."

The EUT uses digital modulation, as such, measurements of the modulation characteristics are not applicable. The applicant has provided a description of the modulation particular to the EUT.

Pursuant to Section 24.238(c), the EUT was tested at it's lowest and highest possible tuned frequencies.

GUIDES:

This device was tested using the following Guide(s):

ETS 300 607-1-1998

PAGE NO. 7 of 21.

NAME OF TEST: Carrier Output Power (Radiated)

SPECIFICATION: 47 CFR 2.1046(a), 24.232(b)

GUIDE: As indicated on page 6

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE (RADIATED)

1. The EUT was placed on an open-field site and its radiated field strength at a known distance was measured by means of a spectrum analyzer. Equivalent loading was calculated from the equation  $P_t = ((E \times R)^2 / 30)$  watts, where  $R = 3m$ .
2. Measurement accuracy is  $\pm 1.5$  dB.

MEASUREMENT RESULTS

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV/m	CF, dB	EIRP, dBm	EIRP, Watts
1850.200000	1850.210000	92.3	33.9	31	1.25
1880.000000	1880.080000	91.4	33.5	29.7	0.93
1909.800000	1909.800000	91.4	33.5	29.8	0.95


SUPERVISED BY:



Morton Flom, P. Eng.

PAGE NO.

8 of 21.

TRANSMITTER RADIATED MEASUREMENTS

Transmitter Radiated Measurements

Asset	Description	s/n
(1) <u>TRANSDUCER</u>		
<u>x</u> i00091	Emco 3115	001469
<u>x</u> i00089	Aprel Log Periodic	001500
(2) <u>HIGH PASS FILTER</u>		
<u>x</u> i00	Narda $\mu$ PAD (In-Band Only)	
<u>x</u> i00	Trilithic (Out-Of-Band Only)	
(3) <u>PREAMP</u>		
<u>x</u> i00028	HP 8449 (+30 dB)	2749A00121
(4) <u>SPECTRUM ANALYZER</u>		
<u>x</u> i00048	HP 8566B	2511A01467
<u>  </u> i00043	HP 8558B	2004A02076
<u>  </u> i00057	HP 8557A	1531A00191
<u>x</u> i00029	HP 8563E	3213A00104

PAGE NO. 9 of 21.

NAME OF TEST: Transmitter Conducted Measurements

SPECIFICATION:  
47 CFR 2.1051: Unwanted (spurious) Emissions  
2.1049(c), 24.238(b): Occupied Bandwidth  
24: Emissions at Band Edges

GUIDE: As indicated on page 6

TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page with the Spectrum Analyzer connected.
2. The low and high channels for all RF powers within the designated frequency block(s) were measured.
3. MEASUREMENT RESULTS: ATTACHED

SUPERVISED BY:



Morton Flom, P. Eng.


PAGE NO.

10 of 21.

TRANSMITTER SPURIOUS EMISSION

TEST A. OCCUPIED BANDWIDTH (IN-BAND SPURIOUS)

TEST B. OUT-OF-BAND SPURIOUS




Asset	Description	s/n
	(as applicable)	

(1)	<u>AUDIO OSCILLATOR/GENERATOR</u>	
i00010	HP 204D	1105A04683
i00017	HP 8903A	2216A01753
i00012	HP 3312A	1432A11250
(2)	<u>COAXIAL ATTENUATOR</u>	
i00122	Narda 766-10	7802
i00123	Narda 766-10	7802A
i00069	Bird 8329 (30 dB)	1006
i00113	Sierra 661A-3D	1059
(3)	<u>FILTERS; NOTCH, HP, LP, BP</u>	
i00126	Eagle TNF-1	100-250
i00125	Eagle TNF-1	50-60
i00124	Eagle TNF-1	250-850
(4)	<u>SPECTRUM ANALYZER</u>	
i00048	HP 8566B	2511A01467
i00029	HP 8563E	3213A00104

PAGE NO.

11 of 21.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g99c0200: 1999-Dec-10 Fri 09:27:00  
 STATE: 2:High Power



POWER: HIGH  
 MODULATION: GSM 1900  
 99% POWER BANDWIDTH


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

12 of 21.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g99c0199: 1999-Dec-10 Fri 09:25:00  
 STATE: 2:High Power



POWER: HIGH  
 MODULATION: GSM 1900  
 UPPER BANDEDGE CHANNEL 810


SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO.

13 of 21.

NAME OF TEST: Emission Masks (Occupied Bandwidth)  
 g99c0198: 1999-Dec-10 Fri 09:19:00  
 STATE: 2:High Power



POWER: HIGH  
 MODULATION: GSM 1900  
 LOWER BANDEDGECHANNEL 512

SUPERVISED BY:

Morton Flom, P. Eng.

PAGE NO. 14 of 21.

NAME OF TEST: Field Strength of Spurious Radiation

SPECIFICATION: 47 CFR 2.1053(a)

GUIDE: As indicated on page 6


TEST EQUIPMENT: As per attached page

MEASUREMENT PROCEDURE

1. A description of the measurement facilities was filed with the FCC and was found to be in compliance with the requirements of Section 15.38, by letter from the FCC dated March 3, 1997, FILE 31040/SIT. All pertinent changes will be reported to the Commission by up-date prior to March 2000.
2. At first, in order to locate all spurious frequencies and approximate amplitudes, and to determine proper equipment functioning, the test sample was set up at a distance of three meters from the test instrument. Valid spurious signals were determined by switching the power on and off.
3. In the field, the test sample was placed on a wooden turntable above ground at three (or thirty) meters away from the search antenna. Excess power leads were coiled near the power supply.

The cables were oriented in order to obtain the maximum response. At each emission frequency, the turntable was rotated and the search antennas were raised and lowered vertically.

4. The emission was observed with both a vertically polarized and a horizontally polarized search antenna and the worst case was used.
6. The field strength of each emission within 20 dB of the limit was recorded and corrected with the appropriate cable and transducer factors.
7. The worst case for all channels is shown.
8. Measurement results: ATTACHED FOR WORST CASE

RADIATED TEST SETUP

## NOTES:

- (a) Search Antenna - Rotatable on boom
- (b) Non-metallic boom
- (c) Non-metallic mast
- (d) Adjustable horizontally
- (e) Equipment Under Test
- (f) Turntable
- (g) Boom adjustable in height.
- (h) External control cables routed horizontally at least one wavelength.
- (i) Rotatable
- (j) Cables routed through hollow turntable center
- (k) 30 cm or less
- (l) External power source
- (m) 10 cm diameter coil of excess cable
- (n) 25 cm (V), 1 m-7 m (V, H)
- (o) 25 cm from bottom end of 'V', 1m normally
- (p) Calibrated Cable at least 10m in length
- (q) Amplifier (optional)
- (r) Spectrum Analyzer

Asset	Description (as applicable)	s/n	Cycle	Last Cal
Per ANSI C63.4-1992, 10.1.4				
<u>TRANSDUCER</u>				
i00088	EMCO 3109-B 25MHz-300MHz	2336	12 mo.	Sep-99
i00089	Aprel 2001 200MHz-1GHz	001500	12 mo.	Sep-99
i00103	EMCO 3115 1GHz-18GHz	9208-3925	12 mo.	Sep-99
i00065	EMCO 3301-B Active Monopole	2635	12 mo.	Sep-99
<u>AMPLIFIER</u>				
i00028	HP 8449A	2749A00121	12 mo.	Mar-99
<u>SPECTRUM ANALYZER</u>				
i00029	HP 8563E	3213A00104	12 mo.	Aug-99
i00033	HP 85462A	3625A00357	12 mo.	May-99
i00048	HP 8566B	2511AD1467	6 mo.	May-99

PAGE NO.

16 of 21.

NAME OF TEST: Field Strength of Spurious Radiation  
 g99c0194: 1999-Dec-09 Thu 10:45:00  
 STATE: 2:High Power

FREQUENCY TUNED, MHz	FREQUENCY EMISSION, MHz	METER, dBuV	CF, dB	EIRP, dBm	MARGIN, dB
1850.200000	3700.470000	21.25	39.43	-34.5	-21.5
1880.000000	3759.995000	26.33	39.56	-29.3	-16.3
1909.800000	3819.695000	23.44	39.7	-32.1	-19.1
1850.200000	5550.593333	39.83	14.33	-41.1	-28
1880.000000	5639.913333	40.5	14.55	-40.2	-27.2
1909.800000	5729.430000	37.5	14.77	-43	-29.9
1850.200000	7400.800000	28.17	19.55	-47.5	-34.5
1880.000000	7520.006667	29.83	19.59	-45.8	-32.8
1909.800000	7639.200000	27.67	19.64	-47.9	-34.9
1850.200000	9251.000000	34.33	22.05	-38.8	-25.8
1880.000000	9400.000000	33	22.96	-39.3	-26.2
1909.800000	9549.000000	35	23.85	-36.4	-23.4
1850.200000	11101.200000	36	23.72	-35.5	-22.5
1880.000000	11280.000000	36.17	23.84	-35.2	-22.2
1909.800000	11458.800000	35.67	23.96	-35.6	-22.6
1850.200000	12951.400000	34.17	26.88	-34.2	-21.2
1880.000000	13160.000000	34.17	26.89	-34.2	-21.1
1909.800000	13368.600000	34.33	26.75	-34.1	-21.1
1850.200000	14801.600000	33.17	23.96	-38.1	-25.1
1880.000000	15040.000000	35	23.51	-36.7	-23.7
1909.800000	15278.400000	34.67	24.13	-36.4	-23.4
1850.200000	16651.800000	34.5	29.1	-31.6	-18.6
1880.000000	16920.000000	34.33	30.35	-30.5	-17.5
1909.800000	17188.200000	34	31.08	-30.1	-17.1

PAGE NO. 17 of 21.

NAME OF TEST: Frequency Stability (Temperature Variation)

SPECIFICATION: 47 CFR 2.1055(a)(1), 24.235

GUIDE: As indicated on page 6

TEST CONDITIONS: As Indicated

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT and test equipment were set up as shown on the following page.
2. With all power removed, the temperature was decreased to -30°C and permitted to stabilize for three hours. Power was applied and the maximum change in frequency was noted within one minute.
3. With power OFF, the temperature was raised in 10°C steps. The sample was permitted to stabilize at each step for at least one-half hour. Power was applied and the maximum frequency change was noted within one minute.
4. The temperature tests were performed for the worst case.


5. MEASUREMENT RESULTS: ATTACHED

PAGE NO.

18 of 21.

TRANSMITTER TEST SET-UP

TEST A. OPERATIONAL STABILITY  
 TEST B. CARRIER FREQUENCY STABILITY  
 TEST C. OPERATIONAL PERFORMANCE STABILITY  
 TEST D. HUMIDITY  
 TEST E. VIBRATION  
 TEST F. ENVIRONMENTAL TEMPERATURE  
 TEST G. FREQUENCY STABILITY: TEMPERATURE VARIATION  
 TEST H. FREQUENCY STABILITY: VOLTAGE VARIATION



Transmitter Test Set-Up

Asset	Description (as applicable)	s/n
(1) <u>TEMPERATURE, HUMIDITY, VIBRATION</u>		
i00027	Tenney Temp. Chamber	9083-765-234
i00	Weber Humidity Chamber	
i00	L.A.B. RVH 18-100	
(2) <u>COAXIAL ATTENUATOR</u>		
i00122	NARDA 766-10	7802
i00123	NARDA 766-10	7802A
i00113	SIERRA 661A-3D	1059
i00069	BIRD 8329 (30 dB)	10066
(3) <u>R.F. POWER</u>		
i00014	HP 435A POWER METER	1733A05839
i00039	HP 436A POWER METER	2709A26776
i00020	HP 8901A POWER MODE	2105A01087
(4) <u>FREQUENCY COUNTER</u>		
i00042	HP 5383A	1628A00959
i00019	HP 5334B	2704A00347
i00020	HP 8901A	2105A01087

PAGE NO. 19 of 21.

NAME OF TEST: Frequency Stability (Temperature Variation)

STATE: Subscriber equipment is synchronized to base station frequency. No variance in transmitter frequency stability observed under any variation of temperature and/or voltage.

---

°C	Change, Hz	Change, ppm
-30	0	0.0
-20	0	0.0
-10	0	0.0
0	0	0.0
10	0	0.0
20	0	0.0
25	0	0.0
30	0	0.0
40	0	0.0
50	0	0.0
60	0	0.0

SUPERVISED BY:



Morton Flom, P. Eng.

PAGE NO. 20 of 21.

NAME OF TEST: Frequency Stability (Voltage Variation)

SPECIFICATION: 47 CFR 2.1055(b)(1)

GUIDE: As indicated on page 6

TEST EQUIPMENT: As per previous page

MEASUREMENT PROCEDURE

1. The EUT was placed in a temperature chamber at  $25\pm5^{\circ}\text{C}$  and connected as for "Frequency Stability - Temperature Variation" test.
2. The power supply voltage to the EUT was varied from 85% to 115% of the nominal value measured at the input to the EUT.
3. The variation in frequency was measured for the worst case.

RESULTS: Frequency Stability (Voltage Variation)

STATE:

LIMIT: Must remain within authorized frequency block.

BATTERY END POINT (Voltage) = 3.1

% of STV	Voltage	Frequency, MHz	Change, Hz	Change, ppm
85	3.3	1880	0	0.0
100	3.9	1880	0	0.0
115	4.5	1880	0	0.0
B.E.P.	3.1	1880	0	0.0

SUPERVISED BY:



Morton Flom, P. Eng.

PAGE NO. 21 of 21.

NAME OF TEST: Necessary Bandwidth and Emission Bandwidth

SPECIFICATION: 47 CFR 2.202(g)

MODULATION = 256KGXW

NECESSARY BANDWIDTH:

NECESSARY BANDWIDTH ( $B_N$ ), kHz = 256  
(measured at the 99.75% power bandwidth)

SUPERVISED BY:  
END OF TEST REPORT



Morton Flom, P. Eng.

TESTIMONIAL  
AND  
STATEMENT OF CERTIFICATION

THIS IS TO CERTIFY THAT:

1. THAT the application was prepared either by, or under the direct supervision of, the undersigned.
2. THAT the technical data supplied with the application was taken under my direction and supervision.
3. THAT the data was obtained on representative units, randomly selected.
4. THAT, to the best of my knowledge and belief, the facts set forth in the application and accompanying technical data are true and correct.

CERTIFYING ENGINEER:



Morton Flom, P. Eng.