

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11a	Test Channel	185
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8250.50	38.28	10.46	48.74	74.00	-25.26	Peak	Horizontal
*	13974.40	31.50	19.09	50.59	88.20	-37.61	Peak	Horizontal
*	14805.70	31.04	19.16	50.20	88.20	-38.00	Peak	Horizontal
	17920.10	15.48	28.08	43.56	54.00	-10.44	Average	Horizontal
	17920.10	30.46	28.08	58.54	74.00	-15.46	Peak	Horizontal
	11985.40	31.44	16.01	47.45	74.00	-26.55	Peak	Vertical
*	14079.80	31.27	19.06	50.33	88.20	-37.87	Peak	Vertical
*	14758.10	32.03	18.89	50.92	88.20	-37.28	Peak	Vertical
	17954.10	10.35	28.54	38.89	54.00	-15.11	Average	Vertical
	17954.10	29.60	28.54	58.14	74.00	-15.86	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11a	Test Channel	189
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11466.90	31.31	16.27	47.58	74.00	-26.42	Peak	Horizontal
*	14132.50	30.91	19.17	50.08	88.20	-38.12	Peak	Horizontal
*	14809.10	30.70	19.15	49.85	88.20	-38.35	Peak	Horizontal
	17960.90	16.14	28.42	44.56	54.00	-9.44	Average	Horizontal
	17960.90	29.40	28.42	57.82	74.00	-16.18	Peak	Horizontal
	10785.20	32.49	14.95	47.44	74.00	-26.56	Peak	Vertical
*	13914.90	31.43	18.73	50.16	88.20	-38.04	Peak	Vertical
*	14790.40	30.77	19.13	49.90	88.20	-38.30	Peak	Vertical
	17947.30	16.32	28.63	44.95	54.00	-9.05	Average	Vertical
	17947.30	30.11	28.63	58.74	74.00	-15.26	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11a	Test Channel	209
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	10863.40	31.72	15.53	47.25	74.00	-26.75	Peak	Horizontal
*	13685.40	31.80	18.22	50.02	88.20	-38.18	Peak	Horizontal
*	14838.00	31.14	18.76	49.90	88.20	-38.30	Peak	Horizontal
	17945.60	14.59	28.60	43.19	54.00	-10.81	Average	Horizontal
	17945.60	29.85	28.60	58.45	74.00	-15.55	Peak	Horizontal
	11524.70	31.27	16.35	47.62	74.00	-26.38	Peak	Vertical
*	14142.70	30.68	19.33	50.01	88.20	-38.19	Peak	Vertical
*	14793.80	30.65	19.14	49.79	88.20	-38.41	Peak	Vertical
	17848.70	16.14	28.54	44.68	54.00	-9.32	Average	Vertical
	17848.70	30.12	28.54	58.66	74.00	-15.34	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11a	Test Channel	229
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	10854.90	32.00	15.56	47.56	74.00	-26.44	Peak	Horizontal
*	14006.70	31.01	18.85	49.86	88.20	-38.34	Peak	Horizontal
*	14804.00	30.92	19.17	50.09	88.20	-38.11	Peak	Horizontal
	17855.50	15.40	28.62	44.02	54.00	-9.98	Average	Horizontal
	17855.50	29.62	28.62	58.24	74.00	-15.76	Peak	Horizontal
	11135.40	31.78	16.16	47.94	74.00	-26.06	Peak	Vertical
*	13870.70	31.27	18.70	49.97	88.20	-38.23	Peak	Vertical
*	14846.50	31.73	18.64	50.37	88.20	-37.83	Peak	Vertical
	17843.60	16.14	28.42	44.56	54.00	-9.44	Average	Vertical
	17843.60	30.11	28.42	58.53	74.00	-15.47	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

STBC Mode:

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Lucas Wang
Test Site	WZ-AC2	Test Date	2025-07-03
Test Mode	802.11ax-HE20	Test Channel	1
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	7939.40	48.75	10.71	59.46	88.20	-28.74	Peak	Horizontal
	11536.60	30.71	16.32	47.03	74.00	-26.97	Peak	Horizontal
*	17483.20	30.65	23.86	54.51	88.20	-33.69	Peak	Horizontal
	17864.00	18.43	28.44	46.87	54.00	-7.13	Average	Horizontal
	17864.00	28.56	28.44	57.00	74.00	-17.00	Peak	Horizontal
*	7939.40	40.33	10.71	51.04	88.20	-37.16	Peak	Vertical
*	13712.60	31.57	18.45	50.02	88.20	-38.18	Peak	Vertical
	15648.90	32.48	17.35	49.83	74.00	-24.17	Peak	Vertical
	17935.40	18.16	28.50	46.66	54.00	-7.34	Average	Vertical
	17935.40	29.66	28.50	58.16	74.00	-15.84	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Ajin Fan
Test Site	WZ-AC2	Test Date	2025-07-03
Test Mode	802.11ax-HE20	Test Channel	49
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8260.70	39.72	10.36	50.08	54.00	-3.92	Average	Horizontal
	8260.70	41.22	10.36	51.58	74.00	-22.42	Peak	Horizontal
*	13892.80	31.07	18.83	49.90	88.20	-38.30	Peak	Horizontal
	15540.10	30.56	17.44	48.00	74.00	-26.00	Peak	Horizontal
	17949.00	28.66	28.64	57.30	74.00	-16.70	Peak	Horizontal
	8260.70	39.54	10.36	49.90	74.00	-24.10	Peak	Vertical
*	13714.30	31.12	18.45	49.57	88.20	-38.63	Peak	Vertical
*	14909.40	30.75	18.78	49.53	88.20	-38.67	Peak	Vertical
	17935.40	28.83	28.50	57.33	74.00	-16.67	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Lucas Wang
Test Site	WZ-AC2	Test Date	2025-07-03
Test Mode	802.11ax-HE20	Test Channel	93
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	8553.10	38.24	11.33	49.57	88.20	-38.63	Peak	Horizontal
	11154.10	31.45	15.92	47.37	74.00	-26.63	Peak	Horizontal
*	17561.40	30.30	24.93	55.23	88.20	-32.97	Peak	Horizontal
	17857.20	17.85	28.61	46.46	54.00	-7.54	Average	Horizontal
	17857.20	28.62	28.61	57.23	74.00	-16.77	Peak	Horizontal
*	8553.10	39.34	11.33	50.67	88.20	-37.53	Peak	Vertical
	11035.10	31.71	15.98	47.69	74.00	-26.31	Peak	Vertical
*	17476.40	29.94	23.80	53.74	88.20	-34.46	Peak	Vertical
	17933.70	17.84	28.49	46.33	54.00	-7.67	Average	Vertical
	17933.70	29.47	28.49	57.96	74.00	-16.04	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Lucas Wang
Test Site	WZ-AC2	Test Date	2025-07-03
Test Mode	802.11ax-HE20	Test Channel	97
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	8580.30	38.11	11.59	49.70	88.20	-38.50	Peak	Horizontal
	11550.20	31.78	16.30	48.08	74.00	-25.92	Peak	Horizontal
*	17510.40	30.68	23.65	54.33	88.20	-33.87	Peak	Horizontal
	17954.10	18.27	28.54	46.81	54.00	-7.19	Average	Horizontal
	17954.10	29.39	28.54	57.93	74.00	-16.07	Peak	Horizontal
*	8580.30	39.55	11.59	51.14	88.20	-37.06	Peak	Vertical
	11478.80	31.27	16.35	47.62	74.00	-26.38	Peak	Vertical
*	17437.30	30.80	23.12	53.92	88.20	-34.28	Peak	Vertical
	17979.60	18.39	27.95	46.34	54.00	-7.66	Average	Vertical
	17979.60	30.57	27.95	58.52	74.00	-15.48	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	105
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	8633.00	37.39	11.64	49.03	88.20	-39.17	Peak	Horizontal
	10725.70	32.63	14.88	47.51	74.00	-26.49	Peak	Horizontal
*	17595.40	30.37	24.45	54.82	88.20	-33.38	Peak	Horizontal
	17938.80	17.95	28.53	46.48	54.00	-7.52	Average	Horizontal
	17938.80	29.15	28.53	57.68	74.00	-16.32	Peak	Horizontal
*	8633.00	36.05	11.64	47.69	88.20	-40.51	Peak	Vertical
	11619.90	30.80	16.30	47.10	74.00	-26.90	Peak	Vertical
*	17530.80	30.03	23.80	53.83	88.20	-34.37	Peak	Vertical
	17949.00	18.17	28.64	46.81	54.00	-7.19	Average	Vertical
	17949.00	28.44	28.64	57.08	74.00	-16.92	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	113
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	7818.70	44.40	10.17	54.57	88.20	-33.63	Peak	Horizontal
	11740.60	31.45	16.07	47.52	74.00	-26.48	Peak	Horizontal
*	17666.80	30.91	26.24	57.15	88.20	-31.05	Peak	Horizontal
	17847.00	18.25	28.53	46.78	54.00	-7.22	Average	Horizontal
	17847.00	29.72	28.53	58.25	74.00	-15.75	Peak	Horizontal
*	7818.70	36.34	10.17	46.51	88.20	-41.69	Peak	Vertical
	10936.50	31.41	15.90	47.31	74.00	-26.69	Peak	Vertical
*	17677.00	30.28	26.24	56.52	88.20	-31.68	Peak	Vertical
	17943.90	18.23	28.58	46.81	54.00	-7.19	Average	Vertical
	17943.90	29.14	28.58	57.72	74.00	-16.28	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	117
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	8712.90	33.37	12.39	45.76	88.20	-42.44	Peak	Horizontal
	11482.20	31.14	16.37	47.51	74.00	-26.49	Peak	Horizontal
*	17578.40	31.26	24.90	56.16	88.20	-32.04	Peak	Horizontal
	17949.00	17.97	28.64	46.61	54.00	-7.39	Average	Horizontal
	17949.00	28.12	28.64	56.76	74.00	-17.24	Peak	Horizontal
*	8712.90	34.24	12.39	46.63	88.20	-41.57	Peak	Vertical
	11109.90	31.22	16.03	47.25	74.00	-26.75	Peak	Vertical
*	17653.20	28.88	25.97	54.85	88.20	-33.35	Peak	Vertical
	17976.20	17.81	28.04	45.85	54.00	-8.15	Average	Vertical
	17976.20	29.65	28.04	57.69	74.00	-16.31	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	149
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8034.60	41.55	10.80	52.35	54.00	-1.65	Average	Horizontal
	8034.60	42.74	10.80	53.54	74.00	-20.46	Peak	Horizontal
*	14237.90	31.21	19.16	50.37	88.20	-37.83	Peak	Horizontal
*	17116.00	31.44	21.37	52.81	88.20	-35.39	Peak	Horizontal
	17932.00	16.25	28.47	44.72	54.00	-9.28	Average	Horizontal
	17932.00	30.79	28.47	59.26	74.00	-14.74	Peak	Horizontal
*	9671.70	33.99	12.61	46.60	88.20	-41.60	Peak	Vertical
	11507.70	31.90	16.40	48.30	74.00	-25.70	Peak	Vertical
*	16957.90	30.49	20.60	51.09	88.20	-37.11	Peak	Vertical
	17966.00	16.89	28.30	45.19	54.00	-8.81	Average	Vertical
	17966.00	30.50	28.30	58.80	74.00	-15.20	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	181
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	13982.90	31.29	19.07	50.36	88.20	-37.84	Peak	Horizontal
*	14809.10	32.82	19.15	51.97	88.20	-36.23	Peak	Horizontal
	15614.90	30.73	17.15	47.88	74.00	-26.12	Peak	Horizontal
	17932.00	16.66	28.47	45.13	54.00	-8.87	Average	Horizontal
	17932.00	30.04	28.47	58.51	74.00	-15.49	Peak	Horizontal
*	14132.50	30.70	19.17	49.87	88.20	-38.33	Peak	Vertical
*	15195.00	32.64	18.06	50.70	88.20	-37.50	Peak	Vertical
	15711.80	30.95	17.37	48.32	74.00	-25.68	Peak	Vertical
	17938.80	16.77	28.53	45.30	54.00	-8.70	Average	Vertical
	17938.80	29.55	28.53	58.08	74.00	-15.92	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	185
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8250.50	41.74	10.46	52.20	54.00	-1.80	Average	Horizontal
	8250.50	42.25	10.46	52.71	74.00	-21.29	Peak	Horizontal
*	13794.20	31.27	18.61	49.88	88.20	-38.32	Peak	Horizontal
*	14797.20	30.20	19.16	49.36	88.20	-38.84	Peak	Horizontal
	17935.40	16.40	28.50	44.90	54.00	-9.10	Average	Horizontal
	17935.40	29.91	28.50	58.41	74.00	-15.59	Peak	Horizontal
	8250.50	39.08	10.46	49.54	74.00	-24.46	Peak	Vertical
*	14168.20	31.12	19.32	50.44	88.20	-37.76	Peak	Vertical
*	14824.40	31.12	19.00	50.12	88.20	-38.08	Peak	Vertical
	17935.40	16.48	28.50	44.98	54.00	-9.02	Average	Vertical
	17935.40	29.23	28.50	57.73	74.00	-16.27	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	189
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11650.50	30.87	16.33	47.20	74.00	-26.80	Peak	Horizontal
*	14001.60	30.33	18.92	49.25	88.20	-38.95	Peak	Horizontal
*	14540.50	30.97	19.08	50.05	88.20	-38.15	Peak	Horizontal
	17960.90	16.57	28.42	44.99	54.00	-9.01	Average	Horizontal
	17960.90	29.61	28.42	58.03	74.00	-15.97	Peak	Horizontal
	11456.70	30.96	16.25	47.21	74.00	-26.79	Peak	Vertical
*	13835.00	31.24	18.59	49.83	88.20	-38.37	Peak	Vertical
*	14787.00	30.77	19.11	49.88	88.20	-38.32	Peak	Vertical
	17879.30	16.48	27.65	44.13	54.00	-9.87	Average	Vertical
	17879.30	30.04	27.65	57.69	74.00	-16.31	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	209
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11128.60	31.01	16.16	47.17	74.00	-26.83	Peak	Horizontal
*	14190.30	30.83	19.03	49.86	88.20	-38.34	Peak	Horizontal
*	14911.10	30.95	18.76	49.71	88.20	-38.49	Peak	Horizontal
	17853.80	16.38	28.60	44.98	54.00	-9.02	Average	Horizontal
	17853.80	30.14	28.60	58.74	74.00	-15.26	Peak	Horizontal
	11534.90	30.64	16.32	46.96	74.00	-27.04	Peak	Vertical
*	14124.00	30.35	19.02	49.37	88.20	-38.83	Peak	Vertical
*	14817.60	31.13	19.11	50.24	88.20	-37.96	Peak	Vertical
	17911.60	16.47	27.85	44.32	54.00	-9.68	Average	Vertical
	17911.60	30.16	27.85	58.01	74.00	-15.99	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE20	Test Channel	229
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11218.70	31.44	16.21	47.65	74.00	-26.35	Peak	Horizontal
*	13969.30	30.80	19.02	49.82	88.20	-38.38	Peak	Horizontal
*	14795.50	30.93	19.15	50.08	88.20	-38.12	Peak	Horizontal
	17870.80	16.24	28.08	44.32	54.00	-9.68	Average	Horizontal
	17870.80	29.90	28.08	57.98	74.00	-16.02	Peak	Horizontal
	11806.90	31.28	16.13	47.41	74.00	-26.59	Peak	Vertical
*	13981.20	30.48	19.08	49.56	88.20	-38.64	Peak	Vertical
*	14887.30	30.75	18.83	49.58	88.20	-38.62	Peak	Vertical
	17926.90	16.35	28.28	44.63	54.00	-9.37	Average	Vertical
	17926.90	29.97	28.28	58.25	74.00	-15.75	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	3
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11582.50	30.54	16.39	46.93	74.00	-27.07	Peak	Horizontal
*	14049.20	31.17	19.04	50.21	88.20	-37.99	Peak	Horizontal
*	17309.80	30.02	22.91	52.93	88.20	-35.27	Peak	Horizontal
	18000.00	16.54	27.93	44.47	54.00	-9.53	Average	Horizontal
	18000.00	26.62	27.93	54.55	74.00	-19.45	Peak	Horizontal
*	10265.00	32.80	13.81	46.61	88.20	-41.59	Peak	Vertical
	11478.80	30.89	16.35	47.24	74.00	-26.76	Peak	Vertical
*	17110.90	29.57	21.33	50.90	88.20	-37.30	Peak	Vertical
	17867.40	16.44	28.26	44.70	54.00	-9.30	Average	Vertical
	17867.40	29.50	28.26	57.76	74.00	-16.24	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	51
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8272.60	38.63	10.33	48.96	74.00	-25.04	Peak	Horizontal
*	14278.70	31.22	19.12	50.34	88.20	-37.86	Peak	Horizontal
*	17214.60	29.86	22.38	52.24	88.20	-35.96	Peak	Horizontal
	17989.80	16.38	27.88	44.26	54.00	-9.74	Average	Horizontal
	17989.80	29.86	27.88	57.74	74.00	-16.26	Peak	Horizontal
*	10256.50	32.54	13.73	46.27	88.20	-41.93	Peak	Vertical
	11495.80	31.74	16.41	48.15	74.00	-25.85	Peak	Vertical
*	17189.10	29.74	21.96	51.70	88.20	-36.50	Peak	Vertical
	17950.70	16.28	28.61	44.89	54.00	-9.11	Average	Vertical
	17950.70	30.09	28.61	58.70	74.00	-15.30	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	91
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9829.80	33.81	13.10	46.91	88.20	-41.29	Peak	Horizontal
	11574.00	30.77	16.35	47.12	74.00	-26.88	Peak	Horizontal
*	17299.60	30.09	22.84	52.93	88.20	-35.27	Peak	Horizontal
	18000.00	16.47	27.93	44.40	54.00	-9.60	Average	Horizontal
	18000.00	26.56	27.93	54.49	74.00	-19.51	Peak	Horizontal
*	10278.60	32.57	13.98	46.55	88.20	-41.65	Peak	Vertical
	11057.20	31.53	15.74	47.27	74.00	-26.73	Peak	Vertical
*	17032.70	30.52	20.97	51.49	88.20	-36.71	Peak	Vertical
	17945.60	16.38	28.60	44.98	54.00	-9.02	Average	Vertical
	17945.60	29.51	28.60	58.11	74.00	-15.89	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	99
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	12126.50	30.82	16.10	46.92	74.00	-27.08	Peak	Horizontal
*	14113.80	31.58	18.89	50.47	88.20	-37.73	Peak	Horizontal
*	17036.10	30.05	20.98	51.03	88.20	-37.17	Peak	Horizontal
	17957.50	16.37	28.48	44.85	54.00	-9.15	Average	Horizontal
	17957.50	30.11	28.48	58.59	74.00	-15.41	Peak	Horizontal
*	10188.50	33.07	13.55	46.62	88.20	-41.58	Peak	Vertical
	11211.90	31.11	16.23	47.34	74.00	-26.66	Peak	Vertical
*	17381.20	30.56	23.23	53.79	88.20	-34.41	Peak	Vertical
	17925.20	16.27	28.23	44.50	54.00	-9.50	Average	Vertical
	17925.20	30.14	28.23	58.37	74.00	-15.63	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	107
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10115.40	33.39	13.20	46.59	88.20	-41.61	Peak	Horizontal
	11347.90	31.28	16.09	47.37	74.00	-26.63	Peak	Horizontal
*	17127.90	30.60	21.40	52.00	88.20	-36.20	Peak	Horizontal
	17943.90	16.54	28.58	45.12	54.00	-8.88	Average	Horizontal
	17943.90	29.82	28.58	58.40	74.00	-15.60	Peak	Horizontal
*	9831.50	32.29	13.10	45.39	88.20	-42.81	Peak	Vertical
	11480.50	30.65	16.36	47.01	74.00	-26.99	Peak	Vertical
*	17044.60	31.03	20.93	51.96	88.20	-36.24	Peak	Vertical
	17949.00	16.54	28.64	45.18	54.00	-8.82	Average	Vertical
	17949.00	29.72	28.64	58.36	74.00	-15.64	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	115
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11111.60	31.92	16.05	47.97	74.00	-26.03	Peak	Horizontal
*	13634.40	33.02	18.36	51.38	88.20	-36.82	Peak	Horizontal
*	17185.70	28.69	21.85	50.54	88.20	-37.66	Peak	Horizontal
	17966.00	16.54	28.30	44.84	54.00	-9.16	Average	Horizontal
	17966.00	29.99	28.30	58.29	74.00	-15.71	Peak	Horizontal
*	10025.30	32.68	13.09	45.77	88.20	-42.43	Peak	Vertical
	10936.50	32.13	15.90	48.03	74.00	-25.97	Peak	Vertical
*	17212.90	31.02	22.38	53.40	88.20	-34.80	Peak	Vertical
	17935.40	16.34	28.50	44.84	54.00	-9.16	Average	Vertical
	17935.40	29.55	28.50	58.05	74.00	-15.95	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	123
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9807.70	32.40	13.06	45.46	88.20	-42.74	Peak	Horizontal
	11448.20	31.58	16.27	47.85	74.00	-26.15	Peak	Horizontal
*	17357.40	31.40	22.77	54.17	88.20	-34.03	Peak	Horizontal
	18000.00	16.34	27.93	44.27	54.00	-9.73	Average	Horizontal
	18000.00	26.93	27.93	54.86	74.00	-19.14	Peak	Horizontal
*	10270.10	32.92	13.86	46.78	88.20	-41.42	Peak	Vertical
	11201.70	31.37	16.17	47.54	74.00	-26.46	Peak	Vertical
*	17105.80	30.16	21.29	51.45	88.20	-36.75	Peak	Vertical
	17945.60	16.24	28.60	44.84	54.00	-9.16	Average	Vertical
	17945.60	30.87	28.60	59.47	74.00	-14.53	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	147
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10248.00	32.72	13.66	46.38	88.20	-41.82	Peak	Horizontal
	11670.90	31.31	16.38	47.69	74.00	-26.31	Peak	Horizontal
*	17014.00	30.15	20.80	50.95	88.20	-37.25	Peak	Horizontal
	17848.70	16.11	28.54	44.65	54.00	-9.35	Average	Horizontal
	17848.70	29.93	28.54	58.47	74.00	-15.53	Peak	Horizontal
*	9760.10	33.59	12.90	46.49	88.20	-41.71	Peak	Vertical
	11550.20	31.21	16.30	47.51	74.00	-26.49	Peak	Vertical
*	17133.00	29.91	21.37	51.28	88.20	-36.92	Peak	Vertical
	17962.60	16.57	28.38	44.95	54.00	-9.05	Average	Vertical
	17962.60	29.50	28.38	57.88	74.00	-16.12	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	179
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	10875.30	33.58	15.36	48.94	74.00	-25.06	Peak	Horizontal
*	13916.60	30.48	18.72	49.20	88.20	-39.00	Peak	Horizontal
*	17195.90	30.61	22.13	52.74	88.20	-35.46	Peak	Horizontal
	17864.00	16.34	28.44	44.78	54.00	-9.22	Average	Horizontal
	17864.00	29.38	28.44	57.82	74.00	-16.18	Peak	Horizontal
*	9914.80	32.62	13.01	45.63	88.20	-42.57	Peak	Vertical
	11472.00	31.51	16.31	47.82	74.00	-26.18	Peak	Vertical
*	17146.60	30.55	21.27	51.82	88.20	-36.38	Peak	Vertical
	17753.50	16.27	27.60	43.87	54.00	-10.13	Average	Vertical
	17753.50	29.71	27.60	57.31	74.00	-16.69	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	187
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10276.90	32.10	13.96	46.06	88.20	-42.14	Peak	Horizontal
	11473.70	31.38	16.32	47.70	74.00	-26.30	Peak	Horizontal
*	16859.30	30.77	20.63	51.40	88.20	-36.80	Peak	Horizontal
	17836.80	16.35	28.00	44.35	54.00	-9.65	Average	Horizontal
	17836.80	30.65	28.00	58.65	74.00	-15.35	Peak	Horizontal
*	10016.80	33.23	13.12	46.35	88.20	-41.85	Peak	Vertical
	11052.10	32.05	15.80	47.85	74.00	-26.15	Peak	Vertical
*	17110.90	30.57	21.33	51.90	88.20	-36.30	Peak	Vertical
	17955.80	16.35	28.51	44.86	54.00	-9.14	Average	Vertical
	17955.80	29.81	28.51	58.32	74.00	-15.68	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	195
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10142.60	33.09	13.17	46.26	88.20	-41.94	Peak	Horizontal
	11538.30	30.63	16.31	46.94	74.00	-27.06	Peak	Horizontal
*	17231.60	29.93	22.25	52.18	88.20	-36.02	Peak	Horizontal
	17932.00	16.24	28.47	44.71	54.00	-9.29	Average	Horizontal
	17932.00	30.15	28.47	58.62	74.00	-15.38	Peak	Horizontal
*	9919.90	32.73	13.02	45.75	88.20	-42.45	Peak	Vertical
	11519.60	30.91	16.37	47.28	74.00	-26.72	Peak	Vertical
*	17058.20	30.03	20.84	50.87	88.20	-37.33	Peak	Vertical
	17959.20	16.34	28.45	44.79	54.00	-9.21	Average	Vertical
	17959.20	30.87	28.45	59.32	74.00	-14.68	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	211
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9831.50	32.98	13.10	46.08	88.20	-42.12	Peak	Horizontal
	11313.90	30.67	16.32	46.99	74.00	-27.01	Peak	Horizontal
*	17002.10	30.14	20.66	50.80	88.20	-37.40	Peak	Horizontal
	17955.80	16.21	28.51	44.72	54.00	-9.28	Average	Horizontal
	17955.80	30.05	28.51	58.56	74.00	-15.44	Peak	Horizontal
*	9828.10	33.95	13.10	47.05	88.20	-41.15	Peak	Vertical
	11040.20	31.80	15.93	47.73	74.00	-26.27	Peak	Vertical
*	16939.20	29.49	20.57	50.06	88.20	-38.14	Peak	Vertical
	17926.90	16.34	28.28	44.62	54.00	-9.38	Average	Vertical
	17926.90	29.98	28.28	58.26	74.00	-15.74	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE40	Test Channel	227
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10030.40	32.64	13.05	45.69	88.20	-42.51	Peak	Horizontal
	11613.10	30.71	16.33	47.04	74.00	-26.96	Peak	Horizontal
*	17484.90	31.67	23.85	55.52	88.20	-32.68	Peak	Horizontal
	17945.60	16.11	28.60	44.71	54.00	-9.29	Average	Horizontal
	17945.60	29.35	28.60	57.95	74.00	-16.05	Peak	Horizontal
*	9911.40	32.79	13.00	45.79	88.20	-42.41	Peak	Vertical
	11380.20	31.03	16.22	47.25	74.00	-26.75	Peak	Vertical
*	16908.60	30.00	20.45	50.45	88.20	-37.75	Peak	Vertical
	17945.60	16.31	28.60	44.91	54.00	-9.09	Average	Vertical
	17945.60	28.95	28.60	57.55	74.00	-16.45	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	7
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	10882.10	32.46	15.30	47.76	74.00	-26.24	Peak	Horizontal
*	14045.80	28.66	19.01	47.67	88.20	-40.53	Peak	Horizontal
*	16862.70	30.67	20.64	51.31	88.20	-36.89	Peak	Horizontal
	18000.00	16.24	27.93	44.17	54.00	-9.83	Average	Horizontal
	18000.00	28.97	27.93	56.90	74.00	-17.10	Peak	Horizontal
*	10106.90	33.99	13.20	47.19	88.20	-41.01	Peak	Vertical
	11585.90	31.04	16.39	47.43	74.00	-26.57	Peak	Vertical
*	17226.50	30.57	22.33	52.90	88.20	-35.30	Peak	Vertical
	17847.00	16.27	28.53	44.80	54.00	-9.20	Average	Vertical
	17847.00	29.70	28.53	58.23	74.00	-15.77	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	55
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8299.80	37.17	10.49	47.66	74.00	-26.34	Peak	Horizontal
*	10020.20	33.01	13.13	46.14	88.20	-42.06	Peak	Horizontal
*	14151.20	30.03	19.38	49.41	88.20	-38.79	Peak	Horizontal
	17943.90	16.32	28.58	44.90	54.00	-9.10	Average	Horizontal
	17943.90	30.31	28.58	58.89	74.00	-15.11	Peak	Horizontal
*	10011.70	32.90	13.09	45.99	88.20	-42.21	Peak	Vertical
	10880.40	32.45	15.30	47.75	74.00	-26.25	Peak	Vertical
*	17211.20	29.41	22.39	51.80	88.20	-36.40	Peak	Vertical
	17940.50	16.24	28.55	44.79	54.00	-9.21	Average	Vertical
	17940.50	29.10	28.55	57.65	74.00	-16.35	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	87
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9823.00	32.49	13.10	45.59	88.20	-42.61	Peak	Horizontal
	11014.70	31.75	15.86	47.61	74.00	-26.39	Peak	Horizontal
*	16886.50	30.39	20.46	50.85	88.20	-37.35	Peak	Horizontal
	17925.20	16.31	28.23	44.54	54.00	-9.46	Average	Horizontal
	17925.20	29.41	28.23	57.64	74.00	-16.36	Peak	Horizontal
*	9948.80	32.57	13.03	45.60	88.20	-42.60	Peak	Vertical
	11548.50	30.83	16.30	47.13	74.00	-26.87	Peak	Vertical
*	16934.10	29.87	20.56	50.43	88.20	-37.77	Peak	Vertical
	17923.50	16.31	28.18	44.49	54.00	-9.51	Average	Vertical
	17923.50	29.93	28.18	58.11	74.00	-15.89	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	103
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10161.30	32.91	13.24	46.15	88.20	-42.05	Peak	Horizontal
	11424.40	30.70	16.38	47.08	74.00	-26.92	Peak	Horizontal
*	17131.30	31.74	21.38	53.12	88.20	-35.08	Peak	Horizontal
	17947.30	16.11	28.63	44.74	54.00	-9.26	Average	Horizontal
	17947.30	29.33	28.63	57.96	74.00	-16.04	Peak	Horizontal
*	9792.40	32.98	12.99	45.97	88.20	-42.23	Peak	Vertical
	11466.90	30.80	16.27	47.07	74.00	-26.93	Peak	Vertical
*	16903.50	29.92	20.44	50.36	88.20	-37.84	Peak	Vertical
	17937.10	16.35	28.52	44.87	54.00	-9.13	Average	Vertical
	17937.10	29.30	28.52	57.82	74.00	-16.18	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	119
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10061.00	32.25	13.00	45.25	88.20	-42.95	Peak	Horizontal
	11652.20	30.86	16.34	47.20	74.00	-26.80	Peak	Horizontal
*	16862.70	30.07	20.64	50.71	88.20	-37.49	Peak	Horizontal
	17850.40	16.30	28.56	44.86	54.00	-9.14	Average	Horizontal
	17850.40	29.98	28.56	58.54	74.00	-15.46	Peak	Horizontal
*	10188.50	32.59	13.55	46.14	88.20	-42.06	Peak	Vertical
	11536.60	31.37	16.32	47.69	74.00	-26.31	Peak	Vertical
*	16912.00	29.77	20.46	50.23	88.20	-37.97	Peak	Vertical
	17952.40	16.21	28.58	44.79	54.00	-9.21	Average	Vertical
	17952.40	30.17	28.58	58.75	74.00	-15.25	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	135
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10103.50	32.69	13.19	45.88	88.20	-42.32	Peak	Horizontal
	11504.30	30.74	16.41	47.15	74.00	-26.85	Peak	Horizontal
*	17058.20	30.72	20.84	51.56	88.20	-36.64	Peak	Horizontal
	17940.50	16.37	28.55	44.92	54.00	-9.08	Average	Horizontal
	17940.50	29.50	28.55	58.05	74.00	-15.95	Peak	Horizontal
*	10197.00	32.74	13.61	46.35	88.20	-41.85	Peak	Vertical
	11470.30	31.49	16.30	47.79	74.00	-26.21	Peak	Vertical
*	17102.40	31.31	21.22	52.53	88.20	-35.67	Peak	Vertical
	17901.40	16.27	27.44	43.71	54.00	-10.29	Average	Vertical
	17901.40	30.91	27.44	58.35	74.00	-15.65	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	151
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10333.00	32.23	14.16	46.39	88.20	-41.81	Peak	Horizontal
	11470.30	31.49	16.30	47.79	74.00	-26.21	Peak	Horizontal
*	17221.40	31.08	22.35	53.43	88.20	-34.77	Peak	Horizontal
	17937.10	16.32	28.52	44.84	54.00	-9.16	Average	Horizontal
	17937.10	30.10	28.52	58.62	74.00	-15.38	Peak	Horizontal
*	9806.00	32.57	13.05	45.62	88.20	-42.58	Peak	Vertical
	11138.80	31.18	16.12	47.30	74.00	-26.70	Peak	Vertical
*	16742.00	30.86	19.96	50.82	88.20	-37.38	Peak	Vertical
	17841.90	16.32	28.32	44.64	54.00	-9.36	Average	Vertical
	17841.90	30.14	28.32	58.46	74.00	-15.54	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	167
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10190.20	31.37	13.57	44.94	88.20	-43.26	Peak	Horizontal
	11427.80	31.61	16.36	47.97	74.00	-26.03	Peak	Horizontal
*	17053.10	30.12	20.86	50.98	88.20	-37.22	Peak	Horizontal
	17857.20	16.32	28.61	44.93	54.00	-9.07	Average	Horizontal
	17857.20	29.22	28.61	57.83	74.00	-16.17	Peak	Horizontal
*	10139.20	32.73	13.17	45.90	88.20	-42.30	Peak	Vertical
	11206.80	30.63	16.24	46.87	74.00	-27.13	Peak	Vertical
*	16723.30	30.57	19.76	50.33	88.20	-37.87	Peak	Vertical
	17959.20	16.24	28.45	44.69	54.00	-9.31	Average	Vertical
	17959.20	30.86	28.45	59.31	74.00	-14.69	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	183
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9930.10	32.99	13.03	46.02	88.20	-42.18	Peak	Horizontal
	11436.30	31.30	16.33	47.63	74.00	-26.37	Peak	Horizontal
*	16920.50	30.88	20.49	51.37	88.20	-36.83	Peak	Horizontal
	17857.20	16.24	28.61	44.85	54.00	-9.15	Average	Horizontal
	17857.20	29.07	28.61	57.68	74.00	-16.32	Peak	Horizontal
*	9936.90	32.92	13.04	45.96	88.20	-42.24	Peak	Vertical
	10955.20	31.95	15.77	47.72	74.00	-26.28	Peak	Vertical
*	16716.50	31.25	19.66	50.91	88.20	-37.29	Peak	Vertical
	17933.70	16.24	28.49	44.73	54.00	-9.27	Average	Vertical
	17933.70	29.71	28.49	58.20	74.00	-15.80	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	199
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11507.70	31.51	16.40	47.91	74.00	-26.09	Peak	Horizontal
*	14192.00	30.95	19.02	49.97	88.20	-38.23	Peak	Horizontal
*	17017.40	29.98	20.86	50.84	88.20	-37.36	Peak	Horizontal
	17857.20	16.11	28.61	44.72	54.00	-9.28	Average	Horizontal
	17857.20	29.76	28.61	58.37	74.00	-15.63	Peak	Horizontal
*	10023.60	33.19	13.11	46.30	88.20	-41.90	Peak	Vertical
	11529.80	30.81	16.33	47.14	74.00	-26.86	Peak	Vertical
*	17204.40	30.08	22.31	52.39	88.20	-35.81	Peak	Vertical
	17974.50	16.24	28.08	44.32	54.00	-9.68	Average	Vertical
	17974.50	30.47	28.08	58.55	74.00	-15.45	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE80	Test Channel	215
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11524.70	31.47	16.35	47.82	74.00	-26.18	Peak	Horizontal
*	14331.40	31.00	19.24	50.24	88.20	-37.96	Peak	Horizontal
*	16850.80	29.98	20.61	50.59	88.20	-37.61	Peak	Horizontal
	17843.60	16.34	28.42	44.76	54.00	-9.24	Average	Horizontal
	17843.60	29.98	28.42	58.40	74.00	-15.60	Peak	Horizontal
*	10276.90	33.08	13.96	47.04	88.20	-41.16	Peak	Vertical
	11380.20	31.60	16.22	47.82	74.00	-26.18	Peak	Vertical
*	17117.70	30.95	21.38	52.33	88.20	-35.87	Peak	Vertical
	17843.60	16.34	28.42	44.76	54.00	-9.24	Average	Vertical
	17843.60	29.98	28.42	58.40	74.00	-15.60	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	15
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8032.90	38.69	10.79	49.48	74.00	-24.52	Peak	Horizontal
*	9889.30	33.05	12.96	46.01	88.20	-42.19	Peak	Horizontal
*	17161.90	30.31	21.29	51.60	88.20	-36.60	Peak	Horizontal
	17993.20	16.24	27.90	44.14	54.00	-9.86	Average	Horizontal
	17993.20	28.47	27.90	56.37	74.00	-17.63	Peak	Horizontal
	8032.90	35.35	10.79	46.14	74.00	-27.86	Peak	Vertical
*	14028.80	31.07	18.83	49.90	88.20	-38.30	Peak	Vertical
*	16949.40	29.52	20.59	50.11	88.20	-38.09	Peak	Vertical
	17930.30	16.34	28.42	44.76	54.00	-9.24	Average	Vertical
	17930.30	29.77	28.42	58.19	74.00	-15.81	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	47
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8247.10	37.37	10.49	47.86	74.00	-26.14	Peak	Horizontal
*	13785.70	31.17	18.49	49.66	88.20	-38.54	Peak	Horizontal
*	16883.10	31.39	20.49	51.88	88.20	-36.32	Peak	Horizontal
	17955.80	16.24	28.51	44.75	54.00	-9.25	Average	Horizontal
	17955.80	29.96	28.51	58.47	74.00	-15.53	Peak	Horizontal
*	9823.00	32.72	13.10	45.82	88.20	-42.38	Peak	Vertical
	11670.90	31.91	16.38	48.29	74.00	-25.71	Peak	Vertical
*	16660.40	30.31	19.33	49.64	88.20	-38.56	Peak	Vertical
	17847.00	16.34	28.53	44.87	54.00	-9.13	Average	Vertical
	17847.00	29.11	28.53	57.64	74.00	-16.36	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	79
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	11381.90	31.29	16.23	47.52	74.00	-26.48	Peak	Horizontal
*	13976.10	31.31	19.10	50.41	88.20	-37.79	Peak	Horizontal
*	17190.80	30.70	22.01	52.71	88.20	-35.49	Peak	Horizontal
	17977.90	16.58	27.99	44.57	54.00	-9.43	Average	Horizontal
	17977.90	30.43	27.99	58.42	74.00	-15.58	Peak	Horizontal
	11560.40	31.17	16.31	47.48	74.00	-26.52	Peak	Vertical
*	14380.70	31.87	19.14	51.01	88.20	-37.19	Peak	Vertical
*	16930.70	30.85	20.55	51.40	88.20	-36.80	Peak	Vertical
	17911.60	16.34	27.85	44.19	54.00	-9.81	Average	Vertical
	17911.60	29.64	27.85	57.49	74.00	-16.51	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	111
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10020.20	32.92	13.13	46.05	88.20	-42.15	Peak	Horizontal
	11237.40	31.09	16.09	47.18	74.00	-26.82	Peak	Horizontal
*	16930.70	30.10	20.55	50.65	88.20	-37.55	Peak	Horizontal
	17959.20	16.18	28.45	44.63	54.00	-9.37	Average	Horizontal
	17959.20	30.44	28.45	58.89	74.00	-15.11	Peak	Horizontal
*	10290.50	31.99	14.10	46.09	88.20	-42.11	Peak	Vertical
	11606.30	30.18	16.36	46.54	74.00	-27.46	Peak	Vertical
*	16849.10	29.80	20.60	50.40	88.20	-37.80	Peak	Vertical
	17974.50	16.24	28.08	44.32	54.00	-9.68	Average	Vertical
	17974.50	30.64	28.08	58.72	74.00	-15.28	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	143
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10069.50	33.16	13.00	46.16	88.20	-42.04	Peak	Horizontal
	11344.50	31.30	16.10	47.40	74.00	-26.60	Peak	Horizontal
*	16973.20	30.10	20.58	50.68	88.20	-37.52	Peak	Horizontal
	17850.40	16.54	28.56	45.10	54.00	-8.90	Average	Horizontal
	17850.40	29.62	28.56	58.18	74.00	-15.82	Peak	Horizontal
*	10259.90	32.12	13.76	45.88	88.20	-42.32	Peak	Vertical
	11120.10	30.85	16.16	47.01	74.00	-26.99	Peak	Vertical
*	17122.80	30.07	21.43	51.50	88.20	-36.70	Peak	Vertical
	17949.00	16.24	28.64	44.88	54.00	-9.12	Average	Vertical
	17949.00	29.63	28.64	58.27	74.00	-15.73	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	175
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10203.80	32.70	13.64	46.34	88.20	-41.86	Peak	Horizontal
	11506.00	31.36	16.40	47.76	74.00	-26.24	Peak	Horizontal
*	17131.30	30.62	21.38	52.00	88.20	-36.20	Peak	Horizontal
	17933.70	16.21	28.49	44.70	54.00	-9.30	Average	Horizontal
	17933.70	30.70	28.49	59.19	74.00	-14.81	Peak	Horizontal
*	10140.90	32.39	13.17	45.56	88.20	-42.64	Peak	Vertical
	11490.70	30.92	16.40	47.32	74.00	-26.68	Peak	Vertical
*	16912.00	30.43	20.46	50.89	88.20	-37.31	Peak	Vertical
	17847.00	16.21	28.53	44.74	54.00	-9.26	Average	Vertical
	17847.00	29.41	28.53	57.94	74.00	-16.06	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11ax-HE160	Test Channel	207
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10215.70	32.87	13.64	46.51	88.20	-41.69	Peak	Horizontal
	11130.30	31.52	16.16	47.68	74.00	-26.32	Peak	Horizontal
*	17127.90	31.13	21.40	52.53	88.20	-35.67	Peak	Horizontal
	17960.90	16.21	28.42	44.63	54.00	-9.37	Average	Horizontal
	17960.90	30.47	28.42	58.89	74.00	-15.11	Peak	Horizontal
*	9950.50	33.74	13.03	46.77	88.20	-41.43	Peak	Vertical
	11614.80	32.48	16.32	48.80	74.00	-25.20	Peak	Vertical
*	16849.10	31.15	20.60	51.75	88.20	-36.45	Peak	Vertical
	17928.60	16.21	28.34	44.55	54.00	-9.45	Average	Vertical
	17928.60	30.73	28.34	59.07	74.00	-14.93	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	1
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8308.30	32.80	10.52	43.32	74.00	-30.68	Peak	Horizontal
*	10037.20	32.81	13.00	45.81	88.20	-42.39	Peak	Horizontal
*	16997.00	29.60	20.62	50.22	88.20	-37.98	Peak	Horizontal
	17949.00	16.24	28.64	44.88	54.00	-9.12	Average	Horizontal
	17949.00	29.62	28.64	58.26	74.00	-15.74	Peak	Horizontal
*	10215.70	33.77	13.64	47.41	88.20	-40.79	Peak	Vertical
	11490.70	30.85	16.40	47.25	74.00	-26.75	Peak	Vertical
*	16991.90	30.54	20.58	51.12	88.20	-37.08	Peak	Vertical
	17864.00	16.21	28.44	44.65	54.00	-9.35	Average	Vertical
	17864.00	30.61	28.44	59.05	74.00	-14.95	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	49
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8260.70	37.77	10.36	48.13	74.00	-25.87	Peak	Horizontal
*	14071.30	30.80	19.10	49.90	88.20	-38.30	Peak	Horizontal
*	16874.60	30.25	20.57	50.82	88.20	-37.38	Peak	Horizontal
	17853.80	16.21	28.60	44.81	54.00	-9.19	Average	Horizontal
	17853.80	29.81	28.60	58.41	74.00	-15.59	Peak	Horizontal
	11480.50	31.15	16.36	47.51	74.00	-26.49	Peak	Vertical
*	14050.90	30.62	19.05	49.67	88.20	-38.53	Peak	Vertical
*	17136.40	30.10	21.34	51.44	88.20	-36.76	Peak	Vertical
	17974.50	16.34	28.08	44.42	54.00	-9.58	Average	Vertical
	17974.50	29.98	28.08	58.06	74.00	-15.94	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	93
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10271.80	32.73	13.88	46.61	88.20	-41.59	Peak	Horizontal
	11438.00	31.06	16.32	47.38	74.00	-26.62	Peak	Horizontal
*	16680.80	30.46	19.41	49.87	88.20	-38.33	Peak	Horizontal
	17937.10	16.32	28.52	44.84	54.00	-9.16	Average	Horizontal
	17937.10	30.71	28.52	59.23	74.00	-14.77	Peak	Horizontal
*	9806.00	33.62	13.05	46.67	88.20	-41.53	Peak	Vertical
	11142.20	30.95	16.08	47.03	74.00	-26.97	Peak	Vertical
*	17116.00	31.30	21.37	52.67	88.20	-35.53	Peak	Vertical
	17828.30	16.21	27.45	43.66	54.00	-10.34	Average	Vertical
	17828.30	30.37	27.45	57.82	74.00	-16.18	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	97
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10020.20	33.71	13.13	46.84	88.20	-41.36	Peak	Horizontal
	11313.90	30.40	16.32	46.72	74.00	-27.28	Peak	Horizontal
*	17136.40	30.51	21.34	51.85	88.20	-36.35	Peak	Horizontal
	17950.70	16.05	28.61	44.66	54.00	-9.34	Average	Horizontal
	17950.70	30.17	28.61	58.78	74.00	-15.22	Peak	Horizontal
*	10161.30	32.12	13.24	45.36	88.20	-42.84	Peak	Vertical
	11230.60	30.62	16.14	46.76	74.00	-27.24	Peak	Vertical
*	17032.70	30.05	20.97	51.02	88.20	-37.18	Peak	Vertical
	17938.80	16.32	28.53	44.85	54.00	-9.15	Average	Vertical
	17938.80	29.09	28.53	57.62	74.00	-16.38	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	105
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10214.00	33.34	13.64	46.98	88.20	-41.22	Peak	Horizontal
	11890.20	31.53	16.06	47.59	74.00	-26.41	Peak	Horizontal
*	17107.50	29.51	21.30	50.81	88.20	-37.39	Peak	Horizontal
	17977.90	16.32	27.99	44.31	54.00	-9.69	Average	Horizontal
	17977.90	29.66	27.99	57.65	74.00	-16.35	Peak	Horizontal
*	10062.70	33.19	13.00	46.19	88.20	-42.01	Peak	Vertical
	11608.00	31.75	16.35	48.10	74.00	-25.90	Peak	Vertical
*	17134.70	30.54	21.35	51.89	88.20	-36.31	Peak	Vertical
	17942.20	16.09	28.57	44.66	54.00	-9.34	Average	Vertical
	17942.20	30.55	28.57	59.12	74.00	-14.88	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	113
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9816.20	33.01	13.09	46.10	88.20	-42.10	Peak	Horizontal
	11434.60	30.98	16.34	47.32	74.00	-26.68	Peak	Horizontal
*	17221.40	31.80	22.35	54.15	88.20	-34.05	Peak	Horizontal
	17831.70	16.54	27.67	44.21	54.00	-9.79	Average	Horizontal
	17831.70	30.50	27.67	58.17	74.00	-15.83	Peak	Horizontal
*	9868.90	32.72	12.96	45.68	88.20	-42.52	Peak	Vertical
	11109.90	31.18	16.03	47.21	74.00	-26.79	Peak	Vertical
*	17107.50	30.31	21.30	51.61	88.20	-36.59	Peak	Vertical
	17911.60	16.32	27.85	44.17	54.00	-9.83	Average	Vertical
	17911.60	30.65	27.85	58.50	74.00	-15.50	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	117
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10132.40	33.95	13.18	47.13	88.20	-41.07	Peak	Horizontal
	11563.80	31.06	16.32	47.38	74.00	-26.62	Peak	Horizontal
*	17109.20	31.63	21.31	52.94	88.20	-35.26	Peak	Horizontal
	17981.30	16.34	27.91	44.25	54.00	-9.75	Average	Horizontal
	17981.30	29.72	27.90	57.62	74.00	-16.38	Peak	Horizontal
*	10195.30	32.30	13.61	45.91	88.20	-42.29	Peak	Vertical
	11132.00	31.43	16.16	47.59	74.00	-26.41	Peak	Vertical
*	17221.40	30.85	22.35	53.20	88.20	-35.00	Peak	Vertical
	17949.00	16.24	28.64	44.88	54.00	-9.12	Average	Vertical
	17949.00	29.87	28.64	58.51	74.00	-15.49	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	149
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8034.60	39.53	10.80	50.33	74.00	-23.67	Peak	Horizontal
*	10042.30	33.12	12.99	46.11	88.20	-42.09	Peak	Horizontal
*	16665.50	29.85	19.36	49.21	88.20	-38.99	Peak	Horizontal
	17940.50	16.24	28.55	44.79	54.00	-9.21	Average	Horizontal
	17940.50	29.20	28.55	57.75	74.00	-16.25	Peak	Horizontal
	8034.60	36.89	10.80	47.69	74.00	-26.31	Peak	Vertical
*	9836.60	32.16	13.08	45.24	88.20	-42.96	Peak	Vertical
*	17105.80	29.81	21.29	51.10	88.20	-37.10	Peak	Vertical
	17760.30	16.14	27.62	43.76	54.00	-10.24	Average	Vertical
	17760.30	29.71	27.62	57.33	74.00	-16.67	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	181
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10171.50	32.55	13.34	45.89	88.20	-42.31	Peak	Horizontal
	11482.20	31.66	16.37	48.03	74.00	-25.97	Peak	Horizontal
*	16849.10	30.06	20.60	50.66	88.20	-37.54	Peak	Horizontal
	17971.10	16.25	28.17	44.42	54.00	-9.58	Average	Horizontal
	17971.10	30.15	28.17	58.32	74.00	-15.68	Peak	Horizontal
*	10215.70	32.37	13.64	46.01	88.20	-42.19	Peak	Vertical
	11582.50	31.77	16.39	48.16	74.00	-25.84	Peak	Vertical
*	17233.30	30.90	22.22	53.12	88.20	-35.08	Peak	Vertical
	17852.10	16.24	28.58	44.82	54.00	-9.18	Average	Vertical
	17852.10	28.95	28.58	57.53	74.00	-16.47	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	185
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8250.50	37.66	10.46	48.12	74.00	-25.88	Peak	Horizontal
*	13904.70	31.45	18.80	50.25	88.20	-37.95	Peak	Horizontal
*	16684.20	31.22	19.41	50.63	88.20	-37.57	Peak	Horizontal
	17913.30	16.25	27.89	44.14	54.00	-9.86	Average	Horizontal
	17913.30	30.50	27.89	58.39	74.00	-15.61	Peak	Horizontal
	8250.50	36.75	10.46	47.21	74.00	-26.79	Peak	Vertical
*	10123.90	32.11	13.20	45.31	88.20	-42.89	Peak	Vertical
*	17117.70	31.47	21.38	52.85	88.20	-35.35	Peak	Vertical
	17864.00	16.24	28.44	44.68	54.00	-9.32	Average	Vertical
	17864.00	30.63	28.44	59.07	74.00	-14.93	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	189
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10178.30	32.56	13.43	45.99	88.20	-42.21	Peak	Horizontal
	11478.80	30.85	16.35	47.20	74.00	-26.80	Peak	Horizontal
*	16789.60	30.93	20.08	51.01	88.20	-37.19	Peak	Horizontal
	17826.60	16.24	27.32	43.56	54.00	-10.44	Average	Horizontal
	17826.60	30.74	27.32	58.06	74.00	-15.94	Peak	Horizontal
*	10560.80	33.47	14.69	48.16	88.20	-40.04	Peak	Vertical
	11650.50	30.87	16.33	47.20	74.00	-26.80	Peak	Vertical
*	16701.20	30.27	19.49	49.76	88.20	-38.44	Peak	Vertical
	17952.40	16.24	28.58	44.82	54.00	-9.18	Average	Vertical
	17952.40	29.53	28.58	58.11	74.00	-15.89	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	209
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10268.40	33.17	13.85	47.02	88.20	-41.18	Peak	Horizontal
	11606.30	31.85	16.36	48.21	74.00	-25.79	Peak	Horizontal
*	16752.20	30.41	20.03	50.44	88.20	-37.76	Peak	Horizontal
	17943.90	16.24	28.58	44.82	54.00	-9.18	Average	Horizontal
	17943.90	30.49	28.58	59.07	74.00	-14.93	Peak	Horizontal
*	10268.40	31.77	13.85	45.62	88.20	-42.58	Peak	Vertical
	11704.90	31.70	16.22	47.92	74.00	-26.08	Peak	Vertical
*	17206.10	29.93	22.34	52.27	88.20	-35.93	Peak	Vertical
	17960.90	16.24	28.42	44.66	54.00	-9.34	Average	Vertical
	17960.90	29.59	28.42	58.01	74.00	-15.99	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT20	Test Channel	229
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9902.90	33.86	12.98	46.84	88.20	-41.36	Peak	Horizontal
	11438.00	30.53	16.32	46.85	74.00	-27.15	Peak	Horizontal
*	16750.50	29.74	20.02	49.76	88.20	-38.44	Peak	Horizontal
	17772.20	16.24	27.19	43.43	54.00	-10.57	Average	Horizontal
	17772.20	30.57	27.19	57.76	74.00	-16.24	Peak	Horizontal
*	9918.20	32.64	13.01	45.65	88.20	-42.55	Peak	Vertical
	11307.10	30.87	16.32	47.19	74.00	-26.81	Peak	Vertical
*	17007.20	30.45	20.71	51.16	88.20	-37.04	Peak	Vertical
	17865.70	16.24	28.35	44.59	54.00	-9.41	Average	Vertical
	17865.70	30.45	28.35	58.80	74.00	-15.20	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	3
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10266.70	32.89	13.83	46.72	88.20	-41.48	Peak	Horizontal
	11458.40	31.43	16.25	47.68	74.00	-26.32	Peak	Horizontal
*	16774.30	31.16	20.10	51.26	88.20	-36.94	Peak	Horizontal
	17935.40	16.24	28.50	44.74	54.00	-9.26	Average	Horizontal
	17935.40	30.45	28.50	58.95	74.00	-15.05	Peak	Horizontal
*	9782.20	33.04	12.93	45.97	88.20	-42.23	Peak	Vertical
	11489.00	30.90	16.39	47.29	74.00	-26.71	Peak	Vertical
*	17148.30	31.36	21.26	52.62	88.20	-35.58	Peak	Vertical
	17763.70	16.24	27.48	43.72	54.00	-10.28	Average	Vertical
	17763.70	29.17	27.48	56.65	74.00	-17.35	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	51
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8274.30	39.87	10.33	50.20	74.00	-23.80	Peak	Horizontal
*	10222.50	32.80	13.63	46.43	88.20	-41.77	Peak	Horizontal
*	17129.60	30.38	21.39	51.77	88.20	-36.43	Peak	Horizontal
	17947.30	16.24	28.63	44.87	54.00	-9.13	Average	Horizontal
	17947.30	29.50	28.63	58.13	74.00	-15.87	Peak	Horizontal
	8272.60	37.29	10.33	47.62	74.00	-26.38	Peak	Vertical
*	10095.00	32.39	13.15	45.54	88.20	-42.66	Peak	Vertical
*	17037.80	30.15	20.97	51.12	88.20	-37.08	Peak	Vertical
	17938.80	16.25	28.53	44.78	54.00	-9.22	Average	Vertical
	17938.80	29.64	28.53	58.17	74.00	-15.83	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	91
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9812.80	32.71	13.08	45.79	88.20	-42.41	Peak	Horizontal
	11657.30	31.46	16.36	47.82	74.00	-26.18	Peak	Horizontal
*	17233.30	30.34	22.22	52.56	88.20	-35.64	Peak	Horizontal
	17857.20	16.24	28.61	44.85	54.00	-9.15	Average	Horizontal
	17857.20	29.45	28.61	58.06	74.00	-15.94	Peak	Horizontal
*	10282.00	32.94	14.01	46.95	88.20	-41.25	Peak	Vertical
	11728.70	31.71	16.10	47.81	74.00	-26.19	Peak	Vertical
*	16849.10	29.29	20.60	49.89	88.20	-38.31	Peak	Vertical
	17972.80	16.24	28.12	44.36	54.00	-9.64	Average	Vertical
	17972.80	30.22	28.12	58.34	74.00	-15.66	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	99
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10103.50	32.90	13.19	46.09	88.20	-42.11	Peak	Horizontal
	11713.40	31.42	16.18	47.60	74.00	-26.40	Peak	Horizontal
*	17146.60	31.22	21.27	52.49	88.20	-35.71	Peak	Horizontal
	17869.10	16.25	28.17	44.42	54.00	-9.58	Average	Horizontal
	17869.10	28.79	28.17	56.96	74.00	-17.04	Peak	Horizontal
*	10095.00	32.85	13.15	46.00	88.20	-42.20	Peak	Vertical
	11529.80	31.01	16.33	47.34	74.00	-26.66	Peak	Vertical
*	16781.10	30.38	20.10	50.48	88.20	-37.72	Peak	Vertical
	17998.30	16.24	27.92	44.16	54.00	-9.84	Average	Vertical
	17998.30	28.48	27.92	56.40	74.00	-17.60	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	107
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8367.80	32.92	10.52	43.44	74.00	-30.56	Peak	Horizontal
*	13994.80	30.63	19.01	49.64	88.20	-38.56	Peak	Horizontal
*	16769.20	30.14	20.09	50.23	88.20	-37.97	Peak	Horizontal
	17843.60	16.24	28.42	44.66	54.00	-9.34	Average	Horizontal
	17843.60	29.50	28.42	57.92	74.00	-16.08	Peak	Horizontal
*	9833.20	32.29	13.09	45.38	88.20	-42.82	Peak	Vertical
	11599.50	30.78	16.39	47.17	74.00	-26.83	Peak	Vertical
*	17124.50	30.46	21.42	51.88	88.20	-36.32	Peak	Vertical
	17945.60	16.24	28.60	44.84	54.00	-9.16	Average	Vertical
	17945.60	29.24	28.60	57.84	74.00	-16.16	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	115
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10016.80	32.02	13.12	45.14	88.20	-43.06	Peak	Horizontal
	11512.80	31.09	16.38	47.47	74.00	-26.53	Peak	Horizontal
*	16944.30	30.23	20.58	50.81	88.20	-37.39	Peak	Horizontal
	17957.50	16.14	28.48	44.62	54.00	-9.38	Average	Horizontal
	17957.50	30.52	28.48	59.00	74.00	-15.00	Peak	Horizontal
*	10475.80	32.90	14.56	47.46	88.20	-40.74	Peak	Vertical
	11300.30	32.17	16.26	48.43	74.00	-25.57	Peak	Vertical
*	17037.80	31.44	20.97	52.41	88.20	-35.79	Peak	Vertical
	17930.30	16.24	28.42	44.66	54.00	-9.34	Average	Vertical
	17930.30	30.30	28.42	58.72	74.00	-15.28	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	123
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	10620.30	33.45	14.60	48.05	74.00	-25.95	Peak	Horizontal
*	14372.20	30.80	19.24	50.04	88.20	-38.16	Peak	Horizontal
*	16889.90	30.11	20.45	50.56	88.20	-37.64	Peak	Horizontal
	17937.10	16.22	28.52	44.74	54.00	-9.26	Average	Horizontal
	17937.10	29.03	28.52	57.55	74.00	-16.45	Peak	Horizontal
*	10280.30	33.02	13.99	47.01	88.20	-41.19	Peak	Vertical
	11648.80	31.20	16.32	47.52	74.00	-26.48	Peak	Vertical
*	17107.50	29.80	21.30	51.10	88.20	-37.10	Peak	Vertical
	17966.00	16.15	28.30	44.45	54.00	-9.55	Average	Vertical
	17966.00	29.77	28.30	58.07	74.00	-15.93	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	147
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10268.40	32.42	13.85	46.27	88.20	-41.93	Peak	Horizontal
	11050.40	31.96	15.82	47.78	74.00	-26.22	Peak	Horizontal
*	17066.70	30.83	20.82	51.65	88.20	-36.55	Peak	Horizontal
	17942.20	16.18	28.57	44.75	54.00	-9.25	Average	Horizontal
	17942.20	29.63	28.57	58.20	74.00	-15.80	Peak	Horizontal
*	9965.80	32.54	12.95	45.49	88.20	-42.71	Peak	Vertical
	11704.90	31.14	16.22	47.36	74.00	-26.64	Peak	Vertical
*	16762.40	30.52	20.09	50.61	88.20	-37.59	Peak	Vertical
	17903.10	16.31	27.51	43.82	54.00	-10.18	Average	Vertical
	17903.10	30.46	27.51	57.97	74.00	-16.03	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	179
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10146.00	32.70	13.17	45.87	88.20	-42.33	Peak	Horizontal
	11616.50	31.73	16.31	48.04	74.00	-25.96	Peak	Horizontal
*	16997.00	30.94	20.62	51.56	88.20	-36.64	Peak	Horizontal
	17938.80	16.24	28.53	44.77	54.00	-9.23	Average	Horizontal
	17938.80	29.99	28.53	58.52	74.00	-15.48	Peak	Horizontal
*	9680.20	34.34	12.66	47.00	88.20	-41.20	Peak	Vertical
	11115.00	32.21	16.10	48.31	74.00	-25.69	Peak	Vertical
*	17148.30	31.44	21.26	52.70	88.20	-35.50	Peak	Vertical
	17957.50	16.24	28.48	44.72	54.00	-9.28	Average	Vertical
	17957.50	30.13	28.48	58.61	74.00	-15.39	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	187
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10263.30	34.12	13.79	47.91	88.20	-40.29	Peak	Horizontal
	11521.30	31.37	16.36	47.73	74.00	-26.27	Peak	Horizontal
*	17117.70	31.14	21.38	52.52	88.20	-35.68	Peak	Horizontal
	17981.30	16.21	27.91	44.12	54.00	-9.88	Average	Horizontal
	17981.30	30.29	27.90	58.19	74.00	-15.81	Peak	Horizontal
*	9843.40	34.12	13.06	47.18	88.20	-41.02	Peak	Vertical
	11528.10	31.17	16.34	47.51	74.00	-26.49	Peak	Vertical
*	17224.80	31.19	22.34	53.53	88.20	-34.67	Peak	Vertical
	17836.80	16.26	28.00	44.26	54.00	-9.74	Average	Vertical
	17836.80	30.58	28.00	58.58	74.00	-15.42	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	195
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10203.80	33.61	13.64	47.25	88.20	-40.95	Peak	Horizontal
	11048.70	32.31	15.84	48.15	74.00	-25.85	Peak	Horizontal
*	17277.50	31.41	22.49	53.90	88.20	-34.30	Peak	Horizontal
	17835.10	16.24	27.89	44.13	54.00	-9.87	Average	Horizontal
	17835.10	30.16	27.89	58.05	74.00	-15.95	Peak	Horizontal
*	9863.80	33.16	12.96	46.12	88.20	-42.08	Peak	Vertical
	11704.90	31.75	16.22	47.97	74.00	-26.03	Peak	Vertical
*	16963.00	30.29	20.59	50.88	88.20	-37.32	Peak	Vertical
	17938.80	16.32	28.53	44.85	54.00	-9.15	Average	Vertical
	17938.80	29.85	28.53	58.38	74.00	-15.62	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	211
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10217.40	32.19	13.64	45.83	88.20	-42.37	Peak	Horizontal
	11390.40	30.52	16.30	46.82	74.00	-27.18	Peak	Horizontal
*	17054.80	29.79	20.85	50.64	88.20	-37.56	Peak	Horizontal
	17853.80	16.20	28.60	44.80	54.00	-9.20	Average	Horizontal
	17853.80	29.65	28.60	58.25	74.00	-15.75	Peak	Horizontal
*	9816.20	32.40	13.09	45.49	88.20	-42.71	Peak	Vertical
	11659.00	31.50	16.37	47.87	74.00	-26.13	Peak	Vertical
*	16769.20	30.61	20.09	50.70	88.20	-37.50	Peak	Vertical
	17972.80	16.32	28.12	44.44	54.00	-9.56	Average	Vertical
	17972.80	29.96	28.12	58.08	74.00	-15.92	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT40	Test Channel	227
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10134.10	34.59	13.18	47.77	88.20	-40.43	Peak	Horizontal
	11475.40	31.50	16.33	47.83	74.00	-26.17	Peak	Horizontal
*	17214.60	30.89	22.38	53.27	88.20	-34.93	Peak	Horizontal
	17855.50	16.21	28.62	44.83	54.00	-9.17	Average	Horizontal
	17855.50	29.41	28.62	58.03	74.00	-15.97	Peak	Horizontal
*	10086.50	33.17	13.10	46.27	88.20	-41.93	Peak	Vertical
	11444.80	30.76	16.28	47.04	74.00	-26.96	Peak	Vertical
*	16759.00	30.54	20.07	50.61	88.20	-37.59	Peak	Vertical
	17850.40	16.31	28.56	44.87	54.00	-9.13	Average	Vertical
	17850.40	29.44	28.56	58.00	74.00	-16.00	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	7
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10365.30	31.60	14.28	45.88	88.20	-42.32	Peak	Horizontal
	11096.30	31.65	15.82	47.47	74.00	-26.53	Peak	Horizontal
*	16944.30	31.61	20.58	52.19	88.20	-36.01	Peak	Horizontal
	17751.80	16.11	27.58	43.69	54.00	-10.31	Average	Horizontal
	17751.80	31.04	27.58	58.62	74.00	-15.38	Peak	Horizontal
*	10171.50	33.25	13.34	46.59	88.20	-41.61	Peak	Vertical
	11579.10	31.37	16.37	47.74	74.00	-26.26	Peak	Vertical
*	16995.30	30.67	20.60	51.27	88.20	-36.93	Peak	Vertical
	17925.20	16.32	28.23	44.55	54.00	-9.45	Average	Vertical
	17925.20	30.11	28.23	58.34	74.00	-15.66	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	55
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9833.20	33.08	13.09	46.17	88.20	-42.03	Peak	Horizontal
	11472.00	31.57	16.31	47.88	74.00	-26.12	Peak	Horizontal
*	17292.80	30.61	22.80	53.41	88.20	-34.79	Peak	Horizontal
	17865.70	16.38	28.35	44.73	54.00	-9.27	Average	Horizontal
	17865.70	29.81	28.35	58.16	74.00	-15.84	Peak	Horizontal
*	10173.20	33.14	13.36	46.50	88.20	-41.70	Peak	Vertical
	11704.90	30.56	16.22	46.78	74.00	-27.22	Peak	Vertical
*	17121.10	31.08	21.41	52.49	88.20	-35.71	Peak	Vertical
	17937.10	16.32	28.52	44.84	54.00	-9.16	Average	Vertical
	17937.10	30.91	28.52	59.43	74.00	-14.57	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	87
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9823.00	32.66	13.10	45.76	88.20	-42.44	Peak	Horizontal
	11577.40	31.55	16.37	47.92	74.00	-26.08	Peak	Horizontal
*	17110.90	30.58	21.33	51.91	88.20	-36.29	Peak	Horizontal
	17874.20	16.34	27.90	44.24	54.00	-9.76	Average	Horizontal
	17874.20	30.66	27.90	58.56	74.00	-15.44	Peak	Horizontal
*	9911.40	33.02	13.00	46.02	88.20	-42.18	Peak	Vertical
	11393.80	31.46	16.34	47.80	74.00	-26.20	Peak	Vertical
*	17201.00	30.72	22.24	52.96	88.20	-35.24	Peak	Vertical
	17835.10	16.27	27.89	44.16	54.00	-9.84	Average	Vertical
	17835.10	29.86	27.89	57.75	74.00	-16.25	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	103
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10074.60	32.64	13.01	45.65	88.20	-42.55	Peak	Horizontal
	11213.60	31.48	16.22	47.70	74.00	-26.30	Peak	Horizontal
*	17124.50	30.38	21.42	51.80	88.20	-36.40	Peak	Horizontal
	17974.50	16.28	28.08	44.36	54.00	-9.64	Average	Horizontal
	17974.50	30.41	28.08	58.49	74.00	-15.51	Peak	Horizontal
*	10263.30	32.47	13.79	46.26	88.20	-41.94	Peak	Vertical
	11443.10	30.77	16.29	47.06	74.00	-26.94	Peak	Vertical
*	16876.30	29.74	20.56	50.30	88.20	-37.90	Peak	Vertical
	17933.70	16.22	28.49	44.71	54.00	-9.29	Average	Vertical
	17933.70	31.10	28.49	59.59	74.00	-14.41	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	119
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10147.70	33.15	13.17	46.32	88.20	-41.88	Peak	Horizontal
	11550.20	31.56	16.30	47.86	74.00	-26.14	Peak	Horizontal
*	16896.70	30.22	20.43	50.65	88.20	-37.55	Peak	Horizontal
	17925.20	16.19	28.23	44.42	54.00	-9.58	Average	Horizontal
	17925.20	30.18	28.23	58.41	74.00	-15.59	Peak	Horizontal
*	10142.60	33.78	13.17	46.95	88.20	-41.25	Peak	Vertical
	11582.50	31.82	16.39	48.21	74.00	-25.79	Peak	Vertical
*	17121.10	32.13	21.41	53.54	88.20	-34.66	Peak	Vertical
	17942.20	16.24	28.57	44.81	54.00	-9.19	Average	Vertical
	17942.20	29.70	28.57	58.27	74.00	-15.73	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	135
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10377.20	32.00	14.36	46.36	88.20	-41.84	Peak	1
	11611.40	31.11	16.34	47.45	74.00	-26.55	Peak	Horizontal
*	17063.30	31.46	20.83	52.29	88.20	-35.91	Peak	Horizontal
	17945.60	16.18	28.60	44.78	54.00	-9.22	Average	Horizontal
	17945.60	29.83	28.60	58.43	74.00	-15.57	Peak	Horizontal
*	9901.20	33.71	12.98	46.69	88.20	-41.51	Peak	Vertical
	11288.40	31.17	16.17	47.34	74.00	-26.66	Peak	Vertical
*	17017.40	31.16	20.86	52.02	88.20	-36.18	Peak	Vertical
	17947.30	16.52	28.63	45.15	54.00	-8.85	Average	Vertical
	17947.30	30.26	28.63	58.89	74.00	-15.11	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	151
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	9947.10	32.79	13.03	45.82	88.20	-42.38	Peak	Horizontal
	11108.20	31.20	16.00	47.20	74.00	-26.80	Peak	Horizontal
*	16672.30	30.92	19.40	50.32	88.20	-37.88	Peak	Horizontal
	17947.30	16.17	28.63	44.80	54.00	-9.20	Average	Horizontal
	17947.30	30.51	28.63	59.14	74.00	-14.86	Peak	Horizontal
*	10341.50	32.56	14.16	46.72	88.20	-41.48	Peak	Vertical
	11470.30	31.44	16.30	47.74	74.00	-26.26	Peak	Vertical
*	17221.40	30.90	22.35	53.25	88.20	-34.95	Peak	Vertical
	17855.50	16.24	28.62	44.86	54.00	-9.14	Average	Vertical
	17855.50	29.23	28.62	57.85	74.00	-16.15	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	167
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10219.10	32.30	13.64	45.94	88.20	-42.26	Peak	Horizontal
	11392.10	31.68	16.32	48.00	74.00	-26.00	Peak	Horizontal
*	17207.80	30.72	22.38	53.10	88.20	-35.10	Peak	Horizontal
	17881.00	16.15	27.60	43.75	54.00	-10.25	Average	Horizontal
	17881.00	30.49	27.60	58.09	74.00	-15.91	Peak	Horizontal
*	10089.90	33.02	13.13	46.15	88.20	-42.05	Peak	Vertical
	11574.00	31.31	16.35	47.66	74.00	-26.34	Peak	Vertical
*	16838.90	30.75	20.46	51.21	88.20	-36.99	Peak	Vertical
	17981.30	16.24	27.91	44.15	54.00	-9.85	Average	Vertical
	17981.30	30.64	27.90	58.54	74.00	-15.46	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	183
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10197.00	32.37	13.61	45.98	88.20	-42.22	Peak	Horizontal
	11562.10	30.86	16.32	47.18	74.00	-26.82	Peak	Horizontal
*	17229.90	30.73	22.28	53.01	88.20	-35.19	Peak	Horizontal
	17979.60	16.32	27.95	44.27	54.00	-9.73	Average	Horizontal
	17979.60	29.00	27.95	56.95	74.00	-17.05	Peak	Horizontal
*	10183.40	33.82	13.50	47.32	88.20	-40.88	Peak	Vertical
	11351.30	31.13	16.08	47.21	74.00	-26.79	Peak	Vertical
*	16572.00	30.87	18.68	49.55	88.20	-38.65	Peak	Vertical
	17932.00	16.24	28.47	44.71	54.00	-9.29	Average	Vertical
	17932.00	30.02	28.47	58.49	74.00	-15.51	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	199
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10259.90	32.59	13.76	46.35	88.20	-41.85	Peak	Horizontal
	11482.20	31.17	16.37	47.54	74.00	-26.46	Peak	Horizontal
*	16653.60	30.95	19.26	50.21	88.20	-37.99	Peak	Horizontal
	17926.90	16.24	28.28	44.52	54.00	-9.48	Average	Horizontal
	17926.90	30.72	28.28	59.00	74.00	-15.00	Peak	Horizontal
*	9773.70	34.19	12.90	47.09	88.20	-41.11	Peak	Vertical
	11538.30	31.98	16.31	48.29	74.00	-25.71	Peak	Vertical
*	16935.80	30.20	20.57	50.77	88.20	-37.43	Peak	Vertical
	17945.60	16.24	28.60	44.84	54.00	-9.16	Average	Vertical
	17945.60	29.41	28.60	58.01	74.00	-15.99	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT80	Test Channel	215
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
*	10231.00	32.85	13.62	46.47	88.20	-41.73	Peak	Horizontal
	11691.30	30.73	16.30	47.03	74.00	-26.97	Peak	Horizontal
*	17025.90	30.16	20.94	51.10	88.20	-37.10	Peak	Horizontal
	17841.90	16.24	28.32	44.56	54.00	-9.44	Average	Horizontal
	17841.90	29.29	28.32	57.61	74.00	-16.39	Peak	Horizontal
*	10234.40	33.26	13.61	46.87	88.20	-41.33	Peak	Vertical
	11611.40	31.57	16.34	47.91	74.00	-26.09	Peak	Vertical
*	17124.50	30.86	21.42	52.28	88.20	-35.92	Peak	Vertical
	17943.90	16.19	28.58	44.77	54.00	-9.23	Average	Vertical
	17943.90	29.35	28.58	57.93	74.00	-16.07	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)

Product	Wi-Fi 7 Tri-band Indoor Wall Plate AP	Test Engineer	Dick Shen
Test Site	WZ-AC2	Test Date	2025-07-07
Test Mode	802.11be-EHT160	Test Channel	15
Remark	1. Average measurement was not performed if peak level lower than average limit. 2. Other frequency was 20dB below limit line within 1-18GHz, there is not show in the report.		

Mark	Frequency (MHz)	Reading Level (dBuV)	Factor (dB/m)	Measure Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Polarization
	8032.90	39.79	10.79	50.58	74.00	-23.42	Peak	Horizontal
*	14144.40	30.54	19.35	49.89	88.20	-38.31	Peak	Horizontal
*	17202.70	30.10	22.27	52.37	88.20	-35.83	Peak	Horizontal
	17855.50	16.32	28.62	44.94	54.00	-9.06	Average	Horizontal
	17855.50	30.10	28.62	58.72	74.00	-15.28	Peak	Horizontal
*	10212.30	33.23	13.65	46.88	88.20	-41.32	Peak	Vertical
	11359.80	31.55	16.09	47.64	74.00	-26.36	Peak	Vertical
*	16855.90	30.99	20.62	51.61	88.20	-36.59	Peak	Vertical
	17872.50	16.21	27.99	44.20	54.00	-9.80	Average	Vertical
	17872.50	30.36	27.99	58.35	74.00	-15.65	Peak	Vertical

Note 1: "*" is not in restricted band.

Note 2: Measure Level (dBuV/m) = Reading Level (dBuV) + Factor (dB/m)

Factor (dB/m) = Cable Loss (dB) + Antenna Factor (dB/m) - Pre_Amplifier Gain (dB)