

Company: Actiontec Electronics Inc

MPE Evaluation of: Actiontec T3200BV

To: FCC CFR 47 Part 1.1310

Report No.: ATEC23-MPE All Bands Rev A

**MPE/RF EXPOSURE TEST REPORT**



# MPE/RF EXPOSURE TEST REPORT

FROM



MPE Evaluation of: Actiontec Electronics Inc T3200BV

to

To: FCC CFR 47 Part 1.1310

Test Report Serial No.: ATEC23-MPE All Bands Rev A

This report supersedes: NONE

Applicant: Actiontec Electronics Inc  
760 N Mary Avenue  
Sunnyvale, California 94085  
USA

Product Function: Bonded VDSL2/G.fast Wireless AC  
Gateway Router

Issue Date: 17th March 2017

## This Test Report is Issued Under the Authority of:

**MiCOM Labs, Inc.**  
575 Boulder Court  
Pleasanton California 94566  
USA  
Phone: +1 (925) 462-0304  
Fax: +1 (925) 462-0306  
[www.micomlabs.com](http://www.micomlabs.com)



MiCOM Labs is an ISO 17025 Accredited Testing Laboratory

## 1. MAXIMUM PERMISSABLE EXPOSURE

### Calculations for Maximum Permissible Exposure Levels

$$\text{Power Density} = P_d \text{ (mW/cm}^2\text{)} = \text{EIRP}/(4\pi d^2)$$

$$\text{EIRP} = P * G$$

P = Peak output power (mW)

G = Antenna numeric gain (numeric)

d = Separation distance (cm)

$$\text{Numeric Gain} = 10^G \text{ (dBi)/10}$$

The calculations in the table below use the highest conducted power values together with the lowest antenna gain specified for the EUT. These calculations represent worst case in terms of the exposure levels.

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Power Density (mW/cm <sup>2</sup> ) @ 20cm	Power Density Limit (mW/cm <sup>2</sup> )	Min Calculated safe distance for Limit (cm)	Calculated Power Density (mW/cm <sup>2</sup> ) @ Safe Distance
5150.0 - 5250.0	5.70	3.72	29.73	940.64	0.70	1.00	17	0.96
5725.0 - 5850.0	5.60	3.63	29.52	895.21	0.65	1.00	17	0.89
2400.0 - 2483.5	2.70	1.86	29.91	978.53	0.36	1.00	13	0.86
5250.0 - 5350.0	5.70	3.72	23.92	246.48	0.18	1.00	9	0.90
5470.0 - 5725.0	5.60	3.63	23.74	236.41	0.17	1.00	9	0.84

Assessment for simultaneous operation:

Freq. Band (MHz)	Ant Gain (dBi)	Numeric Gain (numeric)	Peak Output Power (dBm)	Peak Output Power (mW)	Calculated Safe Distance for Summation (cm)	Power Density Limit (mW/cm <sup>2</sup> ) E <sub>ref</sub>	Power Density (mW/cm <sup>2</sup> ) @New Distance E <sub>i</sub>	Summation E <sub>i</sub> /E <sub>ref</sub>
2400.0 - 2483.5	2.70	1.86	29.91	978.53	21	1.00	0.33	0.33
5150.0 - 5250.0	5.70	3.72	29.73	940.64	21	1.00	0.63	0.63
<b>Total Evaluation:</b>								<b>0.96</b>

The Total Evaluation was calculated using the formula:

$$\sum_{i=1}^n E_i / E_{ref} \leq 1$$

Where

E<sub>i</sub>: calculated E-field Strength for transmitter

E<sub>ref</sub>: E-field strength related limit

Note: for mobile or fixed location transmitters the minimum separation distance is 21cm, even if calculations indicate the MPE distance to be less.

### Specification - Maximum Permissible Exposure Limits

The Limit is defined in Table 1 of FCC §1.1310.

This test report may be reproduced in full only. The document may only be updated by MiCOM Labs personnel. All changes will be noted in the Document History section of the report.



575 Boulder Court  
Pleasanton, California 94566, USA  
Tel: +1 (925) 462 0304  
Fax: +1 (925) 462 0306  
[www.micomlabs.com](http://www.micomlabs.com)