

RF Exposure Evaluation Declaration

FCC ID: LNQT3280B

Applicant: Actiontec Electronics Inc

Product: Wi-Fi 6 DSL Modem Gateway

Model No.: T3280

Brand Name: Actiontec

FCC Classification: Digital Transmission System (DTS)

Unlicensed National Information Infrastructure (NII)

FCC Rule Part(s): Part 2.1091

Result: Complies

Reviewed By:

Kevin Guo

Approved By:

Robin Wu



The test results relate only to the samples tested.

The test results shown in the test report are traceable to the national/international standards through the calibration of the equipment and evaluated measurement uncertainty herein.

The test report shall not be reproduced except in full without the written approval of MRT Technology (Suzhou) Co., Ltd.

Revision History

Report No.	Version	Description	Issue Date	Note
2205RSU015-U4	Rev. 01	Initial Report	2022-07-18	Valid

CONTENTS

Description	Page
1. General Information	4
1.1. Applicant.....	4
1.2. Manufacturer	4
1.3. Testing Facility.....	4
1.4. Product Information.....	5
1.5. Antenna Details.....	5
2. RF Exposure Evaluation.....	7
2.1. Test Limits	7
2.2. Test Result.....	8

1. General Information

1.1. Applicant

Actiontec Electronics Inc

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.2. Manufacturer

Actiontec Electronics Inc

2445 Augustine Drive Suite 501, Santa Clara, California 95054, United States

1.3. Testing Facility

<input checked="" type="checkbox"/>	Test Site – MRT Suzhou Laboratory
	Laboratory Location (Suzhou - Wuzhong)
	D8 Building, No.2 Tian'edang Rd., Wuzhong Economic Development Zone, Suzhou, China
	Laboratory Location (Suzhou - SIP)
	4b Building, Liando U Valley, No.200 Xingpu Rd., Shengpu Town, Suzhou Industrial Park, China
	Laboratory Accreditations
	A2LA: 3628.01 CNAS: L10551
	FCC: CN1166 ISED: CN0001
	VCCI: <input type="checkbox"/> R-20025 <input type="checkbox"/> G-20034 <input type="checkbox"/> C-20020 <input type="checkbox"/> T-20020
	<input type="checkbox"/> R-20141 <input type="checkbox"/> G-20134 <input type="checkbox"/> C-20103 <input type="checkbox"/> T-20104
<input type="checkbox"/>	Test Site – MRT Shenzhen Laboratory
	Laboratory Location (Shenzhen)
	1G, Building A, Junxiangda Building, Zhongshanyuan Road West, Nanshan District, Shenzhen, China
	Laboratory Accreditations
	A2LA: 3628.02 CNAS: L10551
	FCC: CN1284 ISED: CN0105
<input type="checkbox"/>	Test Site – MRT Taiwan Laboratory
	Laboratory Location (Taiwan)
	No. 38, Fuxing 2nd Rd., Guishan Dist., Taoyuan City 333, Taiwan (R.O.C.)
	Laboratory Accreditations
	TAF: L3261-190725
	FCC: 291082, TW3261 ISED: TW3261

1.4. Product Information

Product Name	Wi-Fi 6 DSL Modem Gateway
Model No.	T3280
Wi-Fi Specification	802.11b/g/n/ac/ax
Antenna Information	Refer to Section 1.7
Accessory	
Adapter	<p>MODEL: ADS024T-W 120200</p> <p>INPUT: 100-240V ~ 50/60Hz 0.6A</p> <p>OUTPUT: 12V=2A</p>
Remark: The information of EUT was provided by the manufacturer, and the accuracy of the information shall be the responsibility of the manufacturer.	

1.5. Antenna Details

Antenna Type	Frequency (MHz)	TX Path	Antenna Gain (dBi)				Directional Gain (dBi)		
			Ant 0	Ant 1	Ant 2	Ant 3	Correlated	Uncorrelated	
Wi-Fi Antenna									
PIFA	2412 ~ 2462	3	3.47	4.91	4.24	--	5.90	2.27	
	5150 ~ 5850	4	4.71	5.44	4.61	3.34	6.69	1.80	
Remark:									
<ol style="list-style-type: none"> 1. The antenna gain and directional gain refer to manufacturer's antenna specification. 2. The device supports CDD Mode and STBC mode, details refer to the table as below. 3. CDD signals are correlated, the directional gain as follows, For power measurements: Array Gain = 0 dB for $N_{ANT} \leq 4$, the directional gain = max antenna gain + array gain For power spectral density (PSD) measurements: the max directional gain (each angle) = $10 \log[(10^{G1/20} + 10^{G2/20} + \dots + 10^{GN/20})^2 / N_{ANT}]$ 4. STBC signals are uncorrelated, the directional gain as follows, the max directional gain (each angle) = $10 \log[(10^{G1/10} + 10^{G2/10} + \dots + 10^{GN/10}) / N_{ANT}]$ 									

Test Mode	Tx Paths	CDD Mode	STBC Mode
Wi-Fi 2.4G			
802.11b/g	3	√	X
802.11n/ax	3	X	√
Wi-Fi 5G			
802.11a	4	√	X
802.11n/ac/ax	4	X	√

Remark: “√” means “Support”, “X” means “Not support”.

2. RF Exposure Evaluation

2.1. Test Limits

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b)

LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time (Minutes)
(A) Limits for Occupational/ Control Exposures				
300-1500	--	--	f/300	6
1500-100,000	--	--	5	6
(B) Limits for General Population/ Uncontrolled Exposures				
300-1500	--	--	f/1500	6
1500-100,000	--	--	1	30

f= Frequency in MHz

Calculation Formula: $Pd = (Pout \cdot G) / (4 \cdot \pi \cdot r^2)$

Where

Pd = power density in mW/cm²

Pout = output power to antenna in mW

G = gain of antenna in linear scale

Pi = 3.1416

r = distance between observation point and center of the radiator in cm

Pd is the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

2.2. Test Result

Product	Wi-Fi 6 DSL Modem Gateway
Test Item	RF Exposure Evaluation

Antenna Gain: Refer to clause 1.5.

Test Mode	Frequency Band (MHz)	Conducted Power (dBm)	Tune-up Power (dBm)	Antenna Gain (dBi)	Maximum EIRP (dBm)
802.11b/g/n/ax	2412 ~ 2462	28.66	29.0	4.91	33.91
802.11a/n/ac/ax	5150 ~ 5850	29.16	29.5	5.44	34.94

Test Mode	Frequency Band (MHz)	Maximum EIRP (dBm)	Compliance Distance (cm)	Power Density (mW/cm ²)	Limit of Power Density (mW/cm ²)
802.11b/g/n/ax	2412 ~ 2462	33.91	30	0.2175	1
802.11a/n/ac/ax	5150 ~ 5850	34.94	30	0.2758	1

CONCLUSION:

WLAN 2.4GHz Band and WLAN 5GHz can transmit simultaneously.

The max Power Density at R (30 cm) = $0.2175\text{mW/cm}^2 + 0.2758\text{mW/cm}^2 = 0.4933 < 1\text{mW/cm}^2$.

The End