


REV	ECN #	Description	Date	Drawn	CHK'D	APP'D
1	218:79	Changed R67 from 8R2 to 4R7	10DEC97	MAP		
	218:80	Added buffering to radio output signals				

10 V18
 11 SER
 12 A
 13 0
 14 0
 15 0
 16 0
 17 0
 18 0
 19 0
 20 0
 21 0
 22 0
 23 0
 24 0
 25 0
 26 0
 27 0
 28 0
 29 0
 30 0
 31 0
 32 0
 33 0
 34 0
 35 0
 36 0
 37 0
 38 0
 39 0
 40 0
 41 0
 42 0
 43 0
 44 0
 45 0
 46 0
 47 0
 48 0
 49 0
 50 0
 51 0
 52 0
 53 0
 54 0
 55 0
 56 0
 57 0
 58 0
 59 0
 60 0
 61 0
 62 0
 63 0
 64 0
 65 0
 66 0
 67 0
 68 0
 69 0
 70 0
 71 0
 72 0
 73 0
 74 0
 75 0
 76 0
 77 0
 78 0
 79 0
 80 0
 81 0
 82 0
 83 0
 84 0
 85 0
 86 0
 87 0
 88 0
 89 0
 90 0
 91 0
 92 0
 93 0
 94 0
 95 0
 96 0
 97 0
 98 0
 99 0
 100 0


COPY
 CERTIFIED
 DATE 22 Jun 98

6E
 6F



Q-TRON LTD.
 CALGARY, ALBERTA

TITLE	ER CPU TRANSIENT SUPPRESSOR			
Drawn	EIH	27FEB95	P/N: 5821617.5821617-01	
Checked	WMJ	27FEB95	SIZE: C	REV: 1
Approved	DRB	02MAR95	DWG#: Q-89216-17-A01	
DATE:	Wednesday, December 10, 1997	SHEET	1	OF 2



NOTES:

1. ALL RESISTORS 1/4W 5% UNLESS SPECIFIED.
2. ALL NON-POLARIZED CAPACITORS ARE MONOLITHIC.
50V MINIMUM UNLESS SPECIFIED.
3. ALL POLARIZED CAPACITORS ARE TANTALUM UNLESS SPECIFIED.