

CETECOM ICT Services GmbH

Radio Satellite Communication

Untertürkheimer Straße 6-10 . D-66117 Saarbrücken

Telefon: +49 (0)681 598-9100

Telefax: -9075

RSC14

issue test report consist of

18 Pages

Page 1 (18)

Akkreditiertes Prüflaboratorium

**DAR-Registriernummer:
TTI-P-G 166/98-00 vom 18.09.98**

**Test report no.: 5_2467-B/00
FCC Part 15.231
Volvo NAS Transmitter 509923
Volvo NAS Receiver 509932**

Table of Contents

1 General information

1.1 Notes

1.2 Testing laboratory

1.3 Details of applicant

1.4 Application details

1.5 Test item

1.6 Test standards

2 Technical test

2.1 Summary of test results

2.2 Test report

1 General information

1.1 Notes

The test results of this test report relate exclusively to the item tested as specified in 1.5.

The test report may only be reproduced or published in full. Reproduction or publication of extracts from the report requires the prior written approval of the CETECOM ICT Services GmbH.

CETECOM ICT Services GmbH

Test report no.: 5_2467-B/00

Issue Date: 24.05.00

Page 3 (18)

1.2 Testing laboratory

CETECOM ICT Services GmbH

66117 Saarbrücken

Untertürkheimer Straße 6 - 10

Deutschland

Telefone: + 49 681 598 - 9000

Telefax : + 49 681 598 - 9075

E-mail : Harro.Ames@ict.cetecom.de

Internet : www.cetecom.de

Accredited testing laboratory

DAR-registration number : TTI-P-G-166/98-00 vom 18.09.98

1.3 Details of applicant

Name : Connaught Electronics Ltd.

Street : Dunmore Road

City : Tuam, Co. Galway

Country : Ireland

Telephone : +353 93 251 28

Telefax : +353 93 251 33

Contact : Mr. Pat Lyons

Telephone : +353 93 251 28

1.4 Application details

Date of receipt of application : 22.05.00

Date of receipt of test item : 22.05.00

Date of test : 22.05.00

1.5 Test item

Type of equipment : Transmitter/Receiver for car opening system

Type designation : **Volvo NAS Transmitter 509923**
Volvo NAS Receiver 509932

Manufacturer : - applicant -

Street :

City :

Country :

Additional informations: :

Frequency : 315,0 MHz 14K0A1D

Channel sep: >25 kHz

Number of channels : 1

Power output (EIRP) : 0,01 mW

Antenna : build-in print-antenna

Power supply : Tx: 3V DC Lithium cell

Type of equipment : -

Unmodulated carrier : normally not possible

1.6 Test standards

FCC Part 15.231

2 Technical test

2.1 Summary of test results

No deviations from the technical specification(s) were ascertained in the course of the tests performed.

Technical responsibility for area of testing :

24.05.2000	RSC8414	Ames H.
------------	---------	---------

Date	Section	Name	Signature
------	---------	------	-----------

24.05.2000	RSC8411	Berg M.
------------	---------	---------

Date	Section	Name	Signature
------	---------	------	-----------

2.2 Testreport

TEST REPORT

FCC Part 15.231

Testreport no.: 5_2467-B/00

CETECOM ICT Services GmbH

Test report no.: 5_2467-B/00

Issue Date: 24.05.00

Page 6 (18)

TEST REPORT REFERENCE

LIST OF MEASUREMENTS

The list of measurements called for in FCC Part 15.231 is given below.

Paragraph	PARAMETER TO BE MEASURED	PAGE
	Transmitter parameters	
§15.231 (b)	Maximum field strenght of emission	7
§15.231(a)	Automatic deactivation	8
§15.231(c)	Bandwidth of emission	9
	Test equipment listing	10
	Photographs of the equipment	12

CETECOM ICT Services GmbH

Test report no.: 5_2467-B/00

Issue Date: 24.05.00

Page 7 (18)

Equipment under test: CEL 509923/509932

Temp: 20 Deg.C

Rel. hum: 55%

EMISSION LIMITATIONS (315,0 MHz)

§15.231(b)

EMISSION LIMITATIONS					
all measurements are made up to the 10 th harmonic at 3m					
f (MHz)	polarization	amplitude of emission (µV/m)	limit max. allowed emmission power (interpolation)	actual attenuation below frequency of operation (dB)	results
315,0	vertical	2985	6042 µV/m	-	Operating frequency
629,99	vertical	248	605 µV/m 500µV/m (209)	22	complies
944,97	vertical	263	605 µV/m 500µV/m (209)	21	complies
1259,82	vertical	175	605 µV/m 500µV/m (209)	24	complies
>1259,82	vertical	no peak found	605 µV/m 500µV/m (209)		complies
Measurement uncertainty		± 3dB			

LIMITS

SUBCLAUSE § 15.231

In any 100 kHz bandwidth outside the frequency band at least 20dB below the highest level of the permitted fundamental power. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).

All measurements are made with a CISPR quasi-peak equipment.

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

CETECOM ICT Services GmbH

Test report no.: 5_2467-B/00

Issue Date: 24.05.00

Page 8 (18)

Equipment under test: CEL 509923/509932

Temp: 20 Deg.C

Rel. hum: 55%

AUTOMATIC DEACTIVATION

SUBCLAUSE § 15.231 (a)

The transmitter is automatically deactivated within 5 seconds of being released.

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

CETECOM ICT Services GmbH

Test report no.: 5_2467-B/00

Issue Date: 24.05.00

Page 9 (18)

Equipment under test: CEL 509923/509932

Temp: 20 Deg.C

Rel. hum: 55%

Bandwidth of emissions

SUBCLAUSE § 15.231 (c)

TEST CONDITIONS 315,0 MHz		FREQUENCY (MHz) at which -20 dBc occurs max ±0,78 MHz at 315 MHz	
		low	high
$T_{\text{nom}}(20)^{\circ}\text{C}$	$V_{\text{nom}}(3,0)\text{V}$	314,992	315,006
Measured frequencies (lowest and highest)		$f_L = 314,992 \text{ MHz}$	$f_H = 315,006 \text{ MHz}$
Measurement uncertainty		$\pm 1 \times 10^{-5}$	

LIMITS:

§15.231

Under all test conditions	no wider than 0.25% of the center frequency between 70 to 900 MHz, 0.5% above 900MHz. Bandwidth is determined at 20dB below modulated carrier.
---------------------------	---

REFERENCE NUMBER(S) OF TEST EQUIPMENT USED
(for reference numbers see test equipment listing)

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
01	Spectrum Analyzer	8566 A	Hewlett-Packard	1925A00257
02	Analyzer Display	8566 A	Hewlett-Packard	1925A00860
03	Oscilloscope	7633	Tektronix	230054
04	Radio Analyzer	CMTA 54	Rohde & Schwarz	894 043/010
05	System Power Supply	6038 A	Hewlett-Packard	2848A07027
06	Signal Generator	8111 A	Hewlett-Packard	2215G00867
07	Signal Generator	8662 A	Hewlett-Packard	2224A01012
08	Funktionsgenerator	AFGU	Rohde & Schwarz	862 480/032
09	Regeltrenntrafo	MPL	Erfi	91350
10	Netznachbildung	NNLA 8120	Schwarzbeck	8120331
11	Relais-Matrix	PSU	Rohde & Schwarz	893 285/020
12	Power-Meter	436 A	Hewlett-Packard	2101A12378
13	Power-Sensor	8484 A	Hewlett-Packard	2237A10156
14	Power-Sensor	8482 A	Hewlett-Packard	2237A00616
15	Modulationsmeter	9008	Racal-Dana	2647
16	Frequenzzähler	5340 A	Hewlett-Packard	1532A03899
17	Absorber Schirmkabine	---	MWB	87400/002
18	Spectrum Analyzer	85660 B	Hewlett-Packard	2747A05306
19	Analyzer Display	85662 A	Hewlett-Packard	2816A16541
20	Quasi Peak Adapter	85650 A	Hewlett-Packard	2811A01131
21	RF-Preselector	85685 A	Hewlett-Packard	2833A00768
22	Biconical Antenne	3104	Emco	3758
23	Log. Per. Antenne	3146	Emco	2130
24	Double Ridge Horn	3115	Emco	3088
25	EMI-Testreceiver	ESAI	Rohde & Schwarz	863 180/013
26	EMI-Analyzer-Display	ESAI-D	Rohde & Schwarz	862 771/008
27	Biconical Antenne	HK 116	Rohde & Schwarz	888 945/013
28	Log. Per. Antenne	HL 223	Rohde & Schwarz	825 584/002
29	Relais-Switch-Unit	RSU	Rohde & Schwarz	375 339/002
30	Highpass	HM985955	FSY Microwave	001
31	Amplifier	P42-GA29	Tron-Tech	B 23602
32	Absorber Schirmkabine		Frankonia	
33	Steuerrechner	PSM 7	Rohde & Schwarz	834 621/004
34	EMI Test Reciever	ESMI	Rohde & Schwarz	827 063/010
35	EMI Test Receiver	Display	Rohde & Schwarz	829 808/010

TEST EQUIPMENT AND ANCILLARIES USED FOR TESTS

To simplify the identification on each page of the test equipment used, on each page of the test report, each item of test equipment and ancillaries such as cables are identified (numbered) by the Test Laboratory, below.

No	Instrument/Ancillary	Type	Manufacturer	Serial No.
36	Controler	HD 100	Deisel	100/322/93
37	Relais Matrix	PSN	Rohde & Schwarz	829 065/003
38	Control Unit	GB 016 A2	Rohde & Schwarz	344 122/008
39	Relais Switch Unit	RSU	Rohde & Schwarz	316 790/001
40	Power Supply	6032A	Hewlett Packard	2846A04063
41	Spektrum Monitor	EZM	Rohde & Schwarz	883 720/006
42	Meßempfänger	ESH 3	Rohde & Schwarz	890 174/002
43	Meßempfänger	ESVP	Rohde & Schwarz	891 752/005
44	Biconi Ant. 20-300MHz	HK 116	Rohde & Schwarz	833 162/011
45	Logper Ant. 0.3-1 GHz	HL 223	Rohde & Schwarz	832 914/010
46	Amplifier 0.1-4 GHz	AFS4	Miteq Inc.	206461
47	Logper Ant. 1-18 GHz	HL 024 A2	Rohde & Schwarz	342 662/002
48	Polarisationsnetzwerk	HL 024 Z1	Rohde & Schwarz	341 570/002
49	Double Ridge G Horn Antenne 1-26.5 GHz	3115	EMCO	9107-3696
50	Microw. Sys. Amplifier 0.5- 26.5 GHz	8317A	Hewlett Packard	3123A00105
51				
52				
53				
54				
55				
56				
57				
58				
59				
60				
61				
62				
63				
64				
65				
66				
67				
68				
69				