

DATE: 01 November 2011

I.T.L. (PRODUCT TESTING) LTD.
FCC Radio Test Report
for
ElmoTech Ltd.*


Equipment under test:
Tracking Bracelet

TRX-900F-2*

* See customer's declaration on page 5.

Written by: 
D. Shidlovsky, Documentation

Approved by: 
A. Sharabi, Test Engineer

Approved by: 
I. Raz, EMC Laboratory Manager

This report must not be reproduced, except in full, without the written permission of I.T.L. (Product Testing) Ltd.

This report relates only to items tested.

Measurement/Technical Report for ElmoTech Ltd. Tracking Bracelet

TRX-900F-2

FCC ID: LSQTRX900F2

This report concerns: Original Grant: x

Class I change:

Class II change:

Equipment type: Part 15 Security/Remote Control Transceiver

47CFR15 Section 15231 (a-d)

Measurement procedure used is ANSI C63.4-2003.

Application for Certification:

prepared by:

Shai Avigdori

Elmo Tech Ltd.

2 Habarzel St.

Tel-Aviv, 61131

Israel

Tel: +972-3-767-1700

Fax: +972-3-767-1701

e-mail: Shaia@Attentigroup.com



TABLE OF CONTENTS

1. GENERAL INFORMATION -----	4
1.1 Administrative Information.....	4
1.2 List of Accreditations	6
1.3 Product Description	7
1.4 Test Methodology	7
1.5 Test Facility	7
1.6 Measurement Uncertainty	7
2. SYSTEM TEST CONFIGURATION-----	8
2.1 Justification.....	8
2.2 Special Accessories	8
2.3 Equipment Modifications	8
2.4 Configuration of Tested System	8
3. RADIATED MEASUREMENT TEST SET-UP PHOTOS-----	9
4. AVERAGE FACTOR CALCULATION HELICAL ANTENNA TRANSMITTER-----	11
4.1 Test Instrumentation Used	13
5. PERIODIC OPERATION-----	14
5.1 Specification	14
5.2 Requirements	14
5.3 Results.....	14
5.1 Test Instrumentation Used	17
6. FIELD STRENGTH OF FUNDAMENTAL-----	18
6.1 Test Specification	18
6.2 Test Procedure	18
6.3 Measured Data	18
6.4 Test Instrumentation Used, Field Strength of Fundamental.....	22
7. RADIATED EMISSION, 9 KHZ – 30 MHZ-----	23
7.1 Test Specification	23
7.2 Test Procedure	23
7.3 Measured Data	23
7.4 Test Instrumentation Used, Radiated Measurements.....	24
7.5 Field Strength Calculation	24
8. SPURIOUS RADIATED EMISSION HELICAL ANTENNA TRANSMITTER-----	25
8.1 Test Specification	25
8.2 Test Procedure	25
8.3 Test Data	26
8.4 Test Instrumentation Used, Radiated Measurements.....	28
9. BANDWIDTH -----	29
9.1 Test procedure	29
9.2 Results table.....	30
9.3 Test Equipment Used.....	31
10. APPENDIX A - CORRECTION FACTORS-----	32
10.1 Correction factors for CABLE	32
10.2 Correction factors for CABLE	33
10.3 Correction factors for CABLE	34
12.6 Correction factors for LOG PERIODIC ANTENNA	35
10.4 Correction factors for LOG PERIODIC ANTENNA	36
10.5 Correction factors for BICONICAL ANTENNA	37
10.6 Correction factors for ACTIVE LOOP ANTENNA	38

1. General Information

1.1 Administrative Information

Manufacturer: ElmoTech Ltd.*

Manufacturer's Address: P.O.B. 13236
2 Habarzel St.,
Tel-Aviv, 61132
Israel
Tel: +972-3-767-1700
Fax: +972-3-767-1701

Manufacturer's Representative: Arad Dudkevitz

Equipment Under Test (E.U.T): Tracking Bracelet

Equipment Model No.: TRX-900F-2*

Equipment Serial No.: Not Designated

Date of Receipt of E.U.T: 25.09.11

Start of Test: 25.09.11

End of Test: 26.09.11

Test Laboratory Location: I.T.L (Product Testing) Ltd.
Kfar Bin Nun,
ISRAEL 99780

Test Specifications: FCC Part 15 Subpart C

* See customer's declaration on following page.

Date: 09.10.2011

DECLARATION

I hereby declare that the name and model name of the E.U.T. tested at the I.T.L. EMC/Radio laboratory between 25 and 26 September 2011 is as follows:

E.U.T. Name:	Tracking Bracelet
Model Name:	TRX-900F-2
FCC ID:	LSQTRX900F2

I hereby declare that the product listed above is manufactured by ElmoTech Ltd.
Please use the above names in the test reports.

Thank you,

Signature:



Shai Avigdori
Quality manager
ElmoTech Ltd.

1.2 List of Accreditations

The EMC laboratory of I.T.L. is accredited by the following bodies:

1. The American Association for Laboratory Accreditation (A2LA) (U.S.A.), Certificate No. 1152.01.
2. The Federal Communications Commission (FCC) (U.S.A.), Registration No. 90715.
3. The Israel Ministry of the Environment (Israel), Registration No. 1104/01.
4. The Voluntary Control Council for Interference by Information Technology Equipment (VCCI) (Japan), Registration Numbers: C-1350, R-1285.
5. Industry Canada (Canada), IC File No.: 46405-4025; Site No. IC 4025B-1.
6. TUV Product Services, England, ASLLAS No. 97201.

I.T.L. Product Testing Ltd. is accredited by the American Association for Laboratory Accreditation (A2LA) and the results shown in this test report have been determined in accordance with I.T.L.'s terms of accreditation unless stated otherwise in the report.

1.3 Product Description

The TRX-900F-2 is a small ankle worn device designed for offender monitoring applications.

The device comprises a printed circuit board (PCB) that includes a RF transceiver module with an integral antenna and a microcontroller that controls its operation.

The TRX-900F-2 has one 433 MHz RF channel over which it communicates with its allocated home unit and/or GPS tracking device.

The unit is powered by an internal 3.6V Lithium Thionyl Chloride battery.

The TRX-900F-2 is attached to the ankle of the offender by means of a fiber optic strap. When attached to the offender, the strap is connected in such a way that the optical fiber is facing an IR transmitter on one side and an IR receiver on the other. The IR transmitter sends light signals periodically via the fiber. The reception of these signals by the IR receiver proves the integrity of the strap.

When activated, the TRX-900F-2 transmits signals separated by a pseudorandom interval of between 15 and 16 seconds. After each transmission, the TRX-900F-2 listens for an acknowledge signal in order to ascertain whether its home unit/tracking device is within range. If a defined timeout has expired without receiving an acknowledge signal, the TRX-900-2 activates an internal vibrator so as to warn the offender that they are out of range before a violation event is generated.

1.4 Test Methodology

Radiated testing was performed according to the procedures in ANSI C63.4: 2003. Radiated testing was performed at an antenna to EUT distance of 3 meters.

1.5 Test Facility

The radiated emissions tests were performed at I.T.L.'s testing facility at Kfar Bin-Nun, Israel. This site is a FCC listed test laboratory (FCC Registration No. 90715, date of listing September 3, 2009).

I.T.L.'s EMC Laboratory is also accredited by A2LA, certificate No. 1152.01.

1.6 Measurement Uncertainty

Radiated Emission

Radiated Emission (CISPR 11, EN 55011, CISPR 22, EN 55022, ANSI C63.4) for open site 30-1000MHz:

Expanded Uncertainty (95% Confidence, K=2):

± 4.96 dB

2. System Test Configuration

2.1 ***Justification***

Radiated emission screening was performed in 3 orthogonal orientations. The worst case orientation was the vertical position.

2.2 ***Special Accessories***

No special accessories were needed.

2.3 ***Equipment Modifications***

No modifications were needed in order to achieve compliance

2.4 ***Configuration of Tested System***




Figure 1. Configuration of Tested System

3. Radiated Measurement Test Set-up Photos



Figure 2. Radiated Emission Test 9 kHz – 30 MHz




Figure 3. Radiated Emission Test 30-1000 MHz



Figure 4. Radiated Emission Test Above 1 GHz


4. Average Factor Calculation Helical Antenna Transmitter

1. Burst duration = 2.8msec
2. Time between bursts = 15sec

3. Average Factor = $20 \log \left[\frac{\text{Pulse duration}}{\text{Pulse period}} \times \frac{\text{burst duration}}{100\text{msec}} \times \text{Num of burst within 100msec} \right]$

$$\text{Average Factor} = 20 \log \left[1 \times \frac{4}{100} \right] = -28.0 \text{dB}$$


Note: Pulse duration and pulse period was considered 1 since unit is FSK modulated



Date: 25.SEP.2011 12:04:29

Figure 5. . Burst Duration = 4 msec

Note: The lower pulse is the acknowledge signal transmitted by the base station, not defined under this scope of work.



Date: 25.SEP.2011 11:53:53

Figure 6. Number of Transmissions Within 60 Seconds

4.1 **Test Instrumentation Used**

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	RHODE & SCHWARZ	ESC17	100724	October, 20 2010	1 Year
Antenna Bioconical	ETS	3109	002-3244	July 31, 2011	1 year
Antenna Log Periodic	ARA	LPD-2010/A	1038	January 27, 2011	1 year
Antenna-Log Periodic	A.H.System	SAS-200/511	253	February 21, 2011	2 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A

5. Periodic Operation

5.1 Specification

F.C.C., Part 15, Subpart C, Section 15.231(a)

5.2 Requirements

Requirement	Rationale	Verdict
Continuous transmissions are not permitted.	N/A	Complies
A manually operated transmitter shall be deactivated within not more than 5 seconds after releasing the switch.	N/A	Complies
An automatically operated transmitter shall cease operation within 5 seconds after activation.	N/A	Complies
Periodic transmissions at regular predetermined intervals are not permitted.	N/A	Complies
Polling or supervised transmissions to determine system integrity of transmitter used in security or safety applications shall not exceed more than 2 seconds per hour.	See plots in Figure 7 to Figure 8.	Complies

5.3 Results

JUDGEMENT: Passed

The EUT met the FCC Part 15, Subpart C, Section 15.231(a) specification requirements.

TEST PERSONNEL:

Tester Signature: 


Date: 10.10.11

Typed/Printed Name: A. Sharabi

Periodic Operation

E.U.T Description Tracking Bracelet
 Type TRX-900F-2
 Serial Number: Not Designated

Specification: F.C.C., Part 15, Subpart C, 15.231(a)




Date: 25.SEP.2011 11:53:53

Figure 7. Supervision Signal Once Every 15sec for 4msec

Periodic Operation

E.U.T Description Tracking Bracelet
 Type TRX-900F-2
 Serial Number: Not Designated

Specification: F.C.C., Part 15, Subpart C, 15.231(a)



Date: 25.SEP.2011 12:04:29

Figure 8. Supervision Signal Once Every 15sec
 $[(3600/15) \times 4 \text{ msec} = 960 \text{ msec}] < 2 \text{ sec}$

Note: The lower pulse is the acknowledge signal transmitted by the base station, not defined under this scope of work.

5.1 Test Instrumentation Used

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	RHODE & SCHWARZ	ESC17	100724	October 20 2010	1 Year

6. Field Strength of Fundamental

6.1 ***Test Specification***

F.C.C., Part 15, Subpart C, Section 15.231(b)

6.2 ***Test Procedure***

The E.U.T. operation mode and test set-up are as described in Section 3.

The E.U.T. was placed on a non-conductive table, 0.8 meters above the O.A.T.S. ground plane.

The EMI receiver was set to the E.U.T. Fundamental Frequency (433.92 MHz) and Peak Detection.

The turntable and antenna mast were adjusted for maximum level reading on the EMI receiver.

The measurement was performed for vertical and horizontal polarizations of the test antenna.

The average result is:

Peak Level(dB μ V/m) + E.U.T. Duty Cycle Factor, in 100msec time window (dB)

6.3 ***Measured Data***

JUDGEMENT: Passed by 16.8 dB

The EUT met the FCC Part 15, Subpart C, Section 15.231(b) specification requirements.

The details of the highest emissions are given in Figure 9 to Figure 11.

TEST PERSONNEL:

Tester Signature:  Date: 10.10.11

Typed/Printed Name: A. Sharabi

Field Strength of Fundamental

E.U.T Description Tracking Bracelet

Type TRX-900F-2

Serial Number: Not Designated

Specification: F.C.C., Part 15, Subpart C, 15.231(b)

Antenna Polarization: Horizontal/Vertical

Test Distance: 3 meters

Detector: Peak

Freq.	Pol.	Peak Reading	Average Factor	AVG Result	AVG Specification	Margin
(MHz)	V/H	(dB μ V/m)	(dB)	(dB μ V/m)	(dB μ V/m)	(dB)
433.92	H	92.05	-28.0	64.05	80.83	-16.78
433.92	V	89.18	-28.0	61.18	80.83	-19.65

Figure 9. Field Strength of Fundamental. Antenna Polarization: HORIZONTAL/VERTICAL.

Notes:

1. Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.
2. “Peak Reading.” (dB μ V/m) included the “Correction Factors”.
3. “Correction Factors” (dB) = Test Antenna Correction Factor(dB) + Cable Loss.
4. “Average Result” (dB μ V/m)= Peak Reading (dB μ V/m) + Average Factor (dB)

Field Strength of Fundamental

E.U.T Description Tracking Bracelet
 Type TRX-900F-2
 Serial Number: Not Designated

Specification: F.C.C., Part 15, Subpart C, 15.231(b)

Antenna Polarization: Horizontal

Test Distance: 3 meters

Detector: Peak



ACTV DET: PEAK
 MEAS DET: PEAK QP AVG
 MKR 433.870 MHz
 92.05 dB μ V/m




Figure 10. Field Strength of Fundamental. Antenna Polarization: HORIZONTAL.

Field Strength of Fundamental

E.U.T Description Tracking Bracelet
 Type TRX-900F-2
 Serial Number: Not Designated

Specification: F.C.C., Part 15, Subpart C, 15.231(b)

Antenna Polarization: Vertical

Test Distance: 3 meters

Detector: Peak




Figure 11. Field Strength of Fundamental. Antenna Polarization: VERTICAL.

6.4 **Test Instrumentation Used, Field Strength of Fundamental**

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	HP	85422E	3906A00276	November 24, 2010	1 year
RF Section	HP	85420E	3705A00248	November 24, 2010	1 year
Antenna Log Periodic	ARA	LPD-2010/A	1038	March 23, 2011	1 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

7. Radiated Emission, 9 kHz – 30 MHz

7.1 **Test Specification**

9 kHz-30 MHz, FCC, Part 15, Subpart C, Section 209

7.2 **Test Procedure**

The E.U.T. operation mode and test set-up are as described in Section 3.

A preliminary measurement to characterize the E.U.T was performed inside the shielded room at a distance of 3 meters, using peak detection mode and broadband antennas. The preliminary measurements produced a list of the highest emissions. The E.U.T was then transferred to the open site, and placed on a remote-controlled turntable. The E.U.T was placed on a non-metallic table, 0.8 meters above the ground. The configuration tested is shown in Figure 3.1.

The frequency range 9 kHz-30 MHz was scanned.

The emissions were measured using a computerized EMI receiver complying to CISPR 16 requirements. The specification limits and applicable correction factors are loaded to the receiver via a 3.5" floppy disk.

In the frequency range 9 kHz-30MHz, the loop antenna was rotated on its vertical axis. The antenna height (center of loop) was 1 meter at a distance of 3 meters.

The E.U.T. was operated at the frequency of 433 MHz. This frequency was measured using a peak detector.

7.3 **Measured Data**

JUDGEMENT: Passed

The EUT was tested and it met the requirements of the FCC Part 15, Subpart C, specification.

No signals were detected in the frequency range of 9 kHz – 30 MHz.

TEST PERSONNEL:

Tester Signature: 

Date: 10.10.11

Typed/Printed Name: A. Sharabi

7.4 Test Instrumentation Used, Radiated Measurements

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	HP	85422E	3906A00276	November 24, 2010	1 year
RF Section	HP	85420E	3705A00248	November 24, 2010	1 year
Active Loop Antenna	EMCO	6502	9506-2950	October 19, 2010	1 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A

7.5 Field Strength Calculation

The field strength is calculated directly by the EMI Receiver software, and a "Correction Factors" data disk, using the following equation:

$$FS = RA + AF + CF$$

FS: Field Strength [dB μ V/m]
 RA: Receiver Amplitude [dB μ V]
 AF: Receiving Antenna Correction Factor [dB/m]
 CF: Cable Attenuation Factor [dB]

Example: $FS = 30.7 \text{ dB}\mu\text{V (RA)} + 14.0 \text{ dB (AF)} + 0.9 \text{ dB (CF)} = 45.6 \text{ dB}\mu\text{V}$

No external pre-amplifiers are used.

8. Spurious Radiated Emission Helical Antenna Transmitter

8.1 ***Test Specification***

30 - 4500 MHz, F.C.C., Part 15, Subpart C

8.2 ***Test Procedure***

The E.U.T. operation mode and test set-up are as described in Section 3. See Section 3.1 Justification of the System Test Configuration concerning the E.U.T. orientation for this test.

A preliminary measurement to characterize the E.U.T was performed inside the shielded room at a distance of 3 meters, using peak detection mode and broadband antennas. The preliminary measurements produced a list of the highest emissions. The E.U.T was then transferred to the open site, and placed on a remote-controlled turntable. The E.U.T was placed on a non-metallic table, 0.8 meters above the ground. The configuration tested is shown in Figure 1. The signals from the list of the highest emissions were verified and the list was updated accordingly.

The levels of the emissions within the frequency ranges of the restricted bands (Section 15.205 of FCC Part 15) were compared to the limits of the table in Section 15.209 (a), General Requirements.

The emissions were measured using a computerized EMI receiver complying to CISPR 16 requirements. The specification limits and applicable correction factors are loaded to the receiver via a 3.5" floppy disk.

In the frequency range 2.9 – 4.5 GHz, a spectrum analyzer including a low noise amplifier was used. The test distance was 3 meters. During peak measurements, the I.F. bandwidth was 1 MHz, and video bandwidth 3 MHz. During average measurements, the I.F. bandwidth was 1 MHz and video bandwidth was 100 Hz.

The readings were maximized by adjusting the antenna height between 1-4 meters, the turntable azimuth between 0-360°, and the antenna polarization.

Verification of the E.U.T emissions was based on the following methods: turning the E.U.T on and off; using a frequency span less than 10 MHz; observation of the signal level during turntable rotation. (Background noise is not affected by the rotation of the E.U.T.)

The emissions were measured at a distance of 3 meters.

8.3 **Test Data**

JUDGEMENT: Passed by 25.4 dB

The EUT met the requirements of the F.C.C. Part 15, Subpart C, specification.

The margin between the emission level and the specification limit was 18.6 dB in the worst case at the frequency of 1301.00 MHz, horizontal polarization.

TEST PERSONNEL:

Tester Signature: 

Date: 10.10.11

Typed/Printed Name: A. Sharabi

Radiated Emission

E.U.T Description Tracking Bracelet
 Type TRX-900F-2
 Serial Number: Not Designated

Specification: FCC Part 15, Subpart C

Antenna Polarization: Horizontal/Vertical
 Antenna: 3 meters distance

Frequency range: 30 MHz to 4500 MHz
 Detector: Peak

Frequency (MHz)	Antenna Polarity (H/V)	Peak Reading (dB μ V/m)	Average Factor (dB μ V/m)	Average Result (dB μ V/m)	Average Specification (dB μ V/m)	Margin (dB)
867.00	H	51.7	-28.0	23.7	60.83	-37.13
867.00	V	53.0	-28.0	25.0	60.83	-35.83
1301.00	H	63.4	-28.0	35.4	54.0	-18.6
1301.00	V	61.7	-28.0	33.7	54.0	-20.3

Figure 12. Radiated Emission.

Note: Margin refers to the test results obtained minus specified requirement; thus a positive number indicates failure, and a negative result indicates that the product passes the test.

8.4 ***Test Instrumentation Used, Radiated Measurements***

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	HP	85422E	3906A00276	November 24, 2010	1 year
RF Section	HP	85420E	3705A00248	November 24, 2010	1 year
Low Noise Amplifier	DBS MICROWAVE	LNA-DBS-0411N313	013	November 05, 2010	1 Year
Spectrum Analyzer	HP	8592L	3826A01204	February 21, 2011	1 Year
Antenna Bioconical	ETS	3109	002-3244	July 31, 2011	1 year
Antenna Log Periodic	ARA	LPD-2010/A	1038	March 23, 2011	1 year
Antenna-Log Periodic	A.H.System	SAS-200/511	253	January 27, 2011	2 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

9. Bandwidth

9.1 Test procedure

The transmitter unit operated with normal modulation. The spectrum analyzer was set to 120 kHz resolution BW and center frequency of the transmitter fundamental. The spectrum bandwidth of the transmitter unit was measured and recorded. The BW was measured at 20 dBc points.

The EUT was set up as shown in Figure 1, and its proper operation was checked. The transmitter occupied bandwidth was measured with the EMI receiver as frequency delta between reference points on the modulation envelope.




Figure 13 Bandwidth

9.2 Results table

E.U.T Description: Tracking Bracelet

Model: TRX-900F-2

Serial Number: Not Designated

Specification: F.C.C. Part 15, Subpart C: (15.231(c))

Bandwidth Reading (kHz)	Specification (1) (kHz)	Margin (kHz)
360	1084.8	-724.8

Figure 14 Bandwidth

JUDGEMENT: Passed by 724.8 kHz

TEST PERSONNEL:

Tester Signature:  Date: 10.10.11

Typed/Printed Name: A. Sharabi

(1) 0.25% of the E.U.T. fundamental frequency, Section 15.231(c).

9.3 **Test Equipment Used.**

Bandwidth

Instrument	Manufacturer	Model	Serial Number	Calibration	Period
EMI Receiver	HP	85422E	3906A00276	November 24, 2010	1 year
RF Section	HP	85420E	3705A00248	November 24, 2010	1 year
Antenna Log Periodic	ARA	LPD-2010/A	1038	March 23, 2011	1 year
Antenna Mast	ARA	AAM-4A	1001	N/A	N/A
Turntable	ARA	ART-1001/4	1001	N/A	N/A
Mast & Table Controller	ARA	ACU-2/5	1001	N/A	N/A
Printer	HP	LaserJet 2200	JPKGC19982	N/A	N/A

Figure 15 Test Equipment Used

10. APPENDIX A - CORRECTION FACTORS

10.1 Correction factors for

CABLE

from EMI receiver
to test antenna
at 3 meter range.

FREQUENCY (MHz)	CORRECTION FACTOR (dB)	FREQUENCY (MHz)	CORRECTION FACTOR (dB)
10.0	0.3	1200.0	7.3
20.0	0.6	1400.0	7.8
30.0	0.8	1600.0	8.4
40.0	0.9	1800.0	9.1
50.0	1.1	2000.0	9.9
60.0	1.2	2300.0	11.2
70.0	1.3	2600.0	12.2
80.0	1.4	2900.0	13.0
90.0	1.6		
100.0	1.7		
150.0	2.0		
200.0	2.3		
250.0	2.7		
300.0	3.1		
350.0	3.4		
400.0	3.7		
450.0	4.0		
500.0	4.3		
600.0	4.7		
700.0	5.3		
800.0	5.9		
900.0	6.3		
1000.0	6.7		

NOTES:

1. The cable type is RG-214.
2. The overall length of the cable is 27 meters.
3. The above data is located in file 27MO3MO.CBL on the disk marked "Radiated Emission Tests EMI Receiver".

10.2 Correction factors for

CABLE

from EMI receiver
to test antenna
at 3 meter range.

FREQUENCY (GHz)	CORRECTION FACTOR (dB)
1.0	1.2
2.0	1.6
3.0	2.0
4.0	2.4
5.0	3.0
6.0	3.4
7.0	3.8
8.0	4.2
9.0	4.6
10.0	5.0
12.0	5.8

NOTES:

1. The cable type is RG-8.
2. The overall length of the cable is 10 meters.

10.3 Correction factors for

CABLE

from spectrum analyzer
to test antenna above 2.9 GHz

FREQUENCY (GHz)	CORRECTION FACTOR (dB)	FREQUENCY (GHz)	CORRECTION FACTOR (dB)
1.0	1.9	14.0	9.1
2.0	2.7	15.0	9.5
3.0	3.5	16.0	9.9
4.0	4.2	17.0	10.2
5.0	4.9	18.0	10.4
6.0	5.5	19.0	10.7
7.0	6.0	20.0	10.9
8.0	6.5	21.0	11.2
9.0	7.0	22.0	11.6
10.0	7.5	23.0	11.9
11.0	7.9	24.0	12.3
12.0	8.3	25.0	12.6
13.0	8.7	26.0	13.0

NOTES:

1. The cable type is SUCOFLEX 104 E manufactured by SUHNER.
2. The cable is used for measurements above 2.9 GHz.
3. The overall length of the cable is 10 meters.

12.6 Correction factors for LOG PERIODIC ANTENNA

Type LPD 2010/A
at 3 and 10 meter ranges.

Distance of 3 meters

FREQUENCY (MHz)	AFE (dB/m)
200.0	9.1
250.0	10.2
300.0	12.5
400.0	15.4
500.0	16.1
600.0	19.2
700.0	19.4
800.0	19.9
900.0	21.2
1000.0	23.5

Distance of 10 meters

FREQUENCY (MHz)	AFE (dB/m)
200.0	9.0
250.0	10.1
300.0	11.8
400.0	15.3
500.0	15.6
600.0	18.7
700.0	19.1
800.0	20.2
900.0	21.1
1000.0	23.2

NOTES:

1. Antenna serial number is 1038.
2. The above lists are located in file number 38M30.ANT for a 3 meter range, and file number 38M100.ANT for a 10 meter range.
3. The files mentioned above are located on the disk marked "Radiated Emission Test EMI Receiver".

10.4 Correction factors for

LOG PERIODIC ANTENNA

Type SAS-200/511
at 3 meter range.

FREQUENCY (GHz)	ANTENNA FACTOR (dB)
1.0	24.9
1.5	27.8
2.0	29.9
2.5	31.2
3.0	32.8
3.5	33.6
4.0	34.3
4.5	35.2
5.0	36.2
5.5	36.7
6.0	37.2
6.5	38.1

FREQUENCY (GHz)	ANTENNA FACTOR (dB)
7.0	38.6
7.5	39.2
8.0	39.9
8.5	40.4
9.0	40.8
9.5	41.1
10.0	41.7
10.5	42.4
11.0	42.5
11.5	43.1
12.0	43.4
12.5	44.4
13.0	44.6

NOTES:

1. Antenna serial number is 253.
2. The above lists are located in file number SAS3M0.ANT for a 3 meter range.
3. The files mentioned above are located on the disk marked "Antenna Factors".

10.5 Correction factors for BICONICAL ANTENNA
Type 3109,
at 3 meter range

FREQUENCY (MHz)	AFE (dB/m)
30.0	13.3
40.0	12.7
50.0	11.0
60.0	9.2
70.0	10.0
80.0	7.2
90.0	7.9
100.0	9.4
120.0	11.9
140.0	13.1
160.0	12.3
180.0	12.4
200.0	14.8
250.0	15.3
300.0	17.9

NOTE:

- 1. Antenna serial number is 002-3244.*

10.6 Correction factors for ACTIVE LOOP ANTENNA

Model 6502
S/N 9506-2950

FREQUENCY (MHz)	Magnetic Antenna Factor (dB)	Electric Antenna Factor (dB)
.009	-35.1	16.4
.010	-35.7	15.8
.020	-38.5	13.0
.050	-39.6	11.9
.075	-39.8	11.8
.100	-40.0	11.6
.150	-40.0	11.5
.250	-40.0	11.6
.500	-40.0	11.5
.750	-40.1	11.5
1.000	-39.9	11.7
2.000	-39.5	12.0
3.000	-39.4	12.1
4.000	-39.7	11.9
5.000	-39.7	11.8
10.000	40.2	11.3
15.000	-40.7	10.8
20.000	-40.5	11.0
25.000	-41.3	10.2
30.000	42.3	9.2