



GFSK



DH 1



DH 3



DH 5





8-DPSK



3DH 1



3DH 3



3DH 5



10. MAXIMUM PEAK OUTPUT POWER TEST

10.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.07,22	1 Year
2.	Power meter	Anritsu	ML2487A	6K00002472	Apr.07,22	1 Year
3.	Power sensor	Anritsu	MA2491A	033005	Apr.06,22	1 Year
4.	RF Cable	HUBER+SUHNER	SUCOFLE X-106	505238/6	Apr.07,22	1 Year

10.2. Limit

For frequency hopping systems operating in the 2400-2483.5 MHz band employing at least 75 non-overlapping hopping channels, and all frequency hopping systems in the 5725-5850 MHz band: 1 watt.

10.3. Test Procedure

Use the test method described in ANSI C63.10 clause 7.8.5:

Connected the EUT's antenna port to Power Sensor, and use power meter to test peak output power directly.

10.4. Test Results

EUT: Truck Infotainment Unit		
M/N: Service Entertainment Module 2.5		
Test date: 2022-07-01	Pressure: 102.1 ± 1.0 kpa	Humidity: $53.2 \pm 3.0\%$
Tested by: Xinyao	Test site: RF site	Temperature: 22.3 ± 0.6 °C

Test Mode	Frequency	Peak output Power (dBm)	Limit (dBm)
GFSK	2402	3.155	21
	2441	3.075	
	2480	3.010	
8-DPSK	2402	6.024	21
	2441	5.982	
	2480	5.899	
Conclusion: PASS			

11. BAND EDGE COMPLIANCE TEST

11.1. Test Equipments

Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Interval
1.	PXA Signal Analyzer	Agilent	N9030A	MY51380221	Apr.07,22	1 Year
2.	Amplifier	Agilent	8449B	3008A02495	Apr.07,22	1 Year
3.	Horn Antenna	ETC	MCTD 1209	DRH15F03006	Jul.26,21	1 Year
4.	RF Cable	HUBER+SUHN ER	SUCOFLEX-106	505238/6	Apr.07,22	1 Year

11.2. Limit

All the lower and upper band-edges emissions appearing within 2310MHz to 2390MHz and 2483.5MHz to 2500MHz restricted frequency bands shall not exceed the limits shown in 15.209, all the other emissions outside operation frequency band 2400MHz to 2483.5MHz shall be at least 20dB below the fundamental emissions, or comply with 15.209 limits.

11.3. Test Produce

Use the test method described in ANSI C63.10 clause 7.8.6:

For upper band emissions that are up to two bandwidths(2MHz) away (2483.5MHz to 2485.5MHz) from the band-edge use below produce:

1. Choose a spectrum analyzer span that encompasses both the peak of the fundamental emission and the band-edge emission under investigation. Set the analyzer RBW to 100KHz and with a video bandwidth 300KHz. Record the peak levels of the fundamental emission and the relevant band-edge emission, Observe the stored trace and measure the amplitude delta between the peak of the fundamental and the peak of the band-edge emission. This is not a field strength measurement, it is only a relative measurement to determine the amount by which the emission drops at the band edge relative to the highest fundamental emission level.
2. Subtract the delta measured in step (1) from the maximum field strengths measured in clause 4 .The resultant field strengths are then used to determine band-edge compliance as required by Section 15.205

For emissions above two bandwidths away from the band-edge use below produce:

1. The EUT is placed on a insulating material (up to 12mm thick) worked at highest radiated power.
2. The turntable was rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upperband-edges of the emission:
 - (a) PEAK: RBW=1MHz ;VBW=3MHz, PK detector, Sweep=AUTO
 - (b) This is pulse Modulation device a duty cycle factor was used to calculate average level based measured peak level.


11.4. Test Results

Pass (The testing data was attached in the next pages.)

Note: If the PK measured levels comply with average limit, then the average level were deemed to comply with average limit.

Data: 1 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)

Date: 2022-07-15




Site no. : 3m Chamber Data no. : 1
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 GFSK 2402MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
		(MHz)	(dB/m)		(dB)	(dB)			
1	2390.00	27.89	3.65	49.61	35.24	45.91	74.00	28.09	Peak
2	2402.25	27.89	3.66	94.83	35.24	91.14	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 2 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)




Site no. : 3m Chamber Data no. : 2
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 GFSK 2402MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
		(MHz)	(dB/m)		(dB)	(dB)			
1	2390.00	27.89	3.65	48.79	35.24	45.09	74.00	28.91	Peak
2	2402.25	27.89	3.66	105.45	35.24	101.76	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 15 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)

Date: 2022-07-15




Site no. : 3m Chamber Data no. : 15
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 GFSK 2480MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor (dB)	Emission	Limits (dBuV/m)	Margin (dB)	Remark
		Factor (dB/m)	Loss (dB)			Level (dBuV/m)			
1	2479.84	28.07	3.71	102.00	35.25	98.53	-----	-----	Peak
2	2483.50	28.07	3.71	56.46	35.25	52.99	74.00	21.01	Peak
3	2500.00	28.10	3.72	46.30	35.25	42.87	74.00	31.13	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 16 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)

Date: 2022-07-15




Site no. : 3m Chamber Data no. : 16
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 GFSK 2480MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
		Factor (dB/m)	Loss (dB)						
1	2479.84	28.07	3.71	93.74	35.25	90.27	-----	-----	Peak
2	2483.50	28.07	3.71	48.00	35.25	44.53	74.00	29.47	Peak
3	2500.00	28.10	3.72	46.93	35.25	43.50	74.00	30.50	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 17 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)




Site no. : 3m Chamber Data no. : 17
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : HORIZONTAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 8DPSK 2402MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
		(MHz)	(dB/m)		(dB)	(dB)			
1	2390.00	27.89	3.65	50.61	35.24	46.91	74.00	27.09	Peak
2	2402.06	27.89	3.66	108.81	35.24	105.12	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 18 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)




Site no. : 3m Chamber Data no. : 18
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 8DPSK 2402MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor	Emission Level (dBuV/m)	Limits	Margin	Remark
		(MHz)	Factor (dB/m)		Loss (dB)	(dB)	(dBuV/m)	(dBuV/m)	(dB)
1	2390.00	27.89	3.65	48.82	35.24	45.12	74.00	28.88	Peak
2	2402.06	27.89	3.66	97.91	35.24	94.22	-----	-----	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

Data: 31 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)

Date: 2022-07-15



Site no. : 3m Chamber Data no. : 31
 Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : HORIZONTAL
 Limit : FCC PART 15C PEAK
 Env. / Ins. : 23.8°C/53.5% Engineer : Allen
 Test Mode : BT3.0 8DPSK 2480MHz Tx


No.	Freq. (MHz)	Ant.	Cable	Amp	Emission	Limits	Margin	Remark
		Factor (dB/m)	Loss (dB)	Reading (dBuV)	factor (dB)			
1	2480.07	28.07	3.71	104.60	35.25	101.13	-----	Peak
2	2483.50	28.07	3.71	59.51	35.25	56.04	74.00	17.96
3	2500.00	28.10	3.72	46.46	35.25	43.03	74.00	30.97

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading -Amp factor.
 2. The emission levels that are 20dB below the official limit are not reported.

Frequency (MHz)	Peak level (dBuV/m)	Duty cycle factor (dB)	AV level (dBuV/m)	Limit(dBuV/m)	Conclusion
2483.50	56.04	-30.692	25.348	54	Pass

Data: 32 File: F:\2022 Report\北京摩创\A1Z2206116\A1Z2206116-BT.EM6 (32)

Date: 2022-07-15



Site no. : 3m Chamber Data no. : 32
Dis. / Ant. : 3m 2021 MCTD1209-3006 Ant. pol. : VERTICAL
Limit : FCC PART 15C PEAK
Env. / Ins. : 23.8°C/53.5% Engineer : Allen
Test Mode : BT3.0 8DPSK 2480MHz Tx

No.	Freq. (MHz)	Ant.	Cable	Reading (dBuV)	Amp factor (dB)	Emission Level (dBuV/m)	Limits (dBuV/m)	Margin (dB)	Remark
		Factor (dB/m)	Loss (dB)						
1	2479.97	28.07	3.71	96.79	35.25	93.32	-----	-----	Peak
2	2483.50	28.07	3.71	50.73	35.25	47.26	74.00	26.74	Peak
3	2500.00	28.10	3.72	46.72	35.25	43.29	74.00	30.71	Peak

Remarks: 1. Emission Level= Antenna Factor + Cable Loss + Reading
-Amp factor.
2. The emission levels that are 20dB below the official
limit are not reported.

12. ANTENNA REQUIREMENT

12.1. Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

12.2. Antenna Connected Construction

The antennas used for this product are External Chip Antenna that no antenna other than that furnished by the responsible party shall be used with the device, the maximum peak gain of the transmit antenna is 2.23dBi.

13. DEVIATION TO TEST SPECIFICATIONS

[NONE]

..... **THE END**