

FCC REPORT

Applicant: Shenzhen YIDONG Technology Co., Ltd

Address of Applicant: Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Flat Computer

Model No.: LT8088, EMR0682, S8

FCC ID: LU7-LT8088

Applicable standards: FCC CFR Title 47 Part 15 Subpart B: 2011

Date of sample receipt: 17 Sep., 2012

Date of Test: 18 to 25 Sep., 2012

Date of report issued: 25 Sep., 2012

Test Result : Pass *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.

This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	25 Sep., 2012	<i>Original</i>

Prepared By:




Date:

25 Sep., 2012

Project Engineer

Check By:



Date:

25 Sep., 2012

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF E.U.T.	5
5.3 OPERATING MODES	5
5.4 DESCRIPTION OF SUPPORT UNITS	6
5.5 DEVIATION FROM STANDARDS.....	6
5.6 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
5.7 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
5.8 TEST FACILITY.....	6
5.9 TEST LOCATION	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	8
7.1 CONDUCTED EMISSIONS.....	8
7.2 RADIATED EMISSION	11
8 TEST SETUP PHOTO	17
9 EUT CONSTRUCTIONAL DETAILS	19

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	Pass
Readiated Emissions	Part15.109	Pass

Pass: The EUT complies with the essential requirements in the standard.

5 General Information

5.1 Client Information

Applicant:	Shenzhen YIDONG Technology Co., Ltd
Address of Applicant:	Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China
Manufacturer/ Factory:	Shenzhen YIDONG Technology Co., Ltd
Address of Manufacturer/ Factory:	Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China

5.2 General Description of E.U.T.

Product Name:	Flat Computer
Model No.:	LT8088, EMR0682, S8
AC adapter:	Model: HNC050200U Input: AC 100-240V~50/60Hz 0.35A MAX Output: DC 5.0V 2.0A
Power supply:	DC 3.7V Li-ion battery
Remark	The LT8088, EMR0682 and S8 were identical inside, since the electrical circuit design, layout, components used and internal wiring were identical for the above items, with only difference being the printing and shell color. Base on the difference and the pre-scan, we selected the LT8088, for full test. The highest operation frequency is 1.2GHz.

5.3 Operating Modes

Operating mode	Detail description
Memory Play mode :	Keep the EUT in memory video Play mode
Downloading mode :	Keep the EUT in exchange data with PC by Mini SD and Memory
SD Play mode :	Keep the EUT in Mini SD video Play mode
Recording mode :	Keep the EUT in Recording mode.
Camera Mode :	Keep the EUT in Camera mode.

Pre-scan all modes above mentioned, the downloading mode was the worst case mode which has been shown in this report.

5.4 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC ID/DoC
HP	Printer	P1007	VNFP409729	DoC
HP	PC	Pro 2000MT	N/A	DoC
HP	MONITOR	CompaqLE1851WL	515682-070	DoC
HP	KEYBOARD	SK-2880	434820-AA2	DoC
HP	MOUSE	MOC5UO	N/A	DoC
Kingston	Mini SD card	N/A	N/A	N/A

5.5 Deviation from Standards

None

5.6 Abnormalities from Standard Conditions

None.

5.7 Other Information Requested by the Customer

None.

5.8 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

● **FCC —Registration No.: 600491**

Global United Technology Service Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in out files. Registration 600491, July 20, 2010.

● **Industry Canada (IC)**

The 3m Semi-anechoic chamber of Global United Technology Service Co., Ltd. Has been Registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-1.

5.9 Test Location

All tests were performed at:

Global United Technology Service Co., Ltd.

Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China

Tel: 0755-27798480

Fax: 0755-27798960

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.2(L)*6.2(W)* 6.4(H)	GTS250	Mar. 30 2012	Mar. 29 2013
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	EMI Test Receiver	Rohde & Schwarz	ESU26	GTS203	Jul. 04 2012	Jul. 03 2013
4	BiConiLog Antenna	SCHWARZBECK MESS-ELEKTRONIK	VULB9163	GTS214	Feb. 26 2012	Feb. 25 2013
5	Double -ridged waveguide horn	SCHWARZBECK MESS-ELEKTRONIK	9120D-829	GTS208	June 30 2012	June 29 2013
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
7	Coaxial Cable	GTS	N/A	GTS213	Apr. 01 2012	Mar. 31 2013
8	Coaxial Cable	GTS	N/A	GTS211	Apr. 01 2012	Mar. 31 2013
9	Coaxial cable	GTS	N/A	GTS210	Apr. 01 2012	Mar. 31 2013
10	Coaxial Cable	GTS	N/A	GTS212	Apr. 01 2012	Mar. 31 2013
11	Amplifier(100kHz-3GHz)	HP	8347A	GTS204	Jul. 04 2012	Jul. 03 2013
12	Amplifier(2GHz-20GHz)	HP	8349B	GTS206	Jul. 04 2012	Jul. 03 2013

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS252	Jul. 04 2012	Jul. 03 2013
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	Jul. 04 2012	Jul. 03 2013
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	Jul. 04 2012	Jul. 03 2013
4	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	Jul. 04 2012	Jul. 03 2013
5	Coaxial Cable	GTS	N/A	GTS227	Apr. 01 2012	Mar. 31 2013
6	EMI Test Software	AUDIX	E3	N/A	N/A	N/A


7 Test results and Measurement Data

7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150kHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9kHz, VBW=30kHz																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>0.5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dB μ V)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	0.5-30	60	50
Frequency range (MHz)	Limit (dB μ V)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
0.5-30	60	50															
Test setup:	<p>Reference Plane</p> <p><i>Remark</i> <i>E.U.T: Equipment Under Test</i> <i>LISN: Line Impedance Stabilization Network</i> <i>Test table height=0.8m</i></p>																
Test procedure	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network(L.I.S.N.). They provide a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 																
Test environment:	Temp.:	25 °C	Humid.:	52%	Press.:	1 012mbar											
Measurement Record:						Uncertainty: 3.28dB											
Test Instruments:	Refer to section 6 for details																
Test mode:	Pre-scan all test mode in the section 5.3, and found the below mode which it is the worst case mode.																
Test results:	Pass																

Measurement data:


Line:



Site : CCIS Conducted Test Site
 Condition : FCC CLASS-B QP LISN LINE
 Job NO. : 173RF
 Test Mode : Downloading Mode
 Power Rating: AC 120V/60Hz
 Environment : Temp: 23 °C Huni:56%
 Test engineer: Winner

	Read Freq	LISN Level	Cable Factor	Limit Loss	Line Level	Over Line Limit	Remark
	MHz	dBuV	dB	dB	dBuV	dBuV	dB
1	0.190	44.30	10.22	0.76	55.28	64.02	-8.74 QP
2	0.253	43.49	10.24	0.75	54.48	61.64	-7.16 QP
3	0.299	41.38	10.26	0.74	52.38	60.28	-7.90 QP
4	0.637	31.32	10.21	0.77	42.30	46.00	-3.70 Average
5	0.701	27.20	10.18	0.77	38.15	46.00	-7.85 Average
6	0.724	38.24	10.18	0.78	49.20	56.00	-6.80 QP
7	0.767	39.44	10.19	0.79	50.42	56.00	-5.58 QP
8	0.767	33.46	10.19	0.79	44.44	46.00	-1.56 Average
9	1.088	24.85	10.22	0.82	35.89	46.00	-10.11 Average
10	1.147	32.12	10.22	0.77	43.11	56.00	-12.89 QP
11	1.918	26.78	10.28	0.03	37.09	46.00	-8.91 Average
12	3.258	26.88	10.29	0.90	38.07	46.00	-7.93 Average

Neutral:





Site : CCIS Conducted Test Site
 Condition : FCC PART15 B QP LISN NEUTRAL
 Job NO. : 173RF
 Test Mode : Downloading Mode
 Power Rating : AC 120V/60Hz
 Environment : Temp: 23 °C Humi:56%
 Test Engineer: Winner

Freq	Read	LISN	Cable	Limit	Over	Remark	
	MHz	dBuV	dB	dB	dBuV		
1	0.174	45.30	10.25	0.77	56.32	64.77	-8.45 QP
2	0.230	36.88	10.23	0.75	47.86	52.44	-4.58 Average
3	0.286	42.10	10.24	0.74	53.08	60.63	-7.55 QP
4	0.286	35.93	10.24	0.74	46.91	50.63	-3.72 Average
5	0.346	42.30	10.25	0.73	53.28	59.05	-5.77 QP
6	0.346	34.43	10.25	0.73	45.41	49.05	-3.64 Average
7	0.686	30.02	10.17	0.77	40.96	46.00	-5.04 Average
8	0.694	41.50	10.16	0.77	52.43	56.00	-3.57 QP
9	0.743	42.10	10.17	0.78	53.05	56.00	-2.95 QP
10	0.743	34.57	10.17	0.78	45.52	46.00	-0.48 Average
11	0.804	30.56	10.18	0.80	41.54	46.00	-4.46 Average
12	0.809	38.73	10.18	0.81	49.72	56.00	-6.28 QP

Notes:

1. The following Quasi-Peak and Average measurements were performed on the EUT
2. Final Test Level =Receiver Reading + LISN Factor + Cable Loss.

7.2 Radiated Emission


Test Requirement:	FCC Part15 B Section 15.109				
Test Method:	ANSI C63.4:2003				
Test Frequency Range:	30MHz to 6000MHz				
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)				
Receiver setup:	Frequency	Detector	RBW	VBW	Remark
	30MHz-1GHz	Quasi-peak	100KHz	300KHz	Quasi-peak Value
	Above 1GHz	Peak	1MHz	3MHz	Peak Value
	Peak	1MHz	10Hz		Average Value
Limit:	Frequency	Limit (dBuV/m @3m)		Remark	
	30MHz-88MHz	40.0		Quasi-peak Value	
	88MHz-216MHz	43.5		Quasi-peak Value	
	216MHz-960MHz	46.0		Quasi-peak Value	
	960MHz-1GHz	54.0		Quasi-peak Value	
	Above 1GHz	54.0		Average Value	
		74.0		Peak Value	
Test setup:	<p>Below 1GHz</p>  <p>Above 1GHz</p> 				

Test Procedure:	1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.
Test environment:	Temp.: 25 °C Humid.: 52% Press.: 1 012mbar
Measurement Record:	Uncertainty: 4.88dB
Test Instruments:	Refer to section 6 for details
Test mode:	Pre-scan all test mode in the section 5.3, and found the bleow mode which it is the worst case mode.
Test results:	Passed

Measurement Data

■ Below 1G


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(2012.4.1) HORIZONTAL
 Job No. : 173RF
 Test mode : downloading mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Huni:55%
 Test Engineer: Gavin

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	86.503	55.38	10.89	1.91	30.09	38.09	40.00	-1.91 QP
2	150.011	58.04	8.26	2.52	29.23	39.59	43.50	-3.91 QP
3	480.528	54.77	16.07	3.46	30.52	43.78	46.00	-2.22 QP
4	576.644	51.86	18.03	3.92	30.55	43.26	46.00	-2.74 QP
5	584.790	52.09	18.19	3.92	30.55	43.65	46.00	-2.35 QP
6	721.726	49.64	19.10	4.26	30.55	42.45	46.00	-3.55 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163(2012.4.1) VERTICAL
 Job No. : 173RF
 Test mode : downloading mode
 Power Rating : AC 120V/60Hz
 Environment : Temp:25.5°C Humi:55%
 Test Engineer: Gavin

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Remark
	Level	Factor	Loss	Factor				
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	89.905	48.60	11.90	2.04	30.07	32.47	43.50	-11.03 QP
2	124.133	52.04	9.80	2.21	29.63	34.42	43.50	-9.08 QP
3	138.387	53.89	8.30	2.38	29.40	35.17	43.50	-8.33 QP
4	239.987	58.92	12.09	2.82	29.64	44.19	46.00	-1.81 QP
5	605.659	48.03	18.47	3.93	30.55	39.88	46.00	-6.12 QP
6	893.857	47.70	21.05	3.77	30.16	42.36	46.00	-3.64 QP

■ Above 1G

Vertical:




Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120 (>1GHZ) VERTICAL
 Job No. : 173RF
 Test mode : downloading mode
 Power Rating : AC 120W/60Hz
 Environment : Temp:25.5°C Huni:55%

Test Engineer: Gavin

	Read	Antenna	Cable	Preamp	Limit	Over		
Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1185.000	44.33	24.88	2.58	18.65	53.14	74.00	-20.86 Peak
2	3600.000	40.96	29.16	4.95	27.72	47.35	74.00	-26.65 Peak
3	5135.000	36.50	32.08	6.08	23.87	50.79	74.00	-23.21 Peak
4	5705.000	35.94	32.21	6.39	23.84	50.70	74.00	-23.30 Peak

Horizontal:



Site : 3m chamber

Condition : FCC PART 15 (PK) 3m BBHA9120 (>1GHZ) HORIZONTAL

Job No. : 173RF

Test mode : downloading mode

Power Rating : AC 120V/60Hz

Environment : Temp:25.5°C Huni:55%

Test Engineer: Gavin

Freq	ReadAntenna		Cable		Preamp	Limit	Over	Line	Limit	Remark
	Level	Factor	Loss	Factor						
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	dB	dB	dB
1 1185.000	40.73	24.88	2.58	18.65	49.54	74.00	-24.46	Peak		
2 2260.000	41.91	28.02	3.72	30.50	43.15	74.00	-30.85	Peak		
3 3395.000	40.87	28.46	4.77	28.20	45.90	74.00	-28.10	Peak		
4 5520.000	34.84	32.07	6.29	23.80	49.40	74.00	-24.60	Peak		

Remark:

The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor - Preamplifier Factor

The Peak levels are less than the AV limit, so just recorded the peak Value.