



TEST REPORT

Applicant: Shenzhen YIDONG Technology Co., Ltd.

Address of Applicant: Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China

Equipment Under Test (EUT)

Product Name: Flat Computer

Model No.: PLT9602G, EMR3094

FCC ID: LU7-PLT9602G

Applicable standards: FCC CFR Title 47 Part 15 Subpart B:2012

Date of sample receipt: January 24, 2014

Date of Test: February 07-18, 2014

Date of report issue: February 18, 2014

Test Result : PASS *

* In the configuration tested, the EUT complied with the standards specified above.

Authorized Signature:



Robinson Lo
Laboratory Manager

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product and does not permit the use of the GTS product certification mark. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in this report.


This report may only be reproduced and distributed in full. If the product in this report is used in any configuration other than that detailed in the report, the manufacturer must ensure the new system complies with all relevant standards. Any mention of GTS International Electrical Approvals or testing done by GTS International Electrical Approvals in connection with, distribution or use of the product described in this report must be approved by GTS International Electrical Approvals in writing.

This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 90 days only."

2 Version

Version No.	Date	Description
00	February 18, 2014	Original

Prepared By:



Date:

February 18, 2014

Project Engineer

Check By:



Date:

February 18, 2014

Reviewer

3 Contents

	Page
1 COVER PAGE	1
2 VERSION	2
3 CONTENTS	3
4 TEST SUMMARY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION.....	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE	5
5.4 TEST FACILITY.....	6
5.5 TEST LOCATION.....	6
5.6 DESCRIPTION OF SUPPORT UNITS	6
5.7 DEVIATION FROM STANDARDS	6
5.8 ABNORMALITIES FROM STANDARD CONDITIONS.....	6
5.9 OTHER INFORMATION REQUESTED BY THE CUSTOMER	6
6 TEST INSTRUMENTS LIST	7
7 TEST RESULTS AND MEASUREMENT DATA	8
7.1 CONDUCTED EMISSIONS	8
7.2 RADIATED EMISSION	11
8 TEST SETUP PHOTO	17
9 EUT CONSTRUCTIONAL DETAILS	18

4 Test Summary

Test Item	Section in CFR 47	Result
Conducted Emission	Part15.107	PASS
Radiated Emissions	Part15.109	PASS

PASS: *The EUT complies with the essential requirements in the standard.*

5 General Information

5.1 Client Information

Applicant:	Shenzhen YIDONG Technology Co., Ltd.
Address of Applicant:	Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China
Manufacturer/Factory:	Shenzhen YIDONG Technology Co., Ltd.
Address of Manufacturer/Factory:	Floor 1-5, Building B, Area B, Yuanfen Industrial Zone, Dalang, Bao'an District, Shenzhen, China

5.2 General Description of EUT

Product Name:	Flat Computer
Model No.:	PLT9602G, EMR3094
Power supply:	Adapter 1: Model No.: STC-A515B-D Input: AC 100-240V 50/60Hz 0.3A Output: DC 5.0V 1.5A Adapter 2: Model No.: WRP2U-050200C Input: AC 100-240V 50/60Hz 0.4A max Output: DC 5.0V 2A Or DC 3.7V Li-ion Battery
<i>Remark: Two adapter were tested and found the data of adapter 1 is worse, so only the data of adapter 1 is reported.</i>	

5.3 Test mode

Test mode:	
Video Playing mode	Keep the EUT in video playing mode
PC mode	Keep the EUT in exchanging data mode.
Video Record mode	Keep the EUT in video recording mode.

5.4 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

- **CNAS —Registration No.: CNAS L5775**

CNAS has accredited Global United Technology Services Co., Ltd. To ISO/IEC 17025 General Requirements for the competence of testing and calibration laboratories (CNAS-CL01 Accreditation Criteria for the Competence of Testing and Calibration Laboratories) for the competence in the field of testing.

- **FCC —Registration No.: 600491**

Global United Technology Services Co., Ltd., Shenzhen EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in files. Registration 600491, June 28, 2013.

- **Industry Canada (IC) —Registration No.: 9079A-2**

The 3m Semi-anechoic chamber of Global United Technology Services Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 9079A-2, June 26, 2013.

5.5 Test Location

All tests were performed at:

Global United Technology Services Co., Ltd.
Address: 2nd Floor, Block No.2, Laodong Industrial Zone, Xixiang Road Baoan District, Shenzhen, China
Tel: 0755-27798480
Fax: 0755-27798960

5.6 Description of Support Units

Manufacturer	Description	Model	Serial Number	FCC Approval
HP	Printer	CB495A	05257893	DoC
Lenovo	PC Host	M6900	EA05257893	DoC
DELL	MONITOR	E178FPC	N/A	DoC
DELL	KEYBOARD	SK-8115	N/A	DoC
DELL	MOUSE	MOC5UO	N/A	DoC

5.7 Deviation from Standards

Biconical, log.per. antenna and horn antenna were used instead of dipole antenna.
Semi-anechoic Chamber was used as alternation of open air test sites, and all test suites were performed with radiated method in it.

5.8 Abnormalities from Standard Conditions

None.

5.9 Other Information Requested by the Customer

None.

6 Test Instruments list

Radiated Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	3m Semi- Anechoic Chamber	ZhongYu Electron	9.0(L)*6.0(W)* 6.0(H)	GTS250	Mar. 29 2013	Mar. 28 2015
2	Control Room	ZhongYu Electron	6.2(L)*2.5(W)* 2.4(H)	GTS251	N/A	N/A
3	ESU EMI Test Receiver	R&S	ESU26	GTS203	Jul. 02 2013	Jul. 01 2014
4	BiConiLog Antenna	SCHWARZBECK	VULB9163	GTS214	Feb. 24 2013	Feb. 23 2014
5	Double -ridged waveguide horn	SCHWARZBECK	9120D	GTS208	June 28 2013	June 27 2014
6	RF Amplifier	HP	8347A	GTS204	Jul. 02 2013	Jul. 01 2014
7	Preamplifier	HP	8349B	GTS206	Jul. 02 2013	Jul. 01 2014
8	EMI Test Software	AUDIX	E3	N/A	N/A	N/A
9	Coaxial cable	GTS	N/A	GTS210	Mar. 30 2013	Mar. 29 2014
10	Coaxial Cable	GTS	N/A	GTS211	Mar. 30 2013	Mar. 29 2014
11	Thermo meter	N/A	N/A	GTS256	Jul. 05 2013	Jul. 04 2014

Conducted Emission:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Shielding Room	ZhongYu Electron	7.0(L)x3.0(W)x3.0(H)	GTS264	Sep. 07 2013	Sep. 06 2015
2	EMI Test Receiver	Rohde & Schwarz	ESCS30	GTS223	Jul. 02 2013	Jul. 01 2014
3	10dB Pulse Limita	Rohde & Schwarz	N/A	GTS224	Jul. 02 2013	Jul. 01 2014
4	Coaxial Switch	ANRITSU CORP	MP59B	GTS225	Jul. 02 2013	Jul. 01 2014
5	LISN	SCHWARZBECK MESS-ELEKTRONIK	NSLK 8127	GTS226	Jul. 02 2013	Jul. 01 2014
6	Coaxial Cable	GTS	N/A	GTS227	Jul. 02 2013	Jul. 01 2014
7	EMI Test Software	AUDIX	E3	N/A	N/A	N/A

General used equipment:						
Item	Test Equipment	Manufacturer	Model No.	Inventory No.	Cal.Date (mm-dd-yy)	Cal.Due date (mm-dd-yy)
1	Barometer	ChangChun	DYM3	GTS257	July 09 2013	July 08 2014


7 Test Results and Measurement Data

7.1 Conducted Emissions

Test Requirement:	FCC Part15 B Section 15.107																
Test Method:	ANSI C63.4:2003																
Test Frequency Range:	150KHz to 30MHz																
Class / Severity:	Class B																
Receiver setup:	RBW=9KHz, VBW=30KHz, Sweep time=auto																
Limit:	<table border="1"> <thead> <tr> <th rowspan="2">Frequency range (MHz)</th> <th colspan="2">Limit (dBuV)</th> </tr> <tr> <th>Quasi-peak</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15-0.5</td> <td>66 to 56*</td> <td>56 to 46*</td> </tr> <tr> <td>0.5-5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5-30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>			Frequency range (MHz)	Limit (dBuV)		Quasi-peak	Average	0.15-0.5	66 to 56*	56 to 46*	0.5-5	56	46	5-30	60	50
Frequency range (MHz)	Limit (dBuV)																
	Quasi-peak	Average															
0.15-0.5	66 to 56*	56 to 46*															
0.5-5	56	46															
5-30	60	50															
	<small>* Decreases with the logarithm of the frequency.</small>																
Test setup:	<p>Reference Plane</p> <p>LISN</p> <p>40cm</p> <p>80cm</p> <p>AUX Equipment</p> <p>E.U.T</p> <p>Test table/Insulation plane</p> <p>EMI Receiver</p> <p>Filter</p> <p>AC power</p> <p>Remark E.U.T: Equipment Under Test LISN: Line Impedance Stabilization Network Test table height=0.8m</p>																
Test procedure:	<ol style="list-style-type: none"> 1. The E.U.T and simulators are connected to the main power through a line impedance stabilization network (L.I.S.N.). This provides a 50ohm/50uH coupling impedance for the measuring equipment. 2. The peripheral devices are also connected to the main power through a LISN that provides a 50ohm/50uH coupling impedance with 50ohm termination. (Please refer to the block diagram of the test setup and photographs). 3. Both sides of A.C. line are checked for maximum conducted interference. In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.4: 2003 on conducted measurement. 																
Test Instruments:	Refer to section 6 for details																
Test mode:	Pre-scan all modes in section 5.3, and found the PC mode which is the worst mode, so only the data of worst mode was show on the test report.																
Test results:	Pass																

Measurement Data

Line:



Condition : FCC PART15 CLASSB QP LISN-2013 LINE


Job No. : 0103RF

Test mode : PC mode

Test Engineer: alan

Freq	Read	LISN	Cable	Limit	Over	Remark	
	Level	Factor	Loss				
	MHz	dBuV	dB	dB	dBuV	dB	
1	0.208	35.02	0.13	0.13	35.28	63.27	-27.99 QP
2	0.208	32.02	0.13	0.13	32.28	53.27	-20.99 Average
3	0.484	31.57	0.12	0.11	31.80	56.27	-24.47 QP
4	0.484	27.80	0.12	0.11	28.03	46.27	-18.24 Average
5	0.555	32.13	0.13	0.11	32.37	56.00	-23.63 QP
6	0.555	28.13	0.13	0.11	28.37	46.00	-17.63 Average
7	0.899	30.44	0.14	0.13	30.71	56.00	-25.29 QP
8	0.899	24.44	0.14	0.13	24.71	46.00	-21.29 Average
9	1.527	32.68	0.12	0.14	32.94	56.00	-23.06 QP
10	1.527	26.93	0.12	0.14	27.19	46.00	-18.81 Average
11	20.486	40.65	0.64	0.22	41.51	60.00	-18.49 QP
12	20.486	25.52	0.64	0.22	26.38	50.00	-23.62 Average

Neutral:




Freq	Read	LISN	Cable	Level	Limit	Over	Remark
	MHz	dBuV	Factor		Line	Limit	
1	0.208	39.68	0.13	0.13	39.94	63.27	-23.33 QP
2	0.208	31.68	0.13	0.13	31.94	53.27	-21.33 Average
3	0.277	32.82	0.11	0.10	33.03	60.90	-27.87 QP
4	0.277	23.03	0.11	0.10	23.24	50.90	-27.66 Average
5	0.830	33.35	0.14	0.13	33.62	56.00	-22.38 QP
6	0.830	29.35	0.14	0.13	29.62	46.00	-16.38 Average
7	1.178	34.96	0.13	0.13	35.22	56.00	-20.78 QP
8	1.178	30.22	0.13	0.13	30.48	46.00	-15.52 Average
9	12.318	34.44	0.36	0.20	35.00	60.00	-25.00 QP
10	12.318	27.44	0.36	0.20	28.00	50.00	-22.00 Average
11	20.924	41.93	0.69	0.22	42.84	60.00	-17.16 QP
12	20.924	33.84	0.69	0.22	34.75	50.00	-15.25 Average

Notes:


1. An initial pre-scan was performed on the line and neutral lines with peak detector.
2. Quasi-Peak and Average measurement were performed at the frequencies with maximized peak emission.
3. Final Level =Receiver Read level + LISN Factor + Cable Loss

7.2 Radiated Emission

Test Requirement:	FCC Part15 B Section 15.109																									
Test Method:	ANSI C63.4:2003																									
Test Frequency Range:	30MHz to 6GHz																									
Test site:	Measurement Distance: 3m (Semi-Anechoic Chamber)																									
Receiver setup:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Detector</th> <th>RBW</th> <th>VBW</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-1GHz</td> <td>Quasi-peak</td> <td>120kHz</td> <td>300kHz</td> <td>Quasi-peak Value</td> </tr> <tr> <td>Above 1GHz</td> <td>Peak</td> <td>1MHz</td> <td>3MHz</td> <td>Peak Value</td> </tr> <tr> <td></td> <td>Peak</td> <td>1MHz</td> <td>10Hz</td> <td>Average Value</td> </tr> </tbody> </table>					Frequency	Detector	RBW	VBW	Remark	30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value	Above 1GHz	Peak	1MHz	3MHz	Peak Value		Peak	1MHz	10Hz	Average Value	
Frequency	Detector	RBW	VBW	Remark																						
30MHz-1GHz	Quasi-peak	120kHz	300kHz	Quasi-peak Value																						
Above 1GHz	Peak	1MHz	3MHz	Peak Value																						
	Peak	1MHz	10Hz	Average Value																						
Limit:	<table border="1"> <thead> <tr> <th>Frequency</th> <th>Limit (dBuV/m @3m)</th> <th>Remark</th> </tr> </thead> <tbody> <tr> <td>30MHz-88MHz</td> <td>40.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>88MHz-216MHz</td> <td>43.50</td> <td>Quasi-peak Value</td> </tr> <tr> <td>216MHz-960MHz</td> <td>46.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>960MHz-1GHz</td> <td>54.00</td> <td>Quasi-peak Value</td> </tr> <tr> <td>Above 1GHz</td> <td>54.00</td> <td>Average Value</td> </tr> <tr> <td></td> <td>74.00</td> <td>Peak Value</td> </tr> </tbody> </table>					Frequency	Limit (dBuV/m @3m)	Remark	30MHz-88MHz	40.00	Quasi-peak Value	88MHz-216MHz	43.50	Quasi-peak Value	216MHz-960MHz	46.00	Quasi-peak Value	960MHz-1GHz	54.00	Quasi-peak Value	Above 1GHz	54.00	Average Value		74.00	Peak Value
Frequency	Limit (dBuV/m @3m)	Remark																								
30MHz-88MHz	40.00	Quasi-peak Value																								
88MHz-216MHz	43.50	Quasi-peak Value																								
216MHz-960MHz	46.00	Quasi-peak Value																								
960MHz-1GHz	54.00	Quasi-peak Value																								
Above 1GHz	54.00	Average Value																								
	74.00	Peak Value																								
Test Procedure:	<ol style="list-style-type: none"> 1. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 meter camber. The table was rotated 360 degrees to determine the position of the highest radiation. 2. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. 3. The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement. 4. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rota table was turned from 0 degrees to 360 degrees to find the maximum reading. 5. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode. 6. If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet. 																									
Test setup:	Below 1GHz																									



Above 1GHz



Test environment:	Temp.: 25 °C	Humid.: 52%	Press.: 1 012mbar
Measurement Record:	Uncertainty: $\pm 4.5\text{dB}$		
Test Instruments:	Refer to section 6 for details		
Test mode:	Pre-scan all modes in section 5.3, and found the PC mode which is the worst mode, so only the data of worst mode was show on the test report.		
Test results:	Pass		

Note:


The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:

Final Test Level = Receiver Reading + Antenna Factor + Cable Factor – Preamplifier Factor

Measurement Data

Below 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163-2013M HORIZONTAL
 Job No. : 0103RF
 Test Mode : PC mode
 Test Engineer: Yang

	ReadAntenna	Cable	Preamp	Limit	Over			
Freq	Level	Factor	Loss	Level	Line	Limit	Remark	
MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	98.833	54.88	15.10	1.18	31.76	39.40	43.50	-4.10 QP
2	148.441	58.61	10.25	1.56	31.98	38.44	43.50	-5.06 QP
3	239.987	55.24	14.09	2.07	32.16	39.24	46.00	-6.76 QP
4	346.809	55.05	16.22	2.61	32.03	41.85	46.00	-4.15 QP
5	545.183	50.15	19.46	3.50	31.32	41.79	46.00	-4.21 QP
6	645.120	48.22	20.61	3.89	31.11	41.61	46.00	-4.39 QP

Vertical:




Site : 3m chamber
 Condition : FCC PART15 CLASS B 3m VULB9163-2013M VERTICAL
 Job No. : 0103RF
 Test Mode : PC mode
 Test Engineer: Yang

	Read	Antenna	Cable	Preamp	Limit	Over		
	Freq	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	98.833	53.47	15.10	1.18	31.76	37.99	43.50	-5.51 QP
2	148.441	57.73	10.25	1.56	31.98	37.56	43.50	-5.94 QP
3	239.987	53.43	14.09	2.07	32.16	37.43	46.00	-8.57 QP
4	446.414	51.79	17.57	3.07	31.73	40.70	46.00	-5.30 QP
5	645.120	47.72	20.61	3.89	31.11	41.11	46.00	-4.89 QP
6	744.866	45.14	21.39	4.26	31.25	39.54	46.00	-6.46 QP

Above 1GHz


Horizontal:



Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT(>1GHZ) HORIZONTAL
 Job No. : 0103RF
 Test Mode : PC mode
 Test Engineer: Yang

	ReadAntenna	Cable	Preamp	Limit	Over			
	Freq	Level	Factor	Loss	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB
1	1130.000	42.68	24.89	4.41	32.98	39.00	74.00	-35.00 Peak
2	2225.000	42.24	27.99	5.21	34.21	41.23	74.00	-32.77 Peak
3	2660.000	41.41	27.96	5.63	33.70	41.30	74.00	-32.70 Peak
4	3570.000	39.24	29.10	7.09	32.67	42.76	74.00	-31.24 Peak
5	4705.000	36.77	31.66	8.52	32.04	44.91	74.00	-29.09 Peak
6	5275.000	34.75	31.76	9.17	32.31	43.37	74.00	-30.63 Peak

Vertical:





Site : 3m chamber
 Condition : FCC PART 15 (PK) 3m BBHA9120D ANT (>1GHZ) VERTICAL
 Job No. : 0103RF
 Test Mode : PC mode
 Test Engineer: Yang

	Read	Antenna	Cable	Preamp	Limit	Over			
	Freq	Level	Factor	Loss	Factor	Level	Line	Limit	Remark
	MHz	dBuV	dB/m	dB	dB	dBuV/m	dBuV/m	dB	
1	1265.000	42.66	25.56	4.52	33.21	39.53	74.00	-34.47	Peak
2	2310.000	41.21	27.91	5.30	34.11	40.31	74.00	-33.69	Peak
3	3595.000	39.04	29.13	7.15	32.64	42.68	74.00	-31.32	Peak
4	4430.000	37.02	31.16	8.27	31.91	44.54	74.00	-29.46	Peak
5	5135.000	35.59	32.06	8.97	32.25	44.37	74.00	-29.63	Peak
6	5680.000	33.24	32.44	9.77	32.33	43.12	74.00	-30.88	Peak

8 Test Setup Photo

Radiated Emission



Conducted Emission



9 EUT Constructional Details

Reference to the test report No. GTSE14010010301

----- end -----