

## **SPECIFICATION**

#### **FXP73 Blue Diamond 2.4GHz Band Antenna**

: FXP73.09.0100A Part No.

Product Name : FXP73 Blue Diamond 2.4GHz

Multi Standard Antenna

: 2.5dBi Gain Feature

MMCX(M)RA Connector

10 mm Cable 47\*7\*0.1 mm **RoHS Compliant** 





#### 1. OVERVIEW

The FXP73 Blue Diamond 2.4GHz Antenna works on WiFi, ZigBee, Bluetooth and ISM band at 2.4 GHz. This antenna has been designed with a specific solution to cover the current market applications that require rectangular form-factor, with easy installation through a cable connection.

Many module manufacturers specify peak gain limits for any antennas that are to be connected to that module. Those peak gain limits are based on free-space conditions. In practice, the peak gain of an antenna tested in free-space can degrade by at least 1 or 2dBi when put inside a device. So ideally you should go for a slightly higher peak gain antenna than mentioned on the module specification to compensate for this effect, giving you better performance.

Upon testing of any of our antennas with your device and a selection of appropriate layout, integration technique, or cable, Taoglas can make sure any of our antennas' peak gain will be below the peak gain limits. Taoglas can then issue a specification and/or report for the selected antenna in your device that will clearly show it complying with the peak gain limits, so you can be assured you are meeting regulatory requirements for that module.

For example, a module manufacturer may state that the antenna must have less than 2dBi peak gain, but you don't need to select an embedded antenna that has a peak gain of less than 2dBi in free-space. This will give you a less optimized solution. It is better to go for a slightly higher free-space peak gain of 3dBi or more if available. Once that antenna gets integrated into your device, performance will degrade below this 2dBi peak gain due to the effects of GND plane, surrounding components, and device housing. If you want to be absolutely sure, contact Taoglas and we will test. Choosing a Taoglas antenna with a higher peak gain than what is specified by the module manufacturer and enlisting our help will ensure you are getting the best performance possible without exceeding the peak gain limits.



## 2. ANTENNA CHARACTERISTICS

|                        | Bluetooth         | Wi-Fi     | Zigbee    | 2.4GHz ISM  |
|------------------------|-------------------|-----------|-----------|-------------|
| Communication System   | 2401-             |           |           | 2422 2422 5 |
|                        | 2480              | 2412-2462 | 2410-2480 | 2400-2483.5 |
| Efficiency             | 50%               |           |           |             |
| Gain                   | 2.5dBi            |           |           |             |
| Free Space Peak Gain   | 3.0dBi            |           |           |             |
| Return Loss            | -10dB             |           |           |             |
| Impedance              | 50 Ohms           |           |           |             |
| VSWR                   | ≤ 2:1             |           |           |             |
| Polarization           | Linear            |           |           |             |
| Power Handled          | 5 W               |           |           |             |
| Operation Temperature  | -40 °C ~ +85 °C   |           |           |             |
| Storage Temperature    | -40 °C ~ +85 °C   |           |           |             |
| Dimensions             | 47*7*0.1 mm       |           |           |             |
| Weight                 | 1.2 g             |           |           |             |
| Connector              | MMCX(M)RA)        |           |           |             |
| Cable Standard         | Mini-Coax 1.13 mm |           |           |             |
| Cable Length and color | 100mm, White      |           |           |             |
| RoHS Compliant         | Yes               |           |           |             |
| Adhesive               | 3M 467            |           |           |             |



### 3. TEST SET UP

A ETS 3D Scan System with Anechoic Chamber.




Figure 1. ETS System

Agilent 8753ES Vector Network Analyzer.



Figure 2. Network Analyzer



#### 4. ANTENNA PARAMETERS

The next antenna parameter graphs like Return Loss, Smith Chart and VSWR were measured in the Agilent 8753ES Vector Network Analyzer. The Gain, Efficiency and Radiation Patterns were measured in the reliable ETS 3D Scan System.

#### 4.1 Return Loss Data





Figure 3. Return Loss for the FXP73 Antenna


#### 4.2 Gain Data



igaic of call for the 17th 75 7th terms



### 4.3 Efficiency Data





### 4.4. Radiation Pattern Data




Figure 8. Radiation pattern XY Plane, Figure 1 as reference (dB)






Figure 9. Radiation pattern XZ Plane, Figure 1 as reference (dB).




Figure 10. Radiation pattern YZ plane, Figure 1 as reference (dB).



### 5. MECHANICAL DRAWING





Figure 11. Mechanical Drawing for the FXP73 Antenna



# 6. Packaging





Taoglas makes no warranties based on the accuracy or completeness of the contents of this document and reserves the right to make changes to specifications and product descriptions at any time without notice. Taoglas reserves all rights to this document and the information contained herein.

Reproduction, use or disclosure to third parties without express permission is strictly prohibited. Copyright © Taoglas Ltd.

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taoglas:

FXP73.09.0100A