



TEST REPORT

Product Name : Industrial Radio Remote Controller

Model Number : F22-12D

Data Applies to : F22-12S

Brand Name : TELECRANE

FCC ID : LWN9311F2212

Applicant : LEE' S HI-TECH ENTERPRISE CO., LTD

Address : 8F-1, NO.288-2, Hsin-Ya Rd, Chien-Chen
Zone(806), Kaohsiung, Taiwan, R.O.C.

Received Date : November 25, 2004

Tested Date : November 25, 2004 ~ January 07, 2005

Issued by

Compliance Certification Services Inc.

Hsinchu Lab.

Rm. 258, Bldg. 17, NO.195, Sec.4 Chung Hsing Rd.,
ChuTugn Chen, Hsinchu, Taiwan 310, R.O.C

TEL: (03) 591-8012

FAX: (03) 582-5720

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as separately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.





Test Report Certification

Product Name : Industrial Radio Remote Controller
Model Number : F22-12D
Data Applies to : F22-12S
Brand Name : TELECRANE
FCC ID : LWN9311F2212
Applicant : LEE' S HI-TECH ENTERPRISE CO., LTD

Measurement Standard :

47 CFR Part 15 Subpart B and C(Section 15.231)
ANSI C63.4-2003

Tested By : Ken Tu, **Date** : January 11, 2005
(Ken Tu)
Approved By : C.F. Wu, **Date** : January 11, 2005
(C.F. Wu, Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION	4
1.1 General Statement	4
1.2 General Description of EUT & Power	4
1.3 EUT & Peripherals Setup Diagram.....	5
1.4 EUT Operating Condition	5
1.5 Description of Test Site	5
1.6 Summary of Test Results	6
2. TRANSMITTER AUTO-OFF AND DUTY CYCLE	7
2.1 Test Equipments.....	7
2.2 Test Setup.....	7
2.3 Test Procedures	7
2.4 Uncertainty of Radiated Emission	7
2.5 Test Result.....	8-9
3. RADIATED EMISSION TEST	10
3.1 Test Equipments.....	10
3.2 Test Setup.....	10
3.3 Radiation Limit	11
3.4 Test Procedures	12
3.5 Uncertainty of Radiated Emission	12
3.6 Radiated RF Noise Measurement Results.....	13-18
3.7 Photos of Radiated Test	19-30
4. BANDWIDTH MEASUREMENT	31
4.1 Test Equipments.....	31
4.2 Test Setup.....	31
4.3 Limits of Bandwidth Measurement.....	31
4.4 Test Procedure.....	31
4.5 Uncertainty of Conducted Emission	31
4.6 Test Results	32
4.7 Photo of Bandwidth Measurement.....	33
5. ANTENNA REQUIREMENT	34
5.1 Standard Applicable.....	34
5.2 Antenna Connected Construction	34



1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION : Comply with standard in full

TRACEABILITY : This test result is traceable to national or international std.

1.2 General Description of EUT & Power

Product Name	Industrial Radio Remote Controller
Model Number	F22-12D
Data Applies To	F22-12S
Frequency Band	425MHz ~ 435MHz
Operating Frequency	425.19MHz ~ 434.78MHz
Operated Selection	manual
Type of Modulation	FSK
EUT Description	The EUT was the transmitter of a industrial remote control system. The EUT is for transmission of a control signal used with remote switch. It does not activate automatically and transmit periodically at a regular predetermined interval.
Antenna Type	Helix Antenna, Antenna Gain : 1.5dBi, Connector : PITCH 2.0
Power Source	6VDC (For Transmitter device) from four AA battery


Note :

The difference of the series model

Different Item	Brand	TELECRANE	TELECRANE
	Model	F22-12D	F22-12S
Transmitter PCB		same	same
Transmitter Power Supply		same	same
Transmitter RF Circuits Design		same	same
Transmitter Key Numbers & Spec.		Twelve units of double-speed push-button+ One unit of Start key.	Twelve units of single-speed push-button+ One unit of Start key.

To add a series model for business necessary. (Double-Speed push-button : 3003.0451 ; Single-Speed push-button : B3W-4050)
The products between these for models are all the same except for Transmitter Key Numbers & Spec.

1.3 EUT & Peripherals Setup Diagram



1.4 EUT Operating Condition

- (1) Set up the EUT as described in set up diagram.
- (2) Switch on the operation button.
- (3) Start test.

1.5 Description of Test Site

SITE DESCRIPTION

FCC Certificate NO.	: 90585
BSMI Certificate NO.	: SL2-IN-E-0002
NVLAP Lab Code	: 200118-0
CNLA Certificate NO.	: CNLA-ZL97018E
VCCI Certificate NO.	: R-1189, C-1250
TÜV Rheinland Certificate NO.	: 10008375

NAME OF SITE	: Compliance Certification Services Inc. Hsinchu Lab.
SITE LOCATION	: Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd., Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.



1.6 Summary of Test Results

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.231(b)	Field strength of Fundamental	PASS	Meet the requirement of limit
15.231(b)	Field strength of Harmonics	PASS	Meet the requirement of limit
15.231(b)(3)	Transmitter Radiated Emissions Limit : 15.231(b)	PASS	Meet the requirement of limit
15.231(a)(1)	Deactivate transmission within 5 seconds of being released	PASS	Manually operated only
15.231(a)(2)	Cease transmission within 5 seconds after activation	N/A	Manually operated only
15.231(a)(3)	Transmit periodically at a regular predetermined interval.	N/A	Manually operated only
15.231(c)	Bandwidth Limit: Center frequency $\times$ 0.25%	PASS	Meet the requirement of limit



2. TRANSMITTER AUTO-OFF AND DUTY CYCLE


2.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
R/S SPECTRUM ANALYZER	FSEK30	835253/002	September 06, 2004

2.2 Test Setup

The diagram below shows the test setup that is utilized to perform the measurements for duty cycle and power off duration.



2.3 Test Procedures

1. The tests were performed with the equipment under test (EUT) connected to the spectrum directly.
2. The spectrum was turned to the center frequency of the emission and set to the zero span with proper sweep time.
3. The duration of transmission of ON/OFF was determined by the spectrum with the function of marker and cursor line.
4. The spectrum was used to check whether the EUT stop transmission or not within 5 seconds after the EUT was powered off.

2.4 Uncertainty of Radiated Emission


The uncertainty of time domain measurement is $\pm 1\mu\text{s}$.



2.5 Test Result

1. For the fundamental frequency (425.19MHz)


The transmitter ceases transmission immediately after being released and complied with the requirement in section 15.231(a)(1).





2. For the fundamental frequency (434.78MHz)

The transmitter ceases transmission immediately after being released and complied with the requirement in section 15.231(a)(1).





3. RADIATED EMISSION TEST


3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.


Manufacturer or Type	Model No	Serial No	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2421	June 15, 2004	1 Year	FINAL
R/S SPECTRUM ANALYZER	FSEK30	835253/002	September 06, 2004	1 Year	FINAL
OPEN SITE	-----	No.2	May 07, 2004	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	June 03, 2004	1 Year	FINAL
Horn Antenna	AH-118	10089	April 09, 2004	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	November 24, 2004	1 Year	FINAL
HP High pass filter	84300/80038	002	CAL. ON USE	1 Year	FINAL
Horn Antenna	AH-840	3077	February 25, 2004	1 Year	FINAL

3.2 Test Setup

1. The diagram below shows the test setup that is utilized to make the measurements for emission below 1GHz.(For Transmitter device)



2. The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.(For Transmitter device)



3.3 Radiation Limit

For intentional device, according to § 15.231(b), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following table.

Fundamental Frequency (MHz)	Distance (Meters)	Field Strength of Fundamental ($\mu\text{V/M}$)	Field Strength of Spurious Emission ($\mu\text{V/M}$)
40.66-40.70	3	2250	225
70-130	3	1250	125
130-174	3	1250 to 3750	125 to 375
174-260	3	3750	375
260-470	3	3750 to 12500	375 to 1250
Above 470	3	12500	1250



3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. During performing radiated emission below 1GHz, the EUT (Transmitter device) was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower. During performing radiated emission above 1GHz, the EUT (Transmitter device) was set 3 meters away from the interference-receiving antenna.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is $\pm 2.72\text{dB}$.



3.6 Radiated RF Noise Measurement Results

The frequency spectrum from 30 MHz to 4252 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/02
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	22.1°C, 59%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲425.19	18.26	4.94	47.20	50.40	100.53	70.40	73.60	PK
▲425.19	—	—	—	—	80.53	—	—	AVG
850.39	21.08	7.02	4.50	7.60	80.53	32.60	35.70	PK
850.39	—	—	—	—	60.53	—	—	AVG
1275.58	23.55	8.97	13.40	14.40	80.53	45.93	46.93	PK
1275.58	—	—	—	—	60.53	—	—	AVG
※1700.78	25.86	10.66	13.10	13.50	74.00	49.62	50.02	PK
※1700.78	—	—	—	—	54.00	—	—	AVG
※4252.00	---	---	---	---	74.00	---	---	PK
※4252.00	---	---	---	---	54.00	---	---	AVG

REMARKS :

1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (425.19MHz), X-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.



The frequency spectrum from 30 MHz to 4252 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/02
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	22.1℃, 59%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲425.19	18.26	4.94	52.80	44.90	100.53	76.00	68.10	PK
▲425.19	—	—	—	—	80.53	—	—	AVG
850.39	21.08	7.02	7.60	3.50	80.53	35.70	31.60	PK
850.39	—	—	—	—	60.53	—	—	AVG
1275.58	23.55	8.97	14.30	14.40	80.53	46.83	46.93	PK
1275.58	—	—	—	—	60.53	—	—	AVG
※1700.78	25.86	10.66	13.10	13.20	74.00	49.62	49.72	PK
※1700.78	—	—	—	—	54.00	—	—	AVG
※4252.00	---	---	---	---	74.00	---	---	PK
※4252.00	---	---	---	---	54.00	---	---	AVG

REMARKS :

1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (425.19MHz), Y-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.



The frequency spectrum from 30 MHz to 4252 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/02
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	22.1°C, 59%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲425.19	18.26	4.94	53.20	47.90	100.53	76.40	71.10	PK
▲425.19	—	—	—	—	80.53	—	—	AVG
850.39	21.08	7.02	3.60	2.50	80.53	31.70	30.60	PK
850.39	—	—	—	—	60.53	—	—	AVG
1275.58	23.55	8.97	14.00	14.30	80.53	46.53	46.83	PK
1275.58	—	—	—	—	60.53	—	—	AVG
※1700.78	25.86	10.66	12.40	12.80	74.00	48.92	49.32	PK
※1700.78	—	—	—	—	54.00	—	—	AVG
※4252.00	---	---	---	---	74.00	---	---	PK
※4252.00	---	---	---	---	54.00	---	---	AVG

REMARKS :

1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter Device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (425.19MHz), Z-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.



The frequency spectrum from 30 MHz to 4348 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/09
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	26.5°C , 60%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲434.78	18.21	4.97	50.60	53.20	100.85	73.78	76.38	PK
▲434.78	—	—	—	—	80.85	—	—	AVG
869.56	21.19	7.11	6.40	12.30	80.85	34.70	40.60	PK
869.56	—	—	—	—	60.85	—	—	AVG
※1304.34	23.69	9.04	15.20	16.10	74.00	47.93	48.83	PK
※1304.34	—	—	—	—	54.00	—	—	AVG
1739.12	26.19	10.88	13.00	13.80	80.85	50.06	50.86	PK
1739.12	—	—	—	—	60.85	—	—	AVG
※4347.80	---	---	---	---	74.00	---	---	PK
※4347.80	---	---	---	---	54.00	---	---	AVG

REMARKS :

1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (434.78MHz), X-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.



The frequency spectrum from 30 MHz to 4348 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/09
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	26.5°C, 60%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲434.78	18.21	4.97	54.40	47.50	100.85	77.58	70.68	PK
▲434.78	—	—	—	—	80.85	—	—	AVG
869.56	21.19	7.11	14.60	8.90	80.85	42.90	37.20	PK
869.56	—	—	—	—	60.85	—	—	AVG
※1304.34	23.69	9.04	15.60	15.30	74.00	48.33	48.03	PK
※1304.34	—	—	—	—	54.00	—	—	AVG
1739.12	26.19	10.88	14.70	14.00	80.85	51.76	51.06	PK
1739.12	—	—	—	—	60.85	—	—	AVG
※4347.80	---	---	---	---	74.00	---	---	PK
※4347.80	---	---	---	---	54.00	---	---	AVG

REMARKS :

1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (434.78MHz), Y-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.



The frequency spectrum from 30 MHz to 4348 MHz for Transmitter was investigated. All emissions not reported are much lower than the prescribed limits.

Company	LEE' S HI-TECH ENTERPRISE CO., LTD	Test Date	2004/12/09
Product Name	Industrial Radio Remote Controller	Test By	Ken Tu
Model Name	F22-12D	TEMP & Humidity	26.5°C, 60%

Frequency (MHz)	Antenna Factor (dB/m)	Cable Loss (dB)	Meter Reading at 3m(dBμV)		Limits (dBμV/m)	Emission Level at 3m(dBμV/m)		Detector Mode
			Horizontal	Vertical		Horizontal	Vertical	
30.00	17.01	0.97	*	*	40.00	*	*	PK
▲434.78	18.21	4.97	53.60	45.90	100.85	76.78	69.08	PK
▲434.78	—	—	—	—	80.85	—	—	AVG
869.56	21.19	7.11	9.80	5.90	80.85	38.10	34.20	PK
869.56	—	—	—	—	60.85	—	—	AVG
※1304.34	23.69	9.04	14.00	14.80	74.00	46.73	47.53	PK
※1304.34	—	—	—	—	54.00	—	—	AVG
1739.12	26.19	10.88	14.10	11.70	80.85	51.16	48.76	PK
1739.12	—	—	—	—	60.85	—	—	AVG
※4347.80	---	---	---	---	74.00	---	---	PK
※4347.80	---	---	---	---	54.00	---	---	AVG

REMARKS :



1. * Undetectable
2. Emission level (dBμV/m) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).
3. Remark “▲” means fundamental frequency for Transmitter Device.
4. The emission value below 1GHz is quasi-peak value and the emission value above 1GHz is both peak and average value.
PK : Peak value; AVG : Average value.
5. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
6. Remark “※” means the Restricted band.
7. For the fundamental frequency (434.78MHz), Z-axis direction, detailed in setup photo.
8. Because the peak reading can comply with average limits, average reading is not necessary.

3.7 Photos of Radiated Test


1. For the fundamental frequency (425.19MHz)


(1) X-axis








(2) Y-axis







(3) Z-axis







2. For the fundamental frequency (434.78MHz)
(1) X-axis







(2) Y-axis





(3) Z-axis







4. BANDWIDTH MEASUREMENT


4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	September 06, 2004

Note :

1. The measurement uncertainty is less than +/- 2.6dB, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of Bandwidth Measurement

The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency. Bandwidth is determined at the points 20dB down from the modulated carrier.

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100MHz VBW. The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 20dB.

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 200\text{KHz}$.



4.6 Test Results

Input Power (System)	6VDC (For TX device) from four AA battery	Environmental Conditions	20.9°C, 72%RH
Tested By	Ken Tu		

1. For the fundamental frequency (425MHz)

Center Frequency (MHz)	Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
425.17	336.37	1062.92	PASS

Note : The fundamental frequency of EUT is 425.17MHz. The minimum bandwidth limit will be the 0.25% of the center frequency that is $425.17\text{MHz} \times 0.25\% = 1062.92\text{ kHz}$.

2. For the fundamental frequency (435MHz)


Center Frequency (MHz)	Bandwidth (kHz)	Minimum Limit (kHz)	Pass / Fail
434.76	336.67	1086.90	PASS

Note : The fundamental frequency of EUT is 434.76MHz. The minimum bandwidth limit will be the 0.25% of the center frequency that is $434.76\text{MHz} \times 0.25\% = 1086.90\text{ kHz}$.




4.7 Photo of Bandwidth Measurement

1. For the fundamental frequency (425MHz)



Date: 17.DEC.2004 14:19:26

2. For the fundamental frequency (435MHz)



Date: 17.DEC.2004 14:12:16



5. ANTENNA REQUIREMENT

5.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

5.2 Antenna Connected Construction

The antenna used in this product is Helix antenna. And the maximum Gain of the antenna is only 1.5dBi.