

FCC TEST REPORT

for

47 CFR, Part 15, Subpart C

Equipment : Industrial Radio Remote Controller
Model No. : F21-E1
FCC ID : LWNF21-E1
Filing Type : Certification
Applicant : **Lee's Hi-Tech Enterprise Co., Ltd.**
8F-1, No. 288-2, Hsin Ya Rd., Chien Chen Zone,
KaoHsiung, Taiwan, R.O.C.

- The test result refers exclusively to the test presented test model / sample.
- Without written approval of SPORTON International Inc., the test report shall not be reproduced except in full.
- **Certificate or Test Report must not be used by the applicant to claim the product in this test report endorsement by NVLAP or any agency of U.S. government.**

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

Table of Contents

History of this test report	ii
CERTIFICATE OF COMPLIANCE.....	1
1. General Description of Equipment under Test.....	2
1.1. Applicant	2
1.2. Manufacturer	2
1.3. Basic Description of Equipment under Test.....	2
1.4. Feature of Equipment under Test	2
2. Test Configuration of Equipment under Test.....	3
2.1. Test Manner.....	3
2.2. Description of Test System	3
2.3. Connection Diagram of Test System.....	4
2.4. A plot shows the EUT meet the requirement of 15.231(c).....	5
3. Test Software	7
4. General Information of Test	8
4.1. Test Facility.....	8
4.2. Standard for Methods of Measurement.....	8
4.3. Test in Compliance with.....	8
4.4. Frequency Range Investigated	8
4.5. Test Distance	8
5. Test of Conducted Powerline	9
6. Test of Radiated Emission	10
6.1. Major Measuring Instruments.....	10
6.2. Test Procedures	11
6.3. Typical Test Setup Layout of Radiated Emission	12
6.4. Test Result of Radiated Emission	13
7. Antenna Factor & Cable Loss.....	25
8. EMI Suppression Component List	26
9. List of Measuring Equipments Used	27
10. Uncertainty of Test Site	28
Appendix A. Photographs of EUT	A1 ~ A5

History of this test report

Original Report Issue Date: Aug. 6, 2002

No additional attachment.

Additional attachment were issued as following record:

Attachment No.	Issue Date	Description

CERTIFICATE OF COMPLIANCE

for

47 CFR, Part 15, Subpart C

Equipment : Industrial Radio Remote Controller
Model No. : F21-E1
FCC ID : LWNF21-E1
Applicant : **Lee's Hi-Tech Enterprise Co., Ltd.**
8F-1, No. 288-2, Hsin Ya Rd., Chien Chen Zone,
KaoHsiung, Taiwan, R.O.C.

I HEREBY CERTIFY THAT :

The measurements shown in this test report were made in accordance with the procedures given in **ANSI C63.4 - 1992** and the energy emitted by this equipment was **passed** both radiated and conducted emission limits. Testing was carried out on Jul. 23, 2002 at **SPORTON International Inc. LAB.**


K. J. Lin
Manager

SPORTON International Inc.

6F, No.106, Sec. 1, Hsin Tai Wu Rd., Hsi Chih, Taipei Hsien, Taiwan, R.O.C.

1. General Description of Equipment under Test

1.1. Applicant

Lee's Hi-Tech Enterprise Co., Ltd.
8F1, No. 288-2, Hsin Ya Rd., Chien Chen Zone,
KaoHsiung, Taiwan, R.O.C.

1.2. Manufacturer

Same as 1.1.

1.3. Basic Description of Equipment under Test

Equipment	: Industrial Radio Remote Controller
Model No.	: F21-E1
FCC ID	: LWNF21-E1
Trade Name	: TELECRANE
Power Supply Type	: From Battery (3V)
Power Cord	: N/A

1.4. Feature of Equipment under Test

- Hamming Distance: 4
- I.D. Code: More than 42 billion ID Code(32bit)
- Channel Spacing: 267.5KHz
- Power: Two 1.5Volt Alkaline Batteries AA Size
- Dimensions: 156 61 51mm
- Weight: about 320g W/batteries
- Frequency range: 310MHz ~ 320MHz

2. Test Configuration of Equipment under Test

2.1. Test Manner

- a. The EUT has been associated with peripherals pursuant to ANSI C63.4-1992 and configuration operated in a manner which tended to maximize its emission characteristics in a typical application.
- b. Frequency range investigated: conduction 450 KHz to 30 MHz, radiation 30 MHz to 3200MHz.
- c. The radiated emissions testing was made by rotating three orthogonal axes.
- d. The EUT employs a switch that will automatically deactivate the transmitter within no more than 5 seconds of being released.
- e. The EUT has no periodic transmission at regular predetermined interval.
- f. According to 15.31 (m) of Part 15, 10MHz frequency range, two locations, one near top (310MHz) and one near bottom (320MHz), were measured.
- g. Pursuant to 15.231(c) of Part 15. Subpart C, the bandwidth of the emission at the 20dB point shall be no wider than 0.25% of the center frequency for EUT.
The carrier frequency of EUT is 310.33MHz
 $310.33\text{MHz} * 0.25\% = 775.8 \text{ KHz.}$

The test result is 650KHz (as shown in section 2.4 of this test report) , which is less than 775.8 KHz.

The EUT meet the 20dB point bandwidth requirement

- h. Pursuant to 15.231(c) of Part 15. Subpart C, the bandwidth of the emission at the 20dB point shall be no wider than 0.25% of the center frequency for EUT.
The carrier frequency of EUT is 318.89MHz
 $318.89\text{MHz} * 0.25\% = 797.2 \text{ KHz.}$


The test result is 620KHz (as shown in section 2.4 of this test report) , which is less than 797.2 KHz.

The EUT meet the 20dB point bandwidth requirement

2.2. Description of Test System


The EUT was tested alone. No support devices is needed for testing.

2.3. Connection Diagram of Test System



2.4. A plot shows the EUT meet the requirement of 15.231(c)

<310.33MHz>




Mark 1: 309.970MHz

Mark 3: 310.620MHz

20dB bandwidth=310.620-309.970=0.65MHz

<318.89MHz>



Mark 1: 318.540MHz

Mark 3: 319.160MHz

20dB bandwidth=319.160-318.540=0.62MHz

3. Test Software

No test software was used during testing.

4. General Information of Test

4.1. Test Facility

Test Site Location : No. 52, Hwa Ya 1St Road, Hwa Ya Technology Park,
Kwei-Shan Hsiang, TaoYuan Hsien, Taiwan, R.O.C.
TEL : 886-3-3273456
FAX : 886-3-3180055
Test Site No. : SH03

4.2. Standard for Methods of Measurement

ANSI C63.4-1992

4.3. Test in Compliance with

FCC Part 15, Subpart C

4.4. Frequency Range Investigated

- a. Conduction: from 450 kHz to 30 MHz
- b. Radiation: from 30 MHz to 3200 MHz

4.5. Test Distance

The test distance of radiated emission from antenna to EUT is 3 M.

5. Test of Conducted Powerline

The power supply of EUT is from DC voltage.

Conduction Powerline tests is not applicable for this EUT.

6. Test of Radiated Emission

Radiated emissions from 30 MHz to 3200 MHz were measured with a bandwidth of 120 kHz according to the methods defines in ANSI C63.4-1992. The EUT was placed on a nonmetallic stand in the open-field site, 0.8 meter above the ground plane, as shown in section 6.3. The interface cables and equipment positions were varied within limits of reasonable applications to determine the positions producing maximum radiated emissions.

6.1. Major Measuring Instruments

6.1.1. from 30MHz to 1GHz


- Amplifier (ADVANTEST BB525C)
 - Attenuation 10 dB
 - RF Gain 30 dB
 - Signal Input 9KHz – 3GHz
- Spectrum Analyzer (RAHDE&SCHEARZ & FSP7)
 - Attenuation 10 dB
 - Start Frequency 30 MHz
 - Stop Frequency 1000 MHz
 - Resolution Bandwidth 120 kHz
 - Signal Input 9KHz – 7GHz

6.1.2. from 1GHz to 3.19GHz

- Horn Antenna (COM-POWER AH-118)
 - Attenuation 10 dB
 - Start Frequency 1000 MHz
 - Stop Frequency 3200 MHz
 - Resolution Bandwidth 1 MHz
 - Video Bandwidth 1 MHz
 - Signal Input 1GHz to 18GHz

6.2. Test Procedures

- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a half wave dipole and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was more 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.

6.3. Typical Test Setup Layout of Radiated Emission

6.4. Test Result of Radiated Emission**6.4.1. Orthogonal axes: X (310.33MHz)**

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 20, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

310.330MHz / 71.96 dBuV (HORIZONTAL) Antenna Height 1.1 Meter, Turntable Degree 360°.

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
310.330	H	13.22	3.14	55.60	75.22	5767.66	71.96	3962.78	-3.26	Q.P.
621.700	H	18.81	4.54	24.33	55.22	576.77	47.68	242.10	-7.54	Peak
932.100	H	20.37	5.43	18.75	55.22	576.77	44.55	168.85	-10.67	Peak
1241.320	H						-			Peak, A.V.
1550.000	H	27.12	4.10	8.58	54.00	501.19	39.80	97.72	-14.20	Peak
1860.000	H	28.86	4.52	11.19	55.22	576.77	44.57	169.24	-10.65	Peak
2172.000	H	30.71	4.92	3.16	55.22	576.77	38.79	87.00	-16.43	Peak
2482.640	H						-			Peak, A.V.
2796.000	H	29.76	5.64	3.55	54.00	501.19	38.95	88.61	-15.05	Peak
310.330	V	13.22	3.14	47.26	75.22	5767.66	63.62	1517.05	-11.60	Peak
621.700	V	18.81	4.54	22.01	55.22	576.77	45.36	185.35	-9.86	Peak
932.100	V	20.37	5.43	14.72	55.22	576.77	40.52	106.17	-14.70	Peak
1238.000	V	26.23	3.64	5.57	54.00	501.19	35.44	59.16	-18.56	Peak
1550.000	V	27.12	4.10	8.73	54.00	501.19	39.95	99.43	-14.05	Peak
1860.000	V	28.86	4.52	12.12	55.22	576.77	45.50	188.36	-9.72	Peak
2172.000	V	30.71	4.92	4.73	55.22	576.77	40.36	104.23	-14.86	Peak
2484.000	V	30.01	5.28	5.41	50.00	316.23	40.70	108.39	-9.30	Peak
2796.000	V						-			Peak, A.V.
3103.300	H/V						-			Peak, A.V.

Remark " - ": The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu

Wayue Hsu

6.4.2. Orthogonal axes: Y (310.33MHz)

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 20, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

310330 MHz / 70.94 dBuV (HORIZONTAL) Antenna Height 1.1 Meter, Turntable Degree 360 °.

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

FCC TEST REPORT

Report No. : F261902

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
310.330	H	13.22	3.14	54.58	75.22	5767.66	70.94	3523.71	-4.28	Q.P.
621.700	H	18.81	4.54	24.95	55.22	576.77	48.30	260.02	-6.92	Peak
932.100	H	20.37	5.43	21.08	55.22	576.77	46.88	220.80	-8.34	Peak
1238.000	H	26.23	3.64	5.44	54.00	501.19	35.31	58.28	-18.69	Peak
1550.000	H	27.12	4.10	8.12	54.00	501.19	39.34	92.68	-14.66	Peak
1860.000	H	28.86	4.52	12.65	55.22	576.77	46.03	200.22	-9.19	Peak
2172.000	H	30.71	4.92	4.81	55.22	576.77	40.44	105.20	-14.78	Peak
2484.000	H	30.01	5.28	4.39	54.00	501.19	39.68	96.38	-14.32	Peak
2796.000	H	29.76	5.64	4.28	54.00	501.19	39.68	96.38	-14.32	Peak
310.330	V	13.22	3.14	45.63	75.22	5767.66	61.99	1257.48	-13.23	Peak
621.700	V	18.81	4.54	18.59	55.22	576.77	41.94	125.03	-13.28	Peak
932.100	V	20.37	5.43	14.29	55.22	576.77	40.09	101.04	-15.13	Peak
1238.000	V	26.23	3.64	6.38	54.00	501.19	36.25	64.94	-17.75	Peak
1550.000	V	27.12	4.10	12.66	54.00	501.19	43.88	156.31	-10.12	Peak
1860.000	V	28.86	4.52	13.83	55.22	576.77	47.21	229.35	-8.01	Peak
2172.000	V	30.71	4.92	6.93	55.22	576.77	42.56	134.28	-12.66	Peak
2484.000	V	30.01	5.28	3.37	54.00	501.19	38.66	85.70	-15.34	Peak
2796.000	V						-			Peak, A.V.
3103.300	H/V						-			Peak, A.V.

Remark " - ": The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu

Wayue Hsu

SPORTON International Inc.

TEL : 886-2-2696-2468

FAX : 886-2-2696-2255

FCC ID : LWNF21-E1

Page No. : 16 of 28

Issued Date : Aug. 6, 2002

6.4.3. Orthogonal axes: Z (310.33MHz)

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 20, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

621.700 MHz / 51.43 dBuV (VERTICAL) Antenna Height 1.1 Meter, Turntable Degree 360°.

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Cable Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
310.330	H	13.22	3.14	46.69	75.22	5767.66	63.05	1420.69	-12.17	Peak
618.790	H	18.78	4.52	15.37	55.22	576.77	38.67	85.80	-16.55	Peak
932.100	H	20.37	5.43	16.55	55.22	576.77	42.35	131.07	-12.87	Peak
1238.000	H	26.23	3.64	4.70	54.00	501.19	34.57	53.52	-19.43	Peak
1550.000	H	27.12	4.10	10.21	54.00	501.19	41.43	117.90	-12.57	Peak
1860.000	H	28.86	4.52	10.94	55.22	576.77	44.32	164.44	-10.90	Peak
2172.000	H	30.71	4.92	5.29	55.22	576.77	40.92	111.17	-14.30	Peak
2484.000	H						-			Peak, A.V.
2796.000	H	29.76	5.64	4.23	54.00	501.19	39.63	95.83	-14.37	Peak
310.330	V	13.22	3.14	54.59	75.22	5767.66	70.95	3527.77	-4.27	Peak
621.700	V	18.81	4.54	28.08	55.22	576.77	51.43	372.82	-3.79	Peak
932.100	V	20.37	5.43	18.02	55.22	576.77	43.82	155.24	-11.40	Peak
1238.000	V	26.23	3.64	4.98	54.00	501.19	34.85	55.27	-19.15	Peak
1550.000	V	27.12	4.10	8.43	54.00	501.19	39.65	96.05	-14.35	Peak
1860.000	V	28.86	4.52	13.50	55.22	576.77	46.88	220.80	-8.34	Peak
2172.000	V	30.71	4.92	4.05	55.22	576.77	39.68	96.38	-15.54	Peak
2484.000	V	30.01	5.28	3.43	54.00	501.19	38.72	86.30	-15.28	Peak
2790.000	V	29.76	5.63	5.03	54.00	501.19	40.42	104.95	-13.58	Peak
3103.300	H/V						-			Peak, A.V.

Remark " - " : The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu

Wayue Hsu

6.4.4. Orthogonal axes: X (318.89MHz)

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 23, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

318.890 MHz / 72.05 dBuV (VERTICAL) Antenna Height 3 Meter, Turntable Degree 65°.

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
318.890	H	13.47	3.19	55.39	75.86	6208.69	72.05	4004.05	-3.81	Q.P.
637.220	H	18.97	4.65	18.42	55.86	620.87	42.04	126.47	-13.82	Peak
956.350	H	20.49	5.58	13.14	55.86	620.87	39.21	91.31	-16.65	Peak
1276.000	H	26.41	3.70	6.18	55.86	620.87	36.29	65.24	-19.57	Peak
1590.000	H	27.08	4.15	7.38	54.00	501.19	38.61	85.21	-15.39	Peak
1910.000	H	29.70	4.59	10.20	55.86	620.87	44.49	167.69	-11.37	Peak
2232.230	H						-			Peak, A.V.
2551.120	H	29.95	5.35	8.17	55.86	620.87	43.47	149.11	-12.39	Peak
2870.000	H	29.70	5.72	6.18	54.00	501.19	41.60	120.23	-12.40	Peak
318.890	V	13.47	3.19	47.70	75.86	6208.69	64.36	1651.96	-11.50	Peak
637.220	V	18.97	4.65	20.26	55.86	620.87	43.88	156.31	-11.98	Peak
956.350	V	20.49	5.58	7.04	55.86	620.87	33.11	45.24	-22.75	Peak
1276.000	V	26.41	3.70	7.64	55.86	620.87	37.75	77.18	-18.11	Peak
1590.000	V	27.08	4.15	10.77	54.00	501.19	42.00	125.89	-12.00	Peak
1910.000	V	29.70	4.59	8.84	55.86	620.87	43.13	143.38	-12.73	Peak
2232.230	V						-			Peak, A.V.
2551.120	V	29.95	5.35	5.54	55.86	620.87	40.84	110.15	-15.02	Peak
2870.000	V						-			Peak, A.V.
3188.900	H/V						-			Peak, A.V.

Remark " - " : The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu

Wayue Hsu

6.4.5. Orthogonal axes: Y (318.89MHz)

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 23, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

318.890 MHz / 71.41 dBuV (VERTICAL) Antenna Height 3 Meter, Turntable Degree 65°.

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
318.890	H	13.47	3.19	46.63	75.86	6208.69	63.29	1460.49	-12.57	Peak
637.220	H	18.97	4.65	12.41	55.86	620.87	36.03	63.31	-19.83	Peak
956.350	H	20.49	5.58	9.07	55.86	620.87	35.14	57.15	-20.72	Peak
1276.000	H	26.41	3.70	8.42	55.86	620.87	38.53	84.43	-17.33	Peak
1590.000	H	27.08	4.15	5.77	54.00	501.19	37.00	70.79	-17.00	Peak
1910.000	H	29.70	4.59	12.35	55.86	620.87	46.64	214.78	-9.22	Peak
2232.230	H						-			Peak, A.V.
2550.000	H	29.95	5.35	10.50	55.86	620.87	45.80	194.98	-10.06	Peak
2870.000	H	29.70	5.72	6.56	54.00	501.19	41.98	125.60	-12.02	Peak
318.890	V	13.47	3.19	54.75	75.86	6208.69	71.41	3719.63	-4.45	Q.P.
637.220	V	18.97	4.65	24.05	55.86	620.87	47.67	241.82	-8.19	Peak
956.350	V	20.49	5.58	8.27	55.86	620.87	34.34	52.12	-21.52	Peak
1276.000	V	26.41	3.70	7.32	55.86	620.87	37.43	74.39	-18.43	Peak
1590.000	V	27.08	4.15	13.69	54.00	501.19	44.92	176.20	-9.08	Peak
1910.000	V	29.70	4.59	14.82	55.86	620.87	49.11	285.43	-6.75	Peak
2232.230	V						-			Peak, A.V.
2550.000	V	29.95	5.35	3.89	55.86	620.87	39.19	91.10	-16.67	Peak
2870.000	V	29.70	5.72	4.59	54.00	501.19	40.01	100.12	-13.99	Peak
3188.900	H/V						-			Peak, A.V.

Remark " - " : The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu
Wayue Hsu

6.4.6. Orthogonal axes: Z (318.89MHz)

- Frequency range: 30 ~ 3200MHz
- Test Distance : 3 M
- Temperature : 27.6°C
- Relative Humidity : 57 %
- Test Date : Jul. 23, 2002
- Emission level (dBuV/m) = 20 log Emission level (uV/m)
- Corrected Reading : Antenna Factor + Cable Loss + Reading = Emission

The Radiated Emission test was passed at minimum margin

318.890 MHz / 72.16 dBuV (HORIZONTAL) Antenna Height 3 Meter, Turntable Degree 65 ° .

- **Spurious Emission**

Remark: The emission emitted by the EUT is too low to be measured

- Field strength of fundamental and harmonics

Frequency (MHz)	Antenna Polarity	Cable Factor (dB/m)	Loss (dB)	Reading (dBuV)	Limits (dBuV/m)	(uV/m)	Emission Level (dBuV/m)	(uV/m)	Margin (dB)	Detect Mode
318.890	H	13.47	3.19	55.50	75.86	6208.69	72.16	4055.09	-3.70	Q.P.
637.220	H	18.97	4.65	22.62	55.86	620.87	46.24	205.12	-9.62	Peak
956.350	H	20.49	5.58	14.56	55.86	620.87	40.63	107.52	-15.23	Peak
1270.000	H	26.39	3.69	6.43	55.86	620.87	36.51	66.91	-19.35	Peak
1590.000	H	27.08	4.15	10.35	54.00	501.19	41.58	119.95	-12.42	Peak
1910.000	H	29.70	4.59	11.55	55.86	620.87	45.84	195.88	-10.02	Peak
2232.230	H						-			Peak, A.V.
2550.000	H	29.95	5.35	8.25	55.86	620.87	43.55	150.49	-12.31	Peak
2870.000	H	29.70	5.72	5.94	54.00	501.19	41.36	116.95	-12.64	Peak
318.890	V	13.47	3.19	47.19	75.86	6208.69	63.85	1557.76	-12.01	Peak
637.220	V	18.97	4.65	13.21	55.86	620.87	36.83	69.42	-19.03	Peak
956.350	V	20.49	5.58	7.45	55.86	620.87	33.52	47.42	-22.34	Peak
1276.000	V	26.41	3.70	7.37	55.86	620.87	37.48	74.82	-18.38	Peak
1590.000	V	27.08	4.15	6.11	54.00	501.19	37.34	73.62	-16.66	Peak
1910.000	V	29.70	4.59	13.33	55.86	620.87	47.62	240.44	-8.24	Peak
2230.000	V	30.58	4.98	2.84	54.00	501.19	38.40	83.18	-15.60	Peak
2550.000	V	29.95	5.35	5.48	55.86	620.87	40.78	109.40	-15.08	Peak
2870.000	V	29.70	5.72	6.73	54.00	501.19	42.15	128.09	-11.85	Peak
3188.900	H/V						-			Peak, A.V.

Remark " - " : The emission emitted by the EUT is too low to be measured except the emission listed above,

Test Engineer : Wayue Hsu

Wayue Hsu

7. Antenna Factor & Cable Loss

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)
30	18.10	0.99
35	16.00	1.07
40	13.29	1.13
45	10.75	1.20
50	8.10	1.26
55	6.40	1.32
60	5.36	1.40
65	4.94	1.41
70	5.19	1.51
75	6.05	1.57
80	6.96	1.60
85	8.04	1.70
90	8.76	1.70
95	9.70	1.75
100	10.30	1.79
110	11.17	1.93
120	11.60	1.95
130	11.23	2.01
140	10.61	2.12
150	10.10	2.20
160	9.20	2.26
170	9.01	2.33
180	8.71	2.40
190	8.80	2.52
200	8.24	2.55
220	8.80	2.64
240	10.72	2.78
260	13.20	2.89
280	12.50	2.98
300	12.96	3.11
320	13.50	3.20
340	13.93	3.25
360	14.39	3.44
380	14.70	3.63
400	15.76	3.50
450	16.35	3.82
500	17.29	4.01
550	18.50	4.16
600	18.43	4.39
650	18.85	4.72
700	18.93	4.71
750	19.75	4.83
800	19.92	5.27
850	20.24	5.22
900	20.30	5.22
950	20.46	5.54
1000	20.80	5.81
1000	25.10	3.06
2000	31.00	4.53
3000	30.30	5.19
4000	31.40	7.11
5000	34.10	7.62

8. EMI Suppression Component List

No EMI suppression components.

9. List of Measuring Equipments Used

Instrument	Manufacturer	Model No.	Serial No.	Characteristics	Calibration Date	Remark
Spectrum Analyzer	RAHDE & SCHEARZ	FSP7	838858/039	9KHz – 7GHz	Jan. 07, 2002	Radiation (SH03)
Amplifier	ADVANTEST	BB525C	CH300001	9KHz – 3GHz	Nov. 15, 2001	Radiation (SH03)
Bilog Antenna	SCHAFFNER	CBL61128	2681	30MHz –2GHz	Dec. 23, 2001	Radiation (SH03)
Turn Table	HD	DS 420	420/649/00	0 – 360 degree	N/A	Radiation (SH03)
Antenna Mast	HD	MA 240	240/559/00	1 m - 4 m	N/A	Radiation (SH03)
Halfwave dipole antenna	Schwarzbeck	UHAP VHAP	995+99 1024+1024	30MHz - 1GHz	Sep. 27, 2001	Radiation (SH03)
Horn Antenna	COM-POWER	AH-118	10094	1GHz – 18GHz	Apr. 09, 2002	Radiation (SH03)

Calibration Interval of instruments listed above is one year.

10. Uncertainty of Test Site

Uncertainty of Radiated Emission Measurement

Contribution	Probability Distribution	3m
Antenna factor calibration	normal(k=2)	1
cable loss calibration	normal(k=2)	0.3
RCV/SPA specification	rectangular	2
Antenna Directivity	rectangular	3
Antenna Factor V.S. Height	rectangular	2
Antenna Factor Interpolation for Frequency	rectangular	0.25
site imperfection	rectangular	2
Mismatch Receiver VSWR $\Gamma_1=0.09$ Antenna VSWR $\Gamma_2=0.67$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	0.54
combined standard uncertainty Ue(y)	normal	2.7
Measuring uncertainty for a level of confidence of 95% U=2Ue(y)	normal (k=2)	5.4

$$U = \{(1/2)^2 + (0.3/2)^2 + (2^2 + 0.5^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\} = 2.2 \text{ for 10m test distance}$$

$$U = \{(1/2)^2 + (0.3/2)^2 + (2^2 + 3^2 + 2^2 + 0.25^2 + 2^2)/3 + (0.54)^2/2\} = 2.7 \text{ for 3m test distance}$$

Uncertainty of Conducted Emission Measurement

Contribution	Probability Distribution	150 KHz – 30MHz
Cable and I/P attenuator calibration	normal(k=2)	0.3
RCV/SPA specification	rectangular	2
LISN coupling specification	rectangular	1.5
Transducer factor frequency interpolation	rectangular	0.2
Mismatch Receiver VSWR $\Gamma_1=0.09$ LISN VSWR $\Gamma_2=0.33$ Uncertainty= $20\log(1-\Gamma_1\Gamma_2)$	U-shaped	0.2
combined standard uncertainty Ue(y)	normal	1.66
Measuring uncertainty for a level of confidence of 95% U=2Ue(y)	normal (k=2)	3.32

$$U = \{(0.3/2)^2 + (2^2 + 1.5^2 + 0.2^2)/3 + (0.2)^2/2\} = 1.66$$