



SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241200487503

Page: 1 of 12

RF EXPOSURE EVALUATION REPORT

Application No.: SZCR2412004875ET (SGS HK NO.: T32420360040EM)
Applicant: Winfat Industrial Co., Ltd
Address of Applicant: Room 903-904, 9/F., East Ocean Centre, 98 Granville Road, Tsim Sha Tsui East, Kowloon, Hong Kong, China
Equipment Under Test (EUT):
EUT Name: Please refer to section 2
Item No.: Please refer to section 2 ♣
♣ Please refer to section 2 of this report which indicates which item was actually tested and which were electrically identical.
Country of Origin: CHINA
Labeled Age Grading: 250901:36M+/250902:24M+
FCC ID: LXE250901-2-NL
Standard(s) : FCC Rules 47 CFR §2.1093
KDB 447498 D04 interim General RF Exposure Guidance v01
Date of Receipt: 2024-12-24
Date of Evaluation: 2024-12-31 to 2025-01-07
Date of Issue: 2025-01-21

| | |
|---------------------------|--------------|
| Evaluation Result: | Pass* |
|---------------------------|--------------|

* In the configuration evaluated, the EUT complied with the standards specified above.

Keny Xu
EMC Laboratory Manager



SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch EMC Laboratory

Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.ssgsgroup.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd. Shenzhen Branch

SZEMC-TRF-01 Rev. A/1

Report No.: SZCR241200487503

Page: 2 of 12

| Revision Record | | | | |
|-----------------|---------|------------|----------|----------|
| Version | Chapter | Date | Modifier | Remark |
| 01 | | 2025-01-21 | | Original |
| | | | | |
| | | | | |

| | | | | |
|--------------------------|--|------------------------------|--|--|
| Authorized for issue by: | | | | |
| | | Martin Tang | | |
| | | Martin Tang/Project Engineer | | |
| | | Eric Fu | | |
| | | Eric Fu/Reviewer | | |

2 Contents

| | Page |
|--|------|
| 1 Cover Page | 1 |
| 2 Contents | 3 |
| 3 General Information | 4 |
| 3.1 General Description of E.U.T. | 4 |
| 3.2 Details of E.U.T. | 4 |
| 3.3 Separation Distance | 6 |
| 3.4 Test Location | 7 |
| 3.5 Test Facility | 7 |
| 3.6 Deviation from Standards | 7 |
| 3.7 Abnormalities from Standard Conditions | 7 |
| 4 FCC Radiofrequency radiation exposure limits | 8 |
| 4.1 Blanket 1 mW Blanket Exemption | 8 |
| 4.2 MPE-based Exemption | 8 |
| 4.3 SAR-based Exemption | 9 |
| 5 Measurement and Calculation | 12 |
| 5.1 Maximum transmit power | 12 |
| 5.2 RF Exposure Calculation | 12 |
| 6 EUT Constructional Details (EUT Photos) | 12 |



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing / inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

SGS-CSTC Standards Technical Services Co., Ltd.
Shenzhen Branch Testing & Inspection Laboratory

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com.cn
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

3 General Information

3.1 General Description of E.U.T.

| | |
|---------------|---|
| Product Type: | <input checked="" type="checkbox"/> Portable device |
| | <input type="checkbox"/> Mobile device |
| | <input type="checkbox"/> Fixed device |

3.2 Details of E.U.T.

| | |
|----------------------|---|
| Power Supply: | 4.5V DC(1.5V x 3 "AAA" Size Batteries) for microphone |
| Bluetooth Version: | V5.3 classic |
| Operation Frequency: | 2402MHz to 2480MHz |
| Modulation Type: | GFSK, Pi/4DQPSK, 8DPSK |
| Channel Spacing: | 1MHz |
| Number of Channels: | 79 |
| Antenna Type: | PCB Antenna |
| Antenna Gain: | -0.58dBi |

Remark: The information in this section is provided by the applicant or manufacturer, SGS is not liable to the accuracy, suitability, reliability or/and integrity of the information.

Declaration of EUT Family Grouping:

| Item No. | Item Name |
|-------------------------------|--|
| 250901 250901-01 250901-NL | <p>Karaoke Kid Bluetooth® Mic with Stand</p> <p>Micro Karaoke Kid Bluetooth® avec support</p> <p>Karaoke Kid Bluetooth® Mikrofon mit Ständer</p> <p>Microfono Bluetooth® Ragazzo Karaoke con base</p> <p>Micrófono infantil Bluetooth® con soporte para karaoke</p> <p>Microfone Bluetooth® de karaoke para criança com suporte</p> <p>Mikrofon karaoke Bluetooth® ze stojakiem dla dzieci</p> <p>Детское караоке с Bluetooth® микрофоном и подставкой</p> <p>Karaoke Kid Bluetooth® Mikrofon koos alusega</p> <p>Детски Караоке Bluetooth® Микрофон със Стойка</p> <p>Karaoke Bluetooth® microfoon met standaard voor kinderen</p> <p>Gyermekek Karaoke Bluetooth® Mikrofon, Állvánnyal</p> <p>Μικρόφωνο karaoke Bluetooth® για παιδιά με σταντ</p> <p>Karaoke Çocuk Standlı Bluetooth® Mikrofon</p> <p>노래방 키즈 블루투스® 마이크 및 스탠드</p> <p>カラオケキッズ ブルートゥース®マイクとスタンド</p> <p>للأطفال مع حامل Bluetooth® ميكروفون موسيقى كاريوكي بتقنية</p> |

| | |
|---------------------------------------|---|
| <p>250902 250902-01 250902-NL</p> | <p>Karaoke Kid Bluetooth® Mic Micro Karaoke Kid Bluetooth® Karaoke Kid Bluetooth® Mikrofon Microfono Bluetooth® Ragazzo Karaoke Micrófono infantil Bluetooth® para karaoke Microfone Bluetooth® de karaoke para criança Mikrofon karaoke Bluetooth® dla dzieci Детское караоке с Bluetooth® микрофоном Karaoke Kid Bluetooth® mikrofon Детски Караоке Bluetooth® Микрофон Karaoke Bluetooth® microfoon voor kinderen Gyermekek Karaoke Bluetooth® Mikrofon Μικρόφωνο karaoke Bluetooth® για παιδιά Karaoke Çocuk Bluetooth® Mikrofon 노래방 키즈 블루투스® 마이크 カラオケキッズ ブルートゥース®マイク ميكروفون موسيقى كاريوكي بتقنية Bluetooth® للأطفال</p> |
|---------------------------------------|---|

Only the item 250901 was tested, since according to the declaration from the applicant, the electrical circuit design, layout, components used, internal wiring and functions were identical for the above items, with only difference on item No, color and decorations.

3.3 Separation Distance

| | |
|--|-----|
| Minimum test separation distance: | 5mm |
| <p>Remark: This minimum test separation distance is determined by the smallest distance from the antenna and radiating structures or outer surface of the device, according to the host form factor, exposure conditions and platform requirements, to any part of the body or extremity of a user or bystander.</p> | |

3.4 Test Location

All tests were performed at:

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen Branch

No. 1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China. 518057.

Tel: +86 755 2601 2053 Fax: +86 755 2671 0594

No tests were sub-contracted.

3.5 Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

• A2LA (Certificate No. 3816.01)

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory is accredited by the American Association for Laboratory Accreditation(A2LA). Certificate No. 3816.01.

• VCCI (Member No. 1937)

The 3m Fully-anechoic chamber for above 1GHz, 10m Semi-anechoic chamber for below 1GHz, Shielded Room for Mains Port Conducted Interference Measurement and Telecommunication Port Conducted Interference Measurement of SGS-CSTC Standards Technical Services Co., Ltd.

Shenzhen EMC laboratory have been registered in accordance with the Regulations for Voluntary Control Measures with Registration No.: G-20026, R-14188, C-12383 and T-11153 respectively.

• FCC –Designation Number: CN1336

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized as an accredited testing laboratory.

Designation Number: CN1336. Test Firm Registration Number: 787754.

• Innovation, Science and Economic Development Canada

SGS-CSTC Standards Technical Services Co., Ltd., Shenzhen EMC Laboratory has been recognized by ISED as an accredited testing laboratory.

CAB identifier: CN0006.

IC#: 4620C.

3.6 Deviation from Standards

None

3.7 Abnormalities from Standard Conditions

None

4 FCC Radiofrequency radiation exposure limits

Test exemptions apply for devices used in general population/uncontrolled exposure environments, according to the SAR-based, or MPE-based exemption thresholds.

4.1 Blanket 1 mW Blanket Exemption

The 1 mW Blanket Exemption of §1.1307(b)(3)(i)(A) applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power of no more than 1 mW, regardless of separation distance.

The 1-mW blanket exemption applies at separation distances less than 0.5 cm, including where there is no separation. This exemption shall not be used in conjunction with other exemption criteria other than those for multiple RF sources in paragraph §1.1307(b)(3)(ii)(A).

The 1-mW exemption is independent of service type and covers the full range of 100 kHz to 100 GHz, but it shall not be used in conjunction with other exemption criteria or in devices with higher-power transmitters operating in the same time-averaging period. Exposure from such higher-power transmitters would invalidate the underlying assumption that exposure from the lower-power transmitter is the only contributor to SAR in the relevant volume of tissue.

4.2 MPE-based Exemption

General frequency and separation-distance dependent MPE-based effective radiated power (ERP) thresholds are in Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] to support an exemption from further evaluation from 300 kHz through 100 GHz.

Table B.1—Thresholds For Single RF Sources Subject to Routine Environmental Evaluation

| RF Source Frequency | | | Minimum Distance | | | Threshold ERP |
|--|---|-----------|--------------------|---|--------------------|--------------------------------------|
| f_L MHz | | f_H MHz | $\lambda_L / 2\pi$ | | $\lambda_H / 2\pi$ | W |
| 0.3 | — | 1.34 | 159 m | — | 35.6 m | 1,920 R ² |
| 1.34 | — | 30 | 35.6 m | — | 1.6 m | 3,450 R ² /f ² |
| 30 | — | 300 | 1.6 m | — | 159 mm | 3.83 R ² |
| 300 | — | 1,500 | 159 mm | — | 31.8 mm | 0.0128 R ² f |
| 1,500 | — | 100,000 | 31.8 mm | — | 0.5 mm | 19.2R ² |
| Subscripts L and H are low and high; λ is wavelength. | | | | | | |
| From §1.1307(b)(3)(i)(C), modified by adding Minimum Distance columns. | | | | | | |

The table applies to any RF source (i.e. single fixed, mobile, and portable transmitters) and specifies power and distance criteria for each of the five frequency ranges used for the MPE limits. These criteria apply at separation distances from any part of the radiating structure of at least $\lambda/2\pi$. The thresholds are

based on the general population MPE limits with a single perfect reflection, outside of the reactive near-field, and in the main beam of the radiator.

For mobile devices that are not exempt per Table B.1 [Table 1 of §1.1307(b)(1)(i)(C)] at distances from 20 cm to 40 cm and in 0.3 GHz to 6 GHz, evaluation of compliance with the exposure limits in §1.1310 is necessary if the ERP of the device is greater than ERP_{20cm} in Formula (B.1) [repeated from §2.1091(c)(1); also in §1.1307(b)(1)(i)(B)].

$$P_{th} \text{ (mW)} = ERP_{20 \text{ cm}} \text{ (mW)} = \begin{cases} 2040f & 0.3 \text{ GHz} \leq f < 1.5 \text{ GHz} \\ 3060 & 1.5 \text{ GHz} \leq f \leq 6 \text{ GHz} \end{cases} \quad (\text{B.1})$$

If the ERP is not easily obtained, then the available maximum time-averaged power may be used (i.e., without consideration of ERP only if the physical dimensions of the radiating structure(s) do not exceed the electrical length of $\lambda/4$ or if the antenna gain is less than that of a half-wave dipole.

SAR-based exemptions are constant at separation distances between 20 cm and 40 cm to avoid discontinuities in the threshold when transitioning between SAR-based and MPE-based exemption criteria at 40 cm, considering the importance of reflections.

| Limit calculation | | | |
|-------------------|----------------|----------------------|------------------|
| Frequency range | Frequency(MHz) | $R(\lambda/2\pi)(m)$ | Threshold ERP(W) |
| 300~1500MHz | 915 | 0.0522 | 0.032 |
| 1500~100000MHz | 2480 | 0.0193 | 0.007 |

4.3 SAR-based Exemption

SAR-based thresholds are derived based on frequency, power, and separation distance of the RF source. The formula defines the thresholds in general for either available maximum time-averaged power or maximum time-averaged ERP, whichever is greater.

If the ERP of a device is not easily determined, such as for a portable device with a small form factor, the applicant may use the available maximum time-averaged power exclusively if the device antenna or radiating structure does not exceed an electrical length of $\lambda/4$.

As for devices with antennas of length greater than $\lambda/4$ where the gain is not well defined, but always less than that of a half-wave dipole (length $\lambda/2$), the available maximum time-averaged power generated by the device may be used in place of the maximum time-averaged ERP, where that value is not known.



Unless otherwise agreed in writing, this document is issued by the Company subject to its General Conditions of Service printed overleaf, available on request or accessible at <https://www.sgs.com/en/Terms-and-Conditions>. Attention is drawn to the limitation of liability, indemnification and jurisdiction issues defined therein. Any holder of this document is advised that information contained hereon reflects the Company's findings at the time of its intervention only and within the limits of Client's instructions, if any. The Company's sole responsibility is to its Client and this document does not exonerate parties to a transaction from exercising all their rights and obligations under the transaction documents. This document cannot be reproduced except in full, without prior written approval of the Company. Any unauthorized alteration, forgery or falsification of the content or appearance of this document is unlawful and offenders may be prosecuted to the fullest extent of the law. Unless otherwise stated the results shown in this test report refer only to the sample(s) tested and such sample(s) are retained for 30 days only.

Attention: To check the authenticity of testing /inspection report & certificate, please contact us at telephone: (86-755) 8307 1443, or email: CN.Doccheck@sgs.com

No.1 Workshop, M-10, Middle Section, Science & Technology Park, Nanshan District, Shenzhen, Guangdong, China 518057 t (86-755) 26012053 f (86-755) 26710594 www.sgs.com
中国·广东·深圳市南山区科技园中区M-10栋1号厂房 邮编: 518057 t (86-755) 26012053 f (86-755) 26710594 sgs.china@sgs.com

The separation distance is the smallest distance from any part of the antenna or radiating structure for all persons, during operation at the applicable ERP. In the case of mobile or portable devices, the separation distance is from the outer housing of the device where it is closest to the antenna.

The SAR-based exemption formula of §1.1307(b)(3)(i)(B), repeated here as Formula (B.2), applies for single fixed, mobile, and portable RF sources with available maximum time-averaged power or effective radiated power (ERP), whichever is greater, of less than or equal to the threshold P_{th} (mW).

This method shall only be used at separation distances from 0.5 cm to 40 cm and at frequencies from 0.3 GHz to 6 GHz (inclusive). P_{th} is given by Formula (B.2).

$$P_{th} \text{ (mW)} = \begin{cases} ERP_{20 \text{ cm}} (d/20 \text{ cm})^x & d \leq 20 \text{ cm} \\ ERP_{20 \text{ cm}} & 20 \text{ cm} < d \leq 40 \text{ cm} \end{cases} \quad (\text{B.2})$$

where

$$x = -\log_{10} \left(\frac{60}{ERP_{20 \text{ cm}} \sqrt{f}} \right)$$

and f is in GHz, d is the separation distance (cm), and $ERP_{20 \text{ cm}}$ is per Formula (B.1).

Example values shown in Table B.2 are for illustration only.

Table B.2—Example Power Thresholds (mW)

| Frequency (MHz) | Distance(mm) | | | | | | | | | |
|--------------------|--------------|----|----|-----|-----|-----|-----|-----|-----|-----|
| | 5 | 10 | 15 | 20 | 25 | 30 | 35 | 40 | 45 | 50 |
| 300 | 39 | 65 | 88 | 110 | 129 | 148 | 166 | 184 | 201 | 217 |
| 450 | 22 | 44 | 67 | 89 | 112 | 135 | 158 | 180 | 203 | 226 |
| 835 | 9 | 25 | 44 | 66 | 90 | 116 | 145 | 175 | 207 | 240 |
| 1900 | 3 | 12 | 26 | 44 | 66 | 92 | 122 | 157 | 195 | 236 |
| 2450 | 3 | 10 | 22 | 38 | 59 | 83 | 111 | 143 | 179 | 219 |
| 3600 | 2 | 8 | 18 | 32 | 49 | 71 | 96 | 125 | 158 | 195 |
| 5800 | 1 | 6 | 14 | 25 | 40 | 58 | 80 | 106 | 136 | 169 |

| Limit calculation | | | | |
|----------------------|----------------|-------|--------------|--------------|
| Frequency range(GHz) | Frequency(GHz) | X | Distance(cm) | Pth (mW) |
| 0.3~1.5 | 0.915 | 1.474 | 0.5 | 8.133 |
| 1.5~6 | 2.48 | 1.905 | 0.5 | 2.717 |

5 Measurement and Calculation

5.1 Maximum transmit power

For BT:

| Frequency (MHz) | Maximum conducted power [dBm] | Maximum conducted (mW) |
|-----------------|-------------------------------|------------------------|
| 2480 | -1.26 | 0.75 |

The Power Data is based on the RF Test Report SZCR241200487502.

Antenna Gain: -0.58dBi

5.2 RF Exposure Calculation

The maximum conducted power is 0.75mW. The best case gain of the antenna is -0.58dBi.

Remark: we used the maximum power between the conducted power and ERP/EIRP to perform RF exposure exemption evaluation.

| | Evaluation method | Exempt Limit(mW) | Verdict |
|-------------------------------------|---------------------------------|------------------|---------|
| <input type="checkbox"/> | Blanket 1 mW Blanket Exemption | 1mW | N/A |
| <input type="checkbox"/> | MPE-based Exemption(ERP) | 7mW(ERP) | N/A |
| <input checked="" type="checkbox"/> | SAR-based Exemption(P_{th}) | 2.7mW | Yes |

So, the device is to qualify for SAR test exemption, the exemption report is in lieu of the SAR report.

6 EUT Constructional Details (EUT Photos)

Refer to Appendix – External and Internal Photos for SZCR2412004875ET.

-End of the Report-