

Exhibit E

User's Manual

C-ONE TECHNOLOGY CORP.

FCC ID.: LXLCFVFM5614R

Rockwell 56K CompactModem Card

56K CompactModemTM Card

User's Guide

Copyright 1998. All Rights Reserved.

Information in this document is subject to change without notice. No part of this document may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording.

IBM AT is a registered trademark of International Business Machines Corporation.

MS DOS and Microsoft Windows 3.1, Windows 95, Windows NT, Windows CE are registered trademarks of Microsoft Corporation.

All other brand and product names are trademarks or registered trademarks of their respective holders.

Version 1.0

Table of Contents

<u>CHAPTER 1. INTRODUCTION</u>	1-1
FEATURES	1-1
SYSTEM REQUIREMENTS	1-2
PACKAGE CONTENTS	1-2
<u>CHAPTER 2. INSTALLATION</u>	2-1
HARDWARE INSTALLATION	2-1
SOFTWARE INSTALLATION	2-1
Win CE	2-2
DOS AND WINDOWS 3.1X	2-3
WINDOWS 95	2-4
WINDOWS NT 3.51 OR HIGHER	2-5
OS/2 WARP	2-6
INSTALLING THE POINT ENABLER	2-6
COM PORT AND IRQ SETTINGS	2-8
<u>CHAPTER 3. BASIC AT COMMANDS</u>	3-1
GUIDELINES	3-1
BASIC MODEM COMMANDS	3-2
DIALING TELEPHONE NUMBERS	3-3
ESTABLISHING A CONNECTION MANUALLY	3-4
MULTIPLE COMMANDS ENTRY	3-4
RESULT CODES	3-4
S REGISTERS	3-4
BASIC 'AT' COMMAND SET DESCRIPTION	3-5
<u>CHAPTER 4. TROUBLESHOOTING</u>	4-1

Chapter 1. Introduction

Congratulations on your purchase of the 56K CompactModem™ Card. This CompactModem™ card is world's first and smallest Fax/Modem card designed for Windows CE based Palm PC or Handheld mobile computers with a I/O functionality support CompactFlash slot. The card supports ITU-T V.90 standard and K56flex protocol capable of delivering up to 56Kbps download data transfer rate.

With innovative power management and 3.3V/5V wide-range operating voltage, the card consumes very low power making it the best choice for data/fax communication for your Palm PC and Handheld PC

The card is designed with dual-voltage capability. It is operational in 5V environment. With a CompactFlash adapter, it can be transformed into a Fax/Modem PC card such that you may use the card in any Laptop PC which has PCMCIA slots. Designed for supporting Plug-and-Play in Win95, Win98 and WinCE, the installation is quick and easy with the provided configuration software. The modem is also proven to be compatible with all major modem communication standards.

Features

- CompactFlash sized design
- Support ITU-T V.90 & K56flex Communication Standard
- Up to 56Kbps Data communication
- 14,400bps Send/Receive Fax
- With innovative power-saving management and 3.3V/5V wide range operating voltage capability.
- Plug-and-Play. Easy Installation.
- Hot swapping and card insertion.
- V.42 and MNP 2-4 Error Correction
- V.42bis and MNP 5 Data Compression
- Auto fall back down to 300bps autosynch
- Asynchronous, full duplex
- Auto sleep and wake-up

Chapter 2. Installation

This chapter will provide you with instructions on installing 56K CompactModem™ card in your Palm-size PC, Handheld PC or Notebook. Before you begin, note the operating system you are using.

Hardware Installation

Installing the modem in the computer is a simple step that involves the following:

1. Using CompactModem™ in Palm-size PC or Handheld PC with a CompactFlash slot
 - 1-1 Firmly insert the 56K CompactModem™ card into the CompactFlash slot, with the 50-pin connector facing the CompactFlash slot. Use the arrow on the label as a guide for proper insertion.

Note: The key-guided slot will not allow incorrect insertion, therefore do not force the CompactModem™ card into the CompactFlash slot.

- 1-2 Firmly insert the enclosed cable into the 56K CompactModem Card. The keyed connector will not allow incorrect insertion.
- 1-3 Insert the other end of the cable with the RJ-11 connector into a standard telephone outlet.
2. Using CompactModem™ in Handheld PC/Notebook with PCMCIA slot
 - 2-1 Firmly insert the 56K CompactModem™ card into the CompactFlash adapter and this card become a Fax/Modem PC card.
 - 2-2 Insert this Fax/Modem PC card into the PCMCIA slot.
 - 2-3 Follow the 1-2 and 1-3 steps.

Software Installation

After installing the 56K CompactModem™ card using the above instructions, you need to install the software necessary to communicate with the CompactModem™ in some environment. This section provides the necessary instructions to configure the 56K CompactModem™ card for the following operating system or environment.

- 2-3 In the **Connections** panel, double click the icon of “**Make New Connection**”.
- 2-4 Then follow the instruction to make the connection instruction.
- 2-5 Back to **Connections** panel, pull down the “**Connection**” menu, and choose the “**Connect**” to finish the connection. Now you can send and receive the E-Mail through your internet account.
- 3. If you want to open Internet Explorer, click “**Start**” and then choose “**Channel**” after you have built the Modem connection.
- 4. If you want to know which Website you can connect, click “**Start**”, choose “**Channel**” and then open “**MSNBC**”. The system will tell you how to increase new channel.

With additional CompactFlash adapter, the 56K CompactModem™ card become Fax/Modem PC card and can use in general DOS, Windows 3.1x, Windows 95, Windows 98 and Windows NT. See the following instruction.

Dos and Windows 3.1x

Most notebook/computer comes ship with some form of Card and Socket Services software (refer to the reference manual that come with your computer). To determine if you have Card and Socket Services software, insert the 56K CompactModem™ connected with CompactFlash adapter into the PCMCIA slot after you have finished booting your computer. If the computer beeps, the Card and Socket Services software is loaded.

If the computer does not beep, check the computer screen as it is booting. If you see card Services” or similar verbiage, the Card and Socket Services Software is loaded.

Next, you need to determine whether the 56K CompactModem™ is configured by the Card and Socket Services Software. When the CompactModem™ card is configured, the CompactModem™ card will be assigned a COM port. Please refer to your Card and Socket Services software reference manual or README file on how to determine COM port setting (IRQ and I/O). The COM port setting will be useful for all Data and Fax Communication software.

If you do not have Card and Socket Services software, follow the procedures for **Installing the Point Enabler** software driver in this Chapter.

1. Go to the "**Control Panel**" by clicking on the "**START**" button located on the lower-left end of the screen, select **Settings** and click on **Control Panel**.
2. Double Click on **Modem** icon. Check the COM port that Windows 95 assigned to your CompactModem™ by highlighting the CompactModem™ driver and clicking on the **PROPERTIES** button.

Note: The default connection preferences should be:

Data Bits: 8

Parity: None

Stop Bits: 1

3. You may test your CompactModem™ by clicking on the *Diagnostic* page clicking on the **MORE INFO** button.

Note: If the CompactModem™ does not respond, try changing the COM port setting. Refer to Chapter 4 for Troubleshooting

If you purchase a version of the CompactModem with data communication software, install it now using the following steps:

1. Insert your communication software diskette.
2. Choose the Run command from the **START** menu.
3. At the prompt, type: a:\setup
4. Follow the on screen instructions to install the communications software on your computer.
5. These complete your installation.

If you have questions about the software installation, refer to the communications software User's Guide.

Windows NT 3.51 or higher

Windows NT does not require any special drivers to communicate with the CompactModem™; everything is already built into the operating system.

If you purchase a version of the CompactModem™ with data communication software, refer to the communications software User's Guide for installation.

The Fax/Modem Point Enabler will enable the card directly with the following PCMCIA controllers:

Intel 82365SL Controller (and ExCA Compatible controllers)
Vadem 465 and family
VLSI 82C146 ELC PCMCIA controller
Cirrus CL-PD671X and CL-PD672X families
DataBook TCIC-2/N Controller and family
OKI MSM60802GS-K
ThinkPad 720 Intel for MCA Variant
Sharp Controller
Socket Services 1.0+, 2.0+

To install the Fax/Modem Point Enabler,

1. Insert the Fax/Modem Configuration Diskette into the floppy drive.
2. At the C:\> prompt, type:
 cd\ <enter>
3. Copy the Point Enabler driver to your hard drive by typing:
 copy a:\cardsc.exe c: <enter>

CARDSC.EXE does not terminate and stay in resident, therefore it will not take up any memory from your PC. CARDSC.EXE can be activated in a DOS command or in the AUTOEXEC.BAT file as follows:

- a) DOS command line:
 C:\> CARDSC.EXE /I=I /C=c /M=m /S=s
- b) AUTOEXEC.BAT file:
 C:\CARDSC.EXE /I=I /C=c /M=m /S=s

The valid options and the default assigned value are as follows:

I/O port options (default c=2, COM2)
 c = 1 then base port = 3F8h COM1
 c = 2 then base port = 2F8h COM2
 c = 3 then base port = 3E8h COM3
 c = 4 then base port = 2E8h COM4

IRQ options (default i=3)

 i = 3, 4, 5, 10, 11, 12, 15

MEMORY options (default m=D0)

 m = C0 - DF

SOCKET options (default s=0)

 s = 0, 1, 2, 3

/U will unload the driver when run from DOS prompt

Chapter 3. Basic AT Commands

When using a Fax and Data Communication software, the software will auto-configure the AT commands for you. If you would like to operate the modem directly from the terminal mode, the instructions in this section will provide you with the basic concepts of asynchronous AT commands.

Guidelines

A modem can respond to the stream of characters from an attached computer or terminal (DTE) in two ways. If the characters are data, the modem converts them to analog form and passes them on to the telephone line. If the characters are commands, the modem responds to the commands.

In order to command the modem manually, you must use a terminal, terminal emulation software, or communication software in terminal mode.

When the modem starts up, it is in command mode, and interprets characters arriving from the DTE as commands. The following section describes the modem command format and the proper procedure for entering command and the typical modem response to those commands.

- ◊ With a few minor exceptions, all modem commands always begin with the letters **AT** (for *attention*) and end with an “ *Enter* ” key (the “ **+++** ” command and the “ **/** ” command are the exceptions and will be explained in this section).
- ◊ Multiple commands can be given on one command line, except that the number of characters on one command line should not exceed 40.
- ◊ Spaces created by using the “ *Space* ” bar are not counted as characters and are ignored by the modem.
- ◊ Most commands are executed immediately and can not be aborted once the “ *Enter* ” key is typed.
- ◊ The modem acknowledges a valid AT command by returning the message “ **OK** ” to the DTE. It acknowledges an invalid command by returning “ **ERROR** ”.

Note: As long as the modem is in command mode, no data is transmitted over the phone line.

	Now you have a choice of either returning back to on line with the ATO command or terminate the call with ATH command.
--	--

Dialing Telephone numbers

ATDT###-#### (where ###-#### is the phone number) <i>CONNECT 115200</i>	Dial Command This command is useful for dialing and establishing a connection with a remote PC or a computer with a modem. The D command tells the modem to dial a number and the letter T tells the modem to dial in tone mode. The telephone number follows the T. Once the modem has finished dialing, it waits for the remote modem to answer and then proceeds with the connection. It returns the code CONNECT 115200 when the connection is established successfully. Once the connection is unsuccessful, the result code will be NO CARRIER.
ATDT9,123-4567	Dial Modifiers The comma (,) modifier in a dial string tells the modem to pause for a number of seconds. The dial modifier is useful when you need to wait for the second dial tone on a PBX.
ATDT9W123-4567	The W modifier tells the modem to wait and look for a second dial tone. This is useful when a second dial tone must be present in order for the call to be successful.
ATS0=0 <i>OK</i> <i>RING</i> <i>RING</i>	Answering a Call You may command the modem to answer a call either automatically or manually. One of the S registers, S0, determines the number of rings required for the modem to answer. By setting the S register to 0, you may make the modem completely ignore the call, but the call will register on the screen as the rings occur.
ATS0=2 <i>OK</i>	By setting the S register to any non-zero value, you can dictate the number of rings needed for the modem to answer the call.

Hayes compatible modems store most of their configuration information in 8-bit status registers, or S Registers. You may modify many features of the modem operation by writing directly to these registers, by using AT commands provided for this purpose. An S Register Summary appears in Appendix B.

Basic 'AT' Command Set Description

Command	Default	Parameters/Description
A/	none	Re-execute Command: This command re-executes the last 'AT' command string stored in the command buffer . The A/ command is the only command not preceded by 'AT' and ended by a carriage return.
A	none	Answer Command: This command causes the modem to immediately go off-hook and initiate an answer mode handshake without waiting for an incoming ring signal.
Bn	1	Select CCITT or Bell: This command selects Whether the modem is configured as a CCITT or BELL modem n = 0 Selects CCITT V.22 when the modem is at 1200 bps n = 1 Selects Bell 212A when the modem is at 1200 bps, and Bell 103J when the modem is at 300 bps. *
Cn	1	Carrier Control: This command is reserved for selecting between controlled carrier or constant carrier modes. This modem supports only constant carrier mode. n = 0 Transmit carrier always off (returns an ERROR message) n = 1 Normal transmit carrier *

		<p>! Flash Hook --- Causes the modem to go on-hook for 0.75 seconds.</p> <p>@ Wait for Quiet Answer --- Causes the modem to wait for specified amount of time (S-register S7) followed by 5 seconds of silence be-fore processing the next dial modifier.</p> <p>; Return to Idle State – Causes the modem to enter on-line command mode without initiating a data modem handshake (used for phone directory auto- dialers).</p> <p>-, () Ignored by Modem -- These four characters are ignored by the modem.</p>
En	1	<p>Command Echo: This command selects whether the modem echoes 'AT' commands back to the host in either on-line command mode.</p> <p>n = 0 Echo disabled</p> <p>n = 1 Echo enabled *</p>
Hn	0	<p>Disconnect(Hang-Up): This command is used to control the telephone line relay (OHREL*) and causes the modem to either hang-up or pick-up the telephone line.</p> <p>n = 0 Hang-up telephone line (go on-hook)*</p> <p>n = 1 Pick-up telephone line (go off-hook)</p>
In	0	<p>Identification: This command causes the modem to send product code and hardware setup information to the DTE.</p> <p>n = 0 Report product code *</p> <p>n = 1 Report computed checksum</p> <p>n = 2 Report OK</p> <p>n = 3 Report firmware version, basic model, code</p> <p>n = 4 Report response programmed by an OEM</p> <p>n = 5 Report the country code parameter</p> <p>n = 6 Report modem data pump model and internal version</p>

Basic AT Commands 3-7

Qn	0	Quiet Result Control: This command selects whether the modem will send result codes to the DTE. n = 0 Result codes enabled * n = 1 Result codes disabled
Sn	none	Read/Write S-Register: The modem selects an S-Register, performs an S-Register read or write function, or reports the value of an S-Register n Establishes S-Register n as the last register accessed n = v Sets S-Register n to the value n n? Reports the value of S-Register n
T	none	Set Tone Dial Default: This command configures the modem to use DTMF tones next time the modem dials a telephone number. (See P)
Vn	1	Result Code Form: This command selects the sending of short-form or long-form result codes to DTE. The parameter, if valid, is written to S14 bit 3. n = 0 Enables short-form result codes. Line feed is not issued before a short-form result code n = 1 Enables long-form result codes. *
Wn	0	Connect Message Control: This command Controls the format of CONNECT messages. The Parameter value, if valid, is written to S#! bits 2 and 3. n=0 Upon connection, the modem reports only the DTE speed.* n=1 Upon connection, the modem reports the line speed, the error correction protocol, and the DTE speed, respectively. n=2 Upon connection, the modem reports the DCE speed.

Basic AT Commands 3-9

Yn	0	<p>Long Space Disconnect: This command controls whether the modem will send silence to the remote modem before disconnecting and disconnect after seeing 1.6 seconds of silence from the remote modem.</p> <p>n = 0 Disables long space disconnect *</p> <p>n = 1 Enables long space disconnect. The modem disconnects after receiving 1.6 seconds of silence from the remote modem. Additionally, after receiving an 'ATH0' command, the modem will send at least 4 seconds of silence before hanging up.</p>
Zn	none	<p>Soft Reset and Restore Profile: The modem performs a soft reset and restores (recalls) the configuration profile according to the parameter supplied.</p> <p>n = 0 Soft resets and restore stored profile 0</p> <p>n = 1 Soft resets and restore stored profile 1</p>
&Cn	1	<p>RLSD (DCD) Option: The modem controls the RLSD output in accordance with the parameter supplied. The parameter value, if valid, is written to s21 bit 5</p> <p>n = 0 RLSD remains ON at all times.</p> <p>n = 1 RLSD follows the state of the carrier.*</p>
&Dn	2	<p>Data Terminal Ready (DTR) Option: This command interprets the ON to OFF transition of the DTR signal from the DTE in accordance with the parameter supplied. The parameter value, if valid, is written to S21 bit 3 and 4</p> <p>n = 0 Interpret DTR NO-to-OFF transition per &Qn</p> <p>n = 1 Interpret DTR NO-to-OFF transition per &Qn</p> <p>n = 2 Interpret DTR NO-to-OFF transition per &Qn*</p> <p>n = 3 Interpret DTR NO-to-OFF transition per &Qn</p>

&Mn	0	<p>n = 0 Selects direct asynchronous operation*</p> <p>n = 1 Selects synchronous connect mode with async off-line command mode</p> <p>n = 2 Selects synchronous connect mode with async off-line command mode and enable DTR dialing of directory zero</p> <p>n = 3 Selects synchronous connect mode with async off-line command mode and enable DTR to act as Talk/Data switch</p>
&Pn	0	<p>Select Pulse Dial Make/Break Ratio: This command determines the make/break ratio used during pulse dialing.</p> <p>n = 0 Selects 39%-61% make/break ratio at 10 pulses second.*</p> <p>n = 0 Selects 33%-67% make/break ratio at 10 pulses second.</p> <p>n = 0 Selects 39%-61% make/break ratio at 20 pulses second.</p> <p>n = 0 Selects 33%-67% make/break ratio at 20 pulses second.*</p>
&Qn	0	<p>Sync/Async Mode: This command is an extension of the &M command and is used to control the connection modes permitted. It is used in conjunction with S36 and S48</p> <p>n = 0 Select direct asynchronous mode.*</p> <p>n = 1 Select Sync connect mode with async off-line command mode.</p> <p>n = 2 Select Sync connect mode with async off-line command mode and enables DTR dialing of directory 0</p> <p>n = 3 Select Sync connect mode with async off-line command mode and enables DTR to act as Talk/Data switch</p> <p>n = 4 Select Autosync mode.</p> <p>n = 5 The modem will try to negotiate an error-corrected link</p> <p>n = 6 Select asyn operation in normal mode</p>

	<p>Active Profile: B1 E1 L1 M1 N1 Q0 T V1 W0 X4 Y0 &C1 &D2 &G0 &J0 &K3 &Q5 &R1 &S0 &T5 &X0 &Y0 S00:000 S01:000 S02:043 S03:013 S04:010 S05:008 S06:002 S07:060 S08 :002 S09:006 S10:014 S11:095 S12:050 S14:170 S16:000 S18:000 S21: 048 S22:118 S23:021 S25:005 S26:001 S27:064 S36:007 S37:000 S38:020 S46:138 S48:007 S95:000</p> <p>Stored Profile 1: B1 E1 L1 M1 N1 Q0 T V1 W0 X4 Y0 &C1 &D2 &G0 &J0 &K3 &Q5 &R1 &S0 &T5 &X0 S00:000 S01:000 S02:043 S03:013 S04:010 S05:008 S06:002 S07:060 S08 :002 S09:006 S10:014 S11:095 S12:050 S14:170 S16:000 S18:000 S21: 048 S22:118 S23:021 S25:005 S26:001 S27:064 S36:007 S37:000 S38:020 S46:138 S48:007 S95:000</p> <p>Stored Profile 0: B1 E1 L1 M1 N1 Q0 T V1 W0 X4 Y0 &C1 &D2 &G0 &J0 &K3 &Q5 &R1 &S0 &T5 &X0 S00:000 S01:000 S02:043 S03:013 S04:010 S05:008 S06:002 S07:060 S08 :002 S09:006 S10:014 S11:095 S12:050 S14:170 S16:000 S18:000 S21: 048 S22:118 S23:021 S25:005 S26:001 S27:064 S36:007 S37:000 S38:020 S46:138 S48:007 S95:000</p> <p>Telephone Numbers: 0= 1= 2= 3= OK</p>
--	---

Chapter 4. Troubleshooting

This chapter will provide you with solutions to some frequently asked questions when installing and operating the CompactModem card. Please note that certain solutions may only apply to some operating system or communication software.

If you cannot find the solution to your problem after reading this chapter, please contact your computer manufacturer or the vendor from which you purchased the modem.

Note: Beside referring to the solutions listed in this chapter, you should also refer to the communications software User's Guide for more solutions to software problems.

Why is my modem not responding? My communication software can not find my modem.

- ◆ Check that the CompactModem™ card connected with the CompactFlash adapter is completely inserted into the PCMCIA slot. If you have Card and Socket Services software loaded, your computer should beep when the card is inserted.
- ◆ If your notebook/computer has more than one serial port, the COM port setting assigned to the CompactModem™ card may have a conflict with the built-in serial port or modem. Check your computer BIOS setup, if you do not plan to use the built-in serial port, you may disable it (refer to your notebook/computer manual for more instructions).
- ◆ If you are using Windows 3.1x and the IRQ has been set to IRQ other than 3, 4, and the IO has been set to IO other than 3F8, 2F8, 3E8, 2E8, you will need to configure the COM port setting located in the Control Panel (refer to your Window's manual for more instructions).
- ◆ Check that you have loaded the Point Enabler software driver, if you do not have Card and Socket Services software (refer to installing Point Enabler for more instructions).

Error occurred when I try to download a data file.

- ◆ Try to connect the modems at a slower baud rate (refer to the communication software's manual for more instructions).
- ◆ Try setting the flow control of the communications software to hardware (RTS/CTS) (refer to the communication software's manual for more instructions), which will cause your computer to pause long enough for the file to download. Or you may set it in a terminal mode by typing the AT command " AT&K3 " or add " &K3 " to the initialization string of your communication software (refer to Chapter 3, ***Basic AT Commands***).

Occasionally, my modem gets disconnected in the middle of a connection.

- ◆ If there is another phone extension in the same line, make sure that it is not used by someone else.
- ◆ If you have signed up for call waiting feature with your phone company, call your phone company's support hot-line on how to temporarily disable this feature. In most cases, you will need to add " *70 " before your dial number.
- ◆ The modem at the other end may hang-up or disconnect the connection.

When the modem is connecting to another modem, it reports a higher baud-rate than it really should be.

- ◆ The CompactModem™ card is default to report the modem-to-computer baud-rate when it responds to " CONNECT ". However, you may set your CompactModem™ to report the modem-to-modem baud rate instead by typing the AT command " ATW2 " in a terminal mode or add " W2 " to the initialization string of your communication software (refer to Chapter 3, ***Basic AT Commands***, for more instructions).

After connected to a BBS, the text on the screen is not legible.

- ◆ Some BBS may use a different setting for the data-bits, parity and stop bit, so check with your BBS before dialing. The two most common

Appendix A. AT Commands Summary

Basic Data Modem 'AT' Commands

Command	Default	Parameters/Function
A/ **	none	Re-execute command
A	none	Answer
Bn *	1	Select CCITT or Bell
Cn	1	Carrier control
D	none	Dial command
En *	1	Command echo
Hn	0	Disconnect
In	0	Identification
Ln *	2	Speaker volume control
Mn *	1	Speaker control
Nn *	1	Automode Enable
On	0	Go On-line data mode
P *	none	Select pulse dialing
Qn *	0	Quiet result code control
Sn	none	Select an S-register
Sn=x	none	Write to an S-register
Sn?	none	Read from an S-register
T *	none	Set tone dial default
Vn *	1	Result code form
Wn	0	Connect message control
Xn *	4	Extended result codes
Yn *	0	Long space disconnect
Zn	0	Soft reset and restore profile
&Cn *	1	RLSD (DCD) option
&Dn *	2	DTR option
&Fn	none	Restore factory configuration
&Gn *	0	Select guard tone
&Jn	0	Telephone jack control
&Kn	3	flow control
&Ln	0	Leased line operation
&Mn *	0	Asynch/synch mode selection

+FTH=n	Transmit data with HDLC framing
+FTM=n	Transmit data
+FTS=n	Stop transmission and wait

Fax Class 2 Commands

Command	Function
Service Class ID	
+FCLASS=n	Service class
Fax Class 2 Action Commands	
D	Originate a call
A	Answer a call
+FDT	Data Transmission
+FET=n	Transmit page punctuation
+FDR	Begin or continue phase C receive data
+FK	Session Termination
Fax Class 2 DCE Responses	
+FCON	Facsimile connection response
+FDCS:	Report current session
+FDIS:	Report remote identification
+FCFR	Indicate confirmation to receive
+FTSI:	Report the transmit station ID
+FCSI:	Report the called station ID
+FPTS:	Page transfer status
+FET:	Post page message response
+FHNG	Call termination with status
Fax Class 2 Session Parameter	
+FMFR?	Identify manufacturer
+FMDL?	Identify model
+FREV?	Identify revision
+FDCC=	DCE capabilities parameters
+FDIS=	Current session parameters
+FDCS=	Current session results
+FLID=	Local ID string
+FCR=	Capability to Receive
+FPTS=	Page transfer status
+FAE=	Adaptive answer

	1	Enable MNP 5 data compression
	2	Enable V.42 bis data compression
	3*	Enable both V.42 bis and MNP 5 data compression
\An	0	Set max. block size in MNP to 64
	1	Set max. block size in MNP to 128
	2	Set max. block size in MNP to 192
	3*	Set max. block size in MNP to 256
\Bn	1~9	Transmit break to remote (default n=3)

* Value saved in NVRAM.

MNP 10 Commands

Command	n value	Function
)Mn	0~2	Enable cellular power level adjustment
*Hn	0~2	Link negotiation speed
-Kn	0*	Disables V.42 LAMP to MNP 10 conversion
	1	Enables V.42 LAMP to MNP 10 conversion
	2	Enables V.42 LAMP to MNP 10 conversion detection only
-Qn	0~1	Enable fallback V.22 bis/V.22
-SEC=n	0	Disable MNP 10 EC
	1	Enable MNP 10 EC and set transmit level 0 to 30 (0 to -30 dbm)
@Mn	0~30	Initial cellular power level setting
:En	0~1	Compromise equalizer enable command

*Value saved in NVRAM.

Cellular Commands

Command	Function
^C2	Download cellular phone driver
^I	Identify cellular phone driver
^T6	Indicate status of cellular phone

Appendix B. S Register Summary

Register	Default	Function
S0 *	0	Rings to auto-answer
S1	0	Ring counter
S2 *	43	Escape character
S3	13	Carriage return character
S4	10	Line feed character
S5	8	Backspace character
S6 *	2	Wait time for dial tone
S7 *	50	Wait time for carrier
S8 *	2	Pause time for dial delay modifier
S9 *	6	Carrier detect response time
S10 *	14	Carrier loss disconnect time
S11 *	95	DTMF tone duration
S12 *	50	Escape prompt delay
S13	None	Reserved
S14 *	138	General bit mapped option status
S15	None	Reserved
S16	0	Test mode bit mapped options status (&T)
S17	None	Reserved
S18 *	0	Modem test timer
S19	0	Autosync options
S20 *	0	Autosync HDLC address or BSC sync character
S21 *	52	V.24/general bit mapped options status
S22 *	117	Speaker/result bit mapped options status
S23 *	62	General bit mapped options status
S24 *	0	Sleep inactivity timer
S25	5	Delay to DTR off
S26	1	RTS-to-CTS delay
S27 *	73	General bit-mapped options status
S28 *	0	General bit-mapped options status
S29	70	Flash dial modifier time

Appendix C. FCC Regulations

FCC Certification

The United States Federal Communication Commission (FCC) and the Canadian Department of Communications have established certain rules governing the use of modems and other electronic equipment.

FCC Part 68 Registration

The modem is registered with the FCC as compliant with the rules of Part 68, and use of this modem is subject to the following restrictions:

1. The Federal Communication Commission FCC has established rules which permit this device to be directly connected to the telephone network. Standardized jacks are used for these connections. This equipment should not be used on party lines or coin phones.
2. If this device is malfunctioning, it may also be causing harm to the telephone network; this device should be disconnected until the source of the problem can be determined and until repair has been made. If this is not done, the telephone company may temporarily disconnect service.
3. The telephone company may make changes in it's facilities, equipment, operation and procedures; if such changes affect the compatibility or use of this device, the telephone company is required to give adequate notice of the changes. You will be advised of your right to file a complaint with the FCC.
4. If the telephone company requests information on what equipment is connected to their lines, inform them of:
 - a. The telephone number to which this unit is connected.
 - b. The ringer equivalence number.
 - c. The USOC jack required.
 - d. The FCC Registration number.

Items (b) and (d) are indicated on the label. The Ringer Equivalence Number (REN) is used to determine how many devices can be connected to your telephone line. In most areas, the sum of the REN of all the devices on any one line should not exceed 5.0. If too many devices are attached, they may not ring properly.

FCC Part 15 Registration

This modem complies with Part 15 of FCC rules. Operation is subject to the following two conditions:

Appendix D. Specifications

Dimensions:**Main body:**

36.4mm(L) x 42.8mm(W) x 3.3mm(H)

Extender:

49.2mm(L) x 42.8mm(W) x 15.78mm(H)

Telephone interface: RJ-11C**Operating modes:**

Asynchronous data and fax modem
Automatic or manual answer and origination
Internal DAA for direct connection to Public
Switched Telephone Networks
Full-Duplex or Half-Duplex
Tone or Pulse dialing mode

Data modes:

ITU-T	V.90, V.34+, V.34, V.32bis, V.32 V.22bis, V.22A/B, V.21, V.23
Rockwell	K56flex
Bell	212a, 103

Voice modes:

Enhanced ADPCM
Full-duplex speaker phone (optional)
Audio span/voice view (optional)
ASVD/DSVD (optional)

Fax modes:

EIA	Class 1, Class 2
ITU-T	V.17, V.29, V.27ter, V.21ch2

Data compression:

V.42bis, MNP5

Error correction:

V.42 LAPM, MNP 2-4, MNP 10

Specifications D-1

NOTICE:

RJ-11 Connection Kit

For use with the PRETEC 56K CompactModem card.

Read This First

EMI Suppression Clip

To ensure compliance with FCC/Part 15 Class B Emissions Limits, install the EMI suppression clip provided with your CompactModem RJ-11 connection Kit on the CompactModem RJ-11 Cable. Clamp the EMI suppression clip around the Cable at the CompactModem Card connector end.

BILL OF MATERIAL

Level	NO.	Part-Number	Description	QTY	Unit	Location
1	1	CFVFM-5614RBH01	Rockwell 56K CompactModem	1	SET	
2	1	A024	CompactModem	1	SET	
3	1	70100038	Frame, CF Type I Extender 2	1	PCS	
3	2	70100039	Cover, CF Type I Extender 2	1	PCS	
3	3	70200003	Spring, ESD	1	PCS	
3	4	70507007	Panel, CF Extender-UP	1	PCS	
3	5	70507057	Panel, CF Extender-Down	1	PCS	
2	2	60200072	Capacitor, 33u F, DIP, NP, 25V	1	PCS	C63
2	3	60500027	Socket, 50 pin, 3M	1	PCS	J1
2	4	61500001	Transfomer, ATS-274A, SMD, 1650 VAC	1	PCS	T1
2	5	60500059	Connector, RJ-11, Phone Jack, 87180-066	1	PCS	J3
2	6	CFVFM-5614RB-S	Rockwell 56K CompactModem SMD	1	SET	
3	1	51090017	PCB, CFVFM-5614RB	1	PCS	PCB
3	2	60100006	Resistor, 100K Ω , SMD 0603, 5%	3	PCS	R1,R2,R49
3	3	60100007	Resistor, 10K Ω , SMD 0603, 5%	8	PCS	R3,R11,R12,R13,R18
3						R19,R70,R80
3	4	60100009	Resistor, 0 Ω , SMD 0603, 5%	3	PCS	R58,R74,R79
3	5	60100023	Resistor, 7.5K Ω , 1/2W, SMD 2010	1	PCS	R30
3	6	60100024	Resistor, 33 Ω , 1/2W, SMD 2010	1	PCS	R47
3	7	60100039	Resistor, 20K Ω , SMD 0603, 5%	2	PCS	R5,R26
3	8	60100040	Resistor, 1M Ω , SMD 0603, 5%	1	PCS	R20
3	9	60100085	Resistor, 51K Ω , SMD 0603, 5%	1	PCS	R48
3	10	60100086	Resistor, 1K Ω , SMD 0603, 5%	1	PCS	R34
3	11	60100108	Resistor, 100 Ω , SMD 0603, 5%	2	PCS	R6,R21
3	12	60100109	Resistor, 47 Ω , SMD 0603, 5%	1	PCS	R10
3	13	60100120	Resistor, 100K Ω , SMD 0603, 1%	1	PCS	R39
3	14	60100121	Resistor, 301 Ω , SMD 0603, 1%	1	PCS	R32
3	15	60100200	Resistor, 49.9K Ω , SMD 0603, 1%	1	PCS	R37
3	16	60100202	Resistor, 590 Ω , SMD 0603, 1%	1	PCS	R29
3	17	60100203	Resistor, 180K Ω , SMD 0603, 5%	1	PCS	R4
3	18	60200002	Capacitor, 0.1u F, SMD 0805	10	PCS	C1,C2,C3,C4,C5,C6,C8
3						C11,C12,C67
3	19	60200013	Capacitor, 15p F, X7R, SMD 0805, 10%	1	PCS	C60
3	20	60200044	Capacitor, 0.001u F, X7R, SMD 0805	1	PCS	C34
3	21	60200051	Capacitor, 10u F, Tant, Case A, 10V	4	PCS	C7,C28,C29,C30
3	22	60200055	Capacitor, 10u F, Tant, Case B, 16V	1	PCS	C47
3	23	60200066	Capacitor, 10p F, NPO, SMD 0805, 5%, 60V	4	PCS	C9,C10,C18,C19

BILL OF MATERIAL

Level	NO.	Part-Number	Description	QTY	Unit	Location
1	1	CFVFM-5614RBH01	Rockwell 56K CompactModem	1	SET	
2	1	A024	CompactModem	1	SET	
3	24	60200069	Capacitor, 0.47u F, SMD 1812, 200V	1	PCS	C49
3	25	60300002	Diode, DAN217-146, SOT-23	2	PCS	D6,D7
3	26	60300004	Zener Diode, DTZ 16, SOD-23	2	PCS	D4,D4A
3	27	60300019	Zener Diode, RLZ-12, 3.4*1.5*1.5 mm, 500m W	1	PCS	D3
3	28	60300027	Zener Diode, RLZ-4.3, 3.4*1.5*1.5 mm, 500m W	1	PCS	D5,D5A
3	29	60400009	Transistor, 2SD1834, SOT-89, Darlington, NPN	1	PCS	Q2
3	30	60600003	Switch, Poly Mini SMD 050-2	1	PCS	F1
3	31	60900028	Crystal, 56.448 MHZ, SMD, 50 ppm	1	PCS	Y1
3	32	60900029	Crystal, 28.224 MHZ, SMD, 50 ppm	1	PCS	Y2
3	33	61000007	Inductor, 4.7u H, SMD 1206	1	PCS	L8
3	34	61200001	Ferrite Bead, BLM32A06PT, SMD 1206	2	PCS	L4,L7
3	35	61200002	Ferrite Bead, 70 Ω , SMD 0805, 400m A	1	PCS	L1
3	36	61400002	Photo MosRelay + Coupler, 3750 VAC	1	PCS	U11
3	37	61600002	Varistor, V360CH8, 8.5*5.5*2.0 mm	1	PCS	RV1
3	38	EE025602-1	IC, EEPROM, 24LV02, SOIC, 8Pin, 2.7~5 V	1	PCS	U1
3	39	F5025602-1	IC, Flash, 256K*8, TSOP, 70 ns, 3.3 V	2	PCS	U3
3	40		32 pin			
3		S50128XX-8	IC, SRAM, 128K*8, TSOP, 15ns, 3.3 V	1	PCS	U10
3	41		32 pin			
3		X9000047-3	MCUP, L2702, 128 Pin, Rockwell, TQFP, 3.3 V	1	PCS	U4
3	42	X9000047-4	MDP, R6785, 144 Pin, Rockwell, TQFP, 3.3 V	1	PCS	U9

Power Management:

Operating Voltage : 3.3V~5V +/- 5%

Operating mode :

3.3V 0.2W Typical

5V 0.7W Typical

Sleep mode :

- User programmable inactivity timer for sleep mode
- Wake up via Ring signal detection or any AT command

System Requirement:

CompactFlash slot or PCMCIA Type II slot

PC 386 or higher with 4 MB RAM

DOS, Windows 3.x, Win 95, Win CE, Win 97, Win 98

Environment conditions:

Operating temperature 0°C - 55°C

Storage temperature -20°C - 65°C

Relative humidity 0% - 95%

Altitude 20,000 ft

Pending Agency Approvals:

FCC Part 15 and 68

UL certified accessories

D-2 Specifications

- 1) This device may not cause harmful interface, and
- 2) this device must accept any interface received, including interface that may cause undesired operation.

This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to Part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy, and if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the distance between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Note: Changes or modifications not expressly approved by manufacturer could void the user's authority to operate the equipment.

S30	0	Disconnect inactivity timer
S31 *	194	General bit-mapped options status
S32	17	XON character
S33	19	XOFF character
S36 *	7	LAPM failure control
S37 *	0	Line connection speed
S38	20	Delay before forced hang-up
S39 *	3	Flow control bit mapped options status
S40 *	104	General bit-mapped options status
S41 *	195	General bit-mapped options status
S46 *	138	Data compression control
S48 *	7	V.42 negotiation control
S82	128	LAMP break control
S86		Call failure reason code
S91	10	PSTN transmit attenuation level
S92	10	Fax transmit attenuation level
S95 *	0	Result code message control

- Value saved in NVRAM.

B-2 S Register Summary

Audio Span & DSVD Commands

Command	n value	Function
-SMS=n	x	Audiospan/DSVD/DATA mode select and automatic mode select enable X =0 Data mode 1 DSVD mode 2 AudioSpan mode 3 Automatic mode select (default)
	y	Min. data speed with audio for audiospan
	z	Max. data speed with audio for audiospan
	t	Symbol rate t =0 Auto selection (default)
-SEC=n	0~1	Enable/disable DSVD n = 1 Enable DSVD (default)
-SQS=n	x	Select audiospan modulation mode x = 0 V.61 =1 ML144 =2 ML288
	y	Select audiospan automatic modulation Y = 0 Disable audiospan automodulation = 1 Enable audiospan automodulation
@Mn	0~30	Initial cellular power level setting
:En	0~1	Compromise equalizer enable command

A-6 AT Commands Summary

+FBUF?	Buffer size (read only)
+FPHCTO	Phase C time out
+FAXERR	Fax error value
+FBOR	Phase C data bit order

Voice Commands

Command	Function
#BDR	Select baud rate (turn off autobaud)
#CLS	Select data, fax, or voice
#MDL?	Identify model
#MFR?	Identify manufacturer
#REV?	Identify revision level
#TL	Audio output transmit level
#VBQ?	Query buffer size
#VBS	Bits per sample
#VBT	Beep tone timer
#VCI?	Identify compression method
#VGT	Set playback volume in the command state
#VLS	Voice line select
#VRA	Ringback goes away timer (originate)
#VRN	Ringback never came timer (originate)
#VRX	Voice receive mode
#VSD	Enable silence detection
#VSK	Buffer skid setting
#VSP	Silence detection period (voice receive)
#VSR	Sampling rate selection
#VSS	Silence detection tuner (voice receive)
#VTD	DTMF/tone reporting
#VTM	Enable timing mark placement
#VTS	Generate tone signals
#VTX	Voice transmit mode

Error Correction Commands

Command	n value	Function
%Cn	0	Disable data compression

A-4 AT Commands Summary

&Pn *	0	Pulse dial make/break ratio
&Qn *	0	Asynch/synch mode
&Rn	none	RTS/CTS option
&Sn *	0	DSR override
&Tn	0	Test and Diagnostics
&Vn	none	Display current configuration and stored profile
&V1	none	Display last connection statistics
&Wn	0	Stored current configuration
&Xn	0	Select synchronous clock source
&Yn *	0	Designate a default reset profile
&Zn=x	none	Store telephone number
%En *	2	Enable/disable line quality monitor Auto-retrain or fallback/fall forward
%L *	none	Line signal level
%Qn	none	Line signal quality
%7	none	Plug and play serial number
%8	none	Plug and play vendor ID and product number
\Kn	none	Break control
\N0	none	Select normal speed buffered mode
\N1	none	Select direct mode
\N2	none	Select reliable link mode
\N3	none	Select auto reliable mode
\N4	none	Force LAMP mode
\N5	none	Force MNP mode
+MS	none	Select modulation

Fax Class 1 Commands

Command	Function
Service Class ID	
+FCLASS=n	Service class
Fax Class 1 Commands	
+FAE=n	Data/fax auto answer
+FRH=n	Receive data with HDLC framing
+FRM=n	Receive data
+FRS=n	Receive silence

A-2 AT Commands Summary

settings are: 8 data bits, NO parity, and 1 stop bit (8, N, 1) or 7 data bits, EVEN parity, and 1 stop bit (7,E,1).

- ◆ You may have a poor phone line conditions which generate too much noise. Try hanging-up and dialing-up again, if the problem persevere, call your phone company for assistance, or you may try connecting at a lower baud-rate (refer to your communication software for more instructions).

4-4 Troubleshooting

I can not hear my modem's speaker making any sound when I am connecting to another modem.

- ◆ Check that you have not turn-off the modem's speaker. To turn it back on, you may issue the AT command "ATM1" in a terminal mode (refer to Chapter 3, **Basic AT Commands**), or you may add ' M1' to the initialization string in your communication software.
- ◆ Check that your notebook/computer's speaker is not disable (refer to your notebook/computer manual for more instructions).
- ◆ If you are using Windows 95, refer to its manual or help file on how to turn-on or increase the volume of the modem's speaker.

My modem failed to dial when my communication software tries to dial.

- ◆ Make sure that the CompactModem™ cable is secured to the CompactModem card, and the RJ11C plug is firmly inserted into the phone jack.
- ◆ Check with your phone company that your phone line is analog. The CompactModem card does not operate with digital or PBX phone line.
- ◆ Check that you have dialed the correct number, and the number you dial will have a modem answering.
- ◆ If there is another phone extension in the same line, make sure that it is not used by someone else.
- ◆ Make sure that the number you dial is available and not busy.

I can not get a connection after dialing.

- ◆ Check that the data-bits, parity and stop bit is set up according to your communication software specifications. Some BBS may use a different setting, so check with your BBS before dialing.
- ◆ The problem could be on the modem at the other end, try dialing another number.
- ◆ Make sure that the CompactModem cable is secured to the CompactModem card, and the RJ11C plug is firmly inserted into the phone jack.

4-2 Troubleshooting

&V1	none	<p>Display Last Connection Statistics: Display the last connection statistics in the following format:</p> <p>Termination ReasonLink Disconnect or local Request</p> <p>Last TX data rate33600 bps</p> <p>Highest TX data rate.....33600 bps</p> <p>Last RX data rate33600 bps</p> <p>Highest RX data rate.....33600 bps</p> <p>ERROR correction Protocol..LAPM</p> <p>Data Compression.....V42Bis</p> <p>Line Quality.....030</p> <p>Highest SPX RX state068</p> <p>Highest SPX TX state067</p>
&Wn	None	<p>Store Current configuration: This command causes the modem to store a subset of the active profile command and S-register configuration into the NVRAM user profile 'n'.</p> <p>n = 0 Store current configuration as profile 0</p> <p>n = 1 Store current configuration as profile 1</p>
&Xn	0	<p>Select Synchronous Clock Source: Select the source of the transmit clock for synch mode of operation</p> <p>n = 0 Select internal timing.*</p> <p>n = 1 Select external timing.</p> <p>n = 2 Select slave receive timing.</p>
&Yn	0	<p>Designate a Default Reset Profile: Select which user profile will be after a hard reset.</p> <p>n =0 Select profile 0 *</p> <p>n = 1 Select profile 1</p>
&Zn=x	none	<p>Store Telephone Number: The modem can store up to four telephone numbers and each telephone number dial string can contain up to 34 digital.</p> <p>x =0,9,a,b,c,d,#,* ,T,P,R,W,@, ,!;n = 0-3</p>

3-16 Basic AT Commands

&Rn	1	RTS/CTS :The selects how the modem controls CTS.CTS operation is modified if hardware flow control is selected N = 0 CTS tracks RTS or acts per V.25 n = 1 CTS is always active.*
&Sn	0	Data Set Ready (DSR) Override: This command selects how the modem will control DSR. n = 0 DSR will remain on at all times * n = 1 DSR will become active after answer tone has been detected and inactive after the carrier has been lost .
&Tn	0	Test and Diagnostics: The modem will perform Selected test and diagnostic functions according to the parameter supplied. A test can be run only when in an asynchronous operation in non-error-correction mode. n = 0 Terminates any test in progress * n = 1 Initial local analog loopback n = 2 Returns ERROR n = 3 Initial local digital loopback n = 4 Allow remote digital loopback n = 5 Disallow remote digital loopback request n = 6 Request an RDL without self-test n = 7 Request an RDL with self-test n = 8 Initial local analog loopback with self test
&V	none	Display Current Configuration and Stored Profiles: Reports the current configuration ,The stored profiles, and the first fours stored telephone numbers. Example: AT&V

3-14 Basic AT Commands

&F	none	Restore Factory Configuration: The modem loads the factory default configuration (profile). The factory default are identified for each command and in the S-Register description. n = 0 Restore factory configuration 0 n = 1 Restore factory configuration 1
&Gn	0	Select Guard Tone: The modem generates the guard tone selected by this command according to the parameter supplied. The parameter value, if valid, is written to S23 bits 6 and 7 n = 0 Disable guard tone. * n = 0 Disable guard tone. n = 2 Enable 1800-Hz guard tone.
&Jn	0	Telephone Jack Control: This command is included only for compatibility and performs no function except to load the S-Register. The Parameter value, if valid. Is written to S21 bit 1 n = 0 &J0 command* n = 1 &J1 command
&Kn	3	Flow Control: This command defines DTE/DCE flow control mechanism. The parameter value, if valid, is written to S39 bits 0,1, and 2. n = 0 Disable flow control n = 3 Enable RTS/CTS flow control* n = 4 Enable XON/OFF flow control n = 5 Enable transparent XON/OFF flow control n = 6 Enable both RTS/CTS and XON/OFF flow control
&Ln	0	Leased Line Operation: This command Request leased line or dial-up operation n = 0 Requests dial-up operation. Dial-up operation continues

3-12 Basic AT Commands

Xn	4	<p>Extended Result Code: This command selects which subset of the result messages will be used by the modem to inform the DTE of the results of commands.</p> <p>n = 0 Report basic call progress result codes i.e.: OK, CONNECT, RING, NO CARRIER (also, for busy, if enabled, and dial tone not detected), NO ANSWER and ERROR</p> <p>n = 1 Report basic call progress result codes and connections speeds, i.e.: OK, CONNECT, RING, NO CARRIER (also, for busy, if enabled, And dial tone not detected), ERROR and NO ANSWER</p> <p>n = 2 Report basic call progress result codes and connections speeds, i.e.: OK, CONNECT, RING, NO CARRIER (also, for busy, if enabled, And dial tone not detected), ERROR and NO ANSWER and CONNECT XXXX</p> <p>n = 3 Report basic call progress result codes and connections speeds, i.e., OK, CONNECT RING, NO CARRIER, ERROR and NO DIALING, NO ANSWER and CONNECT XXXX</p> <p>n = 4 Report all call progress result codes and connection speeds, i.e., OK CONNECT, RJNG, NO CARRIER,NO ANSWER and CONNECT XXXX, BUSY, NO DAILING and ERROR* (XXXX = rate)</p>
----	---	---

3-10 Basic AT Commands

Ln	1	<p>Speaker Volume: The command selects the modem speaker volume.</p> <p>n = 0 Low speaker volume n = 1 Low speaker volume* n = 2 Medium speaker volume n = 3 High speaker volume</p>
Mn	1	<p>Speaker Control: This command specifies when the speaker is turned on and off.</p> <p>n = 0 Speaker is always off n = 1 Speaker is on during call establishment, but is off when receiving carrier* n = 2 Speaker is always on n = 3 Speaker is off when receiving carrier and during dialing, but on during answering</p>
Nn	1	<p>Automode Enable: The command enables or automode detection. The parameter value, is written to S31 bit 1.</p> <p>n = 0 Automode detection is disable. A subsequent handshake will be conducted according to the contents of S37 or, if S37 is zero, according to the most recently sensed DTE speed n = 1 Automode detection is enable. A subsequent handshake will be conducted according the automode algorithm supported by the modem. The command is also equivalent to F0*</p>
On	0	<p>Go On-line: This command causes the modem to return back to on-line data mode from on-line command mode.</p> <p>n = 0 Go on-line. * n = 1 Go on-line and initial a retrain sequence.</p>
P	none	Select Pulse Dialing: This command configures the modem to use pulse dialing next time the modem dials a telephone number.

3-8 Basic AT Commands

D	None	<p>Dial Command: This command causes the modem to immediately go off-hook as an originating modem and dial a telephone number with corresponding dial modifiers as parameters that define how the modem should dial the telephone number.</p> <p>Dial Modifiers:</p> <p>0 to 9 Dialing Digits A,B,C Tone Dial Characters D,*,#</p> <p>P Pulse Dial --- Configures the modem to use pulse dialing to dial a telephone number.</p> <p>R Reverse Originate Mode --- Places the modem in answer mode. This modifier should be the last character in the dialing string (e.g., ATDT 123-45678R)</p> <p>S=n Dial NVRAM Telephone Number --- Causes the modem to dial a telephone number previously stored in the NVRAM with the AT&Zn = x (n=0 to 3) number command.</p> <p>T Tone Dial --- Configures the modem to use DTMF tones to dial a telephone number.</p> <p>W Wait for Dial Tone --- Causes the Modem to look for dial tone for a specified amount of time. If no dial tone in the amount of time specified by the S-register S6, the modem will then process the next command in the dial string.</p> <p>,</p> <p>Pause --- Causes the modem to pause or delay implementing the next parameter in the dial string by the time specified in S-register S8.</p>
---	------	---

3-6 Basic AT Commands

<i>RING</i>	
<i>RING</i>	
<i>CONNECT 115200</i>	

Establishing a Connection Manually

ATA	Manual Answer
<i>CONNECT 115200</i>	This command allows you manually answer a call or to retrieve an incoming call and then switch to data connection.

Multiple Commands Entry

AT&FS0=1&W1&Y1	Respective Commands
<i>CONNECT 115200</i>	<ul style="list-style-type: none"> • &F configures the modem for factory defaults. • S0=1 configures the modem to answer after one ring. • &W1 saves the active configuration to user profile 1. • &Y1 configures the modem to use NVRAM user profile 1 as the power-up defaults.

A complete list of AT commands Summary appears in Appendix A. Refer to 'Basic AT Command Set Description' in this Chapter, for a detailed description of the modem command set.

Result Codes

The modem responds to commands and to activity on the telephone line by sending short messages called result codes to the DTE. The most familiar result codes are *OK*, acknowledging acceptance and execution of a command, and *ERROR*, acknowledging an invalid command. Other common result codes reporting line activities are *RING*, *BUSY*, *NO CARRIER*, and the *CONNECT* message indicating successful connection with another modem, which is usually followed by the data rate of the connection.

S Registers

3-4 Basic AT Commands

Basic Modem Commands

The following section describes the basic modem command and response formats.

Note: The modem commands are shown in bold letters and the response is shown in italics.

AT&F <i>OK</i>	Restore Factory Configuration This command resets all modem settings to factory default settings.
ATZ <i>OK</i>	Soft Reset and Reset Profile This command retrieves the setting for the modem from one of the stored profiles. This command also resets modem firmware and restores it to a known setting.
ATE1 <i>OK</i>	Command Echo Normally the modem <i>echoes</i> the characters that are typed. To check if the commands are received properly by the modem, you may turn the echo on and check the responses. E1 enables the echo. E0 disables the echo by the modem.
A/ <i>OK</i>	Re-execute Command This command tells the modem to repeat the last command it has executed. The response could be OK or any other valid response that depending on the last command executed. This command is helpful for redialing. This command is not proceeded by the AT prefix or end by the Enter key.
+++ <i>OK</i>	Escape Command This command is useful to get the attention of the modem and to accept commands from the keyboard when it is on line. When the modem is on line, it transmits all characters from the keyboard to the remote station. It does not interpret any of the characters as a modem command. To get the modem's attention, just type +++ quickly. The modem will respond with OK.

3-2 Basic AT Commands

/H or ? will display the Help messages

To install CARDSC.EXE without the Card and Socket Services software, to save conventional memory, you have to disable the Card and Socket Services software from your system. Please refer to your system documentation to remark all PCMCIA lines in your CONFIG.SYS, AUTOEXEC.BAT and SYSTEM.INI files.

Note: The default IRQ setting is set to 3, however if you set IRQ to 5, notebooks with built-in sound chips may also be using this interrupt. In this situation, it is best to configure the CompactModem™ card to a higher interrupt, such as 7, to avoid any conflicts.

COM Port and IRQ Settings

The most common I/O and IRQ settings use in communications software are as follows:

Port	I/O Address(Hex)	IRQ
COM1	3F8	4
COM2	2F8	3
COM3	3E8	4
COM4	2E8	3

If your notebook computer has two serial ports, then COM1 and COM2 will not be available for your use. You may then need to choose COM3 with a different IRQ other than 3 and 4. Sharing of IRQ will cause system conflict, therefore it is strongly not recommended.

If your system does not have any available IRQ, and you do not use the COM2 on your notebook computer, you may disable it in your BIOS setting, please refer to your notebook reference manual for farther instructions.

2-8 Installation

OS/2 Warp

OS/2 Warp does not require any special drivers to communicate with the CompactModem™; everything is already built into the operating system. This section provides you with the following simple instructions for installing the CompactModem™ card for OS/2 Warp.

1. Ensure that OS/2 Warp is properly setup with the PCMCIA controller chipset.

Note: *It is very important that this information is correct. If the wrong PCMCIA chipset information is selected your modem will not work properly. Your computer manufacturer will be able to supply you with this information.*

2. Insert the CompactModem™ card connected with CompactFlash adapter.
3. OS/2 Warp will auto detect the CompactModem™ card.

Note: *If the modem does not respond properly, you will need to uninstall the PCMCIA support in OS/2, reboot the system and reinstall PCMCIA support.*

4. These complete your installation.

If you purchase a version of the CompactModem™ with data communication software, refer to the communications software User's Guide for installation.

Installing the Point Enabler

The CompactModem™ card Point Enabler software, provided in the Configuration Diskette, let your computer directly interface with the CompactModem™ card. You are only required to use the Point Enabler if:

- your computer does not have a Card and Socket Services Software.
- your Card and Socket Services Software fails to configure the CompactModem™ card.
- more conventional memory is required to run application softwares.

2-6 Installation

Windows 3.1 and Windows for Workgroup 3.11 do not require any special drivers to communicate with the CompactModem™ card once you have been configured by the Card and Socket Services or the Point Enabler. If you purchase a version of the CompactModem with data communication software, install it now using the following steps:

1. Turn on the computer, run Windows, and insert your communication software diskette.
2. Choose the Run command from the File menu in Windows Program Manager.
3. At the prompt, type: a:\setup
4. Follow the on screen instructions to install the communications software on your computer.
5. These complete your installation.

If you have questions about the software installation, refer to the communications software User's Guide.

Windows 95

This section provides you with the following simple instructions for installing the CompactModem™ card connected with CompactFlash adapter for Windows 95.

1. Turn on the computer and let Windows 95 boots-up.
2. After Windows 95 boots-up, insert the CompactModem card connected with CompactFlash adapter into the PCMCIA slot (refer to *Hardware Installation*).
3. Windows 95 will display a pops-up window "**New Hardware Found**".
4. Insert the installation disk into your computer and choose "Driver from disk provided by hardware manufacturer" and click the OK button.
5. Choose the correct drive letter (probably A:\) and click on the OK button.
6. When Windows 95 configures the CompactModem™, you will hear a double beep.

Your installation is now complete. To test your modem and determine the COM port setting, follows the following instructions:

2-4 Installation

- WinCE
- Dos and Windows 3.1x
- Windows 95
- Windows NT 3.51 or higher
- OS/2 Warp

Note: Please refer to the *README* file on the *Fax/Modem* diskette for information not available when this manual was published.

WinCE

WinCE does not require any special drivers to communicate with the CompactModem™. It is Plug-and-Play compliance.

This section provides you with the following simple instructions for configuring and using the 56K CompactModem™ card for your Palm PC or Handheld PC with a CompactFlash slot.

1. Turn on the Palm PC or Handheld PC and let WinCE boots up.
2. After WinCE boot-up, insert the 56K CompactModem™ Card into the CompactFlash slot.(Refer to Hardware Installation).
3. To confirm whether the WinCE sucessfully configure the CompactModem™ card, please follow the following steps:
 - 3-1 Click **Start** button.
 - 3-2 Choose **Settings**, then select **System**.
 - 3-3 In the **System** dialog box, click the **General** label.
 - 3-4 In the **General** windows, see the content of “**Storage card**”. If the WinCE already configure the CompactModem™, it will show “Rockwell_Sem._Sys.-RCD” or “X2_Compatible_56Kbps” message depending on the chips of the CompactModem™.

To test the CompactModem™ card, do the following instructions.

1. Setting “dialing pattern”
 - 1-1 Click **Start** button.
 - 1-2 Choose **Settings**, then select “**Communication**” panel to set the dialing pattern. If you finish the setting, click “**OK**”
2. Setting the connection information Click **Start** button.
 - 2-1 Choose **Program**, then select **Communication**.
 - 2-2 In the **Communication** window, choose **Connections**.

2-2 Installation

- Feature-rich Fax/Data communication software package included
- V.80 and Rockwell Video ready synchronous access modes support Host-based communication protocols
- Voice/audio mode(option)
- VoiceView alternating voice and data (option)
- Analog Cellular direct connect (option)
- GSM direct connection (option)

System Requirements

The minimum and recommended system requirements for the 56K CompactModem™ card are as follows:

- Palm PC/Handheld PC with I/O functionality support CompactFlash slot
- Laptop computer with PCMCIA support
- 4MB or higher of RAM (computer memory).
- A Standard residential (analog) RJ-11 phone line.
- DOS, Windows 3.1, Windows for Workgroup 3.11, Windows 95, Windows NT 3.51 or higher, Windows CE or OS/2 Warp.

Package Contents

- User's Guide
- One 56K CompactModem™ Card
- Configuration diskette
- Cable for connecting to 56K CompactModem™ card and RJ11 Jack
- Fax & Data Communications software with manual *

1-2 Introduction

APPENDIX A. AT COMMANDS SUMMARY **A-1**

BASIC DATA MODEM 'AT' COMMANDS	A-1
FAX CLASS 1 COMMANDS	A-2
FAX CLASS 2 COMMANDS	A-3
VOICE COMMANDS	A-4
ERROR CORRECTION COMMANDS	A-5
MNP 10 COMMANDS	A-5
CELLULAR COMMANDS	A-6
AUDIO & DSVD COMMANDS	A-6

APPENDIX B. S REGISTER SUMMARY **B-1**

APPENDIX C. FCC REGULATIONS **C-1**

FCC CERTIFICATION	C-1
FCC PART 68 REGISTRATION	C-1
FCC PART 15 REGISTRATION	C-1

APPENDIX D. SPECIFICATIONS **D-1**