

5771.4	NO ERRORS	3.8	-6	9.6	14	N/A (4)
5771.3	3.5	3.6	-6	9.6	14	23.6
Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5775						N/A (4)
!	!	!	!	!	!	!
5771.2	4.8	3.5	-6	9.5	14	23.5
5771.1	3.2	3.1	-6	9.1	14	23.1
5771.0	4.9	3	-6	9	14	23
5770.9	1.7	2.6	-6	8.6	14	22.6
5770.8	2.2	2.4	-6	8.4	14	22.4
5770.7	3.8	2.4	-6	8.4	14	22.4
5770.6	4	2.1	-6	8.1	14	22.1
5770.5	4.8	2	-6	8	14	22
5770.4	1.7	1.8	-6	7.8	14	21.8
5770.3	2.8	1.7	-6	7.7	14	21.7
5770.2	3.5	1.4	-6	7.4	14	21.4
5770.1	1.7	1.2	-6	7.2	14	21.2
5770.0	2	1.1	-6	7.1	14	21.1
5769.9	1.9	0.9	-6	6.9	14	20.9
5769.8	2.1	0.7	-6	6.7	14	20.7
5769.7	2.6	0.6	-6	6.6	14	20.6
5769.6	1.9	0.6	-6	6.6	14	20.6
5769.5	1.7	0.4	-6	6.4	14	20.4
5769.4	2.3	0.4	-6	6.4	14	20.4
5769.3	3	0.1	-6	6.1	14	20.1
5769.2	3.2	0	-6	6	14	20
5769.1	4	-0.1	-6	5.9	14	19.9
5769.0	3.5	-0.2	-6	5.8	14	19.8
5768.9	2.5	-0.3	-6	5.7	14	19.7
5768.8	3.8	-0.4	-6	5.6	14	19.6
5768.7	2.1	-0.5	-6	5.5	14	19.5
5768.6	2.4	-0.7	-6	5.3	14	19.3
5768.5	4	-0.8	-6	5.2	14	19.2
5768.4	4.4	-0.9	-6	5.1	14	19.1
5768.3	0.9	-1.1	-6	4.9	14	18.9
5768.2	2.2	-1.3	-6	4.7	14	18.7
5768.1	2.6	-1.3	-6	4.7	14	18.7
5768.0	1.8	-1.5	-6	4.5	14	18.5
5767.9	2.5	-1.5	-6	4.5	14	18.5
5767.8	4.1	-1.7	-6	4.3	14	18.3
5767.7	4.1	-1.7	-6	4.3	14	18.3
5767.6	1	-1.8	-6	4.2	14	18.2
5767.5	1.9	-1.9	-6	4.1	14	18.1
5767.4	1.6	-2	-6	4	14	18
5767.3	4.4	-2	-6	4	14	18
5767.2	5	-2.2	-6	3.8	14	17.8
5767.1	4.1	-2.2	-6	3.8	14	17.8

PROCESS GAIN DATA

5775 (high end) toward low end: 5730 MHz

Unit under test: TX High

PROCESS GAIN DATA

Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5767 toward low end: 5730 MHz				Unit under test: TX High		
5767	4.4	-2.4	-6	3.6	14	17.6
5766.9	2.1	-2.5	-6	3.5	14	17.5
5766.8	1.7	-2.8	-6	3.2	14	17.2
5766.7	1.7	-2.8	-6	3.2	14	17.2
5766.6	1.6	-2.8	-6	3.2	14	17.2
5766.5	0.9	-3.2	-6	2.8	14	16.8
5766.4	1.8	-3.2	-6	2.8	14	16.8
5766.3	2.7	-3.2	-6	2.8	14	16.8
5766.2	2.4	-3.2	-6	2.8	14	16.8
5766.1	2	-3.2	-6	2.8	14	16.8
5766	1.3	-3.2	-6	2.8	14	16.6
5765.9	4	-3.4	-6	2.6	14	16.5
5765.8	4.4	-3.5	-6	2.5	14	16.3
5765.7	1.6	-3.7	-6	2.3	14	16.5
5765.6	1	-3.5	-6	2.5	14	16.2
5765.5	1.5	-3.8	-6	2.2	14	16.1
5765.4	1.3	-3.9	-6	2.1	14	16
5765.3	3.2	-3.9	-6	2.1	14	1
5765.2	1.1	-4.1	-6	1.9	14	15.9
5765.1	3.4	-4.1	-6	1.9	14	15.9
5765	1.1	-4.1	-6	1.9	14	15.9
5764.9	2.5	-4.1	-6	1.9	14	15.9
5764.8	1.3	-4.2	-6	1.8	14	15.8
5764.7	3.8	-4.3	-6	1.7	14	15.7
5764.6	1.1	-4.5	-6	1.5	14	15.5
5764.5	2.2	-4.8	-6	1.2	14	15.2
5764.4	3.7	-4.8	-6	1.2	14	15.2
5764.3	1.1	-5.3	-6	0.7	14	14.7
5764.2	1.2	-5.6	-6	0.4	14	14.6
5764.1	3.6	-5.8	-6	0.2	14	14.2
5764	1.1	-6	-6	0	14	14
5763.9	2.9	-6.3	-6	-0.3	14	13.7
5763.8	4.9	-6.3	-6	-0.3	14	13.7
5763.7	3.4	-6.3	-6	-0.3	14	13.7
5763.6	3.9	-6.3	-6	-0.3	14	13.7
5763.5	4.8	-5.8	-6	0.2	14	14.2
5763.4	4.1	-5.8	-6	0.2	14	14.2
5763.3	4.5	-5.8	-6	0.2	14	14.2
5763.2	3.6	-5.6	-6	0.4	14	14.4
5763.1	4.8	-5.5	-6	0.5	14	14.5
5763	4.5	-5.3	-6	0.7	14	14.7
5762.9	4.5	-5.3	-6	0.7	14	14.7
5762.8	4.5	-5.3	-6	0.7	14	14.7
5762.7	0.8	-5.3	-6	0.7	14	14.7

5762.6	1.5	-5.3	-6	0.7	14	14.7
5762.5	2.4	-5.3	-6	0.7	14	14.7

Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
--------------------	------------	---------------------	--------------------	-----	-----	------------------------

PROCESS GAIN DATA

5762.4 MHz toward low end: 5730 MHz

Unit under test: TX High

5762.4	4.4	-5.3	-6	0.7	14	14.7
5762.3	3.9	-5.3	-6	0.7	14	14.7
5762.2	4.3	-5.3	-6	0.7	14	14.7
5762.1	0.9	-5.4	-6	0.6	14	14.6
5762	1.5	-5.4	-6	0.6	14	14.6
5761.9	1.9	-5.4	-6	0.6	14	14.6
5761.8	1.5	-5.4	-6	0.6	14	14.6
5761.7	4.5	-5.4	-6	0.6	14	14.6
5761.6	1.3	-5.4	-6	0.6	14	14.6
5761.5	2.8	-5.4	-6	0.6	14	14.6
5761.4	2.6	-5.4	-6	0.6	14	14.6
5761.3	2.5	-5.5	-6	0.5	14	14.5
5761.2	2.9	-5.5	-6	0.5	14	14.5
5761.1	3.6	-5.6	-6	0.4	14	14.4
5761	1.7	-5.6	-6	0.4	14	14.4
5760.9	2.9	-5.6	-6	0.4	14	14.4
5760.8	1.5	-5.7	-6	0.3	14	14.3
5760.7	1.7	-5.7	-6	0.3	14	14.3
5760.6	2.5	-5.7	-6	0.3	14	14.3
5760.5	2.7	-5.7	-6	0.3	14	14.3
5760.4	2.4	-5.7	-6	0.3	14	14.3
5760.3	2	-5.7	-6	0.3	14	14.3
5760.2	2.7	-5.7	-6	0.3	14	14.3
5760.1	3.1	-5.7	-6	0.3	14	14.3
5760	1.1	-5.8	-6	0.2	14	14.2
5759.9	1.5	-5.8	-6	0.2	14	14.2
5759.8	1.1	-5.8	-6	0.2	14	14.2
5759.7	4.3	-5.8	-6	0.2	14	14.2
5759.6	1.9	-5.8	-6	0.2	14	14.2
5759.5	1.3	-5.9	-6	0.1	14	14.1
5759.4	3.5	-5.9	-6	0.1	14	14.1
5759.3	4	-5.9	-6	0.1	14	14.1
5759.2	4.7	-5.9	-6	0.1	14	14.1
5759.1	4.6	-5.9	-6	0.1	14	14.1
5759	4.1	-5.9	-6	0.1	14	14.1
5758.9	1.3	-5.9	-6	0.1	14	14.1
5758.8	3.6	-5.9	-6	0.1	14	14.1
5758.7	4.7	-5.9	-6	0.1	14	14.1
5758.6	4.4	-5.9	-6	0.1	14	14.1
5758.5	2.1	-5.9	-6	0.1	14	14.1
5758.4	4.3	-6	-6	0	14	14
5758.3	4.9	-6	-6	0	14	14

5758.2	4.9	-6	-6	0	14	14
5758.1	3.5	-6	-6	0	14	14

Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
--------------------	------------	---------------------	--------------------	-----	-----	------------------------

PROCESS GAIN DATA

5758 MHz toward low end: 5730 MHz

Unit under test: TX High

5758	3.5	-6.1	-6	-0.1	14	13.9
5757.9	2.4	-6.2	-6	-0.2	14	13.8
5757.8	2.7	-6.2	-6	-0.2	14	13.8
5757.7	2.7	-6.2	-6	-0.2	14	13.8
5757.6	1.8	-6.3	-6	-0.3	14	13.7
5757.5	4.8	-6.3	-6	-0.3	14	13.7
5757.4	3.3	-6.3	-6	-0.3	14	13.7
5757.3	4.9	-6.3	-6	-0.3	14	13.7
5757.2	4.9	-6.3	-6	-0.3	14	13.7
5757.1	4	-6.4	-6	-0.4	14	13.6
5757	4.4	-6.5	-6	-0.4	14	13.6
5756.9	1.9	-6.5	-6	-0.5	14	13.5
5756.8	2.3	-6.5	-6	-0.5	14	13.5
5756.7	2.7	-6.5	-6	-0.5	14	13.5
5756.6	3.5	-6.5	-6	-0.5	14	13.5
5756.5	2.2	-6.5	-6	-0.5	14	13.5
5756.4	4.8	-6.5	-6	-0.5	14	13.5
5756.3	3.8	-6.5	-6	-0.5	14	13.5
5756.2	4.9	-6.6	-6	-0.6	14	13.4
5756.1	2.7	-6.6	-6	-0.6	14	13.4
5756	4	-6.8	-6	-0.8	14	13.2
5755.9	4.9	-6.8	-6	-0.8	14	13.2
5755.8	4.9	-6.7	-6	-0.7	14	13.3
5755.7	4.5	-6.7	-6	-0.7	14	13.3
5755.6	1.9	-6.8	-6	-0.8	14	13.2
5755.5	4.1	-6.9	-6	-0.9	14	13.1
5755.4	2.2	-6.9	-6	-0.9	14	13.1
5755.3	4.7	-6.9	-6	-0.9	14	13.1
5755.2	2.9	-6.9	-6	-0.9	14	13.1
5755.1	1.5	-7	-6	-1	14	13
5755	2.2	-7.1	-6	-1.1	14	12.9
5754.9	2.9	-7.1	-6	-1.1	14	12.9
5754.8	3.1	-7.1	-6	-1.1	14	12.9
5754.7	4	-7.1	-6	-1.1	14	12.9
5754.6	2.5	-7.1	-6	-1.1	14	12.9
5754.5	3.7	-7	-6	-1	14	13
5754.4	3.3	-7	-6	-1	14	13
5754.3	3.1	-7	-6	-1	14	13
5754.2	3.6	-7	-6	-1	14	13
5754.1	2.6	-7	-6	-1	14	13
5754	3.9	-7	-6	-1	14	13
5753.9	2.8	-7	-6	-1	14	13
5753.8	4.9	-7	-6	-1	14	13

5753.7	1.8	-7.11	-6	-1.1	14	13
5753.6	2.9	-7.1	-6	-1.1	14	12.9
Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5753.5	4.4	-7.1	-6	-1.1	14	12.9

PROCESS GAIN DATA

5753.4 MHz toward low end: 5730 MHz

Unit under test: TX High

5753.4	3	-7.2	-6	-1.2	14	12.8
5753.3	1.5	-7.3	-6	-1.3	14	12.7
5753.2	4.3	-7.4	-6	-1.4	14	12.6
5753.1	3.5	-7.4	-6	-1.4	14	12.6
5753	3.1	-7.5	-6	-1.5	14	12.5
5752.9	1.7	-7.9	-6	-1.9	14	12.1
5752.8	2.2	-8	-6	-2	14	12
5752.7	1.9	-8.1	-6	-2.1	14	11.9
5752.6	1.8	-8.2	-6	-2.2	14	11.8
5752.5	3.3	-8.2	-6	-2.2	14	11.8
5752.4	1.8	-8.2	-6	-2.2	14	11.8
5752.3	3.5	-8.2	-6	-2.2	14	11.8
5752.2	1.1	-8.1	-6	-2.1	14	11.9
5752.1	1.6	-7.9	-6	-1.9	14	12.1
5752	4.4	-7.7	-6	-1.7	14	12.3
5751.9	1.7	-7.6	-6	-0.6	14	12.4
5751.8	2.2	-7.4	-6	-1.4	14	12.6
5751.7	4.2	-7.3	-6	-1.3	14	12.7
5751.6	4.2	-7.2	-6	-1.2	14	12.8
5751.5	4.4	-7.1	-6	-1.1	14	12.9
5751.4	1.9	-7.1	-6	-1.1	14	12.9
5751.3	3.2	-7.1	-6	-1.1	14	12.9
5751.2	1.8	-7.2	-6	-1.2	14	12.8
5751.1	3.2	-7.2	-6	-1.2	14	12.8
5751	2.2	-7.2	-6	-1.2	14	12.8
5750.9	1.1	-7.1	-6	-1.1	14	12.9
5750.8	2.8	-7.1	-6	-1.1	14	12.9
5750.7	3.4	-7.1	-6	-1.1	14	12.9
5750.6	4.4	-7.1	-6	-1.1	14	12.9
5750.5	4.4	-7.1	-6	-1.1	14	12.9
5750.4	4.9	-7.1	-6	-1.1	14	12.9
5750.3	5	-7.2	-6	-1.2	14	12.8
5750.2	4	-7.2	-6	-1.2	14	12.8
5750.1	3.2	-7.2	-6	-1.2	14	12.8
5750	3.2	-7.2	-6	-1.2	14	12.8
5749.9	1.9	-7.2	-6	-1.2	14	12.8
5749.8	1.5	-7.2	-6	-1.2	14	12.8
5749.7	1.2	-7.1	-6	-1.1	14	12.9
5749.6	3	-7.1	-6	-1.1	14	12.9
5749.5	3.7	-7.1	-6	-1.1	14	12.9
5749.4	2.9	-7.1	-6	-1.1	14	12.9
5749.3	1.4	-7.1	-6	-1.1	14	12.9

5749.2	2.2	-7.1	-6	-1.1	14	12.9
5749.1	1.3	-7.1	-6	-1.1	14	12.7
Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5749	1.3	-7.1	-6	-1.1	14	12.9
5748.9	2.6	-7	-6	-1	14	13

PROCESS GAIN DATA

5748.8 MHz toward low end: 5730 MHz

Unit under test: TX High

5748.8	1.3	-6.9	-6	-0.9	14	13.1
5748.7	2.4	-6.9	-6	-0.9	14	13.1
5748.6	1.8	-6.9	-6	-0.9	14	13.1
5748.5	2.1	-6.9	-6	-0.9	14	13.1
5748.4	0.9	-6.9	-6	-0.9	14	13.1
5748.3	1.5	-6.7	-6	-0.7	14	13.3
5748.2	2.4	-6.8	-6	-0.8	14	13.2
5748.1	0.7	-6.8	-6	-0.8	14	13.2
5748	2	-6.8	-6	-0.7	14	13.3
5747.9	2.3	-6.7	-6	-0.6	14	13.4
5747.8	4	-6.6	-6	-0.6	14	13.4
5747.7	4.2	-6.6	-6	-0.6	14	13.4
5747.6	1.8	-6.6	-6	-0.6	14	13.4
5747.5	1.5	-6.6	-6	-0.6	14	13.4
5747.4	2.6	-6.6	-6	-0.6	14	13.2
5747.3	4.2	-6.6	-6	-0.6	14	13.4
5747.2	2.1	-6.6	-6	-0.6	14	13.4
5747.1	1.7	-6.5	-6	-0.5	14	13.5
5747	3	-6.5	-6	-0.5	14	13.5
5746.9	2.2	-6.6	-6	-0.6	14	13.4
5746.8	3.2	-6.4	-6	-0.4	14	13.6
5746.7	2.4	-6.4	-6	-0.4	14	13.6
5746.6	2.7	-6.4	-6	-0.4	14	13.6
5746.5	3.8	-6.4	-6	-0.4	14	13.6
5746.4	2.4	-6.3	-6	-0.3	14	13.6
5746.3	2.1	-6.3	-6	-0.3	14	13.7
5746.2	2.6	-6.3	-6	-0.3	14	13.7
5746.1	3.7	-6.2	-6	-0.2	14	13.7
5746	3.4	-6.3	-6	-0.3	14	13.8
5745.9	1.5	-6.3	-6	-0.3	14	13.7
5745.8	3	-6.3	-6	-0.3	14	13.7
5745.7	4	-6.2	-6	-0.3	14	13.7
5745.6	3.1	-6.2	-6	-0.2	14	13.7
5745.5	3.8	-6.2	-6	-0.2	14	13.8
5745.4	1.6	-6.2	-6	-0.2	14	13.8
5745.3	3.2	-6.1	-6	-0.1	14	13.8
5745.2	4.8	-6.1	-6	-0.1	14	13.9
5745.1	2.7	-6.1	-6	-0.1	14	13.9
5745	1.9	-6.1	-6	-0.1	14	13.9
5744.9	2.9	-6.1	-6	-0.1	14	13.9
5744.8	3.8	-6.1	-6	-0.1	14	13.9

5744.7	2.4	-6.1	-6	-0.1	14	13.9
5744.6	4.2	-6.1	-6	-0.1	14	13.9
Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5744.5	1.7	-6.1	-6	-0.1	14	13.9
5744.4	3.8	-6.1	-6	-0.1	14	13.9
5744.3	0.1	-6.2	-6	-0.2	14	13.8

PROCESS GAIN DATA

5744.2 MHz toward low end: 5730 MHz

Unit under test: TX High

5744.2	2.7	-6.1	-6	-0.1	14	13.9
5744.1	4.7	-6.2	-6	-0.2	14	13.8
5744	2.8	-6.1	-6	-0.1	14	13.9
5743.9	2.3	-6	-6	0	14	14
5743.8	5.2	-6.1	-6	-0.1	14	13.9
5743.7	1.5	-6.2	-6	-0.2	14	13.8
5743.6	2.2	-6.1	-6	-0.1	14	13.9
5743.5	1.1	-6.1	-6	-0.1	14	13.9
5743.4	4.6	-6	-6	0	14	14
5743.3	2.5	-6.1	-6	-0.1	14	13.9
5743.2	2.2	-6.1	-6	-0.1	14	13.9
5743.1	1.8	-6	-6	0	14	14
5743	2.7	-5.9	-6	0.1	14	14.1
5742.9	1.9	-6	-6	0	14	14
5742.8	4.8	-5.9	-6	0.1	14	14.1
5742.7	4.8	-6	-6	0	14	14
5742.6	4	-6	-6	0	14	14
5742.5	4.9	-6	-6	0	14	14
5742.4	2.2	-6	-6	0	14	14
5742.3	2.3	-5.9	-6	0.1	14	14.1
5742.2	2.1	-5.9	-6	0.1	14	14.1
5742.1	3.7	-5.9	-6	0.1	14	14.1
5742	3.6	-6	-6	0	14	14
5741.9	4.2	-6	-6	0	14	14
5741.8	4	-6.2	-6	-0.2	14	13.8
5741.7	4.9	-6.2	-6	-0.2	14	13.8
5741.6	3.4	-6.4	-6	-0.4	14	13.6
5741.5	4.8	-6.6	-6	-0.6	14	13.4
5741.4	3.7	-6.8	-6	-0.8	14	13.2
5741.3	5.3	-7	-6	-1	14	13
5741.2	4.9	-7.1	-6	-1.1	14	12.9
5741.1	1.6	-7.1	-6	-1.1	14	12.9
5741	2.9	-7.1	-6	-1.1	14	12.9
5740.9	0.9	-7	-6	-1	14	13
5740.8	0.9	-6.9	-6	-0.9	14	13.1
5740.7	1.1	-6.5	-6	-0.5	14	13.5
5740.6	1.1	-6.4	-6	-0.4	14	13.6
5740.5	3.8	-6.2	-6	-0.2	14	13.8
5740.4	1.1	-6	-6	0	14	14
5740.3	1.4	-5.5	-6	0.5	14	14.5

5740.2	3.5	-5.3	-6	0.7	14	14.7
5740.1	3.1	-5.1	-6	0.9	14	14.9
Frequency [MHZ]	BER x 1E-5	Jamming Power, J	Signal Power, S	J/S	S/N	Processing Gain, Gp
5740	3.2	-5	-6	1	14	15
5739.9	3.1	-5	-6	1	14	15
5739.8	4.5	-4.9	-6	1.1	14	15.1
5739.7	4.8	-5	-6	1	14	15

PROCESS GAIN DATA

5739.6 MHz toward low end: 5730 MHz

Unit under test: TX High

5739.6	2.1	-5	-6	1	14	15
5739.5	1.6	-4.9	-6	1.1	14	15.1
5739.4	1.5	-4.8	-6	1.2	14	15.2
5739.3	1.6	-4.7	-6	1.3	14	15.3
5739.2	1.1	-4.6	-6	1.4	14	15.4
5739.1	1.7	-4.5	-6	1.5	14	15.5
5739	0.9	-4.5	-6	1.5	14	15.5
5738.9	2	-4.4	-6	1.6	14	15.6
5738.8	4.9	-4.2	-6	1.8	14	15.8
5738.7	3.4	-4	-6	2	14	16
5738.6	3.3	-4	-6	2	14	16
5738.5	4.1	-3.9	-6	2.1	14	16.1
5738.4	1.4	-0.9	-6	2.1	14	16.1
5738.3	0.9	-3.8	-6	2.2	14	16.2
5738.2	3.8	-3.8	-6	2.2	14	16.2
5738.1	3.7	-3.8	-6	2.2	14	16.2
5738	4.1	-3.7	-6	2.3	14	16.3
5737.9	1.1	-3.7	-6	2.3	14	16.3
5737.8	0.9	-3.6	-6	2.4	14	16.4
5737.7	0.9	-3.5	-6	2.5	14	16.5
5737.6	1.9	-3.3	-6	2.7	14	16.7
5737.5	3.5	-3.2	-6	2.8	14	16.8
5737.4	2.8	-3.1	-6	2.9	14	16.9
5737.3	1.9	-3	-6	3	14	17
5737.2	3	-2.9	-6	3.1	14	17.1
5737.1	1.1	-2.9	-6	3.2	14	17.2
5737	1.1	-2.9	-6	3.2	14	17.2
5736.9	0.9	-2.8	-6	3.3	14	17.3
5736.8	3.4	-2.6	-6	3.4	14	17.4
5736.7	3	-2.6	-6	3.4	14	17.4
5736.6	0.8	-2.4	-6	3.6	14	17.6
5736.5	3.8	-2.2	-6	3.8	14	17.8
5736.4	3.5	-2.1	-6	3.9	14	17.9
5736.3	3	-2.1	-6	3.9	14	17.9
5736.2	1.4	-1.9	-6	4.1	14	18.1
5736.1	0.9	-1.8	-6	4.2	14	18.2
5736	1.8	-1.7	-6	4.3	14	18.3
5735.9	1	-1.6	-6	4.4	14	18.4
5735.8	3.7	-1.3	-6	4.7	14	18.7

