

EMCJ

EMC Japan Corp.

TEST REPORT

ORDER No. : 98122350(B)

DATE : Dec. 8, 1998

CUSTOMER : Advanced Peripherals Technologies, Inc

EMC J a p a n C o r p o r a t i o n

EMC TEST REPORT

Test Order NO. : 98122350(B)

Dec. 8, 1998

1. APPLICANT

• Company name : Advanced Peripherals Technologies, Inc
• Address : 1031 Fujisawa Fujisawa-shi, Kanagawa
251-0052 Japan
Phone: 0466-28-3115

2. EQUIPMENT UNDER TEST (E. U. T.)

• Device Name : Dot Matrix Printer
• Model Number : T2030/9
• Serial Number : 3802727

3. SUMMARY OF TEST RESULTS

Emission test item	Basic standard	Result
RADIATED EMISSION MEASUREMENTS	FCC Part15 Subpart B Class B:1996	Complies
CONDUCTED POWER LINE MEASUREMENT	FCC Part15 Subpart B Class B:1996	Complies

4. DATE OF TEST

• Test Item received : Dec. 3, 1998
• Test Completed on : Dec. 4, 1998

• Test Performed by : T. Nomura Date : Dec. 3, 1998
• Test Report Made by : J. Suzuki Date : Dec. 8, 1998
• Test Report Approved by : [Signature] Date : Dec. 8, 1998

5. TEST PLACE

• Place : EMC Japan Corporation TSUKUI TEST SITE NO. 2
• Address : 1686-4 Nagatake, Tsukui-Machi
Kanagawa, 220-0204 Japan

This report shall not be reproduced, except in full without the written approval of EMC Japan.
The results in this report apply only to the sample tested.

EQUIPMENT

No.	Equipment	Manufacturer	Model No.	Serial No.	Note
1	Dot Matrix Printer	TSE	T2030/9	3802727	EUT FCC ID:M36M96004
2	Personal Computer	IBM(JAPAN)	TYPE 8573-121	99-2501038	HOST PC FCC ID:ACJ9TG8573C
3	Auto Sheet Feeder	TSE	SF2030	——	EUT OPTION
4	RS-232C I/F	TSE	044828	——	EUT OPTION

USED CABLE

No.	Cable Name	Manufacturer	Length (m)	Bundled Length	Shield	Core	Note
a	I/F Cable	——	1.9 m	——	yes	none	PC $\longleftrightarrow$ EUT PARALLEL
b	Serial I/F Cable	——	2.0 m	0.5 m	none	none	
c	Power Cable (961125/3)	VOLEX(Asia) PTE, LTD	1.9 m	——	none	none	EUT
d	Power Cable (PS-2 P7 ϕ 386)	IBM	3.2 m	——	none	yes	HOST PC

RADIATED EMISSION
FCC Part15 Subpart B Class B:1996

List of measurement equipment

ITEM	MANUFACTURER	MODEL	Serial No.
TEST RECEIVER	ROHDE SCHWARZ	ESV	892371/006
RF PRE AMP	HEWLETT PACKARD	8449B	3008A00791
SPECTRUM ANALIZER	HEWLETT PACKARD	8562B	2923A 00418
TEST RECEIVER	ROHDE SCHWARZ	ESH2	892237/016
SPECTRUM ANALIZER	HEWLETT PACKARD	8564E	3650A00686
CAL. DIPOLE ANTENNA	SCHWARZBECK	VHAP	450/451
CAL. DIPOLE ANTENNA	SCHWARZBECK	UHAP	429/430
DIPOLE ANTENNA	SCHWARZBECK	VHA9103	none
DIPOLE ANTENNA	SCHWARZBECK	UHA9105	none
BICONICAL ANTENNA	SCHWARZBECK	BBA9106	none
LOG-PERI ANTENNA	SCHWARZBECK	UHALP9107	none
LISN	ROHDE SCHWARZ	ESH2-Z5	893606/003
LOOP ANTENNA	ROHDE SCHWARZ	HFH2-Z2	893.103/003
HORN ANTENNA	SCHWARZBECK	BBHA 9120-B	121
HORN ANTENNA	SCHWARZBECK	BBHA 9120-B	122
HORN ANTENNA	EMCO (CMT)	3160-07	9603-1048
HORN ANTENNA	EMCO (CMT)	3160-08	9508-1035
HORN ANTENNA	EMCO (CMT)	3160-09	9707-1086
HORN ANTENNA	EMCO (CMT)	3160-10	9704-1051

This report shall not be reproduced, except in full without the written approval of EMC Japan.
The results in this report apply only to the sample tested.

T e s t P l a n

DATE:Dec. 3, 1998	Condition: 10℃ 65%
The size of EUT	(506(W) × 272(H) × 206(D)mm) 8.0 kg
Representative operating conditions of the EUT	PRINT MODE
Disposition	Table Top, above the ground plane 0.8m
The type of test facility	Open site
The position of the receiving antenna	Height 1-4m at 3 meters distance from the EUT
The type of antenna to be used	Biconical(BBA9106), Log-Peri(UHALP9107)
Test frequency	30MHz-1000MHz
The performance criteria which are acceptable	EUT Complies with Limits of FCC Part15 Subpart B Class B:1996
Power Supply	A. C. 120V 60Hz

This report shall not be reproduced, except in full without the written approval of EMC Japan.
The results in this report apply only to the sample tested.

EMCJ

EMC Japan Corp.

Order No.98122350(B) Page 7 of 16

FCC Part15 Subpart B Class B:1996

RADIATED EMISSION TEST RESULTS

COMPANY : APTi
 MODEL NAME : Dot Matrix Printer
 MODEL NO. : T2030/9
 POWER : A. C. 120V 60Hz
 :
 TEMP : 10°C 65%
 DESCRIPTION : Sr. No. 3802727
 :

REPORT NO. : 98122350(B)
 STANDARD : FCC PART 15
 CLASS : B
 DISTANCE : 3m
 TEST MODE : PRINT MODE
 ENGINEER : T. NOMURA

LIMIT1 : FCC Part15 Subpart.B Class B (3m)
 LIMIT2 :

	FREQUENCY [MHz]	METER READING		FACTOR [dB]	FIELD STRENGTH		LIMITS [dBuV/m]	MARGIN		MEMO
		VER. [dBuV]	HOR. [dBuV]		VER. [dBuV/m]	HOR. [dBuV/m]		VER. [dBuV/m]	HOR. [dBuV/m]	
1	30.000	26.2	26.2	-7.1	19.1	19.1	40.0	20.9	20.9	NOISE LEVEL BROAD NOISE
2	58.270	44.1		-16.8	27.3		40.0	12.7		
3	65.340		39.3	-17.8		21.5	40.0		18.5	
4	72.890	45.7	44.6	-18.3	27.4	26.3	40.0	12.6	13.7	
5	85.450	48.9	45.5	-18.1	30.8	27.4	40.0	9.2	12.6	
6	100.530	45.5	42.9	-13.6	31.9	29.3	43.5	11.6	14.2	
7	113.100	43.9	42.4	-11.9	32.0	30.5	43.5	11.5	13.0	
8	123.150	41.4	41.5	-10.6	30.8	30.9	43.5	12.7	12.6	
9	223.680	37.4	39.2	-5.3	32.1	33.9	46.0	13.9	12.1	
10	231.210	37.6	41.2	-5.1	32.5	36.1	46.0	13.5	9.9	
11	243.780	37.6	39.8	-4.6	33.0	35.2	46.0	13.0	10.8	
12	319.170	34.5	43.1	-5.9	28.6	37.2	46.0	17.4	8.8	
13	321.670	34.6	39.5	-5.8	28.8	33.7	46.0	17.2	12.3	
14	1000.000	23.1	23.1	6.2	29.3	29.3	54.0	24.7	24.7	NOISE LEVEL

1998/12/03

No. 2 TEST SITE


EMC JAPAN Corporation

REPORT NO. : 98122350 (B)
STANDARD : FCC PART 15
CLASS : B
DISTANCE : 3m
TEST MODE : PRINT MODE
ENGINEER : T. NOMURA

COMPANY : APTi
MODEL NAME : Dot Matrix Printer
MODEL NO. : T2030/9
POWER : A.C. 120V 60Hz
TEMP : 10°C 65%
DESCRIPTION : Sr. No. 3802727

LIMIT1 : — : FCC Part15 Subpart. B Class B (3m)
LIMIT2 : —

VER. : • HOR. : •



EMCJ

EMC Japan Corp.

Order No.98122350(B) Page 10 of 16

CONDUCTED POWER LINE

FCC Part15 Subpart B Class B:1996

List of measurement equipment

ITEM	MANUFACTURER	MODEL	Serial No.
TEST RECEIVER	ROHDE SCHWARZ	ESH2	892237/016
SPECTRUM ANALIZER	HEWLETT PACKARD	8562B	2923A 00418
LISN	ROHDE SCHWARZ	ESH3-Z6 ESH3-Z6	844950/0024 837172/017

This report shall not be reproduced, except in full without the written approval of EMC Japan.
The results in this report apply only to the sample tested.

T e s t P l a n

DATE:Dec. 3, 1998	Condition: 22℃ 45%
The size of EUT	(506(W) × 272(H) × 206(D)mm) 8.0 kg
Representative operating conditions of the EUT	PRINT MODE
Disposition	Table Top, above the ground plane 0.8m
The type of test facility	Shield Room
Test frequency	450kHz-30MHz
The performance criteria which are acceptable	EUT Complies with Limits of FCC Part15 Subpart B Class B:1996
Power Supply	A. C. 120V 60Hz

This report shall not be reproduced, except in full without the written approval of EMC Japan.
The results in this report apply only to the sample tested.



EMC Japan Corp.

FCC Part15 Subpart B Class B:1996

CONDUCTED POWER LINE TEST RESULTS

EMCJ

Report No. : 98122350(B)

EMC Japan Corp.

Results of Conducted Power Line Measurements. : Quasi Peak

Measuring Method : FCC 15 Sub.B Class B:1996.

N / L1 : Measured Value

EUT : Dot Matrix Printer

Model : T2030/9

Serial No. : 3802727

Test Mode : PRINT MODE

Description : A.C.120V 60Hz

Temp. : 22°C

*** Remarks ***

FCC ID:M36M96004

Frequency (MHz)	RFI Voltage (dBuV)		Limit (dBuV)	Margin (dBuV)
	N	L1		
0.450	36.6	37.2	48.0	10.8
0.491	36.9	37.6	48.0	10.4
12.063	27.6	27.6	48.0	20.4
18.094	37.4	37.2	48.0	10.6
24.124	33.1	32.4	48.0	14.9
27.141	32.5	31.8	48.0	15.5
30.000	15.1	14.3	48.0	32.9

Conclusion : EUT Complies With Limits
of FCC 15 Sub.B Class B:1996.

Results of Conducted Power Line Measurements.

Measuring Method : FCC 15 Sub.B Class B: 1996.

Report No. : 98122350 (B)

EUT : Dot Matrix Printer
Model : T2030/9
Serial No. : 3802727
Test Mode : PRINT MODE

---: Limit Line
x : Measured Value (N)
o : Measured Value (L1)

