



The University of Michigan
Radiation Laboratory
3228 EECS Building
Ann Arbor, MI 48109-2122
Tel: (734) 764-0500

Measured Radio Frequency Emissions
From

Siemens Transmitter
Model(s): 5WY7748, 5WY7749, 5WY7757,
5WY7758, 5WY7777, 5WY7778

Report No. 415031-277
March 7, 2006

Copyright © 2006

For:
Siemens VDO Automotive
4685 Investment Drive
Troy, MI 48098

Contact:
Charles Muma
Tel: 248 763 6783
Fax: 248 764 7183
PO: Verbal

Measurements made by:

Valdis V. Liepa

Tests supervised by:
Report approved by:

Valdis V. Liepa
Valdis V. Liepa
Research Scientist

Summary

Tests for compliance with FCC Regulations Part 15, Subpart C, and Industry Canada RSS-210, were performed on Siemens model(s) 5WY7748, 5WY7749, 5WY7757, 5WY7758, 5WY7777, 5WY7778. This device is subject to the Rules and Regulations as a Transmitter.

In testing completed on February 3, 2006, the device tested in the worst case met the allowed FCC specifications for radiated emissions by 0.5 dB (see p. 6-7). Besides harmonics, there were no other significant spurious emissions found; emissions from digital circuitry were negligible. The conducted emission tests do not apply, since the device is powered from a 3 V dc battery.

1. Introduction

Siemens models 5WY7748, 5WY7749, 5WY7757, 5WY7758, 5WY7777, 5WY7778 were tested for compliance with FCC Regulations, Part 15, adopted under Docket 87-389, April 18, 1989, and with Industry Canada RSS-210/Gen, Issue 6, September 2005. The tests were performed at the University of Michigan Radiation Laboratory Willow Run Test Range following the procedures described in ANSI C63.4-2003 "Methods of Measurement of Radio-Noise Emissions from Low-Voltage Electrical and Electronic Equipment in the Range of 9 kHz to 40 GHz". The Site description and attenuation characteristics of the Open Site facility are on file with FCC Laboratory, Columbia, Maryland (FCC Reg. No: 91050) and with Industry Canada, Ottawa, ON (File Ref. No: IC 2057).

2. Test Procedure and Equipment Used

The pertinent test equipment commonly used in our facility for measurements is listed in Table 2.1 below. The middle column identifies the specific equipment used in these tests.

Table 2.1 Test Equipment.

Test Instrument	Eqpt. Used	Manufacturer/Model
Spectrum Analyzer (0.1-1500 MHz)		Hewlett-Packard, 182T/8558B
Spectrum Analyzer (9kHz-22GHz)	X	Hewlett-Packard 8593A SN: 3107A01358
Spectrum Analyzer (9kHz-26GHz)	X	Hewlett-Packard 8593E, SN: 3412A01131
Spectrum Analyzer (9kHz-26GHz)		Hewlett-Packard 8563E, SN: 3310A01174
Spectrum Analyzer (9kHz-40GHz)		Hewlett-Packard 8564E, SN: 3745A01031
Power Meter		Hewlett-Packard, 432A
Power Meter		Anritsu, ML4803A/MP
Harmonic Mixer (26-40 GHz)		Hewlett-Packard 11970A, SN: 3003A08327
Harmonic Mixer (40-60 GHz)		Hewlett-Packard 11970U, SN: 2332A00500
Harmonic Mixer (75-110 GHz)		Hewlett-Packard 11970W, SN: 2521A00179
Harmonic Mixer (140-220 GHz)		Pacific Millimeter Prod., GMA, SN: 26
S-Band Std. Gain Horn		S/A, Model SGH-2.6
C-Band Std. Gain Horn		University of Michigan, NRL design
XN-Band Std. Gain Horn		University of Michigan, NRL design
X-Band Std. Gain Horn		S/A, Model 12-8.2
X-band horn (8.2- 12.4 GHz)		Narda 640
X-band horn (8.2- 12.4 GHz)		Scientific Atlanta , 12-8.2, SN: 730
K-band horn (18-26.5 GHz)		FXR, Inc., K638KF
Ka-band horn (26.5-40 GHz)		FXR, Inc., U638A
U-band horn (40-60 GHz)		Custom Microwave, HO19
W-band horn(75-110 GHz)		Custom Microwave, HO10
G-band horn (140-220 GHz)		Custom Microwave, HO5R
Bicone Antenna (30-250 MHz)	X	University of Michigan, RLBC-1
Bicone Antenna (200-1000 MHz)	X	University of Michigan, RLBC-2
Dipole Antenna Set (30-1000 MHz)	X	University of Michigan, RLDP-1,-2,-3
Dipole Antenna Set (30-1000 MHz)		EMCO 2131C, SN: 992
Active Rod Antenna (30 Hz-50 MHz)		EMCO 3301B, SN: 3223
Active Loop Antenna (30 Hz-50 MHz)		EMCO 6502, SN:2855
Ridge-horn Antenna (300-5000 MHz)	X	University of Michigan
Amplifier (5-1000 MHz)	X	Avantek, A11-1, A25-1S
Amplifier (5-4500 MHz)	X	Avantek
Amplifier (4.5-13 GHz)		Avantek, AFT-12665
Amplifier (6-16 GHz)		Trek
Amplifier (16-26 GHz)		Avantek
LISN Box		University of Michigan
Signal Generator		Hewlett-Packard 8657B

3. Configuration and Identification of Device Under Test

The DUT is a 315 MHz transmitter, 1.5 x 0.25 x 1 inches in size. The device is capable of transmitting three different protocols. One protocol is used for Remote Start functionality in the vehicle, the second protocol is used for standard Remote Keyless Entry (RKE), and the final protocol is used for Passive Keyless Entry (PKE). The PKE protocol is a shortened version of the RKE protocol. The DUT transmits only ASK data and its carrier is PLL generated, sourced from a 9.04 MHz reference crystal. The antenna is a trace on the PCB.

The DUT was designed and manufactured by Siemens VDO Automotive, 4685 Investment Drive, Troy, MI 48098. It is identified as:

Siemens VDO Automotive Transmitter
Model(s): 5WY7748, 5WY7749, 5WY7757, 5WY7758, 5WY7777, 5WY7778
FCC ID: M3N5WY7777
IC: 267F-5WY7777

All six variants are electronically identical; differences are in packaging. There are four button and five button housings, two types of emblems, and two labels (laser etched) which help the customer differentiate between key #1 and key #2. See labeling exhibit for details. Most populated device was fully tested.

The device may be actuated from either a button press or an LF interrogation from a matching vehicle. The LF interrogation is initiated by the user, Manchester encoded, and the RF response to this actuation (PKE protocol) is a foreshortened version of the RKE mode. Note: In all modes, the device ceases to transmit within 5 seconds of deactivation (see Figure 6.4).

3.1 Modifications Made

There were no modifications made to the DUT by this laboratory.

4. Emission Limits

The DUT tested falls under the category of an Intentional Radiators and the Digital Devices. For FCC, it is subject to Part 15, Subpart C, (Section 15.231), Subpart B, (Section 15.109), and Subpart A, (Section 15.33). For Industry Canada it is subject to RSS-210, (Section 2.6 and 2.7). The applicable testing frequencies with corresponding emission limits are given in Tables 4.1 and 4.2 below. As a digital device, the DUT is considered as a Class B device.

4.1 Radiated Emission Limits

Table 4.1. Radiated Emission Limits (FCC: 15.33, 15.35, 15.109; IC: RSS-210, 2.7 Table 2).
(Digital Class B)

Freq. (MHz)	E_{lim} (3m) μ V/m	E_{lim} dB(μ V/m)
30-88	100	40.0
88-216	150	43.5
216-960	200	46.0
960-2000	500	54.0

Note: Average readings apply above 1000 MHz (1 MHz BW)
Quasi-Peak readings apply to 1000 MHz (120 kHz BW)

Table 4.2. Radiated Emission Limits (FCC: 15.231(b), 15.205(a); IC: RSS-210; 2.7 Table 1).
 (Transmitter)

Frequency (MHz)	Fundamental		Spurious**	
	Ave. E _{lim} (3m) (μ V/m)	dB (μ V/m)	Ave. E _{lim} (3m) (μ V/m)	dB (μ V/m)
260.0-470.0	3750-12500*		375-1250	
322-335.4	Restricted Bands		200	46.0
399.9-410				
608-614				
960-1240/1427(IC)	Restricted Bands		500	54.0
1300-1427				
1435-1626.5				
1645.5-1646.5 (IC)				
1660-1710				
1718.9-1722.2				
2200-2300				

* Linear interpolation, formula: $E = -7083 + 41.67*f$ (MHz)

** Measure up to tenth harmonic; 120 kHz BW up to 1 GHz, 1 MHz BW above 1 GHz

4.3 Conducted Emissions Limits

The conductive emission limits and tests do not apply here, since the DUT is powered by a 3 V dc battery.

4.4 Supply Voltage Variation (FCC 15.31(e))

For intentional radiators, measurements of the variation of the input power or the radiated signal level of the fundamental frequency component of the emission, as appropriate, shall be performed with the supply voltage varied between 85% and 115% of the nominal rated supply voltage. For battery operated equipment, the equipment tests shall be performed using a new battery.

5. Radiated Emission Tests and Results

5.1 Semi-Anechoic Chamber Measurements

To familiarize with the radiated emission behavior of the DUT, the DUT was first studied and measured in a shielded anechoic chamber. In the chamber there is a set-up similar to that of an outdoor 3-meter site, with a turntable, an antenna mast, and a ground plane. Instrumentation includes spectrum analyzers and other equipment as needed.

In testing for radiated emissions, the transmitter was activated using the lock/unlock button with a special wooden clamp for repeated pulse emissions. It was placed on the test table flat, on its side, or on its end.

In the chamber we studied and recorded all the emissions using a Bicone antenna up to 300 MHz and a ridged horn antenna above 200 MHz. The measurements made in the chamber below 1 GHz are used for pre-test evaluation only. The measurements made above 1 GHz are used in pre-test evaluation and in the final compliance assessment. We note that for the horn antenna, the antenna pattern is more directive and hence the measurement is essentially that of free space (no ground reflection). Consequently it is not essential to measure the DUT for both antenna polarizations, as long as the DUT is

measured on all three of its major axis. In the chamber we also recorded the spectrum and modulation characteristics of the carrier. These data are presented in subsequent sections. We also note that in scanning from 30 MHz to 4.5 GHz using Bicone and the ridge horn antennas, there were no other significant spurious emissions observed.

5.2 Open Site Radiated Emission Tests

After the chamber measurements, the emissions were re-measured on the outdoor 3-meter site at fundamental and harmonics up to 1 GHz using tuned dipoles and/or the high frequency Bicone. Photographs included show the DUT on the Open Area Test Site (OATS).

5.3 Computations and Results for Radiated Emissions

To convert the dBm's measured on the spectrum analyzer to dB(μ V/m), we use expression

$$E_3(\text{dB}\mu\text{V/m}) = 107 + P_R + K_A - K_G$$

where P_R = power recorded on spectrum analyzer, dB, measured at 3m

K_A = antenna factor, dB/m

K_G = pre-amplifier gain, including cable loss, dB

When presenting the data, at each frequency the highest measured emission under all of the possible orientations is given. Computations and results are given in Table 5.1. There we see that the DUT meets the limit by 0.5 dB.

5.4 Conducted Emission Tests

These tests do not apply, since the DUT is powered from a 3 V dc battery.

6. Other Measurements

6.1 Correction for Pulse Operation

When the transmitter is activated by push action, it transmits in one of two modes. When the standard Remote Keyless Entry (RKE) buttons are depressed, a minimum of four Manchester encoded words are transmitted. In any given 100 ms window one 47 ms word is encountered with an on time of 54 μ s / 1.035 ms. If the Remote Start (RS) button is pressed, a minimum of six Manchester encoded words are transmitted. As before, one 36.75 ms word is encountered in any 100 ms window with an on time of 54 μ s / 1.035 ms. When LF actuated, the device will respond with two short 6.29 ms words 45.0 ms apart. Each 6.29 ms word is modulated with the same Manchester encoding discussed above with an output power equal to that of the standard RKE mode. See Figure 6.1 for example plots. The duty factor for each protocol is as follows

$$K_{E_RKE} = (47 \text{ ms} / 100 \text{ ms}) \times (54.0 \mu\text{s} / 103.5 \mu\text{s}) = 0.245 \text{ or } -12.2 \text{ dB}$$

$$K_{E_RS} = (36.75 \text{ ms} / 100 \text{ ms}) \times (54.0 \mu\text{s} / 103.5 \mu\text{s}) = 0.192 \text{ or } -14.3 \text{ dB}$$

$$K_{E_LF} = (2 \times 6.29 \text{ ms} / 100 \text{ ms}) \times (54.0 \mu\text{s} / 103.5 \mu\text{s}) = 0.066 < -20.0 \text{ dB}$$

6.2 Emission Spectrum

Using the ridge-horn antenna and DUT placed in its aperture, emission spectrum was recorded and is shown in Figure 6.2.

6.3 Bandwidth of the Emission Spectrum

The measured spectrum of the signal is shown in Figure 6.3. The allowed (-20 dB) bandwidth is 0.25% of 315 MHz, or 787.25 kHz. From the plot we see that the maximum -20 dB bandwidth is 148.0 kHz, and the center frequency is 315 MHz.

6.4 Effect of Supply Voltage Variation

The DUT has been designed to be powered by 3 V dc battery. For this test, the battery was replaced by a laboratory variable power supply. Relative power radiated was measured at the fundamental as the voltage was varied from 2.3 to 3.5 volts. The emission variation is shown in Figure 6.4.

6.5 Input Voltage at Battery Terminals

Batteries:	before testing	$V_{oc} = 3.2 \text{ V (new)}$
	after testing	$V_{oc} = 3.0 \text{ V}$
Ave. current from batteries		$I = 15.2 \text{ mA (CW)}$

Table 5.1 Highest Emissions Measured

Radiated Emission - RF										Siemens, RKE, FCC/IC	
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dB μ V/m	E3lim dB μ V/m	Pass dB	Comments
1	5 Button RKE										
2	315.0	Dip	H	-16.2	Pk	18.6	22.5	74.7	75.6	0.9	flat
3	315.0	Dip	V	-19.5	Pk	18.6	22.5	71.4	75.6	4.2	side
4	630.0	Dip	H	-56.3	Pk	24.4	19.4	43.4	55.6	12.2	flat
5	630.0	Dip	V	-55.4	Pk	24.4	19.4	44.3	55.6	11.3	end
6	945.0	Dip	H	-75.0	Pk	28.8	17.5	31.1	55.6	24.5	flat
7	945.0	Dip	V	-74.3	Pk	28.8	17.5	31.8	55.6	23.8	end
8	1260.0	Horn	H	-54.2	Pk	20.6	28.0	33.2	54.0	20.8	flat
9	1575.0	Horn	H	-39.8	Pk	21.5	28.0	48.5	54.0	5.5	flat
10	1890.0	Horn	H	-53.1	Pk	22.2	28.0	35.9	55.6	19.7	side
11	2205.0	Horn	H	-50.2	Pk	23.0	28.1	39.5	54.0	14.5	side
12	2520.0	Horn	H	-56.3	Pk	23.9	28.3	34.1	55.6	21.6	flat
13	2835.0	Horn	H	-52.8	Pk	24.8	28.2	38.6	54.0	15.4	side
14	3150.0	Horn	H	-52.4	Pk	25.8	27.9	40.3	55.6	15.3	side
15											
16	4 Button RKE										
17	315.0	Dip	H	-15.8	Pk	18.6	22.5	75.1	75.6	0.5	flat
18											
19											
20	* Includes 12.2 dB duty factor										
21											
22											
23											
24	Digital emissions more than 20 dB below FCC/IC Class B Limit.										
25											
26											
27											

Conducted Emissions							
#	Freq. MHz	Line Side	Det. Used	Vtest dB μ V	Vlim dB μ V	Pass dB	Comments
Not applicable							

Meas. 02/03/2006; U of Mich.

Table 5.1 Highest Emissions Measured

Radiated Emission - RF											Siemens, RS, FCC/IC
#	Freq. MHz	Ant. Used	Ant. Pol.	Pr dBm	Det. Used	Ka dB/m	Kg dB	E3* dB μ V/m	E3lim dB μ V/m	Pass dB	Comments
1	315.0	Dip	H	-14.0	Pk	18.6	22.5	74.8	75.6	0.8	flat
2	315.0	Dip	V	-17.1	Pk	18.6	22.5	71.7	75.6	3.9	side
3	630.0	Dip	H	-52.8	Pk	24.4	19.4	44.8	55.6	10.8	flat
4	630.0	Dip	V	-52.1	Pk	24.4	19.4	45.5	55.6	10.1	end
5	945.0	Dip	H	-67.7	Pk	28.8	17.5	36.3	55.6	19.3	flat
6	945.0	Dip	V	-69.6	Pk	28.8	17.5	34.4	55.6	21.2	end
7	1260.0	Horn	H	-44.5	Pk	20.6	28.0	40.8	54.0	13.2	flat
8	1575.0	Horn	H	-38.5	Pk	21.5	28.0	47.7	54.0	6.3	flat
9	1890.0	Horn	H	-42.7	Pk	22.2	28.0	44.2	55.6	11.4	side
10	2205.0	Horn	H	-54.0	Pk	23.0	28.1	33.6	54.0	20.4	side
11	2520.0	Horn	H	-49.6	Pk	23.9	28.3	38.7	55.6	17.0	flat
12	2835.0	Horn	H	-58.9	Pk	24.8	28.2	30.4	54.0	23.6	side
13	3150.0	Horn	H	-49.9	Pk	25.8	27.9	40.7	55.6	14.9	side
14											
15											
16											
17											
18											* Includes 14.3 dB duty factor
19											
20											
21											
22											Digital emissions more than 20 dB below FCC/IC Class B Limit.
23											
24											
25											
26											
27											

Conducted Emissions							
#	Freq. MHz	Line Side	Det. Used	Vtest dB μ V	Vlim dB μ V	Pass dB	Comments
							Not applicable

Meas. 02/03/2006; U of Mich.




Figure 6.1(a). Transmissions modulation characteristics (RKE mode): (top) complete transmission, (center) expanded bit, (bottom) expanded period.

University of Michigan Radiation Laboratory
FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-277




Figure 6.1(b). Transmissions modulation characteristics (RS mode): (top) complete transmission, (center) expanded bit, (bottom) expanded period.

University of Michigan Radiation Laboratory
FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-277





Figure 6.1(c). Transmissions modulation characteristics (LF Actuation): (top) complete transmission, (center) expanded bit, (bottom) expanded period.





Figure 6.2.

Emission spectrum of the DUT (pulsed emission).
The amplitudes are only indicative (not calibrated).
(top) RKE, (bottom) RS





Figure 6.3. Measured bandwidth of the DUT (pulsed emission).
(top) RKE, (bottom) RS

University of Michigan Radiation Laboratory
FCC Part 15, IC RSS-210/Gen - Test Report No. 415031-277




Figure 6.4. Transmitter 5 sec. transmission limit verification (RKE and RS)





Figure 6.5. Relative emission at 315.0 MHz vs. supply voltage. (cw emission).



DUT on OATS



DUT on OATS (close-up)