

General Description

The 09 CKF fob system consists of a RF transmitter integrated into the key and a RF receiver mounted within the control unit. The transmitter is used to transmit information to the receiver for locking, unlocking, opening the trunk, starting the vehicle, and Panic function. RF messages can be transmitted by one of two means. The keypad on the key can be used for locking, unlocking, unlocking the trunk, panic, and remote start (5 button version). Lifting the door handle or pushing the start button in the vehicle will generate a LF field, which the key will respond to with a RF transmission to unlock or start the vehicle.

Variants

There are eight variants of the 215/245/295/322 keys. These variants are described under the device ID section. All variants are electronically identical. The differences are in the packaging. There is a four button housing, and a five button housing as well as two types of emblems. There are also two types of labels (laser etch) which help the customer differentiate between key #1 and key #2.

Device ID

MLFB	Customer part #	Description
5WY8445	25926473	215 4 button TX #1
5WY8446	25926474	215 4 button TX #2
5WY8439	25926479	245 4 button TX #1
5WY8440	25926480	245 4 button TX #2
5WY8419	25943676	295/322 5 button TX #1
5WY8420	25943677	295/322 5 button TX #2
5WY8417	25946298	322 4 button TX #1
5WY8418	25946299	322 4 button TX #2