



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 1 of 64



TEST REPORT

Product Name : IEEE 802.11g 54Mbps Wireless Router

Model Number : XG-2000

Applicant : Z-COM, INC.

Address : 7F-2, NO. 9, PROSPERITY 1 ROAD., SCIENCE-BASED
INDUSTRIAL PARK, HSINCHU, TAIWAN, R.O.C.

Received Date : Jul. 24, 2003

Tested Date : Jul. 24~Aug. 25, 2003

Notes :

1. This report will be invalid if duplicated or photocopied in part.
2. This report refers only to the specimen(s) submitted to testing, and be invalid as seperately used.
3. This report is invalid without examination stamp and signature of this institute.
4. The tested specimen(s) will be preserved for thirty days from the data issued.
5. The report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government.



**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 2 of 64

Test Report Certification

Product Name : IEEE 802.11g 54Mbps Wireless Router**Model Number** : XG-2000**Applicant** : Z-COM, INC.**Measurement Standard :**

47 CFR Part 15, Subpart B and Subpart C (Section 15.247),
ANSI C63.4-2001

Tested By : Alan Fan , Date : (Aug. 25, 2003)
(Alan Fan)

Reviewed By : Roger Sheng , Date : (Aug. 25, 2003)
(Roger Sheng)

Approved By : Chieh-De Tsai , Date : (Aug. 25, 2003)
(Chieh-De Tsai ,Manager)



WE HEREBY CERTIFY THAT: The measurements shown in the attachment were made in accordance with the procedures indicated, and the energy emitted by the equipment was found to be within the limits applicable. We assume full responsibility for the accuracy and completeness of these measurements and vouch for the qualifications of all persons taking them.



TABLE OF CONTENTS

TITLE	PAGE NO.
1. GENERAL INFORMATION	5
1.1 General Statement	5
1.2 General Description of EUT & Power	5
1.3 Description of EUT	5
1.4 Description of Peripherals	6
1.5 EUT & Peripherals Setup Diagram	7
1.7 EUT Operating Condition	8
1.8 Description of Test Site	8
1.9 Summary of Test Results.....	9
2. CONDUCTED POWERLINE TEST	10
2.1 Test Equipments	10
2.2 Test Setup	10
2.3 Conducted Power Line Emission Limit	11
2.4 Test Procedure	11
2.5 Uncertainty of Conducted Emission.....	11
2.6 Conducted Power Line Emission	12
2.7 Photos of Conduction Test	13-14
3. RADIATED EMISSION TEST	15
3.1 Test Equipments	15
3.2 Test Setup	15
3.3 Radiation Limit.....	16
3.4 Test Procedures	17
3.5 Uncertainty of Radiated Emission.....	17
3.6 Radiated Rf Noise Measurement.....	18-37
3.7 Photos of Open Site	38-44
4. 6dB BANDWIDTH MEASUREMENT	45
4.1 Test Equipments	46
4.2 Test Setup	46
4.3 Limits of 6dB Bandwidth Measurement	46
4.4 Test Procedure	46
4.5 Uncertainty of Conducted Emission.....	46
4.6 Test Results	47
4.7 Photo of 6db Bandwidth Measurement	48
5. MAXIMUM PEAK OUTPUT POWER	49
5.1 Test Equipments	50
5.2 Test Setup	50
5.3 Limits of Maximum Peak Output Power.....	50
5.4 Test Procedure	51
5.5 Uncertainty of Conducted Emission.....	51
5.6 Test Results	51
6. POWER SPECTRAL DENSITY MEASUREMENT	52
6.1 Test Equipments	52
6.2 Test Setup	52
6.3 Limits of Power Spectral Density Measurement	52
6.4 Test Procedure	53
6.5 Uncertainty of Conducted Emission.....	53
6.6 Test Results	54
6.7 Photo of Power Spectral Density Measurement	55



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 4 of 64

TABLE OF CONTENTS

TITLE	PAGE NO.
-------	----------

7. OUT OF BAND MEASUREMENT	56
7.1 Test Equipments	57
7.2 Test Setup	57
7.3 Limits of Out of Band Emissions Measurement	57
7.4 Test Procedure	58
7.5 Uncertainty of Conducted Emission	58
7.6 Test Results	58
7.7 Photo of Out of Band Measurement	59-60
8. ANTENNA REQUIREMENT	61
8.1 Standard Applicable	62
8.2 Antenna Connected Construction	62
9. RF EXPOSURE EVALUATION.....	63
9.1 Friis Formula	63
9.2 EUT Operating Condition	63
9.3 Test Result of RF Exposure Evaluation	64
9.3.1 Antenna Gain	64
9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance.....	64



1. GENERAL INFORMATION

1.1 General Statement

MEASUREMENT DEVIATION : Comply with standard in full

TRACEABILITY : This test result is traceable to national or international std.

1.2 General Description of EUT & Power

1.3 Description of EUT

MANUFACTURER	: Z-COM, INC.
SAMPLE NAME	: IEEE 802.11g 54Mbps Wireless Router
MODEL NAME	: XG-2000
FREQUENCY CHANNEL	: 2412MHz to 2462MHz
CHANNEL SPACING	: 5MHz
CHANNEL NUMBER	: 1~11CH
AIR DATA RATE	: 54Mbps (802.11g Mode), 11Mbps(802.11b Mode)
TYPE OF MODULATION	: Orthogonal Frequency Division Multiplex or Direct Sequence Spread Spectrum
FREQUENCY SELECTION	: BY SOFTWARE
ANTENNA TYPE	: 1/2λ Dipole ANTENNA
POWER SOURCE	: 12VDC(From Adapter)

Power Adapter :

Manufacturer	: AC ADAPTOR
Model Number	: SCP48-121000
Input Power	: 120VAC/60Hz, 19W
Output Power	: 12VDC, 1000mA



1.4 Description of Peripherals

(1) PC

MANUFACTURER : HP CORP.
MODEL NUMBER : VECTRA VEI8DT
SERIAL NUMBER : SG1202412
FCC : DOC

(2) PC

MANUFACTURER : HP CORP.
MODEL NUMBER : VECTRA VEI8DT
SERIAL NUMBER : SG1202415
FCC : DOC

(3) PC

MANUFACTURER : HP CORP.
MODEL NUMBER : VECTRA VEI8DT
SERIAL NUMBER : SG1202416
FCC : DOC

(4) Notebook PC

MANUFACTURER : DELL CORP.
MODEL NUMBER : PP01L
SERIAL NUMBER : CN-09C748-48155-1AP-6630
FCC : DOC
POWER CORD : Unshielded, Detachable, 1.8m

(5) CABLE

	Type	Connector	shielded	Length
(A)	Cat5 twisted-pair	RJ-45,Plastic	NO	15m



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd.,ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 7 of 64

1.5 EUT & Peripherals Setup Diagram





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 8 of 64

1.6 EUT Operating Condition

1. Set up all computers like the setup diagram.
2. PC (1) ping 192.168.62.1 -t to EUT.
3. PC (2) ping 192.168.1.80 -t to PC (3).
4. Notebook PC (4) ping 192.168.62.1 -t to EUT.
5. All of the function are under run.
6. Start test.

1.7 Description of Test Site

SITE DESCRIPTION : FCC certificate NO. : 90585

BSMI certificate NO. : SL2-IN-E-0002

NVLAP Lab code : 200118-0

CNLA certificate NO. : CNLA-ZL97018

VCCI certificate NO. : R-1229, C-1250

NAME OF SITE : Ecom Sertech Corp. Hsinchu
(Spin-off from ITRI / ERSO on April. 01, 2003)

SITE LOCATION : Rm.258, Bldg.17, NO.195 , Sec. 4, Chung Hsing Rd.,
Chu-Tung Chen. Hsin-Chu, Taiwan 310 R.O.C.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 9 of 64

1.8 Summary of Test Results

The EUT has been tested according to the following specifications :

APPLIED STANDARD : 47 CFR Part 15, Subpart B and Subpart C			
Standard Section	Test Type and Limit	Result	REMARK
15.107 15.207	AC Power Conducted Emission Limit : sec 15.107	PASS	Meet the requirement of limit
15.247(a)(2)	Spectrum Bandwidth of a Direct Sequence Spread Spectrum System Limit : 6dB bandwidth > 500KHz	PASS	Meet the requirement of limit
15.247(b)	Maximum Peak Output Power Limit : max. 30dBm	PASS	Meet the requirement of limit
15.109 15.205 15.209	Transmitter Radiated Emissions Limit : Table 15.209	PASS	Meet the requirement of limit
15.247(d)	Power Spectral Density Limit : max. 8dBm	PASS	Meet the requirement of limit
15.247(c)	Out of Band Emission and Restricted Band Radiation Limit: 20dB less than peak value of fundamental frequency Restricted band Limit: Table 15.209	PASS	Meet the requirement of limit



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 10 of 64


2. CONDUCTED POWERLINE TEST

2.1 Test Equipments

The following test equipments are used during the conducted powerline tests :

Manufacturer or Type	Model No	Serial No.	Date of Calibration	Calibration Period	Remark
SPECTRUM ANALYZER & DISPLAY	HP 8568A	2235A02320	APR. 01, 2003	1 Year	PRETEST
QUASI-PEAK ADAPTER	HP 85650 A	2341A00672	APR. 01, 2003	1 Year	PRETEST
ISOLATION TRANSFORMER	SOLAR 7032-1	N/A	N/A	N/A	FINAL
L.I.S.N.	EMCO 3850/2	9311-1025 9401-1028	JAN. 08, 2003 For Characteristic impedance MAY 18, 2003 For Insertion loss	1 Year	FINAL
TEST RECEIVER	R/S ESHS30	838550/003	JUN. 07, 2003	1 Year	FINAL
SHIELDED ROOM	KEENE 5983	NO.1	N/A	N/A	FINAL
PULSE LIMIT	R/S EHS3Z2	357.8810.52	JUL. 10, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	-----	-----	JUL. 10, 2003	1 Year	FINAL
50Ω TERMINATOR	-----	-----	JUL. 10, 2003	1 Year	FINAL

2.2 Test Setup





2.3 Conducted Power Line Emission Limit

For unintentional device, according to § 15.107(a) Line Conducted Emission Limits is as following :

Frequency (MHz)	Maximum Rf Line Voltage (Db μ v)			
	CLASS A		CLASS B	
	Q.P.	Ave.	Q.P.	Ave.
0.15 - 0.50	79	66	66-56	56-46
0.50 - 5.00	73	60	56	46
5.00 - 30.0	73	60	60	50

For intentional device, according to § 15.207(a) Line Conducted Emission Limit is same as above table.

2.4 Test Procedure

The test procedure is performed in a 12ft×12ft×8ft(L×W×H) shielded room. the EUT along with its peripherals were placed on a 1.0m(W)× 1.5m(L) and 0.8m in height wooden table and the EUT was adjusted to maintain a 0.4 meter space from a vertical reference plane. The EUT was connected to power mains through a line impedance stabilization network (LISN) which provides 50 ohm coupling impedance for measuring instrument and the chassis ground was bounded to the horizontal ground plane of shielded room. All peripherals were connected to the second LISN and the chassis ground also bounded to the horizontal ground plane of shielded room. The excess power cable between the EUT and the LISN was bundled. The power cables of peripherals were unbundled. All connecting cables of EUT and peripherals were moved to find the maximum emission.

2.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.36 dB.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 12 of 64

2.6 Conducted Power Line Emission

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 24 °C

Humidity : 64 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dBμV)		L2 Emission (dBμV)		Limits (dBμV)	
			L1(dBμV)		L2(dBμV)							
	L1	L2	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
0.150	0.1	0.2	*	*	*	*	*	*	*	*	66.00	56.00
0.156	0.1	0.2	*	*	47.30	*	*	*	47.50	*	65.67	55.67
0.168	0.1	0.2	48.00	18.50	*	*	48.10	18.60	*	*	65.06	55.06
0.486	0.1	0.2	*	*	45.00	15.45	*	*	45.20	15.65	56.24	46.24
0.555	0.1	0.2	44.90	15.80	*	*	45.00	15.90	*	*	56.00	46.00
0.615	0.1	0.2	*	*	40.80	12.30	*	*	41.00	12.50	56.00	46.00
0.642	0.1	0.2	43.10	20.20	*	*	43.20	20.30	*	*	56.00	46.00
1.101	0.1	0.2	29.00	*	*	*	29.10	*	*	*	56.00	46.00
1.857	0.1	0.2	*	*	30.70	*	*	*	30.90	*	56.00	46.00
2.598	0.2	0.2	*	*	31.00	*	*	*	31.20	*	56.00	46.00
3.711	0.2	0.2	32.40	*	*	*	32.60	*	*	*	56.00	46.00
5.937	0.3	0.3	34.80	*	*	*	35.20	*	*	*	60.00	50.00
7.422	0.3	0.3	*	*	34.40	*	*	*	34.70	*	60.00	50.00
10.764	0.5	0.5	37.50	*	*	*	38.00	*	*	*	60.00	50.00
11.133	0.5	0.5	*	*	37.40	*	*	*	37.90	*	60.00	50.00
15.585	0.7	0.7	*	*	32.80	*	*	*	33.50	*	60.00	50.00
15.957	0.7	0.7	32.20	*	*	*	32.90	*	*	*	60.00	50.00
30.000	1.4	1.8	*	*	*	*	*	*	*	*	60.00	50.00

- REMARKS : 1. * Undetectable or the Q.P. value is lower than the limits of Ave.
2. According to technical experiences, the power line emissions of the EUT in transmitting and receiving mode are almost the same. The EUT was set to transmitting mode at channel 1 (2412MHz) while performing final test.
3. For 802.11b mode.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 13 of 64

The frequency spectrum from 0.15 MHz to 30 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

Temperature : 24 °C

Humidity : 64 % RH

Frequency (MHz)	Loss(dB)		Measurement				L1 Emission (dBμV)		L2 Emission (dBμV)		Limits (dBμV)	
			L1(dBμV)		L2(dBμV)							
	L1	L2	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.	Q.P.	A.V.
0.150	0.1	0.2	*	*	*	*	*	*	*	*	66.00	56.00
0.156	0.1	0.2	*	*	47.50	17.80	*	*	47.70	18.00	65.67	55.67
0.186	0.1	0.2	46.30	16.40	*	*	46.40	16.50	*	*	64.21	54.21
0.480	0.1	0.2	*	*	45.30	15.60	*	*	45.50	15.80	56.34	46.34
0.498	0.1	0.2	46.50	16.50	*	*	46.60	16.60	*	*	56.03	46.03
0.594	0.1	0.2	*	*	41.70	13.10	*	*	41.90	13.30	56.00	46.00
0.645	0.1	0.2	43.80	20.30	*	*	43.90	20.40	*	*	56.00	46.00
1.140	0.1	0.2	29.30	*	*	*	29.40	*	*	*	56.00	46.00
1.482	0.1	0.2	*	*	32.70	*	*	*	32.90	*	56.00	46.00
2.598	0.2	0.2	32.70	*	*	*	32.90	*	*	*	56.00	46.00
3.711	0.2	0.2	*	*	31.60	*	*	*	31.80	*	56.00	46.00
4.824	0.2	0.2	32.80	*	*	*	33.00	*	*	*	56.00	46.00
7.422	0.3	0.3	*	*	34.60	*	*	*	34.90	*	60.00	50.00
10.389	0.5	0.5	*	*	37.60	*	*	*	38.10	*	60.00	50.00
10.395	0.5	0.5	37.00	*	*	*	37.50	*	*	*	60.00	50.00
15.588	0.7	0.7	*	*	32.70	*	*	*	33.40	*	60.00	50.00
15.594	0.7	0.7	33.10	*	*	*	33.80	*	*	*	60.00	50.00
30.000	1.4	1.8	*	*	*	*	*	*	*	*	60.00	50.00

- REMARKS : 1. * Undetectable or the Q.P. value is lower than the limits of Ave.
2. According to technical experiences, the power line emissions of the EUT in transmitting and receiving mode are almost the same. The EUT was set to transmitting mode at channel 1 (2412MHz) while performing final test.
3. For 802.11g mode.

2.7 Photos of Conduction Test



3. RADIATED EMISSION TEST


3.1 Test Equipments

The following test equipments are utilized in making the measurements contained in this report.


Manufacturer or Type	Model No	Serial No	Date of Calibration	Calibration Period	Remark
CHASE BI-LOG ANTENNA	CBL6112B	2421	MAY 07, 2003	1 Year	FINAL
R/S SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003	1 Year	FINAL
OPEN SITE	-----	No.2	JAN. 10, 2003	1 Year	FINAL
N TYPE COAXIAL CABLE	CHA9525	4	JUL. 13, 2003	1 Year	FINAL
Horn Antenna	AH-118	10089	FEB. 25, 2003	1 Year	FINAL
HP Pre-amplifier	8449B	3008A01471	OCT. 11, 2002	1 Year	FINAL
HP High pass filter	84300/80038	011	cal. on use	1 Year	FINAL
Horn Antenna	AH-840	03077	FEB. 25, 2003	1 Year	FINAL

3.2 Test Setup

The diagram below shows the test setup that is utilized to make the measurements for emission from 30 to 1GHz.



The diagram below shows the test setup that is utilized to make the measurements for emission above 1GHz.



Antenna Elevation Variable

3.3 Radiation Limit

For unintentional device, according to § 15.109(a), except for Class A digital devices, the field strength of radiated emissions from unintentional radiators at a distance of 3 meters shall not exceed the following values :

Frequency (MHz)	Distance (METERS)	Radiated (dBμV/M)	Radiated (μV/M)
30-88	3	40.0	100
88-216	3	43.5	150
216-960	3	46.0	200
Above 960	3	54.0	500

For intentional device, according to § 15.209(a), the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the above table.

3.4 Test Procedures

- a. The EUT was placed on the top of a rotating table 0.8 meters above the ground at a 10 meter open area test site. The table was rotated 360 degrees to determine the position of the highest radiation.
- b. The EUT was set 3 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- c. The antenna is a broadband antenna, and its height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarization of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- e. The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- f. If the emission level of the EUT in peak mode was 10 dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10 dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

NOTE :

1. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 KHz for Peak detection (PK) and Quasi-peak detection (QP) at frequency below 1GHz.
2. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 1 MHz for Peak detection and frequency above 1GHz.
3. The resolution bandwidth of test receiver/spectrum analyzer is 1 MHz and the video bandwidth is 10 Hz for Average detection (AV) at frequency above 1GHz.

3.5 Uncertainty of Radiated Emission

The uncertainty of radiated emission is $\pm 2.72\text{dB}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 18 of 64

3.6 Radiated RF Noise Measurement

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 24.5°C

Humidity : 64 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 3m(dBμV/M)		Limits at 3m (dBμV/M)	Emission Level at 3m(dBμV/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	21.39	0.90	*	*	40.00	*	*
40.00	15.73	1.10	20.30	20.50	40.00	37.13	37.33
65.75	6.99	1.46	20.20	22.40	40.00	28.65	30.85
119.99	13.31	2.00	21.30	19.50	43.50	36.61	34.81
131.99	13.23	2.15	26.10	25.60	43.50	41.48	40.98
159.99	11.26	2.50	17.00	15.40	43.50	30.76	29.16
199.99	10.39	2.80	21.90	18.70	43.50	35.09	31.89
250.00	13.09	3.20	19.80	17.10	46.00	36.09	33.39
263.99	13.20	3.31	26.20	18.10	46.00	42.72	34.62
299.99	13.50	3.60	17.50	17.90	46.00	34.60	35.00
395.99	17.09	4.18	18.50	17.10	46.00	39.77	38.37
499.99	18.32	4.90	19.10	20.10	46.00	42.32	43.32
527.99	18.66	5.04	17.40	18.60	46.00	41.10	42.30
1000.00	21.58	7.00	*	*	54.00	*	*

REMARKS : 1. * Undetectable

2. Emission level (dBμV/M) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).

3. The EUT was operated in stand-by, receiving and transmitting mode, after a preliminary scan, we found the EUT in transmitting mode generate the highest emission power. The EUT is set transmitting mode at final test to get the worst-case emission.

4. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.

5. Mode : Transmitting test

6. For Wireless 802.11b mode.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 19 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum from 30 MHz to 1000 MHz was investigated. All emissions not reported below are more than 20 dB below the prescribed limits.

All readings are quasi-peak values.

Temperature : 24.5°C

Humidity : 64 % RH

Frequency (MHz)	Antenna Factor (dB)	Cable Loss (dB)	Meter Reading at 3m(dBμV/M)		Limits at 3m (dBμV/M)	Emission Level at 3m(dBμV/M)	
			Horizontal	Vertical		Horizontal	Vertical
30.00	21.39	0.90	*	*	40.00	*	*
40.00	15.73	1.10	20.00	20.10	40.00	36.83	36.93
65.75	6.99	1.46	19.90	21.90	40.00	28.35	30.35
119.99	13.31	2.00	21.10	19.30	43.50	36.41	34.61
131.99	13.23	2.15	25.70	25.20	43.50	41.08	40.58
159.99	11.26	2.50	17.30	15.50	43.50	31.06	29.26
199.99	10.39	2.80	21.40	18.90	43.50	34.59	32.09
250.00	13.09	3.20	19.60	17.50	46.00	35.89	33.79
263.99	13.20	3.31	26.40	18.70	46.00	42.92	35.22
299.99	13.50	3.60	17.60	18.10	46.00	34.70	35.20
395.99	17.09	4.18	18.80	17.30	46.00	40.07	38.57
499.99	18.32	4.90	19.30	20.00	46.00	42.52	43.22
527.99	18.66	5.04	17.60	18.20	46.00	41.30	41.90
1000.00	21.58	7.00	*	*	54.00	*	*

REMARKS : 1. * Undetectable

2. Emission level (dBμV/M) = Antenna Factor (dB/m) + Cable loss (dB) + Meter Reading (dBμV).

3. The EUT was operated in stand-by, receiving and transmitting mode, after a preliminary scan, we found the EUT in transmitting mode generate the highest emission power. The EUT is set transmitting mode at final test to get the worst-case emission.

4. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.

5. Mode : Transmitting test.

6. For Wireless 802.11g mode.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 20 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.89	48.02	34.44	2.77	35.38	9.5	0	40.35	74	-33.65	P	1.00
4823.89	40.78	34.44	2.77	35.38	9.5	0	33.11	54	-20.89	A	1.00
7237.43	44.80	39.81	3.95	35.56	9.5	0	43.49	74	-30.51	P	1.05
7237.43	33.94	39.81	3.95	35.56	9.5	0	32.63	54	-21.37	A	1.05
9647.99	53.70	38.54	4.10	35.67	9.5	0	51.16	74	-22.84	P	1.10
9647.99	49.84	38.54	4.10	35.67	9.5	0	47.30	54	-6.70	A	1.10

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 21 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.89	53.31	34.44	2.77	35.38	9.5	0	45.64	74	-28.36	P	1.08
4823.89	49.91	34.44	2.77	35.38	9.5	0	42.24	54	-11.76	A	1.08
7236.28	44.09	39.81	3.94	35.56	9.5	0	42.78	74	-31.22	P	1.06
7236.28	33.64	39.81	3.94	35.56	9.5	0	32.33	54	-21.67	A	1.06
9647.95	57.97	38.54	4.10	35.67	9.5	0	55.43	74	-18.57	P	1.02
9647.95	55.09	38.54	4.10	35.67	9.5	0	52.55	54	-1.45	A	1.02

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow : Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
9. For Wireless 802.11b mode at 11Mbps.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 22 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.93	47.02	34.77	2.80	35.40	9.5	0	39.69	74	-34.31	P	1.02
4873.93	39.27	34.77	2.80	35.40	9.5	0	31.94	54	-22.06	A	1.02
7310.99	44.84	39.78	4.00	35.57	9.5	0	43.55	74	-30.45	P	1.10
7310.99	33.70	39.78	4.00	35.57	9.5	0	32.41	54	-21.59	A	1.10
9748.09	52.77	38.53	4.02	35.72	9.5	0	50.09	74	-23.91	P	1.03
9748.09	49.55	38.53	4.02	35.72	9.5	0	46.87	54	-7.13	A	1.03

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow : Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 23 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.99	51.69	34.77	2.80	35.40	9.5	0	44.36	74	-29.64	P	1.00
4873.99	48.54	34.77	2.80	35.40	9.5	0	41.21	54	-12.79	A	1.00
7311.45	43.82	39.78	4.00	35.57	9.5	0	42.53	74	-31.47	P	1.00
7311.45	33.11	39.78	4.00	35.57	9.5	0	31.82	54	-22.18	A	1.00
9747.97	57.61	38.53	4.02	35.72	9.5	0	54.93	74	-19.07	P	1.00
9747.97	55.38	38.53	4.02	35.72	9.5	0	52.70	54	-1.30	A	1.00

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow : Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
9. For Wireless 802.11b mode at 6Mbps.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 24 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 RX				Measurement Distance at 1m					Horizontal polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.89	47.52	35.10	2.83	35.41	9.5	0	40.54	74	-33.46	P	1.00
4923.89	40.24	35.10	2.83	35.41	9.5	0	33.26	54	-20.74	A	1.00
7386.23	43.57	39.75	4.06	35.57	9.5	0	42.30	74	-31.70	P	1.01
7386.23	32.77	39.75	4.06	35.57	9.5	0	31.50	54	-22.50	A	1.01
9847.88	53.71	38.52	3.93	35.77	9.5	0	50.89	74	-23.11	P	1.02
9847.88	50.24	38.52	3.93	35.77	9.5	0	47.42	54	-6.58	A	1.02

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11b mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 25 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4924.01	51.52	35.10	2.83	35.41	9.5	0	44.54	74	-29.46	P	1.06
4924.01	48.32	35.10	2.83	35.41	9.5	0	41.34	54	-12.66	A	1.06
7386.45	43.23	39.75	4.06	35.57	9.5	0	41.96	74	-32.04	P	1.03
7386.45	32.88	39.75	4.06	35.57	9.5	0	31.61	54	-22.39	A	1.03
9847.91	57.53	38.52	3.93	35.77	9.5	0	54.71	74	-19.29	P	1.00
9847.91	55.36	38.52	3.93	35.77	9.5	0	52.54	54	-1.46	A	1.00

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 26 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 RX				Measurement Distance at 1m Horizontal polarity							
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.92	45.59	34.44	2.77	35.38	9.5	0	37.92	74	-36.08	P	1.00
4823.92	39.35	34.44	2.77	35.38	9.5	0	31.68	54	-22.32	A	1.00
7236.28	43.69	39.81	3.94	35.56	9.5	0	42.38	74	-31.62	P	1.05
7236.28	33.01	39.81	3.94	35.56	9.5	0	31.70	54	-22.30	A	1.05
9647.89	51.97	38.54	4.10	35.67	9.5	0	49.43	74	-24.57	P	1.10
9647.89	47.93	38.54	4.10	35.67	9.5	0	45.39	54	-8.61	A	1.10

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 27 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4823.96	52.16	34.44	2.77	35.38	9.5	0	44.49	74	-29.51	P	1.08
4823.96	48.52	34.44	2.77	35.38	9.5	0	40.85	54	-13.15	A	1.08
7236.37	43.61	39.81	3.94	35.56	9.5	0	42.30	74	-31.70	P	1.06
7236.37	33.28	39.81	3.94	35.56	9.5	0	31.97	54	-22.03	A	1.06
9647.88	56.42	38.54	4.10	35.67	9.5	0	53.88	74	-20.12	P	1.02
9647.88	54.36	38.54	4.10	35.67	9.5	0	51.82	54	-2.18	A	1.02

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 28 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 RX				Measurement Distance at 1m Horizontal polarity							
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.93	46.51	34.77	2.80	35.40	9.5	0	39.18	74	-34.82	P	1.02
4873.93	38.48	34.77	2.80	35.40	9.5	0	31.15	54	-22.85	A	1.02
7311.73	43.71	39.78	4.00	35.57	9.5	0	42.42	74	-31.58	P	1.10
7311.73	33.15	39.78	4.00	35.57	9.5	0	31.86	54	-22.14	A	1.10
9747.98	54.19	38.53	4.02	35.72	9.5	0	51.51	74	-22.49	P	1.03
9747.98	51.03	38.53	4.02	35.72	9.5	0	48.35	54	-5.65	A	1.03

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 29 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4873.94	51.23	34.77	2.80	35.40	9.5	0	43.90	74	-30.10	P	1.00
4873.94	47.59	34.77	2.80	35.40	9.5	0	40.26	54	-13.74	A	1.00
7311.27	43.07	39.78	4.00	35.57	9.5	0	41.78	74	-32.22	P	1.00
7311.27	32.93	39.78	4.00	35.57	9.5	0	31.64	54	-22.36	A	1.00
9747.97	57.71	38.53	4.02	35.72	9.5	0	55.03	74	-18.97	P	1.00
9747.97	55.17	38.53	4.02	35.72	9.5	0	52.49	54	-1.51	A	1.00

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow : Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
9. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 30 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 RX				Measurement Distance at 1m Horizontal polarity							
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.97	46.52	35.10	2.83	35.41	9.5	0	39.54	74	-34.46	P	1.00
4923.97	38.79	35.10	2.83	35.41	9.5	0	31.81	54	-22.19	A	1.00
7385.94	43.79	39.75	4.06	35.57	9.5	0	42.52	74	-31.48	P	1.01
7385.94	32.77	39.75	4.06	35.57	9.5	0	31.50	54	-22.50	A	1.01
9847.87	54.14	38.52	3.93	35.77	9.5	0	51.32	74	-22.68	P	1.02
9847.87	50.66	38.52	3.93	35.77	9.5	0	47.84	54	-6.16	A	1.02

1. Measurement was up to 18GHz harmonic, "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow :
Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 31 of 64

Test Requirement: 15.109, 15.209

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 RX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
4923.91	51.69	35.10	2.83	35.41	9.5	0	44.71	74	-29.29	P	1.06
4923.91	47.81	35.10	2.83	35.41	9.5	0	40.83	54	-13.17	A	1.06
7386.12	42.92	39.75	4.06	35.57	9.5	0	41.65	74	-32.35	P	1.03
7386.12	32.44	39.75	4.06	35.57	9.5	0	31.17	54	-22.83	A	1.03
9847.94	57.54	38.52	3.93	35.77	9.5	0	54.72	74	-19.28	P	1.00
9847.94	55.63	38.52	3.93	35.77	9.5	0	52.81	54	-1.19	A	1.00

1. Measurement was up to 18GHz harmonic, “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
5. The result basic equation calculation as follow : Level = Reading + AF + Closs - Preamp + Filter - Dist, Margin = Level - Limit
6. The test limit distance is 3M limit.
7. The other emission levels were very low against the limit.
8. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
9. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 32 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
*2387.54	51.21	(delta between carrier and local max emission)					50.90	74	-23.10	P	1.00
*2387.54	51.21	(delta between carrier and local max emission)					43.83	54	-10.17	A	1.00
2413.29	77.46	31.79	2.36	0.00	9.50	0.00	102.11	Fundamental Frequency		P	1.03
2413.29	70.39	31.79	2.36	0.00	9.50	0.00	95.04			A	1.03
*4824.04	50.37	34.44	2.77	35.38	9.50	1.00	43.70	74	-30.30	P	1.01
*4824.04	44.40	34.44	2.77	35.38	9.50	1.00	37.73	54	-16.27	A	1.01
7238.57	49.05	39.80	3.95	35.56	9.50	1.00	48.74	74	-25.26	P	1.17
7238.57	34.03	39.80	3.95	35.56	9.50	1.00	33.72	54	-20.28	A	1.17
9647.98	51.29	38.54	4.10	35.67	9.50	1.00	49.75	74	-24.25	P	1.07
9647.98	46.33	38.54	4.10	35.67	9.50	1.00	44.79	54	-9.21	A	1.07
*12066.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14479.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16893.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19306.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21719.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24132.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 33 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	27.9°C , 46%

CH1 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
*2387.54	51.21	(delta between carrier and local max emission)					60.06	74	-13.94	P	1.00
*2387.54	51.21	(delta between carrier and local max emission)					52.86	54	-1.14	A	1.00
2413.29	86.62	31.79	2.36	0.00	9.50	0.00	111.27	Fundamental Frequency		P	1.04
2413.29	79.42	31.79	2.36	0.00	9.50	0.00	104.07			A	1.04
*4823.91	52.45	34.44	2.77	35.38	9.50	1.00	45.78	74	-28.22	P	1.00
*4823.91	44.41	34.44	2.77	35.38	9.50	1.00	37.74	54	-16.26	A	1.00
7239.85	52.31	39.80	3.95	35.56	9.50	1.00	52.00	74	-22.00	P	1.00
7239.85	34.35	39.80	3.95	35.56	9.50	1.00	34.04	54	-19.96	A	1.00
9647.91	55.17	38.54	4.10	35.67	9.50	1.00	53.63	74	-20.37	P	1.12
9647.91	53.37	38.54	4.10	35.67	9.50	1.00	51.83	54	-2.17	A	1.12
*12066.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14479.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16893.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19306.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21719.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24132.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 34 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	27.9°C , 46%

CH6 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2438.29	77.43	31.76	2.43	0.00	9.50	0.00	102.12	Fundamental Frequency		P	1.08
2438.29	70.36	31.76	2.43	0.00	9.50	0.00	95.05			A	1.08
*4873.98	51.31	34.77	2.80	35.40	9.50	1.00	44.98	74	-29.02	P	1.00
*4873.98	45.46	34.77	2.80	35.40	9.50	1.00	39.13	54	-14.87	A	1.00
*7311.06	44.97	39.78	4.00	35.57	9.50	1.00	44.68	74	-29.32	P	1.00
*7311.06	34.46	39.78	4.00	35.57	9.50	1.00	34.17	54	-19.83	A	1.00
9748.03	52.64	38.53	4.02	35.72	9.50	1.00	50.96	74	-23.04	P	1.00
9748.03	46.83	38.53	4.02	35.72	9.50	1.00	45.15	54	-8.85	A	1.00
*12191.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14629.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17068.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19506.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21944.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24382.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist,Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 35 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	27.9°C , 46%

CH6 TX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2438.29	85.68	31.76	2.43	0.00	9.50	0.00	110.37	Fundamental Frequency		P	1.17
2438.29	78.68	31.76	2.43	0.00	9.50	0.00	103.37			A	1.17
*4874.05	53.69	34.77	2.80	35.40	9.50	1.00	47.36	74	-26.64	P	1.04
*4874.05	50.42	34.77	2.80	35.40	9.50	1.00	44.09	54	-9.91	A	1.04
*7310.04	51.16	39.78	4.00	35.57	9.50	1.00	50.87	74	-23.13	P	1.02
*7310.04	33.56	39.78	4.00	35.57	9.50	1.00	33.27	54	-20.73	A	1.02
9747.94	55.62	38.53	4.02	35.72	9.50	1.00	53.94	74	-20.06	P	1.08
9747.94	52.61	38.53	4.02	35.72	9.50	1.00	50.93	54	-3.07	A	1.08
*12191.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14629.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17068.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19506.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21944.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24382.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs+Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 36 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	27.9°C , 46%

CH11 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2463.29	76.70	31.74	2.49	0.00	9.50	0.00	101.43	Fundamental Frequency		P	1.03
2463.29	69.35	31.74	2.49	0.00	9.50	0.00	94.08			A	1.03
*2483.65	50.18	(delta between carrier and local max emission)					51.25	74	-22.75	P	1.00
*2483.65	50.18	(delta between carrier and local max emission)					43.90	54	-10.10	A	1.00
*4924.04	49.00	35.10	2.83	35.41	9.50	1.00	43.02	74	-30.98	P	1.01
*4924.04	42.97	35.10	2.83	35.41	9.50	1.00	36.99	54	-17.01	A	1.01
*7386.04	42.07	39.75	4.06	35.57	9.50	1.00	41.80	74	-32.20	P	1.01
*7386.04	30.58	39.75	4.06	35.57	9.50	1.00	30.31	54	-23.69	A	1.01
9847.92	52.71	38.52	3.93	35.77	9.50	1.00	50.89	74	-23.11	P	1.04
9847.92	48.69	38.52	3.93	35.77	9.50	1.00	46.87	54	-7.13	A	1.04
*12316.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14779.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17243.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19706.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22169.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24632.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 37 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	27.9°C , 46%

CH11 TX				Measurement Distance at 1m					Vertical polarity		
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2463.29	85.41	31.74	2.49	0.00	9.50	0.00	110.14	Fundamental Frequency		P	1.00
2463.29	78.37	31.74	2.49	0.00	9.50	0.00	103.10			A	1.00
*2483.65	50.18	(delta between carrier and local max emission)					59.96	74	-14.04	P	1.00
*2483.65	50.18	(delta between carrier and local max emission)					52.92	54	-1.08	A	1.00
*4923.92	52.75	35.10	2.83	35.41	9.50	1.00	46.77	74	-27.23	P	1.00
*4923.92	49.09	35.10	2.83	35.41	9.50	1.00	43.11	54	-10.89	A	1.00
*7389.34	53.71	39.74	4.06	35.57	9.50	1.00	53.44	74	-20.56	P	1.00
*7389.34	32.70	39.74	4.06	35.57	9.50	1.00	32.43	54	-21.57	A	1.00
9848.11	55.21	38.52	3.93	35.77	9.50	1.00	53.39	74	-20.61	P	1.89
9848.11	51.41	38.52	3.93	35.77	9.50	1.00	49.59	54	-4.41	A	1.89
*12316.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14779.74	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17243.03	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19706.32	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22169.61	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24632.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11b mode at 11Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 38 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
*2389.35	50.57	(delta between carrier and local max emission)					52.38	74	-21.62	P	1.00
*2389.35	50.57	(delta between carrier and local max emission)					42.84	54	-11.16	A	1.00
2412.69	78.30	31.79	2.36	0.00	9.50	0.00	102.95	Fundamental Frequency		P	1.03
2412.69	68.76	31.79	2.36	0.00	9.50	0.00	93.41			A	1.03
*4824.04	47.07	34.44	2.77	35.38	9.50	1.00	40.40	74	-33.60	P	1.01
*4824.04	38.13	34.44	2.77	35.38	9.50	1.00	31.46	54	-22.54	A	1.01
7236.95	39.16	39.81	3.94	35.56	9.50	1.00	38.85	74	-35.15	P	1.17
7236.95	29.04	39.81	3.94	35.56	9.50	1.00	28.73	54	-25.27	A	1.17
9647.94	52.95	38.54	4.10	35.67	9.50	1.00	51.41	74	-22.59	P	1.07
9647.94	49.26	38.54	4.10	35.67	9.50	1.00	47.72	54	-6.28	A	1.07
*12063.45	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14476.14	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16888.83	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19301.52	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21714.21	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24126.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11g mode at 6Mbps.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 39 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH1 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
*2389.35	50.57	(delta between carrier and local max emission)					55.75	74	-18.25	P	1.00
*2389.35	50.57	(delta between carrier and local max emission)					46.20	54	-7.80	A	1.00
2413.70	81.67	31.79	2.36	0.00	9.50	0.00	106.32	Fundamental Frequency		P	1.04
2413.70	72.12	31.79	2.36	0.00	9.50	0.00	96.77			A	1.04
*4823.97	50.30	34.44	2.77	35.38	9.50	1.00	43.63	74	-30.37	P	1.00
*4823.97	43.20	34.44	2.77	35.38	9.50	1.00	36.53	54	-17.47	A	1.00
7234.79	43.62	39.81	3.94	35.56	9.50	1.00	43.31	74	-30.69	P	1.00
7234.79	33.90	39.81	3.94	35.56	9.50	1.00	33.59	54	-20.41	A	1.00
9647.92	56.15	38.54	4.10	35.67	9.50	1.00	54.61	74	-19.39	P	1.12
9647.92	53.90	38.54	4.10	35.67	9.50	1.00	52.36	54	-1.64	A	1.12
*12068.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*14482.20	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
16895.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19309.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21723.30	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24137.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark “---” means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark “*” means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
10. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 40 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2439.30	76.12	31.76	2.43	0.00	9.50	0.00	100.81	Fundamental Frequency		P	1.08
2439.30	67.94	31.76	2.43	0.00	9.50	0.00	92.63			A	1.08
*4874.08	46.16	34.77	2.80	35.40	9.50	1.00	39.83	74	-34.17	P	1.00
*4874.08	46.27	34.77	2.80	35.40	9.50	1.00	39.94	54	-14.06	A	1.00
*7311.72	42.85	39.78	4.00	35.57	9.50	1.00	42.56	74	-31.44	P	1.00
*7311.72	33.47	39.78	4.00	35.57	9.50	1.00	33.18	54	-20.82	A	1.00
9747.93	52.47	38.53	4.02	35.72	9.50	1.00	50.79	74	-23.21	P	1.00
9747.93	49.11	38.53	4.02	35.72	9.50	1.00	47.43	54	-6.57	A	1.00
*12196.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14635.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17075.10	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19514.40	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21953.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24393.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 41 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH6 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2439.30	79.41	31.76	2.43	0.00	9.50	0.00	104.10	Fundamental Frequency		P	1.17
2439.30	71.13	31.76	2.43	0.00	9.50	0.00	95.82			A	1.17
*4873.90	50.87	34.77	2.80	35.40	9.50	1.00	44.54	74	-29.46	P	1.04
*4873.90	44.62	34.77	2.80	35.40	9.50	1.00	38.29	54	-15.71	A	1.04
*7311.75	43.22	39.78	4.00	35.57	9.50	1.00	42.93	74	-31.07	P	1.02
*7311.75	33.28	39.78	4.00	35.57	9.50	1.00	32.99	54	-21.01	A	1.02
9747.91	56.83	38.53	4.02	35.72	9.50	1.00	55.15	74	-18.85	P	1.08
9747.91	54.11	38.53	4.02	35.72	9.50	1.00	52.43	54	-1.57	A	1.08
*12196.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14635.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17075.10	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19514.40	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
21953.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24393.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
10. For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 42 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 TX				Measurement Distance at 1m				Horizontal polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2464.40	76.23	31.736	2.50	0.00	9.50	0.00	100.96	Fundamental Frequency		P	1.03
2464.40	68.18	31.736	2.50	0.00	9.50	0.00	92.91			A	1.03
*2483.65	49.74	(delta between carrier and local max emission)					51.22	74	-22.78	P	1.00
*2483.65	49.74	(delta between carrier and local max emission)					43.17	54	-10.83	A	1.00
*4923.99	45.11	35.10	2.83	35.41	9.50	1.00	39.13	74	-34.87	P	1.01
*4923.99	36.29	35.10	2.83	35.41	9.50	1.00	30.31	54	-23.69	A	1.01
*7386.12	42.04	39.75	4.06	35.57	9.50	1.00	41.77	74	-32.23	P	1.01
*7386.12	32.15	39.75	4.06	35.57	9.50	1.00	31.88	54	-22.12	A	1.01
9847.47	52.78	38.52	3.94	35.77	9.50	1.00	50.96	74	-23.04	P	1.04
9847.47	48.47	38.52	3.94	35.77	9.50	1.00	46.65	54	-7.35	A	1.04
*12322.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14786.40	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17250.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19715.20	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22179.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24644.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

- The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
- AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
- Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
- Remark "*" means that Restricted band.
- Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
- The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
- The other emission levels were very low against the limit
- The test limit distance is 3M limit.
- For Wireless 802.11g mode at 6Mbps.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 43 of 64

Test Requirement: 15.205

The frequency spectrum above 1 GHz was investigated. All emissions not reported below are more than 40 dB below the prescribed limits. Readings are both peak and average values.

Company	Z-COM, INC	Test Date :	2003/8/20
Product Name	IEEE 802.11g 54Mbps Wireless Router	Test By:	Alan Fan
Model Name	XG-2000	TEMP&Humidity :	25.4°C , 57%

CH11 TX				Measurement Distance at 1m				Vertical polarity			
Freq.	Reading	AF	Cable	Pre-amp	Dist	Filter	Level	Limit	Margin	Mark	Height
(MHz)	(dBuV)	(dBuV)	(dB)	(dB)	dB	dB	(dBuV/m)	(dBuV/m)	(dB)	(P/Q/A)	(Meter)
2464.10	79.15	31.74	2.50	0.00	9.50	0.00	103.88	Fundamental Frequency		P	1.00
2464.10	70.79	31.74	2.50	0.00	9.50	0.00	95.52			A	1.00
*2483.65	49.74	(delta between carrier and local max emission)					54.14	74	-19.86	P	1.00
*2483.65	49.74	(delta between carrier and local max emission)					45.78	54	-8.22	A	1.00
*4923.87	48.29	35.10	2.83	35.41	9.50	1.00	42.31	74	-31.69	P	1.00
*4923.87	42.68	35.10	2.83	35.41	9.50	1.00	36.70	54	-17.30	A	1.00
*7386.60	43.78	39.75	4.06	35.57	9.50	1.00	43.51	74	-30.49	P	1.00
*7386.60	33.75	39.75	4.06	35.57	9.50	1.00	33.48	54	-20.52	A	1.00
9847.99	56.64	38.52	3.93	35.77	9.50	1.00	54.82	74	-19.18	P	1.89
9847.99	54.18	38.52	3.93	35.77	9.50	1.00	52.36	54	-1.64	A	1.89
*12320.50	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
14784.60	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
17248.70	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*19712.80	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
*22176.90	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00
24641.00	-----	-----	-----	-----	9.50	1.00	-----	-----	-----	-----	1.00

Note :

1. The measurement was searched to 10th harmonic, Remark "---" means that the emissions level is too low to be measured.
2. AF: Antenna Factor, Closs: Cable Loss, Pre-Amp: Preamplifier gain, Filter: High Pass Filter Insertion Loss (3.5GHz)
3. Analyzer setting P(Peak): RBW=1MHz, VBW=1MHz, A(Average): RBW=1MHz, VBW=10Hz
4. Remark "*" means that Restricted band.
5. Dist : correction to extra plate reading to 3m specification distance 1m measurement distance = -9.5dB
6. The result basic equation calculation is as follow:
Level=Reading+AF+Closs-Preamp+Filter-Dist, Margin=Level-Limit
7. The other emission levels were very low against the limit
8. The test limit distance is 3M limit.
9. The test data marked in gray background means the EUT emission data is located in the margin uncertainty range of emission limits.
10. For Wireless 802.11g mode at 6Mbps.

3.7 Photos of Open Site





Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing
Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 45 of 64



4. 6dB BANDWIDTH MEASUREMENT


4.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

4.2 Test Setup



4.3 Limits of 6dB Bandwidth Measurement

The minimum of 6dB Bandwidth Measurement is $>500\text{KHz}$

4.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator. The bandwidth of the fundamental frequency was measured by spectrum analyzer with 100 KHz RBW and 100 KHz VBW. The 6dB bandwidth is defined as the total spectrum the power of which is higher than peak power minus 6dB.

4.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 200\text{KHz}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 47 of 64

4.6 Test Results

Input Power (System)	12VDC (Form Adapter)	Environmental Conditions	30.1°C, 47%RH,
Tested By	Alan Fan		

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	11.50	0.5	PASS
6	2437	11.08	0.5	PASS
11	2462	11.48	0.5	PASS

Note :

1. For 11Mbps (802.11b mode).
2. At final test to get the worst-case emission at 11Mbps.

Channel	Channel Frequency (MHz)	6dB Bandwidth (MHz)	Minimum Limit (MHz)	Pass / Fail
1	2412	15.05	0.5	PASS
6	2437	15.01	0.5	PASS
11	2462	14.88	0.5	PASS

Note :

3. For 54Mbps (802.11g mode).
4. At final test to get the worst-case emission at 6Mbps.



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000


Report No. : ER03-07-066FRF

Page 48 of 64


4.7 Photo of 6db Bandwidth Measurement



Channel 1



Channel 6



Channel 11

Note : For 11Mbps (802.11b mode)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720


FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF


Page 49 of 64



Channel 1



Channel 6



Note : For 54Mbps (802.11g mode)



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 50 of 64

5. MAXIMUM PEAK OUTPUT POWER


5.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

5.2 Test Setup



5.3 Limits of Maximum Peak Output Power

The Maximum Peak Output Power Measurement is 30dBm.



Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 51 of 64

5.4 Test Procedure

The RF power output was measured with a Power meter connected to the RF Antenna connector (conducted measurement) while EUT was operating in transmit mode at the appropriate center frequency.

5.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

5.6 Test Results

Input Power (System)	12VDC(Form Adapter)	Environmental Conditions	30.1°C, 47%RH,
Tested By	Alan Fan		

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	18.95	30	PASS
6	2437	18.04	30	PASS
11	2462	17.12	30	PASS

Note :

1. For 11Mbps (802.11b mode).
2. At final test to get the worst-case emission at 11Mbps.
3. The result basic equation calculation as follow :
Peak Power Output = Peak Power Reading + Cable loss + Attenuator

Channel	Channel Frequency (MHz)	Peak Power Output (dBm)	Peak Power Limit (dBm)	Pass / Fail
1	2412	16.55	30	PASS
6	2437	15.79	30	PASS
11	2462	14.99	30	PASS

Note :

1. For 54Mbps (802.11g mode).
2. At final test to get the worst-case emission at 6Mbps.
3. The result basic equation calculation as follow :
Peak Power Output = Peak Power Reading + Cable loss + Attenuator



6. POWER SPECTRAL DENSITY MEASUREMENT


6.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

6.2 Test Setup



6.3 Limits of Power Spectral Density Measurement

The Maximum Power Spectral Density Measurement is 8dBm.



6.4 Test Procedure

The transmitter output was connected to the spectrum analyzer through an attenuator, the bandwidth of the fundamental frequency was measured with the spectrum analyzer using 3KHz RBW and 30KHz VBW, set sweep time=span / 3KHz.

The power spectral density was measured and recorded.

The sweep time is allowed to be longer than span / 3KHz for a full response of the mixer in the spectrum analyzer.

6.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is $\pm 1.82\text{dB}$.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 54 of 64

6.6 Test Results

Input Power (System)	12VDC(Form Adapter)	Environmental Conditions	30.1℃, 47%RH,
Tested By	Alan Fan		

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	-7.66	8	PASS
6	2437	-8.94	8	PASS
11	2462	-9.92	8	PASS

Note :

1. For 11Mbps (802.11b mode) at final test to get the worst-case emission at 11Mbps.
2. Power Spectral Density= Power spectral density reading + attenuator + cable loss.
The measurement value of RF Power Level + 10dB attenuator
= Final RF Power Level

Channel	Channel Frequency (MHz)	Final RF Power Level in 3KHz BW (dBm)	Maximum Limit (dBm)	Pass / Fail
1	2412	-13.34	8	PASS
6	2437	-14.89	8	PASS
11	2462	-15.71	8	PASS

Note :

1. For 54Mbps (802.11g mode) at final test to get the worst-case emission at 6Mbps.
2. Power Spectral Density= Power spectral density reading + attenuator + cable loss.
The measurement value of RF Power Level + 10dB attenuator
= Final RF Power Level



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000


Report No. : ER03-07-066FRF

Page 55 of 64


6.7 Photo of Power Spectral Density Measurement



Channel 1



Channel 6




Channel 11
For 802.11b mode (11Mbps)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720


FCC ID : M4Y-XG2000
Report No. : ER03-07-066FRF
Page 56 of 64



Channel 1



Channel 6



Channel 11
For 802.11g mode (6Mbps)



7. OUT OF BAND MEASUREMENT


7.1 Test Equipments

Description & Manufacturer	Model No.	Serial No.	Date Of Calibration
ROHDE & SCHWARZ SPECTRUM ANALYZER	FSEK30	835253/002	JUN. 17, 2003
HP ATTENUATOR	8496B	3247A18505	Cal. on use
HP PLOTTER	7750A	725A 852141	N/A

NOTE :

1. The measurement uncertainty is less than $\pm 2.6\text{dB}$, which is calculated as per the NAMAS document NIS81.
2. The calibration interval of the above test instruments is 12 months and the calibrations are traceable to NML/ROC and NIST/USA.

7.2 Test Setup



7.3 Limits of Out of Band Emissions Measurement

1. Below -20dB of the highest emission level of operating band (in 100KHz Resolution Bandwidth).
2. Fall in the restricted bands listed in section 15.205. The maximum permitted average field strength is listed in section 15.209.



7.4 Test Procedure

The transmitter output was connected to the spectrum analyzer via a low loss cable. Set both RBW and VBW of spectrum analyzer to 100KHz with suitable frequency span including 100KHz bandwidth from band edge. The band edges were measured and recorded.

7.5 Uncertainty of Conducted Emission

The uncertainty of conducted emission is ± 1.82 dB.

7.6 Test Results

A. Conducted

Refer to 7.7 photo of out band Emission measurement

B. Radiated

For 802.11b mode (11Mbps)

NOTE1: The band edge emission plot on the following first figure shows 51.21 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.3875 GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 104.07 dBuV/m(AV), so the maximum field strength in restrict band is $104.07 - 51.21 = 52.86$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 50.18 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.4836GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 103.10 dBuV/m(AV), so the maximum field strength in restrict band is $103.10 - 50.18 = 52.92$ dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	12VDC(Form Adapter)	Environmental Conditions	30.1°C, 47%RH,
Tested By	Alan Fan		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 59 of 64

For 802.11g mode (6Mbps)

NOTE1: The band edge emission plot on the following first figure shows 50.57 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.3893GHz). The emission of carrier strength list in the test result of channel 1 at the item 3.6 is 96.77 dBuV/m(AV), so the maximum field strength in restrict band is $96.77 - 50.57 = 46.20$ dBuV/m which is under 54 dBuV/m limit.

NOTE2: The band edge emission plot on the following second figure shows 49.74 dBuV/m delta between carrier maximum power and local maximum emission in restrict band (2.4836GHz). The emission of carrier strength list in the test result of channel 11 at the item 3.6 is 95.52 dBuV/m(AV), so the maximum field strength in restrict band is $95.52 - 49.74 = 45.78$ dBuV/m which is under 54 dBuV/m limit.

Input Power (System)	12VDC(Form Adapter)	Environmental Conditions	30.1℃, 47%RH,
Tested By	Alan Fan		

Channel Frequency (MHz)	Required Limit (dBc)	Pass / Fail
<2400	>20	PASS
>2483.5	>20	PASS



Ecom Sertech Corp.


Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000


Report No. : ER03-07-066FRF

Page 60 of 64

7.7 Photo of Out of Band Measurement



FRONT



BACK

Note : For 11Mbps (802.11b mode)




Ecom Sertech Corp.

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., ChuTung Chen, Hsinchu, Taiwan 310, R.O.C
TEL:886-3-5918012 FAX : 886-3-5825720


FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 61 of 64



FRONT



BACK

Note : For 54Mbps (802.11b mode)



8. ANTENNA REQUIREMENT

8.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

And according to FCC 47 CFR Section 15.247 (b), if transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6dBi.

8.2 Antenna Connected Construction

The antenna used in this product is dipole antenna. The dipole antenna connector is MMCX And the maximum Gain of these antennas are only 2dBi.



9. RF EXPOSURE EVALUATION

According to FCC 1.1310 : The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1307(b) LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Average Time
(A) Limits for Occupational / Control Exposures				
300-1,500	--	--	F/300	6
1,500-100,000	--	--	5	6
(B) Limits for General Population / Uncontrol Exposures				
300-1,500	--	--	F/1500	6
1,500-100,000	--	--	1	30

9.1 Friis Formula

Friis transmission formula : $P_d = (P_{out} * G) / (4 * \pi * r^2)$

Where

P_d = power density in mW/cm²

P_{out} = output power to antenna in mW

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d is the limit of MPE, 1 mW/cm². If we know the maximum gain of the antenna and the total power input to the antenna, through the calculation, we will know the distance r where the MPE limit is reached.

9.2 EUT Operating Condition

A software provided by client enabled the EUT to transmit and receive data at lowest, middle and highest channel individually.

**Ecom Sertech Corp.**

Rm. 258, Bldg. 17, NO.195, Sec. 4 Chung Hsing Rd., Chu Tung Chen, Hsinchu, Taiwan 310, R.O.C
TEL: 886-3-5918012 FAX: 886-3-5825720

FCC ID : M4Y-XG2000

Report No. : ER03-07-066FRF

Page 64 of 64

9.3 Test Result of RF Exposure Evaluation

Test Item : RF Exposure Evaluation Data

Test Mode : Normal Operation

9.3.1 Antenna Gain

Antenna Gain : The maximum Gain measured in fully anechoic chamber is 2dBi linear scale.

9.3.2 Output Power into Antenna & RF Exposure Evaluation Distance

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density at 20cm (mW/cm ²)	LIMITS (mW/cm ²)
CH1	2412.00	18.95	0.024759	1
CH6	2437.00	18.04	0.020078	1
CH11	2462.00	17.12	0.016245	1

Note: For 802.11b mode (11Mbps).

Channel	Channel Frequency (MHz)	Output Power to Antenna (dBm)	Power Density at 20cm (mW/cm ²)	LIMITS (mW/cm ²)
CH1	2412.00	16.55	0.014247	1
CH6	2437.00	15.79	0.011960	1
CH11	2462.00	14.99	0.009948	1

Note: For 802.11g mode (54Mbps).

The power density Pd (4th column) at a distance of 20cm calculated from the Friis transmission formula is far below the limit of 1 mW/cm². So, RF exposure limit warning or SAR test are not required.