

TABLE OF CONTENTS

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

TEST REPORT CONTAINING:

PAGE	1-2.....	TEST PROCEDURE
PAGE	2.....	TEST PROCEDURE CONTD & CIRCUIT DESCRIPTION
PAGE	3.....	RADIATION INTERFERENCE TEST DATA
PAGE	4.....	RADIATION INTEFERENCE CONTD. AND POWERLINE CONDUCTED INTERFERENCE

EXHIBIT ATTACHMENTS:

EXHIBIT	1.....	POWER OF ATTORNEY LETTER
EXHIBIT	2A-2B.....	15.121 COMPLIANCE STATEMENT
EXHIBIT	3A-3B.....	BLOCK DIAGRAMS
EXHIBIT	4A-4F.....	SCHEMATICS
EXHIBIT	5A-5J.....	INSTRUCTION MANUAL
EXHIBIT	6.....	POWERLINE CONDUCTED PLOT - LINE 1
EXHIBIT	7.....	POWERLINE CONDUCTED PLOT - LINE 2
EXHIBIT	8.....	FCC ID LABEL SAMPLE AND SKETCH OF LOCATION
EXHIBIT	9.....	EXTERNAL PHOTO - FRONT VIEW
EXHIBIT	10.....	EXTERNAL PHOTO - BACK VIEW
EXHIBIT	11.....	INTERNAL CPU BOARD - COMPONENT SIDE
EXHIBIT	12.....	INTERNAL CPU BOARD - COPPER SIDE
EXHIBIT	13.....	INTERNAL CPU BOARD - COPPER SIDE
EXHIBIT	14.....	INTERNAL RX BOARD - COMPONENT SIDE
EXHIBIT	15.....	INTERNAL RX BOARD - COMPONENT SIDE
EXHIBIT	16.....	INTERNAL RX BOARD - COPPER SIDE

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

REPORT #: F:\CUS\0\OPT0\OPT136C8.RPT

PAGE: TABLE OF CONTENTS LIST

APPLICANT: OPTOELECTRONICS, INC.
FCC ID: M5MOPTOCOM

TEST EQUIPMENT LIST

1. Spectrum Analyzer: Hewlett Packard 8566B, with preselector HP 85685A, & Quasi-Peak Adapter HP 85650A, & HP 8449B OPT H02 Cal. 9/30/97
2. Eaton Biconnical Antenna Model 94455-1 20-200 MHz Serial No. 0997 Cal. 9/17/97
3. Electro-Metric Dipole Kit, 20-1000 MHz, Model TDA 25 cal. 5/15/97
4. Electro-Metric Horn 1-18 GHz, Model RGA-180, Cal. 9/24/97
5. Electro-Metric Antennas Model TDS-25-1, TDS-25-2, 9/3/97
6. Electro-Metric Line Impedance Stabilization Network Model No. EM-7821, Serial No. 101; 100KHz-30MHz 50uH. 9/30/97
7. Electro-Metric Line Impedance Stabilization Network Model No. EM-7820, Serial No. 2682; 10KHz-30MHz 50uH. 9/30/97

TEST PROCEDURE

GENERAL: This report shall NOT be reproduced except in full without the written approval of TIMCO ENGINEERING, INC.

RADIATION INTERFERENCE: The test procedure used was ANSI STANDARD C63.4-1992 using a HEWLETT PACKARD spectrum analyzer with a preselector. The bandwidth of the spectrum analyzer was 100 kHz with an appropriate sweep speed. The analyzer was calibrated in dB above a microvolt at the output of the antenna. The resolution bandwidth was 100KHz and the video bandwidth was 300KHz. The ambient temperature of the UUT was 79.7oF with a humidity of 64%.

FORMULA OF CONVERSION FACTORS: The Field Strength at 3m was established by adding the meter reading of the spectrum analyzer (which is set to read in units of dBuV) to the antenna correction factor supplied by the antenna manufacturer. The antenna correction factors are stated in terms of dB. The gain of the Preselector was accounted for in the Spectrum Analyzer Meter Reading.

Example:

Freq (MHz)	METER READING + ACF = FS
33	20 dBuV + 10.36 dB = 30.36 dBuV/m @ 3m

POWER LINE CONDUCTED INTERFERENCE: The procedure used was ANSI STANDARD C63.4-1992 using a 50uH LISN. Both lines were observed. The bandwidth of the spectrum analyzer was 10kHz with an appropriate sweep speed. The ambient temperature of the UUT was 79.7oF with a humidity of 64%.

APPLICANT: OPTOELECTRONICS, INC.
FCC ID: M5MOPTOCOM
REPORT #: F:\CUS\0\OPT0\OPT136C8.RPT
PAGE #: 1

TEST PROCEDURES CONTINUED

APPLICANT: OPTOELECTRONICS, INC.
FCC ID: M5MOPTOCOM

ANSI STANDARD C63.4-1992 10.1.7 MEASUREMENT PROCEDURES: The unit under test was placed on a table 80 cm high and with dimensions of 1m by 1.5m. The table used for radiated measurements is capable of continuous rotation.

When an emission was found, the table was rotated to produce the maximum signal strength. At this point, the antenna was raised and lowered from 1m to 4m. The antenna was placed in both the horizontal and vertical planes.

The situation was similar for the conducted measurement except that the table did not rotate. The EUT was setup as described in ANSIC63.4-1992 with the EUT 40 cm from the vertical ground wall.

CIRCUIT DESCRIPTION

2.1033 (b)(4) CIRCUIT DESCRIPTION:

This unit is a near field radio receiver. The integrated circuit IC10 is a PLL which drives 4 different switches, Q29, Q30, Q28, Q34, Q36, which in turn drive 3 different VCO's. The VCO's Q27, Q33, Q35 then drive the tunable BPF and the 1st mixer. The 2nd PLL IC11 drives a low pass filter and VCO and buffer amplifier Q44 which feeds the 2nd mixer, Q9. From the 2nd mixer the signal goes to the 2nd IF amplifier Q11 and then to the 3rd mixer Q13. For AM signals the output of the 2nd mixer also drives the 2nd AM/IF amplifier Q15 & Q16 and then the oscillator/mixer IC2. From the 2nd AM mixer the signal is fed through a ceramic filter and then to an AM detector Q17. Integrated circuits IC4, 5, & 6 performs amplification and most of the remaining receiver functions.

ANTENNA & GROUND:

This unit uses a short telescoping antenna for the receiving antenna. The antenna is self contained and there is no provision for connecting an external antenna.

No ground connection is provided. The only ground used is the ground track on the PC Board.

APPLICANT: OPTOELECTRONICS, INC.
FCC ID: M5MOPTOCOM
REPORT #: F:\CUS\0\OPT0\OPT136C8.RPT
PAGE #: 2

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

NAME OF TEST: RADIATION INTERFERENCE

RULES PART NUMBER: 15.109

REQUIREMENTS: 30 to 80 MHz: 40.0 dBuV/M @ 3 METERS
88 to 216 MHz: 43.5 dBuV/M
216 to 960 MHz: 46.0 dBuV/M
ABOVE 960 MHz: 54.0 dBuV/M

TEST RESULTS: A search was made of the spectrum from 30 to 1000 MHz and the measurements indicate that the unit DOES meet the FCC requirements.

TEST DATA:

TUNED FREQ. MHZ	EMISSION FREQUENCY MHZ	METER READING @ 3m dBuV	COAX LOSS dB	A.C.F. dB	FIELD STRENGTH dBuV/m@3m	MARGIN dB	ANT.
27.15	33.22	9.30	0.25	10.37	19.92	20.08	V
27.15	564.38	13.90	1.60	19.82	35.32	10.68	V
27.15	639.99	20.90	1.60	20.98	43.48	2.52	H
27.15	1128.69	5.70	1.00	24.51	31.21	22.79	H
27.15	1288.60	2.40	1.00	25.15	28.55	25.45	H
27.15	1693.05	5.60	1.00	26.77	33.37	20.63	V
27.15	1919.98	13.60	1.02	27.68	42.30	11.70	H
510.00	563.62	14.20	1.60	19.81	35.61	10.39	V
510.00	1122.00	16.70	1.00	24.49	42.19	11.81	V
510.00	1690.51	4.90	1.00	26.76	32.66	21.34	V
1250.00	563.65	14.10	1.60	19.81	35.51	10.49	V
1250.00	638.00	18.90	1.60	20.94	41.44	4.56	H
1250.00	1276.00	22.80	1.00	25.10	48.90	5.10	V
1250.00	1690.51	5.60	1.00	26.76	33.36	20.64	H
1250.00	1914.10	17.20	1.02	27.66	45.87	8.13	H
1250.00	1276.00	22.80	1.00	25.10	48.90	5.10	V

SAMPLE CALCULATION: FSdBuV/m = MR(dBuV) + ACFdB.

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

REPORT #: F:\CUS\0\OPT0\OPT136C8.RPT

PAGE #: 3

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

NAME OF TEST: RADIATION INTERFERENCE

TEST PROCEDURE: ANSI STANDARD C63.4-1992 using a Hewlett Packard Model 8566B spectrum analyzer, a Hewlett Packard Model 85685A Preselector, a Hewlett Packard Model 85650A Quasi-Peak adapter, an Electro-Metric Dipole Kit, and an Eaton Model 94455-1 Biconical Antenna. The bandwidth of spectrum analyzer was 100 kHz with an appropriate sweep speed. When an emission was found, the table was rotated to produce the maximum signal strength. The antenna was placed in both the horizontal and vertical planes and the worse case emissions were reported. The receiver was put into the coherent mode by placing an antenna driven by a signal generator off site. The UUT was tested in 3 orthogonal planes.

NAME OF TEST: POWER LINE CONDUCTED INTERFERENCE

RULES PART NUMBER: 15.107(a)

REQUIREMENTS: .45 - 30 MHz 250 uV

TEST PROCEDURE: ANSI STANDARD C63.4-1992. The spectrum was scanned from .45 to 30 MHz.

TEST DATA:

THE HIGHEST EMISSION READ FOR LINE 1 WAS 21.354 uV @ 28.82 MHz.

THE HIGHEST EMISSION READ FOR LINE 2 WAS 91.090 uV @ 13.22 MHz.

THE FOLLOWING IN EXHIBITS 6 AND 7 REPRESENT THE EMISSIONS TAKEN FOR THIS DEVICE.

TEST RESULTS: Both lines were observed. The measurements indicate that the unit DOES appear to meet the FCC requirements for this class of equipment.

APPLICANT: OPTOELECTRONICS, INC.

FCC ID: M5MOPTOCOM

REPORT #: F:\CUS\0\OPT0\OPT136C8.RPT

PAGE #: 4